

Special Notice

SUBJECT* Intent To Sole Source - Immunofluorescence Microscope John D. Dingell VAMC, Detroit, MI

GENERAL INFORMATION

CONTRACTING OFFICE'S ZIP CODE*	46240
SOLICITATION NUMBER*	36C25025Q0397
RESPONSE DATE/TIME/ZONE	03-19-2025 16:00 EASTERN TIME, NEW YORK, USA
ARCHIVE	30 DAYS AFTER THE RESPONSE DATE
RECOVERY ACT FUNDS	N
PRODUCT SERVICE CODE*	6650
NAICS CODE*	334516
CONTRACTING OFFICE ADDRESS	Department of Veterans Affairs Network Contracting Office 10 8888 Keystone Crossing Suite 325 Indianapolis IN 46240
POINT OF CONTACT*	Contracting Officer James Howard james.howard3@va.gov

ADDITIONAL INFORMATION

AGENCY'S URL

URL DESCRIPTION

AGENCY CONTACT'S EMAIL ADDRESS

EMAIL DESCRIPTION

***= Required Field**

Special Notice

Special Notice

Special Notice

DESCRIPTION

DEPARTMENT OF VETERANS AFFAIRS
VETERANS HEALTH ADMINISTRATION

March 17th, 2025

SPECIAL NOTICE – NOTICE OF INTENT TO SOLE-SOURCE
Immunofluorescence Microscope
36C25025Q0397

The Department of Veterans Affairs, John D. Dingell VA Medical Center, VISN 10 Contracting Activity, intends to negotiate a sole source contract under Simplified Acquisition Procedures and the authority of FAR Part 6.302-1, Only One Responsible Source, for the following items listed below. The associated NAICS code for this equipment is 334516. The vendor, Carl Zeiss Microscopy, LLC, is an “Other Than Small Business” entity, and is located at One North Broadway, White Plains 10601-2310.

Description of equipment requirements:

Immunofluorescence Microscope. Carl Zeiss Microscopy, LLC is the only manufacturer that can provide the microscope (and accompanying add-ons) that can meet the requirements of the JDDVAMC’s Research Department.

Special Notice

0001	Microscope Axio Observer 3/5/7 KMAT Consisting of the following items: Stand Axio Observer 5 Microscope stand Axio Observer 5 - 6-position nosepiece, H DIC M27 cod. - manual focus drive incl. focus stop - z-drive operation, flat; left - 1x tube lens to fit with optional available 1-position tube lens mount or 3-position optovar turret cod. - slider mount for PlasDIC and analyzer module - circular operation key unit right - keys for switching TL/RL illumination - light manager - interfaces CAN, RS 232, USB and TCP/IP - trigger socket (In/Out) for shutter - connecting socket for external UNIBLITZ shutter - integrated 12V DC 100W power supply, stabilized, 100V-127V and 200V-240VAC / 50-60Hz / max. 300VA - USB cable and country-specific line cable - Optovar Mount 1 Position Fixed Sideport 60N L 100/100 2 pos f/Observer Beam deflection assy VIS - Condenser LD 0.35 H/Ph0/Ph1/Ph2/DIC Reflected-light illuminator FL Reflected-light illuminator FL - slider mounts for manual sliders - beam path apochromatic corrected slider mount for 3-position filter slider, dia. 25 mm transmission from 375 to 825 nm >80%Reflector turret 6x motDust cover L600xW420xH620 mm
0002	Binoc Tube 45/23 f/ Axio Observer
0003	Eyepiece PL 10x/23 Br foc
0004	C-Mount Adapter 60N C 1" 1.0x
0005	Camera Axiocam 305 color
0006	FL Filter Set 49 DAPI,EX G365 S free
0007	G FL Filter Set 38 HE GFP shift free Filter set 38 HE eGFP shift free (E) EX BP 470/40, BS FT 495, EM BP 525/50, recommended for white light fluorescence light sources or ZEISS LED fluorescence light sources.
0008	G FL Filter Set 64 HE mPlum shift free Filter set 64 HE mPlum shift free (E) EX BP 587/25, BS FT 605, EM BP 647/70, recommended for white light fluorescence light sources or ZEISS LED fluorescence light sources.
0009	G-Reflector Module FL EC P&C
0010	X-Cite mini XMPS (365nm) X-Cite mini+ System, XMPS (365nm)Includes:-LED head, miniCUBE controller, speedDIAL remote-Microscope Coupling Flange,Accessory Kit (tools, USB cable, power cord)"
0011	Mechanical stage 130x85 R/L Mechanical stage 130x85 R/L for mounting frames K 160 x 110 mm and Z-PIEZO, compatible with objectives autocorr
0012	Objective LD A-Plan 40x/0.55 Objective LD A-Plan 40x/0.55 M27 (WD=2.5mm at D=1mm polystyrene)
0013	G-EC Plan-Neofluar 10x/0.30 WD=5.2 M27
0014	G-Objective PApo 20x/0.8 Objective Plan-Apochromat 20x/0.8 M27 (FWD=0.55mm), incl. Cover glasses, high performance,CG=0.17mm, box with 100 pc Lead-free
0015	Microscopy Workstation Compact HP Z2 G9 Microscopy Workstation Compact HP Z2 G9 Rev. 2 (O) -HP Z2 Tower G9 Workstation-Chipset: Intel W680-Memory Expansion Slots: 4 x DDR5-RAM modules, 4400MHz-Memory: max. 128 / 192 GB RAM-PCI Express Connectors:1x PCI Express Generation 5 x161x PCI Express Generation 3 x4 (x16 connector)1x PCI Express Generation 3 x41x PCI Express Generation 3 x1 (x4 connector)-Graphics Card onboard: Intel UHD Graphics 7702 x Display Port 1.4 (max. 3840 x 2160 Pixel)-SSD: 1 x 512 GB M.2 NVMe-Hard disks: 1 x 8 TB SATA 7200 rpm-Network controller: 1 x GbE LAN interface (RJ 45)-USB: 4 x Type-A SuperSpeed USB 10 Gbps (front)2 x Type-A SuperSpeed USB 10 Gbps, 1 x Type-A SuperSpeed USB 5Gbps, 3 x Hi-Speed USB 480 Mbps (rear) -Certifications and Declarations: CE, CSA, UL, FCC, CCC, KCC-TPM BIOS selectable, default off-Power Supply 700W, wide-ranging with country specific plug-Chassis Dimensions: (H x W x D): 356 x 169 x 385 mm-USB Mouse-Rescue Kit, SysConf2 HPZ2G9 Windows10LTSC2021 SystemSystem Configuration 2 for HP Z2 G9 (O) Installation of Windows 10 IoT Enterprise LTSC 2021 x64 incl. Windows 10 License -with system integration and ZEN software installation for respectivesystem-only for 410201-9913-000 Microscopy Workstation Compact HP Z2 G9, Processor Intel Core i5-12500 (hpZ2G9) Processor Intel Core i5-12500 (HP Z2 G9) (O) Default processor configuration -Intel Core i5-12500 (3.0 GHz 18 MB cache 6 cores 12 threads)-only for 410201-9913-000 Microscopy Workstation Compact HP Z2 G9, Memory 16 GB (1x16) DDR5-4800 (hpZ2G9)Memory 16 GB (1x16) DDR5-4800 (HP Z2 G9) (O) consisting of 1 x 16 GB module -DDR5 4800 MHz nonECC unbuffered DIMM-can be extended to 32GB (2 x 410201-1606-000) or 64 GB(4 x 410201-1606-000)-only for 410201-9913-000 Microscopy Workstation Compact HP Z2 G9,Language pack english USLanguage Pack English US (O)
0016	Monitor TFT 27" HP S7 Pro 727pk (68cm)Monitor TFT 27" HP Series 7 Pro 727pk (68 cm) (O) Visible diagonal: 68 cm, 16:9 Maximum resolution: 3840 x 2160 pixel @ 60 Hz Brightness: 400 nits Contrast: 2000:1 Viewing angle: horizontal 178 degree, vertical 178 degree Video input: DisplayPort 1.4, HDMI 2.0, USB-C Data connectors: 1 x USB Type-C 10Gbps (upstream), 1 x USB Type-C 10Gbps, 5 x USB Type-A 10Gbps Power consumption: Maximum 215 W, Typical 43 W, Standby 0.5 W Dimensions incl. stand (H x W x D): 54.05 cm x 61.34 cm x 22.52 cm Weightincl. stand: 6.5 kg Ergonomic features: Tilt: -5°to +20°, Swivel: -45° to +45°, Height adjustable 15 cm, Pivot rotation: -90° to +90° Certification and compliance: CE, CB, GS, T?V, FCC, TCO Operating voltage: 100-240 V, country-specific power cable
0017	G-Universal Mounting Frame K
0018	Universal Mounting Frame K-M Universal mounting frame K-M for multiwell plates with glass bottom and foot print 125...127 mm x 83...86 mm
0019	Carrier Transmitted Light LCD Shutter
0020	Illuminator VIS-LED
0021	SW ZEN 3.11 DLic ZEN 3.11 Image acquisition and processing under Windows 10 / Windows 11 x64 User interface configurable, control of the ZEISS microscope systems and components, extensive acquisition and analysis, CZI image format The following functions are included: -Basic 3D viewing-Colocalization -Connect basic-Direct processing-Manual EDF-Measurement-Panorama-Spectral unmixing-ZEN Data Storage Client-Acquisition Base (time series and multichannel)

Special Notice

A firm fixed price contract is anticipated and shall be awarded. It is the Government's belief that only the proposed candidate possesses the capability to successfully meet this requirement. It is the Government's intention to solicit and negotiate with only this source.

This is not a Request for Proposal; this is a Notice of Intent to Sole Source a requirement.