# GENERAL NOTES

1. ALL WORK (MATERIALS, EQUIPMENT, DEVICES, COMPONENTS, SYSTEMS, SUPPORTS, ETC.) MUST COMPLY WITH THE REQUIREMENTS OF ALL CODES, CODE AMENDMENTS, AND ORDINANCES AS USED, ADOPTED AND/OR ENFORCED BY THE LOCAL JURISDICTION, COUNTY AND STATE.
2. ALL WORK IS TO BE FABRICATED AND/OR ERECTED USING CONTRACTOR'S FIELD MEASUREMENTS FOR PROPER COORDINATION WITH WORK OF OTHER TRADES.
3. ALL CONTRACT DOCUMENTS ARE DIAGRAMMATIC AND INDICATE THE GENERAL ARRANGEMENTS OR GEOMETRICAL RELATIONSHIPS OF THE WORK. THEY ARE NOT INTENDED TO SPECIFY OR SHOW EVERY OFFSET, SEQUENCE, DEVICE, OPTION, FITTING, OR COMPONENT. DO NOT SCALE DRAWINGS FOR FABRICATION PURPOSES.
4. COORDINATE PLACEMENT OF ALL WORK WITH OTHER TRADES. DO NOT LOCATE, POSITION OR INSTALL ANY WORK IN SUCH A WAY THAT SYSTEM COMPONENTS OR ACCESS DOORS WILL BE INACCESSIBLE, UNUSABLE OR UN-MAINTAINABLE AFTER CONSTRUCTION IS COMPLETED.
5. GRAVITY DRAINAGE SYSTEMS HAVE PRIORITY WITH REGARD TO ROUTING. COORDINATE INSTALLATION OF WORK SO AS NOT TO INHIBIT THE INSTALLATION OR REQUIRED SLOPES FOR GRAVITY DRAINAGE SYSTEMS.
6. ALL WORK MUST BE SUPPORTED FROM STRUCTURE ABOVE, FROM WALLS, OR FROM THE FLOOR UNLESS OTHERWISE INDICATED. DO NOT USE THE INSTALLED WORK OF OTHER TRADES FOR SUPPORT OR BRACING. ALL PIPING SUPPORTS SHALL BE CONSTRUCTED OF ALUMINUM.
7. ALL LOW VOLTAGE WIRING FOR CONTROLS, ETC. SHALL BE INSTALLED IN CONDUIT. MATERIALS AND INSTALLATION MUST COMPLY WITH NEC, NFPA, STATE AND LOCAL CODES AND ORDINANCES.
8. ALL PIPE PENETRATIONS THRU WALLS MUST BE PROVIDED WITH METAL SLEEVES OR THIMBLES. SLEEVES AND THIMBLES SHALL BE AT LEAST 3/8 INCH LARGER THAN THE OUTSIDE DIAMETER OF THE PIPING PLUS INSULATION. CAULK BETWEEN SLEEVE AND PIPE WITH FLEXIBLE CAULKING MATERIAL (RATED FOR SURFACE TEMPERATURE OF PIPE OR INSULATION) TO ALLOW MOVEMENT OF PIPE.
9. MAINTAIN MARKED AS-BUILTS THAT INDICATE FINAL ROUTING OF ALL VALVES, BELOW GRADE PIPING, ETC.
10. DEMOLITION AND NEW CONSTRUCTION SHALL BE PHASED IN ACCORDANCE WITH THE PHASING PLAN.




1 M-103 MECHANICAL PLAN: RENOVATION - BID OPTION #2
SCALE: 3/32"=1'-0"




KEYPLAN
NTS




LEGEND:

- POINT OF CONNECTION
- 1" ISOLATION VALVE

16' 8' 0 16'
SCALE: 3/32" = 1'-0"

The Johnson-McAdams Firm P.A.
ARCHITECTS/ENGINEERS • PLANNING • SURVEYING • MANAGEMENT
P.O. BOX 213, GREENWOOD, MISSISSIPPI • (662) 455-4843

| NO. | DATE | BY | DESCRIPTION |
|---|---|---|---|
| | | | |
| REVISIONS | | | |

| A-E FIRM | USDA |
|---|---|
| PROJECT MANAGER BP | EPM XXX |
| DESIGNER JH | PPM XXX |
| CHECKED BY JGM | SAFETY & HEALTH XXX |
| JOB # 4825 | REAL PROPERTY XXX |

USDA
USDA Agricultural Research Service

USDA AGRICULTURAL RESEARCH SERVICE
US HORTICULTURAL RESEARCH LABORATORY
REPAIR TORNADO DAMAGE
FT. PIERCE, FL
MECHANICAL PLAN
RENOVATION - BID OPTION #2

| PROJECT NO. XXX | AGRICULTURAL RESEARCH SERVICE | SHEET |
|---|---|---|
| DATE 04/27/26 | SOUTHEAST AREA<br>STONEVILLE, MS | M-103<br>80 OF 108 |

J:\greenwood\2025 Jobs\4825 USDA Tornado Damage Repair Ft. Pierce FL\07 Working Folder\Mech\M-103.dwg
Apr 27, 2026 - 10:02am

# GENERAL NOTES

1. ALL WORK (MATERIALS, EQUIPMENT, DEVICES, COMPONENTS, SYSTEMS, SUPPORTS, ETC.) MUST COMPLY WITH THE REQUIREMENTS OF ALL CODES, CODE AMENDMENTS, AND ORDINANCES AS USED, ADOPTED AND/OR ENFORCED BY THE LOCAL JURISDICTION, COUNTY AND STATE.
2. ALL WORK IS TO BE FABRICATED AND/OR ERECTED USING CONTRACTOR'S FIELD MEASUREMENTS FOR PROPER COORDINATION WITH WORK OF OTHER TRADES.
3. ALL CONTRACT DOCUMENTS ARE DIAGRAMMATIC AND INDICATE THE GENERAL ARRANGEMENTS OR GEOMETRICAL RELATIONSHIPS OF THE WORK. THEY ARE NOT INTENDED TO SPECIFY OR SHOW EVERY OFFSET, SEQUENCE, DEVICE, OPTION, FITTING, OR COMPONENT. DO NOT SCALE DRAWINGS FOR FABRICATION PURPOSES.
4. COORDINATE PLACEMENT OF ALL WORK WITH OTHER TRADES. DO NOT LOCATE, POSITION OR INSTALL ANY WORK IN SUCH A WAY THAT SYSTEM COMPONENTS OR ACCESS DOORS WILL BE INACCESSIBLE, UNUSABLE OR UN-MAINTAINABLE AFTER CONSTRUCTION IS COMPLETED.
5. GRAVITY DRAINAGE SYSTEMS HAVE PRIORITY WITH REGARD TO ROUTING. COORDINATE INSTALLATION OF WORK SO AS NOT TO INHIBIT THE INSTALLATION OR REQUIRED SLOPES FOR GRAVITY DRAINAGE SYSTEMS.
6. ALL WORK MUST BE SUPPORTED FROM STRUCTURE ABOVE, FROM WALLS, OR FROM THE FLOOR UNLESS OTHERWISE INDICATED. DO NOT USE THE INSTALLED WORK OF OTHER TRADES FOR SUPPORT OR BRACING. ALL PIPING SUPPORTS SHALL BE CONSTRUCTED OF ALUMINUM.
7. ALL LOW VOLTAGE WIRING FOR CONTROLS, ETC. SHALL BE INSTALLED IN CONDUIT. MATERIALS AND INSTALLATION MUST COMPLY WITH NEC, NFPA, STATE AND LOCAL CODES AND ORDINANCES.
8. ALL PIPE PENETRATIONS THRU WALLS MUST BE PROVIDED WITH METAL SLEEVES OR THIMBLES. SLEEVES AND THIMBLES SHALL BE AT LEAST 3/8 INCH LARGER THAN THE OUTSIDE DIAMETER OF THE PIPING PLUS INSULATION. CAULK BETWEEN SLEEVE AND PIPE WITH FLEXIBLE CAULKING MATERIAL (RATED FOR SURFACE TEMPERATURE OF PIPE OR INSULATION) TO ALLOW MOVEMENT OF PIPE.
9. MAINTAIN MARKED AS-BUILTS THAT INDICATE FINAL ROUTING OF ALL VALVES, BELOW GRADE PIPING, ETC.
10. DEMOLITION AND NEW CONSTRUCTION SHALL BE PHASED IN ACCORDANCE WITH THE PHASING PLAN.
11. PROVIDE TEMPORARY GAS AND DOMESTIC WATER. UTILITY PATH IS SHOWN ON P-100.




N

1 M-104 MECHANICAL PLAN: RENOVATION - BID OPTION #3

SCALE: 3/32"=1'-0"




## KEYPLAN

NTS

SAMUEL MAYRANT ENGLISH LICENSE No. 90054 04/27/26 STATE OF FLORIDA PROFESSIONAL ENGINEER

LEGEND:

- POINT OF CONNECTION
- 1" ISOLATION VALVE

16' 8' 0 16'

SCALE: 3/32" = 1'-0"

| NO. | DATE | BY | DESCRIPTION |
|---|---|---|---|
| | | | |

REVISIONS

The Johnson-McAdams Firm P.A. ARCHITECTS/ENGINEERS • PLANNING • SURVEYING • MANAGEMENT P.O. BOX 513, GREENWOOD, MISSISSIPPI

| A-E FIRM | USDA |
|---|---|
| PROJECT MANAGER BP | EPM XXX |
| DESIGNER JH | PPM XXX |
| CHECKED BY JGM | SAFETY & HEALTH XXX |
| JOB # 4825 | REAL PROPERTY XXX |

USDA

USDA Agricultural Research Service

USDA AGRICULTURAL RESEARCH SERVICE
US HORTICULTURAL RESEARCH LABORATORY
REPAIR TORNADO DAMAGE
FT. PIERCE, FL
MECHANICAL PLAN
RENOVATION - BID OPTION #3

| PROJECT NO. | AGRICULTURAL RESEARCH SERVICE | SHEET |
|---|---|---|
| XXX | SOUTHEAST AREA | M-104 |
| DATE 04/27/26 | STONEVILLE, MS | 81 OF 108 |

J:\jgreenwood\2025 Jobs\4825 USDA Tornado Damage Repair Ft. Pierce FL\07 Working Folder\Mech\M-104.dwg
Apr 27, 2026 - 10:02am




2 / M-105 BID OPTION #4 MECHANICAL FLOOR PLAN HOOP HOUSE
SCALE: 1/4"=1'-0"




1 / M-105 GREENHOUSE MECHANICAL PLAN BID OPTION #4
SCALE: 1/4"=1'-0"




KEYPLAN - PICOS FARM SITE
NTS

0 2' 4' 8' 12'
SCALE: 1/4"= 1'-0"


THE Johnson-McAdams FIRM P.A.
ARCHITECTS/ENGINEERS • PLANNING • SURVEYING • MANAGEMENT
P.O. BOX 513, GREENWOOD, MISSISSIPPI - (662) 455-4943


| NO. | DATE | BY | DESCRIPTION |
|---|---|---|---|
| | | | |
| | | | |
| | | | |

REVISIONS

| A-E FIRM | USDA |
|---|---|
| PROJECT MANAGER BP | EPM XXX |
| DESIGNER JH | PPM XXX |
| CHECKED BY JGM | SAFETY & HEALTH XXX |
| JOB # 4825 | REAL PROPERTY XXX |

USDA

USDA Agricultural Research Service

USDA AGRICULTURAL RESEARCH SERVICE
US HORTICULTURAL RESEARCH LABORATORY
REPAIR TORNADO DAMAGE
FT. PIERCE, FL
MECHANICAL PLAN
RENOVATION - BID OPTION #4

| PROJECT NO. XXX | AGRICULTURAL RESEARCH SERVICE | SHEET |
|---|---|---|
| DATE 04/27/26 | SOUTHEAST AREA STONEVILLE, MS | M-105 82 OF 108 |

J:\greenwood\2025 Jobs\4825 USDA Tornado Damage Repair Ft. Pierce FL\07 Working Folder\Mech\M-105.dwg
Apr 27, 2026 - 10:02am




1 M-106 GREENHOUSE MECHANICAL PLAN - BID OPTION #5

SCALE: 3/32"=1'-0"




KEYPLAN

NTS


16' 8' 0 16'

SCALE: 3/32" = 1'-0"

The Johnson-McAdams Firm P.A.

| NO. | DATE | BY | DESCRIPTION |
|---|---|---|---|
| | | | |
| | | | |
| | | | |

REVISIONS

| A-E FIRM | USDA |
|---|---|
| PROJECT MANAGER BP | EPM XXX |
| DESIGNER JH | PPM XXX |
| CHECKED BY JGM | SAFETY & HEALTH XXX |
| JOB # 4825 | REAL PROPERTY XXX |

USDA

USDA Agricultural Research Service

USDA AGRICULTURAL RESEARCH SERVICE
US HORTICULTURAL RESEARCH LABORATORY
REPAIR TORNADO DAMAGE
FT. PIERCE, FL
MECHANICAL PLAN
RENOVATION - BID OPTION #5

| PROJECT NO. XXX | AGRICULTURAL RESEARCH SERVICE | SHEET |
|---|---|---|
| DATE 04/27/26 | SOUTHEAST AREA STONEVILLE, MS | M-106 83 OF 108 |

J:\jgreenwood\2025 Jobs\4825 USDA Tornado Damage Repair Ft. Pierce FL\07 Working Folder\Mech\M-106.dwg
Apr 27, 2026 - 10:02am




N 1 M-401 ENLARGED MECHANICAL PLAN - BID OPTION #1

SCALE: 3/32"=1'-0"

# GENERAL NOTES

1. ALL WORK (MATERIALS, EQUIPMENT, DEVICES, COMPONENTS, SYSTEMS, SUPPORTS, ETC.) MUST COMPLY WITH THE REQUIREMENTS OF ALL CODES, CODE AMENDMENTS, AND ORDINANCES AS USED, ADOPTED AND/OR ENFORCED BY THE LOCAL JURISDICTION, COUNTY AND STATE.
2. ALL WORK SHALL BE FABRICATED AND/OR ERECTED USING CONTRACTOR'S FIELD MEASUREMENTS FOR PROPER COORDINATION WITH WORK OF OTHER TRADES.
3. ALL CONTRACT DOCUMENTS ARE DIAGRAMMATIC AND INDICATE THE GENERAL ARRANGEMENTS OR GEOMETRICAL RELATIONSHIPS OF THE WORK. THEY ARE NOT INTENDED TO SPECIFY OR SHOW EVERY OFFSET, SEQUENCE, DEVICE, OPTION, FITTING, OR COMPONENT. DO NOT SCALE DRAWINGS FOR FABRICATION PURPOSES.
4. COORDINATE PLACEMENT OF ALL WORK WITH OTHER TRADES. DO NOT LOCATE, POSITION OR INSTALL ANY WORK IN SUCH A WAY THAT SYSTEM COMPONENTS OR ACCESS DOORS WILL BE INACCESSIBLE, UNUSABLE OR UN-MAINTAINABLE AFTER CONSTRUCTION IS COMPLETED.
5. GRAVITY DRAINAGE SYSTEMS HAVE PRIORITY WITH REGARD TO ROUTING. COORDINATE INSTALLATION OF WORK SO AS NOT TO INHIBIT THE INSTALLATION OR REQUIRED SLOPES FOR GRAVITY DRAINAGE SYSTEMS.
6. ALL WORK SHALL BE SUPPORTED FROM STRUCTURE ABOVE, FROM WALLS, OR FROM THE FLOOR UNLESS OTHERWISE INDICATED. DO NOT USE THE INSTALLED WORK OF OTHER TRADES FOR SUPPORT OR BRACING. ALL PIPING SUPPORTS SHALL BE CONSTRUCTED OF ALUMINUM.
7. ALL LOW VOLTAGE WIRING FOR CONTROLS, ETC. SHALL BE INSTALLED IN CONDUIT. MATERIALS AND INSTALLATION MUST COMPLY WITH NEC, NFPA, STATE AND LOCAL CODES AND ORDINANCES.
8. ALL PIPE PENETRATIONS THRU WALLS MUST BE PROVIDED WITH METAL SLEEVES OR THIMBLES. SLEEVES AND THIMBLES SHALL BE AT LEAST 3/8 INCH LARGER THAN THE OUTSIDE DIAMETER OF THE PIPING PLUS INSULATION. CAULK BETWEEN SLEEVE AND PIPE WITH FLEXIBLE CAULKING MATERIAL (RATED FOR SURFACE TEMPERATURE OF PIPE OR INSULATION) TO ALLOW MOVEMENT OF PIPE.
9. MAINTAIN MARKED AS-BUILTS THAT INDICATE FINAL ROUTING OF ALL VALVES, BELOW GRADE PIPING, ETC.
10. DEMOLITION AND NEW CONSTRUCTION SHALL BE PHASED IN ACCORDANCE WITH THE PHASING PLAN.

# KEYED NOTES

1. PROVIDE AIR HANDLING UNIT MOUNTED FROM ABOVE. MOUNT UNIT AT THE SAME HEIGHT OF EXISTING EQUIPMENT. RECONNECT TO EXISTING DUCTWORK AND CONDENSATE PIPING.
2. PROVIDE GROUND MOUNTED PACKAGED HEAT PUMP. RECONNECT TO EXISTING DUCT WORK.

AREA OF WORK






16' 8' 0 16'

SCALE: 3/32" = 1'-0"

THE Johnson • McAdams FIRM P.A.
ARCHITECTS/ENGINEERS • PLANNING • SURVEYING • MANAGEMENT
P.O. BOX 513, GREENWOOD, MISSISSIPPI - (662) 455-4943

| NO. | DATE | BY | DESCRIPTION |
|---|---|---|---|
| | | | |
| | | | |
| | | | |

REVISIONS

USDA Agricultural Research Service

USDA AGRICULTURAL RESEARCH SERVICE
US HORTICULTURAL RESEARCH LABORATORY
REPAIR TORNADO DAMAGE
FT. PIERCE, FL
ENLARGED MECHANICAL PLAN- BID OPTION #1

| A-E FIRM | USDA |
|---|---|
| PROJECT MANAGER BP | EPM XXX |
| DESIGNER JH | PPM XXX |
| CHECKED BY JGM | SAFETY & HEALTH XXX |
| JOB # 4825 | REAL PROPERTY XXX |

| PROJECT NO. XXX | AGRICULTURAL RESEARCH SERVICE | SHEET |
|---|---|---|
| DATE 04/27/26 | SOUTHEAST AREA STONEVILLE, MS | M-401 84 OF 108 |

## UNIT HEATER SCHEDULE (EACH)

| MARK | TYPE | INPUT (BTUH) | OUTPUT (BTUH) | THERMAL EFFICIENCY | FAN (CFM) | FAN (HP) | VOLTAGE | AMPS | REMARKS |
|---|---|---|---|---|---|---|---|---|---|
| UH-1 | NATURAL GAS | 75,000 | 62,250 | 83% | 961 | 2/3 | 120/1 | 3.7 | SEE NOTES |
| UH-2 | ELECTRIC | 10,200 | 10,200 | N/A | 380 | 1/40 | 208/3 | 8.3 | SEE NOTES |
| UH-3 | PROPANE | 75,000 | 62,250 | 83% | 961 | 2/3 | 120/1 | 3.7 | SEE NOTES |

NOTES:
1. INTERGRATE WITH GREENHOUSE CONTROL SYSTEM.
2. PROVIDE WITH MOUNTING KIT.
3. EQUIPMENT SHALL COMPLY WITH THE "BUY AMERICAN ACT".

## GREENHOUSE FAN SCHEDULE

| MARK | MATERIAL | DIAMETER | TYPE | AIRFLOW (CFM) | RPM | E.S.P. (IN W.G.) | DRIVE | MOTOR | | | REMARKS |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | HP | VOLTS | PHASE | |
| EF-1 | ALUMINUM | 36" | SIDEWALL PROP | 10500 | 495 | 0.1" | BELT | 1/2 | 208 | 3 | SEE NOTE 1,2,3 |
| EF-2 | ALUMINUM | 36" | SIDEWALL PROP | 10500 | 495 | 0.1" | BELT | 1/2 | 208 | 1 | SEE NOTE 1,2,3 |
| EF-3 | ALUMINUM | 30" | SIDEWALL PROP | 5770 | 450 | .1" | BELT | 1/4 | 208 | 3 | SEE NOTE 1,2,3 |
| HF | ALUMINUM | 18" | CEILING MOUNTED HORIZONTAL | 2000 | 1100 | NA | DIRECT | 1/15 | 115 | 1 | SEE NOTE 1 |

NOTES:
1. PROVIDE SINGLE-SPEED MOTOR.
2. PROVIDE WITH SLANT WALL HOUSING
3. PROVIDE WITH ALUMINUM BACKDRAFT SHUTTER.

## EVAPORATIVE COOLING PAD

| MARK | CONSTRUCTION | TROUGH | LENGTH | HEIGHT | GPM | EAT | | LAT | | MEDIA THICKNESS | MAX. FACE VELOCITY | REMARKS |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | DB(°F) | WB(°F) | DB(°F) | WB(°F) | | | |
| ECP-1 | STAINLESS STEEL AND PVC | ONE PIECE PVC | 36' | 4' | 68.3 | 95 | 78 | 83 | 83 | 6" | 125 | SEE NOTES |
| ECP-2 | STAINLESS STEEL AND PVC | ONE PIECE PVC | 22' | 4' | 68.3 | 95 | 78 | 83 | 83 | 6" | 125 | SEE NOTES |
| ECP-3 | STAINLESS STEEL AND PVC | ONE PIECE PVC | 6' | 4' | 68.3 | 95 | 78 | 83 | 83 | 6" | 125 | SEE NOTES |

NOTES:
1. INTERLOCK ECP CONTROL WITH GREENHOUSE MASTER CONTROLLER.
2. INSTALL SYSTEM IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS.
3. PROVIDE WITH SUMP PUMP 110 VAC.
4. CONNECT TO ADJACENT DOMESTIC WATER LINE FOR MAKE UP WATER SUPPLY

## GREENHOUSE AIR CURTAIN SCHEDULE

| MARK | NOZZLE WIDTH | NOZZLE VELOCITY | AIR VOLUME | POWER | WEIGHT | MOTOR | | | REMARKS |
|---|---|---|---|---|---|---|---|---|---|
| | | | | | | HP | VOLTS | PHASE | |
| DAC-1 | 111" | 3,300 FPM | 3500 CFM | 1.5 KW | 120 LBS | 3 @ 1/2 | 115 | 1 | ALL |

NOTES:
1. PROVIDE SINGLE-SPEED MOTOR.
2. PROVIDE WITH DOOR ACTIVATION.

## HEAT PUMP SCHEDULE

| MARK | SYSTEM TYPE | COOLING CAPACITY (BTU/HR) | SENSIBLE CAPACITY (BTU/HR) | SEER | OUTDOOR TEMPERATURE (F) | VOLTS/ PHASE | MCA | MOCP | WEIGHT (LBS) | REMARKS |
|---|---|---|---|---|---|---|---|---|---|---|
| HP-1 | AIR-COOLED | 46180 | 34476 | 15.2 | 95 | 230/3 | 18.1 | 30 | 251 | ALL |
| HP-2 | AIR-COOLED | 56927 | 42229 | 14.30 | 95 | 230/3 | 28.2 | 35 | 251 | ALL |
| HP-3 | AIR-COOLED | 23030 | 16647 | 16.00 | 95 | 230/1 | 13 | 20 | 174 | ALL |
| HP-4 | AIR-COOLED | 23030 | 16647 | 16.00 | 95 | 230/1 | 13 | 20 | 174 | ALL |
| HP-5 | AIR-COOLED | 46180 | 34476 | 15.2 | 95 | 230/3 | 18.1 | 30 | 251 | ALL |

REMARKS
1. PROVIDE AND INSTALL REFRIGERANT SUPPLY AND RETURN LINES PER MANUFACTURER'S RECOMMENDATIONS.

## PACKAGED UNIT SCHEDULE

| MARK | TYPE | SUPPLY AIRFLOW DATA | | | | DX COOLING | | | | ELECTRIC HEATING | | | FILTER | EER | SEER2 | VOLTS/ PHASE | OPER. WEIGHT (LBS) | MOP | MCA | REMARKS |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | SA FLOW (CFM) | ESP (IN H2O) | TSP (IN H2O) | FAN SPEED (RPM) | CAPACITY | | AIR SIDE | | CAPACITY | AIR SIDE | | | | | | | | | |
| | | | | | | TOTAL MBH | SENS MBH | EAT °F (DB/WB) | LAT °F (DB/WB) | KW | EAT °F | LAT °F | | | | | | | | |
| AC-1 | PACKAGED | 1200 | 2.0 | 2.5 | 1241 | 36.8 | 25.5 | 80/67 | 59.0/57.0 | 11.27 | 60 | 90 | MERV 8 | 11.0 | 13.8 | 208/1 | 400 | 70 | 68 | SEE NOTES |

NOTES:
1. PROVIDE DOUBLE WALL CONSTRUCTION
2. PROVIDE WITH HORIZONTAL DISCHARGE.
3. PROVIDE WITH UNIT MICROPROCESSOR CONTROLLER CAPABLE OF STANDALONE OPERATION WITH INTEGRAL SCHEDULE AND OPERATIONS SETPOINTS (ADJ.). LOCATE MICROPROCESSOR CONTROL ADJACENT TO THERMOSTAT.
4. PROVIDE BAROMETRIC RELIEF.

## AIR HANDLING UNIT SCHEDULE

| MARK | UNIT TYPE | AIRFLOW (CFM) | COOLING | | | | | | HEATING | | | UNIT WT (LBS) | ELECTRICAL DATA | | | REMARKS |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | CAPACITY | | AIRSIDE | | | | CAPACITY | AIRSIDE | | | | | | |
| | | | TOTAL (BTU/HR) | SENSIBLE (BTU/HR) | EAT (db °F) | EAT (wb °F) | LAT (db °F) | LAT (wb °F) | TOTAL (BTU/HR) | EAT (db °F) | LAT (db °F) | | VOLTS/ PHASE | MCA | MOCP | |
| AHU-1 | HORIZONTAL DUCTED | 1600 | 46184 | 34476 | 80 | 67 | 59.70 | 57.6 | 46170 | 70 | 86 | 170 | 230/1 | 9.0 | 15 | ALL |
| AHU-2 | HORIZONTAL DUCTED | 1900 | 56927 | 42229 | 80 | 67 | 59.1 | 57.2 | 52500 | 70 | 86 | 170 | 230/1 | 9.0 | 15 | ALL |
| AHU-3 | HORIZONTAL DUCTED | 700 | 23030 | 16647 | 80 | 67 | 57.6 | 56.1 | 22200 | 70 | 88 | 140 | 230/1 | 5.0 | 15 | ALL |
| AHU-4 | HORIZONTAL DUCTED | 700 | 23030 | 16647 | 80 | 67 | 57.6 | 56.1 | 22200 | 70 | 88 | 140 | 230/1 | 5.0 | 15 | ALL |
| AHU-5 | HORIZONTAL DUCTED | 1600 | 46184 | 34476 | 80 | 67 | 59.70 | 57.6 | 46170 | 70 | 86 | 170 | 230/1 | 9.0 | 15 | ALL |

REMARKS
1. AHU SHALL HAVE MERV 8 RATED FILTERS.
2. PROVIDE WITH THERMOSTAT BY UNIT MANUFACTURER.

## PACKAGED WALL MOUNT UNIT SCHEDULE

| MARK | UNIT TYPE | AIRFLOW (CFM) | COMPRESSOR TYPE | COOLING CAPACITY (BTU/HR) | EER | UNIT WT (LBS) | ELECTRICAL DATA | | | REMARKS |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | VOLTS/ PHASE | MCA | MOCP | |
| WMU-1 | WALL MOUNTED | 1700 | VARIABLE CAPACITY ECU | 67000 | 10 | 600 | 230/3 | 39 | 60 | ALL |

REMARKS
1. AHU SHALL HAVE MERV 8 RATED FILTERS.
2. PROVIDE WITH THERMOSTAT BY UNIT MANUFACTURER.

## GREENHOUSE BAY CONTROLLER INPUT/ OUTPUT SUMMARY

| | ANALOG INPUT | ANALOG OUTPUT | BINARY INPUT | BINARY OUTPUT |
|---|---|---|---|---|
| TEMPERATURE SENSOR | X | | | |
| HUMIDITY SENSOR | X | | | |
| FAN #1 START/STOP | | | | X |
| FAN #2 START/STOP (LOW SPEED) | | | | X |
| FAN #2 START/STOP (HIGH SPEED) | | | | X |
| VENT WALL MOTOR (OPEN) | | | | X |
| VENT WALL MOTOR (CLOSE) | | | | X |
| VENT ROOF MOTOR (OPEN) | | | | X |
| VENT ROOF MOTOR (CLOSE) | | | | X |
| EVAPORATING COOLING WALL START/STOP | | | | X |
| UNIT HEATER | | X | | |
| WALL VENT WALL OPEN LIMIT | | | X | |
| WALL VENT CLOSE WALL LIMIT | | | X | |
| ROOF VENT WALL OPEN LIMIT | | | X | |
| ROOF VENT CLOSE WALL LIMIT | | | X | |
| ADD ALT #1 CIRC, FANS START/STOP | | | | X |

NOTE: PROVIDE CONTROLLERS AS REQUIRED FOR THE INPUT/OUTPUT/OUTPUT SUMMARY ABOVE. PROVIDE CENTRAL MONITORING STATION IN THE GREENHOUSE MANAGERS OFFICE.

## WEATHER STATION CONTROLLER INPUT/ OUTPUT SUMMARY

| | ANALOG INPUT | ANALOG OUTPUT | BINARY INPUT | BINARY OUTPUT |
|---|---|---|---|---|
| RAIN | | | X | |
| WIND DIRECTION | X | | | |
| WIND SPEED | X | | | |
| SOLAR K-LUX | X | | | |
| OUTDOOR TEMPERATURE | X | | | |

NOTE: PROVIDE CONTROLLERS AS REQUIRED FOR THE INPUT/OUTPUT/OUTPUT SUMMARY ABOVE. WEATHER STATION CONTROLLER TO BE BY SAME MANUFACTURER TO GREENHOUSE BAY CONTROLLER.

## SEQUENCE OF OPERATION

OCCUPIED COOLING: STEPS TO MAINTAIN ADJUSTABLE SETPOINT AS MEASURED BY TEMPERATURE SENSOR
- STEP 1: OPEN SIDE VENTS.
- STEP 2: COOLING 1 - ACTIVATE LOW SPEED OF TWO SPEED FANS.
- STEP 3: COOLING 2 - ACTIVATE HIGH SPEED OF TWO SPEED FANS.
- STEP 4: COOLING 3 - ACTIVATE EVAPORATIVE COOLING WALL SYSTEM.

HEATING: STEPS TO MAINTAIN ADJUSTABLE SETPOINT
- STEP 1: CLOSE ROOF AND SIDE VENTS.
- STEP 2: HEATING 1 - MODULATE THE NEW ELECTRONIC VALVE ACTUATOR TO MAINTAIN TEMPERATURE SETPOINT.

CONTROL SYSTEM SHALL MONITOR INDOOR AIR TEMPERATURE AND HUMIDITY, OUTDOOR AIR TEMPERATURE, RAIN CONDITIONS, WIND DIRECTION AND SPEED, AND SOLAR KLUX. CONTROL SYSTEM SHALL PROTECT GREENHOUSE VENTILATION SYSTEMS FROM HIGH WINDS AND RAIN DAMAGE. PROVIDE MANUAL OVERRIDE FOR ROOF VENTS. PROVIDE ALL WIRING AND CONTROLS FOR A COMPLETE OPERATIONAL SYSTEM.





THE Johnson • McAdams FIRM P.A.
ARCHITECTS/ENGINEERS • PLANNING • SURVEYING • MANAGEMENT
P.O. BOX 513, GREENWOOD, MISSISSIPPI - (662) 455-4943


| NO. | DATE | BY | DESCRIPTION |
|---|---|---|---|
| REVISIONS | | | |

| A-E FIRM | USDA |
|---|---|
| PROJECT MANAGER BP | EPM XXX |
| DESIGNER JH | PPM XXX |
| CHECKED BY JGM | SAFETY & HEALTH XXX |
| JOB # 4825 | REAL PROPERTY XXX |

USDA

USDA Agricultural Research Service

USDA AGRICULTURAL RESEARCH SERVICE
US HORTICULTURAL RESEARCH LABORATORY
REPAIR TORNADO DAMAGE
FT. PIERCE, FL

MECHANICAL SCHEDULES

| PROJECT NO. XXX | AGRICULTURAL RESEARCH SERVICE | SHEET |
|---|---|---|
| DATE 04/27/26 | SOUTHEAST AREA<br>STONEVILLE, MS | M-601<br>85 OF 108 |




1 M602 WEATHER STATION DETAIL
SCALE: NOT TO SCALE




2 M602 CONDENSATE DRAIN P-TRAP DETAIL
SCALE: NOT TO SCALE




3 M602 GAS FIRED UNIT HEATER DETAIL
SCALE: NOT TO SCALE




6 M602 EVAPORITIVE COOLING PAD & PUMP DETAIL
SCALE: NOT TO SCALE




4 M602 ELECTRIC UNIT HEATER DETAIL
SCALE: NOT TO SCALE




5 M602 HAF DETAIL
SCALE: NOT TO SCALE







7 M602 ROOF VENT DETAIL
SCALE: NOT TO SCALE




8 M-602 PIPE HANGER DETAILS
SCALE: N.T.S

9 M-602 WALL FAN MOUNTING DETAIL
SCALE: NOT TO SCALE

SAMUEL MAYRANT ENGLE LICENSE No. 90034 STATE OF FLORIDA PROFESSIONAL ENGINEER 04/27/26

Johnson-McAdams FIRM P.A.
ARCHITECTS/ENGINEERS • PLANNING • SURVEYING • MANAGEMENT

| NO. | DATE | BY | DESCRIPTION |
|---|---|---|---|
| REVISIONS | | | |

USDA Agricultural Research Service

| A-E FIRM | USDA |
|---|---|
| PROJECT MANAGER BP | EPM XXX |
| DESIGNER JH | PPM XXX |
| CHECKED BY JGM | SAFETY & HEALTH XXX |
| JOB # 4825 | REAL PROPERTY XXX |

USDA

USDA AGRICULTURAL RESEARCH SERVICE
US HORTICULTURAL RESEARCH LABORATORY
REPAIR TORNADO DAMAGE
FT. PIERCE, FL

MECHANICAL DETAILS

| PROJECT NO. XXX | AGRICULTURAL RESEARCH SERVICE | SHEET |
|---|---|---|
| DATE 4/27/26 | SOUTHEAST AREA STONEVILLE, MS | M-602 86 OF 108 |

J:\greenwood\2025 Jobs\4825 USDA Tornado Damage Repair Ft. Pierce FL\07 Working Folder\Mech\M-602.dwg Apr 27, 2026 - 10:02am

## GENERAL SYMBOLS LEGEND

*(NOT ALL SYMBOLS MAY APPLY, TYP.)*

| SYMBOL / KEY | DESCRIPTION |
|---|---|
| 99 | KEY NOTE DESIGNATION. |
| 9 | REVISION TAG DESIGNATION. |
| 1 | TOP DESIGNATION IS PLAN / ENLARGED PLAN / DETAIL NUMBER. |
| EP101 | BOTTOM DESIGNATION IS SHEET LOCATION (STANDARD SYMBOL SCALED DOWN FOR LEGEND). |
| | CONDUCTORS IN CONDUIT CONCEALED WITHIN WALL OR CEILING. TIC MARKS INDICATE NUMBER OF CONDUCTORS. THE EQUIPMENT GROUNDING CONDUCTOR IS NOT SHOWN, BUT SHALL BE PROVIDED. SIZE THE EQUIPMENT GROUNDING CONDUCTOR AND THE CONDUIT PER THE NEC. THE ABSENCE OF TIC MARKS SIGNIFIES THAT TWO CONDUCTORS PLUS AN EQUIPMENT GROUNDING CONDUCTOR SHOULD BE PROVIDED. FOR EXAMPLE, THE MARKINGS TO THE LEFT SIGNIFY THAT THREE CONDUCTORS PLUS AN EQUIPMENT GROUNDING CONDUCTOR SHOULD BE PROVIDED. |
| 10 | THE TEXT INSIDE THE ARC INDICATES THE AWG SIZE OF THE CONDUCTORS THAT SHALL BE RUN IN THE CONDUIT. THE ABSENCE OF TEXT SIGNIFIES THAT THE CONDUCTORS SHOULD BE #12 AWG. |
| | CIRCUITRY RUN IN STRAIGHT LINE SEGMENTS SIGNIFIES EXPOSED SURFACE-MOUNTED RACEWAY (SEE SPECIFICATIONS). |
| | CONDUCTORS IN CONDUIT CONCEALED BELOW GRADE OR FLOOR. TIC MARKS INDICATE NUMBER OF CONFUCTORS. THE EQUIPMENT GROUNDING CONDUCTOR IS NOT SHOWN, BUT SHALL BE PROVIDED. SIZE THE EQUIPMENT GROUNDING CONDUCTOR AND THE CONDUIT PER THE NEC. THE ABSENCE OF TIC MARKS SIGNIFIES THAT TWO CONDUCTORS PLUS AN EQUIPMENT GROUNDING CONDUCTOR SHOULD BE PROVIDED. THE MARKINGS TO THE LEFT SIGNIFY THAT THREE CONDUCTORS PLUS AN EQUIPMENT GROUNDING CONDUCTOR SHOULD BE PROVIDED. |
| LA-1 | HOMERUN TO PANELBOARD. ARC DENOTES CONCEALED CIRCUITRY. TEXT DENOTES PANELBOARD NAME WITH CIRCUIT NUMBER. DEVICES HAVING CIRCUIT NUMBERS LOCATED BESIDE THEM MAY NOT SHOW THE CIRCUIT NUMBERS AT THE HOMERUN ARROWS. |
| LA-1 | PARTIAL HOMERUN TO PANELBOARD. COMBINE ALL PARTIAL HOMERUNS THAT ARE ON THE SAME CIRCUIT IN A JUNCTION BOX PRIOR TO ENTERING THE PANELBOARD. |
| | LOW VOLTAGE CONDUCTORS USED FOR MOTION DETECTOR CIRCUITRY. SEE MANUFACTURER'S RECOMMENDATIONS FOR CONDUCTOR REQUIREMENTS. |
| LA1-13 | PANELBOARD AND CIRCUIT DESIGNATION |

## POWER OUTLET AND COMMUNICATIONS LEGEND

| SYMBOL / KEY | DESCRIPTION |
|---|---|
| ? | SINGLE RECEPTACLE, NEMA 5-30R, MOUNTED 18" A.F.F. TO CENTERLINE OF BOX UNLESS NOTED OTHERWISE. |
| ? | DUPLEX RECEPTACLE, NEMA 5-20R, MOUNTED 18" A.F.F. TO CENTERLINE OF BOX UNLESS NOTED OTHERWISE. |
| (42) | ELECTRICAL OR COMMUNICATION DEVICE, MH = AT ELEVATION AFF INDICATED (42" AFF SHOWN) |
| ? | DUPLEX RECEPTACLE, NEMA 5-20R, SUSPENDED FROM CEILING. SEE DETAIL 3/E-002. |
| ? | DUPLEX RECEPTACLE, NEMA 5-20R, MOUNTED WITH BOTTOM OF BOX 2" ABOVE COUNTER BACKSPLASH. WHERE THERE IS NO BACKSPLASH MOUNT 6" ABOVE COUNTER. WHERE RECEPTACLE IS SHOWN IN AN AREA WITH NO COUNTER, MOUNT 45" A.F.F. TO CENTERLINE OF BOX. |
| T | TELEPHONE MOUNTED IN BOX WITH HINGED DOOR |
| | JUNCTION BOX FOR FUTURE TELEPHONE |
| © | CELLULAR AMPLIFIER ANTENNA |
| | TELEPHONE TERMINAL CABINET OR BACKBOARD |

## LIGHTING AND SWITCHING LEGEND

| SYMBOL / KEY | DESCRIPTION | SYMBOL / KEY | DESCRIPTION |
|---|---|---|---|
| | SURFACE MOUNTED OR SUSPENDED FIXTURE. | $ | SINGLE -POLE, SINGLE-THROW SWITCH. |
| | SURFACE MOUNTED OR SUSPENDED EMERGENCY FIXTURE. | $^T | HORSEPOWER RATED SWITCH WITH THERMAL OVERLOADS (MANUAL MOTOR STARTER). |
| MD | PASSIVE INFRARED AND ULTRASONIC DUAL TECHNOLOGY OCCUPANCY SENSOR WITH A 26' RADIAL COVERAGE. SURFACE MOUNTED TO CEILING. | $^2 | DOUBLE POLE. |
| | | $^3 | THREE WAY. |
| PP | POWER PACK SURFACE MOUNTED TO CEILING. | $^{3P} | THREE POLE. |

UPPERCASE INDICATES TYPE OF FIXTURE — A1 c — LOWERCASE INDICATES FIXTURES TO BE CONTROLLED TOGETHER. c $ LOWERCASE INDICATES GROUP OF FIXTURES TO BE CONTROLLED BY SWITCH.

## FIRE ALARM AND ACCESS LEGEND

| SYMBOL / KEY | DESCRIPTION | SYMBOL / KEY | DESCRIPTION |
|---|---|---|---|
| F | MANUAL PULL STATION. MOUNT 48"A.F.F. TO CENTERLINE OF BOX. | M | MOTION DETECTOR TO RELEASE MAGNETIC LOCK. |
| F | STROBE. MOUNT 80" A.F.F. TO BOTTOM OF BOX. | CR | CARD READER. |
| | | PX | PUSH TO EXIT BUTTON. |
| F | COMBINATION HORN & STROBE. MOUNT 80"A.F.F. TO BOTTOM OF BOX. | PB | PUSH BUTTON. |
| | | ML | MAGNETIC LOCK. |
| ACP | ACCESS CONTROL PANEL. | PS | POWER SUPPLY. |

## ONE-LINE DIAGRAM, SCHEDULE, AND DISTRIBUTION LEGEND

| SYMBOL / KEY | DESCRIPTION | SYMBOL / KEY | DESCRIPTION |
|---|---|---|---|
| #### | FEEDER KEY | J | CEILING MOUNTED JUNCTION BOX. |
| | DISCONNECT SWITCH DIST BOARD MTD. | J | WALL MOUNTED JUNCTION BOX. |
| | | ~ | FLEX. CONNECTION TO EQUIPMENT. |
| | CKT BREAK DIST BOARD MTD. | ? | PANELBOARD. |
| | FUSE DIST BOARD MTD. | | MAGNETIC MOTOR STARTER. |
| | FUSED DISC SWITCH 600V & UNDER. | ?/?/? | NON-FUSED DISCONNECT SWITCH. TEXT INDICATES AMPACITY/NUMBER OF POLES/ENCLOSURE TYPE. |
| | GROUND | | |
| | XFMR | ?/?/? F-? | FUSED DISCONNECT SWITCH. TEXT INDICATES AMPACITY/NUMBER OF POLES/ENCLOSURE TYPE; F-(RATING OF FUSES). |
| | EQUIPMENT | | |
| | GENERATOR | | |
| M | METER | # | CONTINUATION, UPSTREAM LABEL |
| SPD | SURGE PROTECTION DEVICE. | C | LOCAL CONTACTOR |
| GFI | GROUND FAULT INTERRUPTER. | PNL | PANELBOARD (ONE-LINE) |
| TC | TIMECLOCK | | |
| PES | PHOTOELECTRIC SWITCH | | TRANSFER SWITCH (ATS : AUTOMATIC) (MTS: MANUAL) |
| J | JUNCTION BOX | | |
| PB | PULL BOX | | MOTOR |
| T | TRANSFORMER (PLAN VIEW) | | AIR TERMINAL |
| GR | 3/4" X 10' COPPER CLAD STEEL GROUND ROD DRIVEN W/ TOP ATLEAST 18" BELOW GRADE. | | |

## VOLTAGE DROP CHART FOR 20A, 1Ø CIRCUITS

| VOLTAGE | CIRCUIT LENGTH | CONDUCTOR SIZE (AWG) |
|---|---|---|
| 120 | <50' | #12 |
| 120 | >50' | #10 |
| 120 | >90' | #8 |
| 120 | >140' | #6 |
| 277 | <130' | #12 |
| 277 | >130' | #10 |
| 277 | >200' | #8 |
| 277 | >330' | #6 |

VOLTAGE DROP CHART NOTES:

1) CIRCUIT SIZES INDICATED ON THE DRAWINGS ARE MINIMUM REQUIREMENTS. REFER TO THIS CHART FOR UPSIZING CONDUCTORS AS NEEDED.

2) DO NOT CONNECT CONDUCTORS LARGER THAN #10 DIRECTLY TO A RECEPTACLE OR A SWITCH. PROVIDE A JUNCTION BOX TO DOWNSIZE THE CONDUCTOR TO #12 AT THE DEVICE.

3) FOR CIRCUITS LONGER THAN THOSE LISTED ABOVE, CONSULT WITH THE ENGINEER FOR CONDUCTOR SIZES.

## MASTER NOTES - ELECTRICAL:

1. THE CONTRACTOR MUST ABIDE BY ALL FEDERAL, STATE, AND/OR LOCAL CODES. IF A DISCREPANCY BETWEEN CODES OCCURS, THE MOST STRINGENT SHALL PREVAIL.
2. THE CONTRACTOR MUST FIELD VERIFY EXISTING CONDITIONS PRIOR TO THE COMMENCEMENT OF ANY WORK. SHOULD DISCREPANCIES BE DISCOVERED, THE CONTRACTOR MUST VERIFY INTENT WITH THE ENGINEER/CONTRACTING OFFICER BEFORE PROCEEDING.
3. COORDINATE LOCATIONS OF ALL CEILING MOUNTED DEVICES WITH OTHER TRADES PRIOR TO INSTALLATION.
4. COORDINATE ALL ROUGH-IN REQUIREMENTS FOR GOVERNMENT FURNISHED EQUIPMENT WITH THE OWNER PRIOR TO BEGINNING WORK. THESE DRAWINGS ARE BASED ON EXISTING BUILDING CONSTRUCTION DRAWINGS, SITE SURVEYS, AND OWNER FURNISHED EQUIPMENT SPECIFICATIONS.
5. RECEPTACLES MUST NOT BE CONNECTED IN A FEED-THRU MANNER. WIRE CONNECTIONS IN RECEPTACLE BOXES MUST BE MADE IN A PIGTAIL MANNER AS SHOWN IN DETAIL 1/E-001.
6. REFER TO ARCHITECTURAL DETAIL 1/G-103 FOR INFORMATION REGARDING AREAS OF WORK FOR EACH BID OPTION AND PHASING.

## BID OPTION NOTES:

1. THE CONTRACTOR SHALL PROVIDE SEPARATE PRICING, INCLUDING ALL DEMOLITION AND NEW WORK, BASED ON THE AREAS SHOWN ON THE BID OPTION KEY PLAN. NO WORK SHALL BE EXCLUDED BASED ON AREA BOUNDARIES; THE CONTRACTOR IS RESPONSIBLE FOR COORDINATING ALL SCOPE NECESSARY TO DELIVER A COMPLETE AND FUNCTIONAL RESULT FOR EACH BID OPTION.

## GENERAL NOTES:

1. DEVICES NOTED AS 'GFI' SHALL BE GROUND FAULT CIRCUIT INTERRUPTING DEVICES.
2. DEVICES NOTED AS 'WP' SHALL BE WEATHERPROOF WHILE-IN-USE.
3. PROVIDE UNSWITCHED POWER TO THE EMERGENCY BATTERY PACKS.
4. 'W/E' DENOTES PROVIDED WITH EQUIPMENT.
5. MINIMUM RACEWAY SIZE SHALL BE 3/4". INCREASE RACEWAY SIZE AS REQUIRED TO LIMIT RACEWAY FILL RATIO TO LESS THAN 40% FULL.
6. THE ELECTRICAL CONTRACTOR SHALL CAREFULLY COORDINATE WORK WITH OTHER TRADES THROUGH THE GENERAL CONTRACTOR AND SHALL BE RESPONSIBLE FOR SECURING SPACE REQUIREMENTS FOR ELECTRICAL EQUIPMENT AND CORRECT ROUGH-IN LOCATIONS OF ELECTRICAL CONNECTIONS.
7. VERIFY DOOR SWINGS WITH ARCHITECTURAL DRAWINGS BEFORE ROUGHING IN WALL SWITCHES. SWITCHES IN THE SAME LOCATION SHALL BE GANGED TOGETHER IN ONE COMMON BACKBOX AND SHALL HAVE ONE COMMON FACE PLATE.
8. ALL FEEDERS AND BRANCH CIRCUITS SHALL INCLUDE A GREEN INSULATED GROUND CONDUCTOR, SIZED PER THE NATIONAL ELECTRICAL CODE, OR AS SHOWN, CONNECTED TO EACH DEVICE AND OUTLET BOX ON THE CIRCUIT AND TO THE PANELBOARD GROUND BUS. PROVIDE A DEDICATED NEUTRAL CONDUCTOR FOR EACH BRANCH CIRCUIT. MULTIPLE BRANCH CIRCUITS IN ONE RACEWAY REQUIRE ONLY ONE GROUND CONDUCTOR.
9. VERIFY LUMINAIRE, CEILING MOUNTED OCCUPANCY SENSOR LOCATIONS WITH ARCHITECTURAL REFLECTED CEILING PLANS FOR EXACT LOCATIONS AND DIMENSIONS PRIOR TO INSTALLATION. VERIFY EXACT LOCATIONS OF MOTORS AND EQUIPMENT BEFORE ROUGHING-IN.
10. "PROVIDE" IS AN INCLUSIVE TERM USED TO DESCRIBE ASPECTS OF THE WORK TO BE ACCOMPLISHED, AND IS HEREBY DEFINED TO REQUIRE TO STORE, FURNISH, INSTALL, MOUNT, CONNECT, CONTROL AND POWER EQUIPMENT INDICATED, AS WELL AS ALL APPURTENANCES REQUIRED TO MAKE ELECTRICAL SYSTEMS OPERATE AS INDICATED WITHIN THESE DRAWINGS AND SPECIFICATIONS AND TO FULFILL THE SCOPE OF WORK.
11. ALL CONDUCTORS SHALL BE COPPER
12. CONTRACTOR SHALL FIELD VERIFY ALL EXISTING CONDITIONS, DIMENSIONS AND ELEVATIONS BEFORE PROCUREMENT OF ANY MATERIALS AND DEVELOPMENT OF ANY SHOP DRAWINGS OR SUBMITTALS.
13. PROVIDE LABELS ON ALL RECEPTACLES, WALL MOUNTED LIGHT SWITCHES/OCCUPANCY SENSORS AND JUNCTION BOXES INDICATING THE SOURCE PANEL & CIRCUIT(S). TEXT SHALL BE BLACK, 1/4". LABELS ABOVE FINISHED CEILING CAN BE HANDWRITTEN WITH AN INDELIBLE MARKER.
14. CIRCUIT SIZES INDICATED ON THE DRAWINGS ARE MINIMUM REQUIREMENTS.
15. DO NOT CONNECT CONDUCTORS LARGER THAN #10 DIRECTLY TO A RECEPTACLE OR A SWITCH. PROVIDE A JUNCTION BOX TO DOWNSIZE THE CONDUCTOR TO #12 AT THE DEVICE.
16. FOR INSTALLATION OF LIGHTING SWITCHES, MOUNT CENTERLINE OF BOX AT 46" A.F.F., UNLESS OTHERWISE INDICATED.




1 E-001 RECEPTACLE DETAIL

SCALE: NONE

## RECEPTACLE DETAIL NOTES:

A. THESE DRAWINGS ARE BASED ON THE BEST INFORMATION AVAILABLE AT THE TIME OF DESIGN. COORDINATE WITH THE MILLWORK CONTRACTOR TO DETERMINE THE EXACT LOCATION OF OUTLETS BEING PLACED IN AND AROUND MILLWORK.

B. RECEPTACLES SHOWN AS GFI MAY BE NON GFI TYPE RECEPTACLES IF FED FROM A 20/1 GFI BREAKER OR THE LOAD SIDE OF A GFI RECEPTACLE IN THE SAME ROOM, ON THE SAME CIRCUIT AND RATED 20 AMP FEED-THRU CAPACITY. COVER PLATES SHALL BE CLEARLY MARKED GFI.

C. NON GFI RECEPTACLES SHALL NOT BE CONNECTED IN A FEED-THRU MANNER. WIRE CONNECTIONS IN RECEPTACLE BOXES SHALL BE MADE IN A PIGTAIL MANNER AS SHOWN IN RECEPTACLE DETAIL.

BRADEN T. DUKE PROFESSIONAL ENGINEER 35781 STATE OF MISSISSIPPI 04/27/26

THE Johnson McAdams FIRM P.A.
ARCHITECTS/ENGINEERS PLANNING SURVEYING MANAGEMENT
P.O. BOX 513, GREENWOOD, MISSISSIPPI - (662) 455-4943

| NO. | DATE | BY | DESCRIPTION |
|---|---|---|---|

REVISIONS

| A-E FIRM | USDA |
|---|---|
| PROJECT MANAGER BP | EPM XXX |
| DESIGNER EH | PPM XXX |
| CHECKED BY BTD | SAFETY & HEALTH XXX |
| JOB # 4825 | REAL PROPERTY XXX |

USDA

USDA Agricultural Research Service

USDA AGRICULTURAL RESEARCH SERVICE
US HORTICULTURAL RESEARCH LABORATORY
REPAIR TORNADO DAMAGE
FT. PIERCE, FL

ELECTRICAL LEGEND

PROJECT NO. XXX
DATE 04/27/2026

AGRICULTURAL RESEARCH SERVICE
FT. PIERCE, FL

SHEET E-001



J:\greenwood\2025 Jobs\4825 USDA Tornado Damage Repair Ft. Pierce FL\07 Working Folder\Elec\CAD\E-001.dwg
Apr 27, 2026 - 9:53am

NOTE: CONTROL CIRCUITS MAY BE COMBINED INTO ONE CONDUIT. CONTROL CIRCUITRY CONDUIT MUST HAVE LESS THAN 40% FILL RATIO PER THE NATIONAL ELECTRICAL CODE.




NOTE: THE GREENHOUSE ENVIRONMENTAL CONTROL SYSTEM (MICROGROW OR APPROVED EQUAL) FURNISHED BY THE MECHANICAL CONTRACTOR AND INSTALLED BY THE ELECTRICAL CONTRACTOR SHALL BE PROGRAMMED AND COMMISSIONED AS A COMPLETE AND FULLY OPERATIONAL SYSTEM. THE CONTRACTOR SHALL COORDINATE DIRECTLY WITH THE GREENHOUSE CONTROL SYSTEM MANUFACTURER AND/OR AUTHORIZED REPRESENTATIVE TO VERIFY ALL EQUIPMENT REQUIREMENTS, WIRING METHODS, NETWORK ARCHITECTURE, ANNUNCIATION, AND REMOTE MONITORING FEATURES.

## 1 E-002 GREENHOUSE CONTROLLER, ANNUNCIATOR, AND REMOTE VIEWING DETAIL

SCALE: NONE

## RECEPTACLE DROP NOTES:

A. THE COMPLETE RECEPTACLE DROP INSTALLATION SHALL BE COMPRISED OF COMPONENTS UL LISTED FOR THE INTENDED PURPOSE.




## 3 E-002 CEILING MOUNTED SUSPENDED RECEPTACLE DETAIL

SCALE: NONE




## 4 E-002 DOUBLE GREENHOUSE PANEL DETAIL

SCALE: NONE




## 5 E-002 SINGLE GREENHOUSE PANEL DETAIL

SCALE: NONE




NOTE: JUNCTION, PULL AND OUTLET BOXES SHALL BE 4" x 4" x 2-1/8" OR LARGER.

NOTE: ALL CONDUIT SHALL BE UV-RESISTANT SCH. 80 PVC. ALL JUNCTION BOXES SHALL BE WATERTIGHT POLYCARBONATE BOXES WITH WEATHERPROOF GASKET AND FITTINGS.

CONDUIT INSTALLAITION SHALL COMPLY WITH THE REQUIREMENTS LISTED IN ARTICLE 352 OF THE NATIONAL ELECTRICAL CODE.

## 2 E-002 JUNCTION AND OUTLET BOX DETAIL

SCALE: NONE




NOTES:
COORDINATE ACCESS CONTROL REQUIREMENTS WITH USDA MAINTENANCE PERSONNEL PRIOR TO INSTALLATION. UTILIZE 20/1 CIRCUIT BREAKER LOCATED IN PANEL '1GE'.

THE CONTRACTOR SHALL REMOVE THE EXISTING ACCESS CONTROL SYSTEM AT GREENHOUSE 101 AND 102 IN ITS ENTIREETY AND PROVIDE A COMPLETE NEW ACCESS CONTROL SYSTEM FOR GREENHOUSE 101 AND 102. THE SYSTEM SHALL INCLUDE, BUT IS NOT LIMITED TO CARD READERS, ELECTROMAGNETIC LOCKS, DOOR POSITION SWITCHES, REQUEST-TO-EXIT DEVICES, POWER SUPPLIES, CONTROL MODULES, ASSOCIATED WIRING, AND ALL REQUIRED ACCESSORIES.

## 6 E-002 MAG-LOCK ACCESS CONTROL DETAIL

SCALE: NONE

| NO. | DATE | BY | DESCRIPTION |
|---|---|---|---|
| | | | |
| | | | |
| | | | |

REVISIONS

Johnson, McAdams Firm, P.A. ARCHITECTS/ENGINEERS PLANNING SURVEYING MANAGEMENT

| A-E FIRM | USDA |
|---|---|
| PROJECT MANAGER BP | EPM XXX |
| DESIGNER EH | PPM XXX |
| CHECKED BY BTD | SAFETY & HEALTH XXX |
| JOB # 4825 | REAL PROPERTY XXX |

USDA

USDA Agricultural Research Service

USDA AGRICULTURAL RESEARCH SERVICE
US HORTICULTURAL RESEARCH LABORATORY
REPAIR TORNADO DAMAGE
FT. PIERCE, FL

ELECTRICAL DETAILS

PROJECT NO. XXX
DATE 04/27/2026
AGRICULTURAL RESEARCH SERVICE
FT. PIERCE, FL
SHEET E-002
88 OF 108

04/27/26

J:\greenwood\2025 Jobs\4825 USDA Tornado Damage Repair Ft. Pierce FL\07 Working Folder\Elec\CAD\E-002.dwg
Apr 27, 2026 - 9:53am


1 SINGLE LINE DIAGRAM
E601 SCALE: NO SCALE

## LEGEND

AFC: xxxxxA — CALCULATED AVAILABLE FAULT CURRENT
- (ALL SWITCHBOARDS, SWITCHGEAR, AND PANELBOARDS SHALL HAVE THE AVAILABLE FAULT CURRENT AND THE DATE THE CALCULATION WAS PERFORMED FIELD MARKED ON THE ENCLOSURE PER NEC ARTICLES 408.6 AND 110.21(B)(3).) THE CALCULATIONS SHALL BE UPDATED BY THE ELECTRICAL ENGINEER ONCE ALL CIRCUITRY IS INSTALLED AND CIRCUITRY LENGTHS DOCUMENTED ON THE "AS-BUILT" DRAWINGS. CALCULATIONS SHOWN ARE BASED ON THE ASSUMPTIONS LISTED.

VD: X.XX% — VOLTAGE DROP
- THE VOLTAGE DROP IS CALCULATED BASED ON THE ASSUMPTIONS LISTED.

## (X) KEYED NOTES

1. EXISTING CONDUIT AND CIRCUITRY TO REMAIN AND BE UTILIZED TO FEED NEW INSTALLATION.
2. EXTEND CIRCUITRY TO NEW PANEL AS REQUIRED. UTILIZE INSULATED POLARIS LUGS OR EQUAL (TYPICAL OF ALL PANELS). SPLICE MUST OCCUR IN ACCESSIBLE LOCATION. PROVIDE NEMA 4X BOX BELOW PANEL WHERE SPLICE IS REQUIRED. SEE FEEDER SCHEDULE FOR WIRE SIZE

## FEEDER SCHEDULE

| ID | FEEDER AMPS | FEEDER |
|---|---|---|
| 60 | 60 | 4#4, #8(G) |
| 90 | 90 | 4#2, #8(G) |
| 125 | 125 | 4#1/0, #6(G) |

| NO. | DATE | BY | DESCRIPTION |
|---|---|---|---|
| | | | |

REVISIONS

Johnson, Mirmiran & Adams
ARCHITECTS/ENGINEERS PLANNING SURVEYING MANAGEMENT

| A-E FIRM | USDA |
|---|---|
| PROJECT MANAGER BP | EPM XXX |
| DESIGNER EH | PPM XXX |
| CHECKED BY BTD | SAFETY & HEALTH XXX |
| JOB # 4825 | REAL PROPERTY XXX |

USDA Agricultural Research Service

USDA AGRICULTURAL RESEARCH SERVICE
US HORTICULTURAL RESEARCH LABORATORY
REPAIR TORNADO DAMAGE
FT. PIERCE, FL

SINGLE LINE DIAGRAM

PROJECT NO. XXX
DATE 04/27/2026
AGRICULTURAL RESEARCH SERVICE
FT. PIERCE, FL
SHEET E-601
89 OF 108

J:\greenwood\2025 Jobs\4825 USDA Tornado Damage Repair Ft. Pierce FL\07 Working Folder\Elec\CAD\E-601.dwg
Apr 27, 2026 – 9:53am

## PANEL 1GA

LOCATION: **GREENHOUSE CORRIDOR** — LUG LOCATION: **BOTTOM FEED**
VOLT: **208Y/120V, 3Ø, 4W** — MAIN BUS: **60A MAIN BREAKER** — **NEMA 3R ENCLOSURE**
BUS: **100A** — MOUNTING: **SURFACE** — PANELBOARD SCCR RATING (A): **10,000**

| CIRCUIT NO. | BREAKER AMPS | BREAKER POLES | DESCRIPTION | PHASE LOAD (KVA) A | | B | | C | | DESCRIPTION | BREAKER AMPS | BREAKER POLES | CIRCUIT NO. |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 20 | 1 | LIGHTING | 0.3 | 0.3 | | | | | GREENHOUSE 110 EF-1 | 15 | 3 | 2 |
| 3 | 20 | 1 | GREENHOUSE 110 CONTROL PANEL | | | 0.5 | 0.3 | | | - | - | - | 4 |
| 5 | 20 | 1 | SPARE | | | | | 0.5 | 0.3 | - | - | - | 6 |
| 7 | 20 | 1 | GREENHOUSE 110 RECS. | 0.5 | 0.3 | | | | | GREENHOUSE 110 EF-1 | 15 | 3 | 8 |
| 9 | 20 | 1 | GREENHOUSE 110 RECS. | | | 0.5 | 0.3 | | | - | - | - | 10 |
| 11 | 20 | 1 | GREENHOUSE 110 RECS. | | | | | 0.7 | 0.3 | - | - | - | 12 |
| 13 | 20 | 1 | GREENHOUSE 110 OVERHEAD RECS. | 0.5 | 0.3 | | | | | GREENHOUSE 110 EF-1 | 15 | 3 | 14 |
| 15 | 20 | 1 | GREENHOUSE 110 OVERHEAD RECS. | | | 0.5 | 0.3 | | | - | - | - | 16 |
| 17 | 20 | 1 | GREENHOUSE 110 OVERHEAD RECS. | | | | | 0.5 | 0.3 | - | - | - | 18 |
| 19 | 20 | 1 | GREENHOUSE 110 OVERHEAD RECS. | 0.5 | 0.2 | | | | | GREENHOUSE 110 UH-1 | 20 | 1 | 20 |
| 21 | 20 | 1 | GREENHOUSE 110 OVERHEAD RECS. | | | 0.4 | 0.2 | | | GREENHOUSE 110 UH-1 | 20 | 1 | 22 |
| 23 | 20 | 1 | GREENHOUSE 110 OVERHEAD RECS. | | | | | 0.4 | 0.5 | GREENHOUSE 110 HF | 20 | 1 | 24 |
| 25 | 20 | 1 | GREENHOUSE 110 ECP SUMP PUMP | 0.5 | 0.5 | | | | | GREENHOUSE 110 HF | 20 | 1 | 26 |
| 27 | 20 | 1 | GREENHOUSE 110 ROOF VENT | | | 0.2 | 0.0 | | | SPARE | 30 | 1 | 28 |
| 29 | 20 | 1 | GREENHOUSE 110 SIDE VENT | | | | | 0.2 | 0.0 | SPARE | 20 | 1 | 30 |
| 31 | 20 | 1 | SPARE | 0.0 | 0.0 | | | | | SPARE | 20 | 1 | 32 |
| 33 | 20 | 1 | SPARE | | | 0.0 | 0.0 | | | SPARE | 20 | 1 | 34 |
| 35 | 20 | 1 | SPARE | | | | | 0.0 | 0.0 | SPARE | 20 | 1 | 36 |
| 37 | 20 | 1 | SPARE | 0.0 | 0.0 | | | | | SPARE | 20 | 1 | 38 |
| 39 | 20 | 1 | SPARE | | | 0.0 | 0.0 | | | SPARE | 20 | 1 | 40 |
| 41 | 20 | 1 | SPARE | | | | | 0.0 | 0.0 | SPARE | 20 | 1 | 42 |
| TOTAL | | | | 4.0 | | 3.2 | | 3.7 | | * GFCI BREAKER | | | |

## PANEL 1GC

LOCATION: **GREENHOUSE CORRIDOR** — LUG LOCATION: **BOTTOM FEED**
VOLT: **208Y/120V, 3Ø, 4W** — MAIN BUS: **60A MAIN BREAKER** — **NEMA 3R ENCLOSURE**
BUS: **100A** — MOUNTING: **SURFACE** — PANELBOARD SCCR RATING (A): **10,000**

| CIRCUIT NO. | BREAKER AMPS | BREAKER POLES | DESCRIPTION | PHASE LOAD (KVA) A | | B | | C | | DESCRIPTION | BREAKER AMPS | BREAKER POLES | CIRCUIT NO. |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 20 | 1 | LIGHTING | 0.3 | 0.3 | | | | | GREENHOUSE 116 EF-1 | 15 | 3 | 2 |
| 3 | 20 | 1 | GREENHOUSE 116 CONTROL PANEL | | | 0.5 | 0.3 | | | - | - | - | 4 |
| 5 | 20 | 1 | SPARE | | | | | 0.5 | 0.3 | - | - | - | 6 |
| 7 | 20 | 1 | GREENHOUSE 116 RECS. | 0.5 | 0.3 | | | | | GREENHOUSE 116 EF-1 | 15 | 3 | 8 |
| 9 | 20 | 1 | GREENHOUSE 116 RECS. | | | 0.5 | 0.3 | | | - | - | - | 10 |
| 11 | 20 | 1 | GREENHOUSE 116 RECS. | | | | | 0.7 | 0.3 | - | - | - | 12 |
| 13 | 20 | 1 | GREENHOUSE 116 OVERHEAD RECS. | 0.5 | 0.3 | | | | | GREENHOUSE 116 EF-1 | 15 | 3 | 14 |
| 15 | 20 | 1 | GREENHOUSE 116 OVERHEAD RECS. | | | 0.5 | 0.3 | | | - | - | - | 16 |
| 17 | 20 | 1 | GREENHOUSE 116 OVERHEAD RECS. | | | | | 0.5 | 0.3 | - | - | - | 18 |
| 19 | 20 | 1 | GREENHOUSE 116 OVERHEAD RECS. | 0.5 | 0.2 | | | | | GREENHOUSE 116 UH-1 | 20 | 1 | 20 |
| 21 | 20 | 1 | GREENHOUSE 116 OVERHEAD RECS. | | | 0.4 | 0.2 | | | GREENHOUSE 116 UH-1 | 20 | 1 | 22 |
| 23 | 20 | 1 | GREENHOUSE 116 OVERHEAD RECS. | | | | | 0.4 | 0.5 | GREENHOUSE 116 HF | 20 | 1 | 24 |
| 25 | 20 | 1 | GREENHOUSE 116 ECP SUMP PUMP | 0.5 | 0.5 | | | | | GREENHOUSE 116 HF | 20 | 1 | 26 |
| 27 | 20 | 1 | GREENHOUSE 116 ROOF VENT | | | 0.2 | 0.0 | | | SPARE | 30 | 1 | 28 |
| 29 | 20 | 1 | GREENHOUSE 116 SIDE VENT | | | | | 0.2 | 0.0 | SPARE | 20 | 1 | 30 |
| 31 | 20 | 1 | SPARE | 0.0 | 0.0 | | | | | SPARE | 20 | 1 | 32 |
| 33 | 20 | 1 | SPARE | | | 0.0 | 0.0 | | | SPARE | 20 | 1 | 34 |
| 35 | 20 | 1 | SPARE | | | | | 0.0 | 0.0 | SPARE | 20 | 1 | 36 |
| 37 | 20 | 1 | SPARE | 0.0 | 0.0 | | | | | SPARE | 20 | 1 | 38 |
| 39 | 20 | 1 | SPARE | | | 0.0 | 0.0 | | | SPARE | 20 | 1 | 40 |
| 41 | 20 | 1 | SPARE | | | | | 0.0 | 0.0 | SPARE | 20 | 1 | 42 |
| TOTAL | | | | 4.0 | | 3.2 | | 3.7 | | * GFCI BREAKER | | | |

## PANEL 1GE

LOCATION: **GREENHOUSE CORRIDOR** — LUG LOCATION: **BOTTOM FEED**
VOLT: **208Y/120V, 3Ø, 4W** — MAIN BUS: **60A MAIN BREAKER** — **NEMA 3R ENCLOSURE**
BUS: **100A** — MOUNTING: **SURFACE** — PANELBOARD SCCR RATING (A): **10,000**

| CIRCUIT NO. | BREAKER AMPS | BREAKER POLES | DESCRIPTION | PHASE LOAD (KVA) A | | B | | C | | DESCRIPTION | BREAKER AMPS | BREAKER POLES | CIRCUIT NO. |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 20 | 1 | LIGHTING | 0.3 | 0.3 | | | | | GREENHOUSE 122 EF-1 | 15 | 3 | 2 |
| 3 | 20 | 1 | GREENHOUSE 122 CONTROL PANEL | | | 0.5 | 0.3 | | | - | - | - | 4 |
| 5 | 20 | 1 | SPARE | | | | | 0.5 | 0.3 | - | - | - | 6 |
| 7 | 20 | 1 | GREENHOUSE 122 RECS. | 0.5 | 0.3 | | | | | GREENHOUSE 122 EF-1 | 15 | 3 | 8 |
| 9 | 20 | 1 | GREENHOUSE 122 RECS. | | | 0.5 | 0.3 | | | - | - | - | 10 |
| 11 | 20 | 1 | GREENHOUSE 122 RECS. | | | | | 0.7 | 0.3 | - | - | - | 12 |
| 13 | 20 | 1 | GREENHOUSE 122 OVERHEAD RECS. | 0.5 | 0.3 | | | | | GREENHOUSE 122 EF-1 | 15 | 3 | 14 |
| 15 | 20 | 1 | GREENHOUSE 122 OVERHEAD RECS. | | | 0.5 | 0.3 | | | - | - | - | 16 |
| 17 | 20 | 1 | GREENHOUSE 122 OVERHEAD RECS. | | | | | 0.5 | 0.3 | - | - | - | 18 |
| 19 | 20 | 1 | GREENHOUSE 122 OVERHEAD RECS. | 0.5 | 0.2 | | | | | GREENHOUSE 122 UH-1 | 20 | 1 | 20 |
| 21 | 20 | 1 | GREENHOUSE 122 OVERHEAD RECS. | | | 0.4 | 0.2 | | | GREENHOUSE 122 UH-1 | 20 | 1 | 22 |
| 23 | 20 | 1 | GREENHOUSE 122 OVERHEAD RECS. | | | | | 0.4 | 0.5 | GREENHOUSE 122 HF | 20 | 1 | 24 |
| 25 | 20 | 1 | GREENHOUSE 122 ECP SUMP PUMP | 0.5 | 0.5 | | | | | GREENHOUSE 122 HF | 20 | 1 | 26 |
| 27 | 20 | 1 | GREENHOUSE 122 ROOF VENT | | | 0.2 | 1.5 | | | DAC-1 | 30 | 1 | 28 |
| 29 | 20 | 1 | GREENHOUSE 122 SIDE VENT | | | | | 0.2 | 0.2 | FOYER ENTRANCE UH-1 | 20 | 1 | 30 |
| 31 | 20 | 1 | SPARE | 0.0 | 0.2 | | | | | WALKWAY UH-1 | 20 | 1 | 32 |
| 33 | 20 | 1 | SPARE | | | 0.0 | 0.0 | | | SPARE | 20 | 1 | 34 |
| 35 | 20 | 1 | SPARE | | | | | 0.0 | 0.0 | SPARE | 20 | 1 | 36 |
| 37 | 20 | 1 | SPARE | 0.0 | 0.0 | | | | | SPARE | 20 | 1 | 38 |
| 39 | 20 | 1 | SPARE | | | 0.0 | 0.0 | | | SPARE | 20 | 1 | 40 |
| 41 | 20 | 1 | HALLWAY LIGHTING | | | | | 0.2 | 0.0 | SPARE | 20 | 1 | 42 |
| TOTAL | | | | 4.1 | | 4.7 | | 4.1 | | * GFCI BREAKER | | | |

## PANEL 1GG

LOCATION: **GREENHOUSE CORRIDOR** — LUG LOCATION: **BOTTOM FEED**
VOLT: **208Y/120V, 3Ø, 4W** — MAIN BUS: **60A MAIN BREAKER** — **NEMA 3R ENCLOSURE**
BUS: **100A** — MOUNTING: **SURFACE** — PANELBOARD SCCR RATING (A): **10,000**

| CIRCUIT NO. | BREAKER AMPS | BREAKER POLES | DESCRIPTION | PHASE LOAD (KVA) A | | B | | C | | DESCRIPTION | BREAKER AMPS | BREAKER POLES | CIRCUIT NO. |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 20 | 1 | LIGHTING | 0.3 | 0.3 | | | | | GREENHOUSE 109 EF-1 | 15 | 3 | 2 |
| 3 | 20 | 1 | GREENHOUSE 109 CONTROL PANEL | | | 0.5 | 0.3 | | | - | - | - | 4 |
| 5 | 20 | 1 | SPARE | | | | | 0.5 | 0.3 | - | - | - | 6 |
| 7 | 20 | 1 | GREENHOUSE 109 RECS. | 0.5 | 0.3 | | | | | GREENHOUSE 109 EF-1 | 15 | 3 | 8 |
| 9 | 20 | 1 | GREENHOUSE 109 RECS. | | | 0.5 | 0.3 | | | - | - | - | 10 |
| 11 | 20 | 1 | GREENHOUSE 109 RECS. | | | | | 0.7 | 0.3 | - | - | - | 12 |
| 13 | 20 | 1 | GREENHOUSE 109 OVERHEAD RECS. | 0.5 | 0.3 | | | | | GREENHOUSE 109 EF-1 | 15 | 3 | 14 |
| 15 | 20 | 1 | GREENHOUSE 109 OVERHEAD RECS. | | | 0.5 | 0.3 | | | - | - | - | 16 |
| 17 | 20 | 1 | GREENHOUSE 109 OVERHEAD RECS. | | | | | 0.5 | 0.3 | - | - | - | 18 |
| 19 | 20 | 1 | GREENHOUSE 109 OVERHEAD RECS. | 0.5 | 0.2 | | | | | GREENHOUSE 109 UH-1 | 20 | 1 | 20 |
| 21 | 20 | 1 | GREENHOUSE 109 OVERHEAD RECS. | | | 0.4 | 0.2 | | | GREENHOUSE 109 UH-1 | 20 | 1 | 22 |
| 23 | 20 | 1 | GREENHOUSE 109 OVERHEAD RECS. | | | | | 0.4 | 0.5 | GREENHOUSE 109 HF | 20 | 1 | 24 |
| 25 | 20 | 1 | GREENHOUSE 109 ECP SUMP PUMP | 0.5 | 0.5 | | | | | GREENHOUSE 109 HF | 20 | 1 | 26 |
| 27 | 20 | 1 | GREENHOUSE 109 ROOF VENT | | | 0.2 | 0.0 | | | SPARE | 30 | 1 | 28 |
| 29 | 20 | 1 | GREENHOUSE 109 SIDE VENT | | | | | 0.2 | 0.0 | SPARE | 20 | 1 | 30 |
| 31 | 20 | 1 | SPARE | 0.0 | 0.0 | | | | | SPARE | 20 | 1 | 32 |
| 33 | 20 | 1 | SPARE | | | 0.0 | 0.0 | | | SPARE | 20 | 1 | 34 |
| 35 | 20 | 1 | SPARE | | | | | 0.0 | 0.0 | SPARE | 20 | 1 | 36 |
| 37 | 20 | 1 | SPARE | 0.0 | 0.0 | | | | | SPARE | 20 | 1 | 38 |
| 39 | 20 | 1 | SPARE | | | 0.0 | 0.0 | | | SPARE | 20 | 1 | 40 |
| 41 | 20 | 1 | SPARE | | | | | 0.0 | 0.0 | SPARE | 20 | 1 | 42 |
| TOTAL | | | | 4.0 | | 3.2 | | 3.7 | | * GFCI BREAKER | | | |

## PANEL 1GJ

LOCATION: **GREENHOUSE CORRIDOR** — LUG LOCATION: **BOTTOM FEED**
VOLT: **208Y/120V, 3Ø, 4W** — MAIN BUS: **60A MAIN BREAKER** — **NEMA 3R ENCLOSURE**
BUS: **100A** — MOUNTING: **SURFACE** — PANELBOARD SCCR RATING (A): **10,000**

| CIRCUIT NO. | BREAKER AMPS | BREAKER POLES | DESCRIPTION | PHASE LOAD (KVA) A | | B | | C | | DESCRIPTION | BREAKER AMPS | BREAKER POLES | CIRCUIT NO. |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 20 | 1 | LIGHTING | 0.3 | 0.3 | | | | | GREENHOUSE 115 EF-1 | 15 | 3 | 2 |
| 3 | 20 | 1 | GREENHOUSE 115 CONTROL PANEL | | | 0.5 | 0.3 | | | - | - | - | 4 |
| 5 | 20 | 1 | SPARE | | | | | 0.5 | 0.3 | - | - | - | 6 |
| 7 | 20 | 1 | GREENHOUSE 115 RECS. | 0.5 | 0.3 | | | | | GREENHOUSE 115 EF-1 | 15 | 3 | 8 |
| 9 | 20 | 1 | GREENHOUSE 115 RECS. | | | 0.5 | 0.3 | | | - | - | - | 10 |
| 11 | 20 | 1 | GREENHOUSE 115 RECS. | | | | | 0.7 | 0.3 | - | - | - | 12 |
| 13 | 20 | 1 | GREENHOUSE 115 OVERHEAD RECS. | 0.5 | 0.3 | | | | | GREENHOUSE 115 EF-1 | 15 | 3 | 14 |
| 15 | 20 | 1 | GREENHOUSE 115 OVERHEAD RECS. | | | 0.5 | 0.3 | | | - | - | - | 16 |
| 17 | 20 | 1 | GREENHOUSE 115 OVERHEAD RECS. | | | | | 0.5 | 0.3 | - | - | - | 18 |
| 19 | 20 | 1 | GREENHOUSE 115 OVERHEAD RECS. | 0.5 | 0.2 | | | | | GREENHOUSE 115 UH-1 | 20 | 1 | 20 |
| 21 | 20 | 1 | GREENHOUSE 115 OVERHEAD RECS. | | | 0.4 | 0.2 | | | GREENHOUSE 115 UH-1 | 20 | 1 | 22 |
| 23 | 20 | 1 | GREENHOUSE 115 OVERHEAD RECS. | | | | | 0.4 | 0.5 | GREENHOUSE 115 HF | 20 | 1 | 24 |
| 25 | 20 | 1 | GREENHOUSE 115 ECP SUMP PUMP | 0.5 | 0.5 | | | | | GREENHOUSE 115 HF | 20 | 1 | 26 |
| 27 | 20 | 1 | GREENHOUSE 115 ROOF VENT | | | 0.2 | 0.0 | | | SPARE | 30 | 1 | 28 |
| 29 | 20 | 1 | GREENHOUSE 115 SIDE VENT | | | | | 0.2 | 0.0 | SPARE | 20 | 1 | 30 |
| 31 | 20 | 1 | SPARE | 0.0 | 0.0 | | | | | SPARE | 20 | 1 | 32 |
| 33 | 20 | 1 | SPARE | | | 0.0 | 0.0 | | | SPARE | 20 | 1 | 34 |
| 35 | 20 | 1 | SPARE | | | | | 0.0 | 0.0 | SPARE | 20 | 1 | 36 |
| 37 | 20 | 1 | SPARE | 0.0 | 0.0 | | | | | SPARE | 20 | 1 | 38 |
| 39 | 20 | 1 | SPARE | | | 0.0 | 0.0 | | | SPARE | 20 | 1 | 40 |
| 41 | 20 | 1 | SPARE | | | | | 0.0 | 0.0 | SPARE | 20 | 1 | 42 |
| TOTAL | | | | 4.0 | | 3.2 | | 3.7 | | * GFCI BREAKER | | | |

## PANEL 1GL

LOCATION: **GREENHOUSE CORRIDOR** — LUG LOCATION: **BOTTOM FEED**
VOLT: **208Y/120V, 3Ø, 4W** — MAIN BUS: **60A MAIN BREAKER** — **NEMA 3R ENCLOSURE**
BUS: **100A** — MOUNTING: **SURFACE** — PANELBOARD SCCR RATING (A): **10,000**

| CIRCUIT NO. | BREAKER AMPS | BREAKER POLES | DESCRIPTION | PHASE LOAD (KVA) A | | B | | C | | DESCRIPTION | BREAKER AMPS | BREAKER POLES | CIRCUIT NO. |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 20 | 1 | LIGHTING | 0.3 | 0.3 | | | | | GREENHOUSE 121 EF-1 | 15 | 3 | 2 |
| 3 | 20 | 1 | GREENHOUSE 121 CONTROL PANEL | | | 0.5 | 0.3 | | | - | - | - | 4 |
| 5 | 20 | 1 | SPARE | | | | | 0.5 | 0.3 | - | - | - | 6 |
| 7 | 20 | 1 | GREENHOUSE 121 RECS. | 0.5 | 0.3 | | | | | GREENHOUSE 121 EF-1 | 15 | 3 | 8 |
| 9 | 20 | 1 | GREENHOUSE 121 RECS. | | | 0.5 | 0.3 | | | - | - | - | 10 |
| 11 | 20 | 1 | GREENHOUSE 121 RECS. | | | | | 0.7 | 0.3 | - | - | - | 12 |
| 13 | 20 | 1 | GREENHOUSE 121 OVERHEAD RECS. | 0.5 | 0.3 | | | | | GREENHOUSE 121 EF-1 | 15 | 3 | 14 |
| 15 | 20 | 1 | GREENHOUSE 121 OVERHEAD RECS. | | | 0.5 | 0.3 | | | - | - | - | 16 |
| 17 | 20 | 1 | GREENHOUSE 121 OVERHEAD RECS. | | | | | 0.5 | 0.3 | - | - | - | 18 |
| 19 | 20 | 1 | GREENHOUSE 121 OVERHEAD RECS. | 0.5 | 0.2 | | | | | GREENHOUSE 121 UH-1 | 20 | 1 | 20 |
| 21 | 20 | 1 | GREENHOUSE 121 OVERHEAD RECS. | | | 0.4 | 0.2 | | | GREENHOUSE 121 UH-1 | 20 | 1 | 22 |
| 23 | 20 | 1 | GREENHOUSE 121 OVERHEAD RECS. | | | | | 0.4 | 0.5 | GREENHOUSE 121 HF | 20 | 1 | 24 |
| 25 | 20 | 1 | GREENHOUSE 121 ECP SUMP PUMP | 0.5 | 0.5 | | | | | GREENHOUSE 121 HF | 20 | 1 | 26 |
| 27 | 20 | 1 | GREENHOUSE 121 ROOF VENT | | | 0.2 | 0.0 | | | WALKWAY EF-1 | 15 | 3 | 28 |
| 29 | 20 | 1 | GREENHOUSE 121 SIDE VENT | | | | | 0.2 | 0.0 | - | - | - | 30 |
| 31 | 20 | 1 | SPARE | 0.0 | 0.0 | | | | | - | - | - | 32 |
| 33 | 20 | 1 | SPARE | | | 0.0 | 0.0 | | | SPARE | 20 | 1 | 34 |
| 35 | 20 | 1 | SPARE | | | | | 0.0 | 0.0 | SPARE | 20 | 1 | 36 |
| 37 | 20 | 1 | SPARE | 0.0 | 0.0 | | | | | SPARE | 20 | 1 | 38 |
| 39 | 20 | 1 | SPARE | | | 0.0 | 0.0 | | | SPARE | 20 | 1 | 40 |
| 41 | 20 | 1 | SPARE | | | | | 0.0 | 0.0 | SPARE | 20 | 1 | 42 |
| TOTAL | | | | 4.0 | | 3.2 | | 3.7 | | * GFCI BREAKER | | | |

## PANEL 1GP

LOCATION: **GREENHOUSE CORRIDOR** — LUG LOCATION: **BOTTOM FEED**
VOLT: **208Y/120V, 3Ø, 4W** — MAIN BUS: **60A MAIN BREAKER** — **NEMA 3R ENCLOSURE**
BUS: **100A** — MOUNTING: **SURFACE** — PANELBOARD SCCR RATING (A): **10,000**

| CIRCUIT NO. | BREAKER AMPS | BREAKER POLES | DESCRIPTION | PHASE LOAD (KVA) A | | B | | C | | DESCRIPTION | BREAKER AMPS | BREAKER POLES | CIRCUIT NO. |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 20 | 1 | LIGHTING | 0.3 | 0.3 | | | | | GREENHOUSE 127 EF-1 | 15 | 3 | 2 |
| 3 | 20 | 1 | GREENHOUSE 127 CONTROL PANEL | | | 0.5 | 0.3 | | | - | - | - | 4 |
| 5 | 20 | 1 | SPARE | | | | | 0.5 | 0.3 | - | - | - | 6 |
| 7 | 20 | 1 | GREENHOUSE 127 RECS. | 0.5 | 0.3 | | | | | GREENHOUSE 127 EF-1 | 15 | 3 | 8 |
| 9 | 20 | 1 | GREENHOUSE 127 RECS. | | | 0.5 | 0.3 | | | - | - | - | 10 |
| 11 | 20 | 1 | GREENHOUSE 127 RECS. | | | | | 0.7 | 0.3 | - | - | - | 12 |
| 13 | 20 | 1 | GREENHOUSE 127 OVERHEAD RECS. | 0.5 | 0.3 | | | | | GREENHOUSE 127 EF-1 | 15 | 3 | 14 |
| 15 | 20 | 1 | GREENHOUSE 127 OVERHEAD RECS. | | | 0.5 | 0.3 | | | - | - | - | 16 |
| 17 | 20 | 1 | GREENHOUSE 127 OVERHEAD RECS. | | | | | 0.5 | 0.3 | - | - | - | 18 |
| 19 | 20 | 1 | GREENHOUSE 127 OVERHEAD RECS. | 0.5 | 0.2 | | | | | GREENHOUSE 127 UH-1 | 20 | 1 | 20 |
| 21 | 20 | 1 | GREENHOUSE 127 OVERHEAD RECS. | | | 0.4 | 0.2 | | | GREENHOUSE 127 UH-1 | 20 | 1 | 22 |
| 23 | 20 | 1 | GREENHOUSE 127 OVERHEAD RECS. | | | | | 0.4 | 0.5 | GREENHOUSE 127 HF | 20 | 1 | 24 |
| 25 | 20 | 1 | GREENHOUSE 127 ECP SUMP PUMP | 0.5 | 0.5 | | | | | GREENHOUSE 127 HF | 20 | 1 | 26 |
| 27 | 20 | 1 | GREENHOUSE 127 ROOF VENT | | | 0.2 | 1.5 | | | WALKWAY DAC-1 | 30 | 1 | 28 |
| 29 | 20 | 1 | GREENHOUSE 127 SIDE VENT | | | | | 0.2 | 0.4 | WALKWAY RECEPTACLES | 20 | 1 | 30 |
| 31 | 20 | 1 | SPARE | 0.0 | 0.3 | | | | | WALKWAY EF-1 | 15 | 3 | 32 |
| 33 | 20 | 1 | SPARE | | | 0.0 | 0.3 | | | - | - | - | 34 |
| 35 | 20 | 1 | SPARE | | | | | 0.0 | 0.3 | - | - | - | 36 |
| 37 | 20 | 1 | SPARE | 0.0 | 0.3 | | | | | WALKWAY EF-1 | 15 | 3 | 38 |
| 39 | 20 | 1 | SPARE | | | 0.0 | 0.3 | | | - | - | - | 40 |
| 41 | 20 | 1 | SPARE | | | | | 0.0 | 0.3 | - | - | - | 42 |
| TOTAL | | | | 4.6 | | 5.3 | | 4.7 | | * GFCI BREAKER | | | |

## PANEL 1GU

LOCATION: **GREENHOUSE CORRIDOR** — LUG LOCATION: **BOTTOM FEED**
VOLT: **208Y/120V, 3Ø, 4W** — MAIN BUS: **60A MAIN BREAKER** — **NEMA 3R ENCLOSURE**
BUS: **100A** — MOUNTING: **SURFACE** — PANELBOARD SCCR RATING (A): **10,000**

| CIRCUIT NO. | BREAKER AMPS | BREAKER POLES | DESCRIPTION | PHASE LOAD (KVA) A | | B | | C | | DESCRIPTION | BREAKER AMPS | BREAKER POLES | CIRCUIT NO. |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 20 | 1 | LIGHTING | 0.3 | 0.3 | | | | | GREENHOUSE 104 EF-1 | 15 | 3 | 2 |
| 3 | 20 | 1 | GREENHOUSE 104 CONTROL PANEL | | | 0.5 | 0.3 | | | - | - | - | 4 |
| 5 | 20 | 1 | SPARE | | | | | 0.5 | 0.3 | - | - | - | 6 |
| 7 | 20 | 1 | GREENHOUSE 104 RECS. | 0.5 | 0.3 | | | | | GREENHOUSE 104 EF-1 | 15 | 3 | 8 |
| 9 | 20 | 1 | GREENHOUSE 104 RECS. | | | 0.5 | 0.3 | | | - | - | - | 10 |
| 11 | 20 | 1 | GREENHOUSE 104 RECS. | | | | | 0.7 | 0.3 | - | - | - | 12 |
| 13 | 20 | 1 | GREENHOUSE 104 OVERHEAD RECS. | 0.5 | 0.3 | | | | | GREENHOUSE 104 EF-1 | 15 | 3 | 14 |
| 15 | 20 | 1 | GREENHOUSE 104 OVERHEAD RECS. | | | 0.5 | 0.3 | | | - | - | - | 16 |
| 17 | 20 | 1 | GREENHOUSE 104 OVERHEAD RECS. | | | | | 0.5 | 0.3 | - | - | - | 18 |
| 19 | 20 | 1 | GREENHOUSE 104 OVERHEAD RECS. | 0.5 | 0.2 | | | | | GREENHOUSE 104 UH-1 | 20 | 1 | 20 |
| 21 | 20 | 1 | GREENHOUSE 104 OVERHEAD RECS. | | | 0.4 | 0.2 | | | GREENHOUSE 104 UH-1 | 20 | 1 | 22 |
| 23 | 20 | 1 | GREENHOUSE 104 OVERHEAD RECS. | | | | | 0.4 | 0.5 | GREENHOUSE 104 HF | 20 | 1 | 24 |
| 25 | 20 | 1 | GREENHOUSE 104 ECP SUMP PUMP | 0.5 | 0.5 | | | | | GREENHOUSE 104 HF | 20 | 1 | 26 |
| 27 | 20 | 1 | GREENHOUSE 104 ROOF VENT | | | 0.2 | 1.5 | | | DAC-1 | 30 | 1 | 28 |
| 29 | 20 | 1 | GREENHOUSE 104 SIDE VENT | | | | | 0.2 | 0.0 | SPARE | 20 | 1 | 30 |
| 31 | 20 | 1 | SPARE | 0.0 | 0.0 | | | | | SPARE | 20 | 1 | 32 |
| 33 | 20 | 1 | SPARE | | | 0.0 | 0.0 | | | SPARE | 20 | 1 | 34 |
| 35 | 20 | 1 | SPARE | | | | | 0.0 | 0.0 | SPARE | 20 | 1 | 36 |
| 37 | 20 | 1 | SPARE | 0.0 | 0.0 | | | | | SPARE | 20 | 1 | 38 |
| 39 | 20 | 1 | SPARE | | | 0.0 | 0.0 | | | SPARE | 20 | 1 | 40 |
| 41 | 20 | 1 | SPARE | | | | | 0.0 | 0.0 | SPARE | 20 | 1 | 42 |
| TOTAL | | | | 4.0 | | 4.7 | | 3.7 | | * GFCI BREAKER | | | |

## PANEL 1GX

LOCATION: **GREENHOUSE CORRIDOR** — LUG LOCATION: **BOTTOM FEED**
VOLT: **208Y/120V, 3Ø, 4W** — MAIN BUS: **60A MAIN BREAKER** — **NEMA 3R ENCLOSURE**
BUS: **100A** — MOUNTING: **SURFACE** — PANELBOARD SCCR RATING (A): **10,000**

| CIRCUIT NO. | BREAKER AMPS | BREAKER POLES | DESCRIPTION | PHASE LOAD (KVA) A | | B | | C | | DESCRIPTION | BREAKER AMPS | BREAKER POLES | CIRCUIT NO. |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 20 | 1 | LIGHTING 103 | 0.3 | 0.3 | | | | | GREENHOUSE 103 EF-1 | 15 | 3 | 2 |
| 3 | 20 | 1 | GREENHOUSE 103 CONTROL PANEL | | | 0.5 | 0.3 | | | - | - | - | 4 |
| 5 | 20 | 1 | SPARE | | | | | 0.5 | 0.3 | - | - | - | 6 |
| 7 | 20 | 1 | GREENHOUSE 103 RECS. | 0.5 | 0.3 | | | | | GREENHOUSE 103 EF-1 | 15 | 3 | 8 |
| 9 | 20 | 1 | GREENHOUSE 103 RECS. | | | 0.5 | 0.3 | | | - | - | - | 10 |
| 11 | 20 | 1 | GREENHOUSE 103 RECS. | | | | | 0.7 | 0.3 | - | - | - | 12 |
| 13 | 20 | 1 | GREENHOUSE 103 OVERHEAD RECS. | 0.5 | 0.3 | | | | | GREENHOUSE 103 EF-1 | 15 | 3 | 14 |
| 15 | 20 | 1 | GREENHOUSE 103 OVERHEAD RECS. | | | 0.5 | 0.3 | | | - | - | - | 16 |
| 17 | 20 | 1 | GREENHOUSE 103 OVERHEAD RECS. | | | | | 0.5 | 0.3 | - | - | - | 18 |
| 19 | 20 | 1 | GREENHOUSE 103 OVERHEAD RECS. | 0.5 | 0.2 | | | | | GREENHOUSE 103 UH-1 | 20 | 1 | 20 |
| 21 | 20 | 1 | GREENHOUSE 103 OVERHEAD RECS. | | | 0.4 | 0.2 | | | GREENHOUSE 103 UH-1 | 20 | 1 | 22 |
| 23 | 20 | 1 | GREENHOUSE 103 OVERHEAD RECS. | | | | | 0.4 | 0.5 | GREENHOUSE 103 HF | 20 | 1 | 24 |
| 25 | 20 | 1 | GREENHOUSE 103 ECP SUMP PUMP | 0.5 | 0.5 | | | | | GREENHOUSE 103 HF | 20 | 1 | 26 |
| 27 | 20 | 1 | GREENHOUSE 103 ROOF VENT | | | 0.2 | 1.5 | | | DAC-1 | 30 | 1 | 28 |
| 29 | 20 | 1 | GREENHOUSE 103 SIDE VENT | | | | | 0.2 | 0.2 | HALLWAY EXIT UH-1 | 20 | 1 | 30 |
| 31 | 20 | 1 | SPARE | 0.0 | 0.3 | | | | | HALLWAY EXIT EF-1 | 15 | 3 | 32 |
| 33 | 20 | 1 | SPARE | | | 0.0 | 0.3 | | | - | - | - | 34 |
| 35 | 20 | 1 | SPARE | | | | | 0.0 | 0.3 | - | - | - | 36 |
| 37 | 20 | 1 | SPARE | 0.0 | 0.0 | | | | | SPARE | 20 | 1 | 38 |
| 39 | 20 | 1 | SPARE | | | 0.0 | 0.0 | | | SPARE | 20 | 1 | 40 |
| 41 | 20 | 1 | SPARE | | | | | 0.0 | 0.0 | SPARE | 20 | 1 | 42 |
| TOTAL | | | | 4.3 | | 5.0 | | 4.2 | | * GFCI BREAKER | | | |

## PANEL 1GQ

LOCATION: **GREENHOUSE CORRIDOR** — LUG LOCATION: **BOTTOM FEED**
VOLT: **208Y/120V, 3Ø, 4W** — MAIN BUS: **90A MAIN BREAKER** — **NEMA 3R ENCLOSURE**
BUS: **100A** — MOUNTING: **SURFACE** — PANELBOARD SCCR RATING (A): **10,000**

| CIRCUIT NO. | BREAKER AMPS | BREAKER POLES | DESCRIPTION | PHASE LOAD (KVA) A | | B | | C | | DESCRIPTION | BREAKER AMPS | BREAKER POLES | CIRCUIT NO. |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 20 | 1 | LIGHTING | 0.1 | 4.2 | | | | | WMU-1 | 60 | 3 | 2 |
| 3 | 20 | 1 | GENERAL USE RECS. | | | 0.4 | 4.2 | | | - | - | - | 4 |
| 5 | 20 | 1 | GENERAL USE RECS. | | | | | 0.4 | 4.2 | - | - | - | 6 |
| 7 | 20 | 1 | E-128 UH-1 | 0.5 | 0.1 | | | | | EF-3 | 15 | 3 | 8 |
| 9 | 20 | 1 | HF FAN | | | 0.2 | 0.1 | | | - | - | - | 10 |
| 11 | 20 | 1 | GREENHOUSE CONTROL PANEL | | | | | 0.5 | 0.1 | - | - | - | 12 |
| 13 | 20 | 1 | SPARE | 0.0 | 0.0 | | | | | SPARE | 20 | 1 | 14 |
| 15 | 20 | 1 | SPARE | | | 0.0 | 0.0 | | | SPARE | 20 | 1 | 16 |
| 17 | 20 | 1 | SPARE | | | | | 0.0 | 0.0 | SPARE | 20 | 1 | 18 |
| 19 | 20 | 1 | SPARE | 0.0 | 0.0 | | | | | SPARE | 20 | 1 | 20 |
| 21 | 20 | 1 | SPARE | | | 0.0 | 0.0 | | | SPARE | 20 | 1 | 22 |
| 23 | 20 | 1 | SPARE | | | | | 0.0 | 0.0 | SPARE | 20 | 1 | 24 |
| TOTAL | | | | 4.9 | | 4.8 | | 5.2 | | * GFCI BREAKER | | | |

## PANEL 1GR

LOCATION: **GREENHOUSE CORRIDOR** — LUG LOCATION: **BOTTOM FEED**
VOLT: **208Y/120V, 3Ø, 4W** — MAIN BUS: **90A MAIN BREAKER** — **NEMA 3R ENCLOSURE**
BUS: **100A** — MOUNTING: **SURFACE** — PANELBOARD SCCR RATING (A): **10,000**

| CIRCUIT NO. | BREAKER AMPS | BREAKER POLES | DESCRIPTION | PHASE LOAD (KVA) A | | B | | C | | DESCRIPTION | BREAKER AMPS | BREAKER POLES | CIRCUIT NO. |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 20 | 1 | LIGHTING | 0.1 | 4.2 | | | | | WMU-1 | 60 | 3 | 2 |
| 3 | 20 | 1 | GENERAL USE RECS. | | | 0.4 | 4.2 | | | - | - | - | 4 |
| 5 | 20 | 1 | GENERAL USE RECS. | | | | | 0.4 | 4.2 | - | - | - | 6 |
| 7 | 20 | 1 | E-130 UH-1 | 0.5 | 0.1 | | | | | EF-3 | 15 | 3 | 8 |
| 9 | 20 | 1 | HF FAN | | | 0.2 | 0.1 | | | - | - | - | 10 |
| 11 | 20 | 1 | GREENHOUSE CONTROL PANEL | | | | | 0.5 | 0.1 | - | - | - | 12 |
| 13 | 20 | 1 | SPARE | 0.0 | 0.0 | | | | | SPARE | 20 | 1 | 14 |
| 15 | 30 | 1 | DAC-1 | | | 1.5 | 0.0 | | | SPARE | 20 | 1 | 16 |
| 17 | 20 | 1 | HALLWAY UH-1 | | | | | 0.2 | 0.0 | SPARE | 20 | 1 | 18 |
| 19 | 15 | 3 | HALLWAY EF-1 | 0.3 | 0.0 | | | | | SPARE | 20 | 1 | 20 |
| 21 | - | - | - | | | 0.3 | 0.0 | | | SPARE | 20 | 1 | 22 |
| 23 | - | - | - | | | | | 0.3 | 0.0 | SPARE | 20 | 1 | 24 |
| TOTAL | | | | 4.9 | | 4.8 | | 5.2 | | * GFCI BREAKER | | | |

## PANEL 1GS

LOCATION: **GREENHOUSE CORRIDOR** — LUG LOCATION: **BOTTOM FEED**
VOLT: **208Y/120V, 3Ø, 4W** — MAIN BUS: **90A MAIN BREAKER** — **NEMA 3R ENCLOSURE**
BUS: **100A** — MOUNTING: **SURFACE** — PANELBOARD SCCR RATING (A): **10,000**

| CIRCUIT NO. | BREAKER AMPS | BREAKER POLES | DESCRIPTION | PHASE LOAD (KVA) A | | B | | C | | DESCRIPTION | BREAKER AMPS | BREAKER POLES | CIRCUIT NO. |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 20 | 1 | LIGHTING | 0.1 | 4.2 | | | | | WMU-1 | 60 | 3 | 2 |
| 3 | 20 | 1 | GENERAL USE RECS. | | | 0.4 | 4.2 | | | - | - | - | 4 |
| 5 | 20 | 1 | GENERAL USE RECS. | | | | | 0.4 | 4.2 | - | - | - | 6 |
| 7 | 20 | 1 | E-129 UH-1 | 0.5 | 0.1 | | | | | EF-3 | 15 | 3 | 8 |
| 9 | 20 | 1 | HF FAN | | | 0.2 | 0.1 | | | - | - | - | 10 |
| 11 | 20 | 1 | GREENHOUSE CONTROL PANEL | | | | | 0.5 | 0.1 | - | - | - | 12 |
| 13 | 20 | 1 | SPARE | 0.0 | 0.0 | | | | | SPARE | 20 | 1 | 14 |
| 15 | 20 | 1 | SPARE | | | 0.0 | 0.0 | | | SPARE | 20 | 1 | 16 |
| 17 | 20 | 1 | SPARE | | | | | 0.0 | 0.0 | SPARE | 20 | 1 | 18 |
| 19 | 20 | 1 | SPARE | 0.0 | 0.0 | | | | | SPARE | 20 | 1 | 20 |
| 21 | 20 | 1 | SPARE | | | 0.0 | 0.0 | | | SPARE | 20 | 1 | 22 |
| 23 | 20 | 1 | SPARE | | | | | 0.0 | 0.0 | SPARE | 20 | 1 | 24 |
| TOTAL | | | | 4.9 | | 4.8 | | 5.2 | | * GFCI BREAKER | | | |

## PANEL 1GT

LOCATION: **GREENHOUSE CORRIDOR** — LUG LOCATION: **BOTTOM FEED**
VOLT: **208Y/120V, 3Ø, 4W** — MAIN BUS: **90A MAIN BREAKER** — **NEMA 3R ENCLOSURE**
BUS: **100A** — MOUNTING: **SURFACE** — PANELBOARD SCCR RATING (A): **10,000**

| CIRCUIT NO. | BREAKER AMPS | BREAKER POLES | DESCRIPTION | PHASE LOAD (KVA) A | | B | | C | | DESCRIPTION | BREAKER AMPS | BREAKER POLES | CIRCUIT NO. |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 20 | 1 | LIGHTING | 0.1 | 4.2 | | | | | WMU-1 | 60 | 3 | 2 |
| 3 | 20 | 1 | GENERAL USE RECS. | | | 0.4 | 4.2 | | | - | - | - | 4 |
| 5 | 20 | 1 | GENERAL USE RECS. | | | | | 0.4 | 4.2 | - | - | - | 6 |
| 7 | 20 | 1 | E-131UH-1 | 0.5 | 0.1 | | | | | EF-3 | 15 | 3 | 8 |
| 9 | 20 | 1 | HF FAN | | | 0.2 | 0.1 | | | - | - | - | 10 |
| 11 | 20 | 1 | GREENHOUSE CONTROL PANEL | | | | | 0.5 | 0.1 | - | - | - | 12 |
| 13 | 20 | 1 | SPARE | 0.0 | 0.0 | | | | | SPARE | 20 | 1 | 14 |
| 15 | 20 | 1 | SPARE | | | 0.0 | 0.0 | | | SPARE | 20 | 1 | 16 |
| 17 | 20 | 1 | SPARE | | | | | 0.0 | 0.0 | SPARE | 20 | 1 | 18 |
| 19 | 20 | 1 | SPARE | 0.0 | 0.0 | | | | | SPARE | 20 | 1 | 20 |
| 21 | 20 | 1 | SPARE | | | 0.0 | 0.0 | | | SPARE | 20 | 1 | 22 |
| 23 | 20 | 1 | SPARE | | | | | 0.0 | 0.0 | SPARE | 20 | 1 | 24 |
| TOTAL | | | | 4.9 | | 4.8 | | 5.2 | | * GFCI BREAKER | | | |

### PANEL LEGEND

| | | |
|---|---|---|
| 1GA | 1GC | 1GE |
| 1GG | 1GJ | 1GL |
| 1GP | 1GU | 1GX |
| 1GQ | 1GR | |
| 1GS | 1GT | |

THE Johnson ◦ Mc Adams FIRM P.A.
ARCHITECTS/ENGINEERS · PLANNING · SURVEYING · MANAGEMENT
P.O. BOX 513, GREENWOOD, MISSISSIPPI – (662) 455-4943

| NO. | DATE | BY | DESCRIPTION |
|---|---|---|---|
| | | | |
| | | | |
| | | | |

REVISIONS

| A-E FIRM | USDA |
|---|---|
| PROJECT MANAGER BP | EPM XXX |
| DESIGNER EH | PPM XXX |
| CHECKED BY BTD | SAFETY & HEALTH XXX |
| JOB # 4825 | REAL PROPERTY XXX |

USDA Agricultural Research Service

USDA AGRICULTURAL RESEARCH SERVICE
US HORTICULTURAL RESEARCH LABORATORY
REPAIR TORNADO DAMAGE
FT. PIERCE, FL

# ELECTRICAL PANEL SCHEDULES

PROJECT NO. XXX
DATE 04/27/2026
AGRICULTURAL RESEARCH SERVICE
FT. PIERCE, FL
SHEET E-701
90 OF 108

C:\Users\EVANHE~1\AppData\Local\Temp\AcPublish_1748\E-701.dwg
Apr 27, 2026 – 9:53am

PANEL **1GB**
LOCATION: **GREENHOUSE CORRIDOR**
VOLT: **208Y/120V, 3Ø, 4W**
BUS: **225A**
LUG LOCATION: **BOTTOM FEED**
MAIN BUS: **100A MAIN BREAKER**
MOUNTING: **SURFACE**
**NEMA 3R ENCLOSURE**
PANELBOARD SCCR RATING (A): **10,000**

| CIRCUIT NO. | BREAKER AMPS | BREAKER POLES | DESCRIPTION | PHASE LOAD (KVA) A | | B | | C | | DESCRIPTION | BREAKER AMPS | BREAKER POLES | CIRCUIT NO. |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 20 | 1 | LIGHTING | 0.5 | 0.3 | | | | | GREENHOUSE 111 EF-1 | 15 | 3 | 2 |
| 3 | 20 | 1 | GREENHOUSE 111 CONTROL PANEL | | | 0.5 | 0.3 | | | - | - | - | 4 |
| 5 | 20 | 1 | GREENHOUSE 112 CONTROL PANEL | | | | | 0.5 | 0.3 | - | - | - | 6 |
| 7 | 20 | 1 | GREENHOUSE 111 RECS. | 0.5 | 0.3 | | | | | GREENHOUSE 111 EF-1 | 15 | 3 | 8 |
| 9 | 20 | 1 | GREENHOUSE 111 RECS. | | | 0.5 | 0.3 | | | - | - | - | 10 |
| 11 | 20 | 1 | GREENHOUSE 111 RECS. | | | | | 0.7 | 0.3 | - | - | - | 12 |
| 13 | 20 | 1 | GREENHOUSE 111 OVERHEAD RECS. | 0.5 | 0.3 | | | | | GREENHOUSE 111 EF-1 | 15 | 3 | 14 |
| 15 | 20 | 1 | GREENHOUSE 111 OVERHEAD RECS. | | | 0.5 | 0.3 | | | - | - | - | 16 |
| 17 | 20 | 1 | GREENHOUSE 111 OVERHEAD RECS. | | | | | 0.5 | 0.3 | - | - | - | 18 |
| 19 | 20 | 1 | GREENHOUSE 111 OVERHEAD RECS. | 0.5 | 0.3 | | | | | GREENHOUSE 112 EF-1 | 15 | 3 | 20 |
| 21 | 20 | 1 | GREENHOUSE 111 OVERHEAD RECS. | | | 0.4 | 0.3 | | | - | - | - | 22 |
| 23 | 20 | 1 | GREENHOUSE 111 OVERHEAD RECS. | | | | | 0.4 | 0.3 | - | - | - | 24 |
| 25 | 20 | 1 | GREENHOUSE 111 ECP SUMP PUMP | 0.5 | 0.3 | | | | | GREENHOUSE 112 EF-1 | 15 | 3 | 26 |
| 27 | 20 | 1 | GREENHOUSE 112 RECS. | | | 0.5 | 0.3 | | | - | - | - | 28 |
| 29 | 20 | 1 | GREENHOUSE 112 RECS. | | | | | 0.5 | 0.3 | - | - | - | 30 |
| 31 | 20 | 1 | GREENHOUSE 112 RECS. | 0.7 | 0.3 | | | | | GREENHOUSE 112 EF-1 | 15 | 3 | 32 |
| 33 | 20 | 1 | GREENHOUSE 112 OVERHEAD RECS. | | | 0.5 | 0.3 | | | - | - | - | 34 |
| 35 | 20 | 1 | GREENHOUSE 112 OVERHEAD RECS. | | | | | 0.5 | 0.3 | - | - | - | 36 |
| 37 | 20 | 1 | GREENHOUSE 112 OVERHEAD RECS. | 0.5 | 0.4 | | | | | GREENHOUSE 111 UH-1 | 20 | 1 | 38 |
| 39 | 20 | 1 | GREENHOUSE 112 OVERHEAD RECS. | | | 0.5 | 1.0 | | | GREENHOUSE 111 HF | 20 | 1 | 40 |
| 41 | 20 | 1 | GREENHOUSE 112 OVERHEAD RECS. | | | | | 0.4 | 0.5 | GREENHOUSE 111 ROOF VENT | 20 | 1 | 42 |
| 43 | 20 | 1 | GREENHOUSE 112 OVERHEAD RECS. | 0.4 | 0.5 | | | | | GREENHOUSE 111 SIDE VENT | 20 | 1 | 44 |
| 45 | 20 | 1 | GREENHOUSE 112 ECP SUMP PUMP | | | 0.5 | 0.4 | | | GREENHOUSE 112 UH-1 | 20 | 1 | 46 |
| 47 | 20 | 1 | SPARE | | | | | 0.0 | 1.0 | GREENHOUSE 112 HF | 20 | 1 | 48 |
| 49 | 20 | 1 | SPARE | 0.0 | 0.5 | | | | | GREENHOUSE 112 ROOF VENT | 20 | 1 | 50 |
| 51 | 20 | 1 | SPARE | | | 0.0 | 0.5 | | | GREENHOUSE 112 SIDE VENT | 20 | 1 | 52 |
| 53 | 20 | 1 | SPARE | | | | | 0.0 | 0.0 | SPARE | 20 | 1 | 54 |
| TOTAL | | | | 7.4 | | 7.7 | | 6.9 | | * GFCI BREAKER | | | |

PANEL **1GD**
LOCATION: **GREENHOUSE CORRIDOR**
VOLT: **208Y/120V, 3Ø, 4W**
BUS: **225A**
LUG LOCATION: **BOTTOM FEED**
MAIN BUS: **100A MAIN BREAKER**
MOUNTING: **SURFACE**
**NEMA 3R ENCLOSURE**
PANELBOARD SCCR RATING (A): **10,000**

| CIRCUIT NO. | BREAKER AMPS | BREAKER POLES | DESCRIPTION | PHASE LOAD (KVA) A | | B | | C | | DESCRIPTION | BREAKER AMPS | BREAKER POLES | CIRCUIT NO. |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 20 | 1 | LIGHTING | 0.5 | 0.3 | | | | | GREENHOUSE 117 EF-1 | 15 | 3 | 2 |
| 3 | 20 | 1 | GREENHOUSE 117 CONTROL PANEL | | | 0.5 | 0.3 | | | - | - | - | 4 |
| 5 | 20 | 1 | GREENHOUSE 118 CONTROL PANEL | | | | | 0.5 | 0.3 | - | - | - | 6 |
| 7 | 20 | 1 | GREENHOUSE 117 RECS. | 0.5 | 0.3 | | | | | GREENHOUSE 117 EF-1 | 15 | 3 | 8 |
| 9 | 20 | 1 | GREENHOUSE 117 RECS. | | | 0.5 | 0.3 | | | - | - | - | 10 |
| 11 | 20 | 1 | GREENHOUSE 117 RECS. | | | | | 0.7 | 0.3 | - | - | - | 12 |
| 13 | 20 | 1 | GREENHOUSE 117 OVERHEAD RECS. | 0.5 | 0.3 | | | | | GREENHOUSE 117 EF-1 | 15 | 3 | 14 |
| 15 | 20 | 1 | GREENHOUSE 117 OVERHEAD RECS. | | | 0.5 | 0.3 | | | - | - | - | 16 |
| 17 | 20 | 1 | GREENHOUSE 117 OVERHEAD RECS. | | | | | 0.5 | 0.3 | - | - | - | 18 |
| 19 | 20 | 1 | GREENHOUSE 117 OVERHEAD RECS. | 0.5 | 0.3 | | | | | GREENHOUSE 118 EF-1 | 15 | 3 | 20 |
| 21 | 20 | 1 | GREENHOUSE 117 OVERHEAD RECS. | | | 0.4 | 0.3 | | | - | - | - | 22 |
| 23 | 20 | 1 | GREENHOUSE 117 OVERHEAD RECS. | | | | | 0.4 | 0.3 | - | - | - | 24 |
| 25 | 20 | 1 | GREENHOUSE 117 ECP SUMP PUMP | 0.5 | 0.3 | | | | | GREENHOUSE 118 EF-1 | 15 | 3 | 26 |
| 27 | 20 | 1 | GREENHOUSE 118 RECS. | | | 0.5 | 0.3 | | | - | - | - | 28 |
| 29 | 20 | 1 | GREENHOUSE 118 RECS. | | | | | 0.5 | 0.3 | - | - | - | 30 |
| 31 | 20 | 1 | GREENHOUSE 118 RECS. | 0.7 | 0.3 | | | | | GREENHOUSE 118 EF-1 | 15 | 3 | 32 |
| 33 | 20 | 1 | GREENHOUSE 118 OVERHEAD RECS. | | | 0.5 | 0.3 | | | - | - | - | 34 |
| 35 | 20 | 1 | GREENHOUSE 118 OVERHEAD RECS. | | | | | 0.5 | 0.3 | - | - | - | 36 |
| 37 | 20 | 1 | GREENHOUSE 118 OVERHEAD RECS. | 0.5 | 0.4 | | | | | GREENHOUSE 117 UH-1 | 20 | 1 | 38 |
| 39 | 20 | 1 | GREENHOUSE 118 OVERHEAD RECS. | | | 0.5 | 1.0 | | | GREENHOUSE 117 HF | 20 | 1 | 40 |
| 41 | 20 | 1 | GREENHOUSE 118 OVERHEAD RECS. | | | | | 0.4 | 0.5 | GREENHOUSE 117 ROOF VENT | 20 | 1 | 42 |
| 43 | 20 | 1 | GREENHOUSE 118 OVERHEAD RECS. | 0.4 | 0.5 | | | | | GREENHOUSE 117 SIDE VENT | 20 | 1 | 44 |
| 45 | 20 | 1 | GREENHOUSE 118 ECP SUMP PUMP | | | 0.5 | 0.4 | | | GREENHOUSE 118 UH-1 | 20 | 1 | 46 |
| 47 | 20 | 1 | SPARE | | | | | 0.0 | 1.0 | GREENHOUSE 118 HF | 20 | 1 | 48 |
| 49 | 20 | 1 | SPARE | 0.0 | 0.5 | | | | | GREENHOUSE 118 ROOF VENT | 20 | 1 | 50 |
| 51 | 20 | 1 | SPARE | | | 0.0 | 0.5 | | | GREENHOUSE 118 SIDE VENT | 20 | 1 | 52 |
| 53 | 20 | 1 | SPARE | | | | | 0.0 | 0.0 | SPARE | 20 | 1 | 54 |
| TOTAL | | | | 7.4 | | 7.7 | | 6.9 | | * GFCI BREAKER | | | |

PANEL **1GF**
LOCATION: **GREENHOUSE CORRIDOR**
VOLT: **208Y/120V, 3Ø, 4W**
BUS: **225A**
LUG LOCATION: **BOTTOM FEED**
MAIN BUS: **100A MAIN BREAKER**
MOUNTING: **SURFACE**
**NEMA 3R ENCLOSURE**
PANELBOARD SCCR RATING (A): **10,000**

| CIRCUIT NO. | BREAKER AMPS | BREAKER POLES | DESCRIPTION | PHASE LOAD (KVA) A | | B | | C | | DESCRIPTION | BREAKER AMPS | BREAKER POLES | CIRCUIT NO. |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 20 | 1 | LIGHTING | 0.5 | 0.3 | | | | | GREENHOUSE 108 EF-1 | 15 | 3 | 2 |
| 3 | 20 | 1 | GREENHOUSE 108 CONTROL PANEL | | | 0.5 | 0.3 | | | - | - | - | 4 |
| 5 | 20 | 1 | GREENHOUSE 107 CONTROL PANEL | | | | | 0.5 | 0.3 | - | - | - | 6 |
| 7 | 20 | 1 | GREENHOUSE 108 RECS. | 0.5 | 0.3 | | | | | GREENHOUSE 108 EF-1 | 15 | 3 | 8 |
| 9 | 20 | 1 | GREENHOUSE 108 RECS. | | | 0.5 | 0.3 | | | - | - | - | 10 |
| 11 | 20 | 1 | GREENHOUSE 108 RECS. | | | | | 0.7 | 0.3 | - | - | - | 12 |
| 13 | 20 | 1 | GREENHOUSE 108 OVERHEAD RECS. | 0.5 | 0.3 | | | | | GREENHOUSE 108 EF-1 | 15 | 3 | 14 |
| 15 | 20 | 1 | GREENHOUSE 108 OVERHEAD RECS. | | | 0.5 | 0.3 | | | - | - | - | 16 |
| 17 | 20 | 1 | GREENHOUSE 108 OVERHEAD RECS. | | | | | 0.5 | 0.3 | - | - | - | 18 |
| 19 | 20 | 1 | GREENHOUSE 108 OVERHEAD RECS. | 0.5 | 0.3 | | | | | GREENHOUSE 107 EF-1 | 15 | 3 | 20 |
| 21 | 20 | 1 | GREENHOUSE 108 OVERHEAD RECS. | | | 0.4 | 0.3 | | | - | - | - | 22 |
| 23 | 20 | 1 | GREENHOUSE 108 OVERHEAD RECS. | | | | | 0.4 | 0.3 | - | - | - | 24 |
| 25 | 20 | 1 | GREENHOUSE 108 ECP SUMP PUMP | 0.5 | 0.3 | | | | | GREENHOUSE 107 EF-1 | 15 | 3 | 26 |
| 27 | 20 | 1 | GREENHOUSE 107 RECS. | | | 0.5 | 0.3 | | | - | - | - | 28 |
| 29 | 20 | 1 | GREENHOUSE 107 RECS. | | | | | 0.5 | 0.3 | - | - | - | 30 |
| 31 | 20 | 1 | GREENHOUSE 107 RECS. | 0.7 | 0.3 | | | | | GREENHOUSE 107 EF-1 | 15 | 3 | 32 |
| 33 | 20 | 1 | GREENHOUSE 107 OVERHEAD RECS. | | | 0.5 | 0.3 | | | - | - | - | 34 |
| 35 | 20 | 1 | GREENHOUSE 107 OVERHEAD RECS. | | | | | 0.5 | 0.3 | - | - | - | 36 |
| 37 | 20 | 1 | GREENHOUSE 107 OVERHEAD RECS. | 0.5 | 0.4 | | | | | GREENHOUSE 108 UH-1 | 20 | 1 | 38 |
| 39 | 20 | 1 | GREENHOUSE 107 OVERHEAD RECS. | | | 0.5 | 1.0 | | | GREENHOUSE 108 HF | 20 | 1 | 40 |
| 41 | 20 | 1 | GREENHOUSE 107 OVERHEAD RECS. | | | | | 0.4 | 0.5 | GREENHOUSE 108 ROOF VENT | 20 | 1 | 42 |
| 43 | 20 | 1 | GREENHOUSE 107 OVERHEAD RECS. | 0.4 | 0.5 | | | | | GREENHOUSE 108 SIDE VENT | 20 | 1 | 44 |
| 45 | 20 | 1 | GREENHOUSE 107 ECP SUMP PUMP | | | 0.5 | 0.4 | | | GREENHOUSE 107 UH-1 | 20 | 1 | 46 |
| 47 | 20 | 1 | SPARE | | | | | 0.0 | 1.0 | GREENHOUSE 107 HF | 20 | 1 | 48 |
| 49 | 20 | 1 | SPARE | 0.0 | 0.5 | | | | | GREENHOUSE 107 ROOF VENT | 20 | 1 | 50 |
| 51 | 20 | 1 | SPARE | | | 0.0 | 0.5 | | | GREENHOUSE 107 SIDE VENT | 20 | 1 | 52 |
| 53 | 20 | 1 | SPARE | | | | | 0.0 | 0.0 | SPARE | 20 | 1 | 54 |
| TOTAL | | | | 7.4 | | 7.7 | | 6.9 | | * GFCI BREAKER | | | |

PANEL **1GH**
LOCATION: **GREENHOUSE CORRIDOR**
VOLT: **208Y/120V, 3Ø, 4W**
BUS: **225A**
LUG LOCATION: **BOTTOM FEED**
MAIN BUS: **100A MAIN BREAKER**
MOUNTING: **SURFACE**
**NEMA 3R ENCLOSURE**
PANELBOARD SCCR RATING (A): **10,000**

| CIRCUIT NO. | BREAKER AMPS | BREAKER POLES | DESCRIPTION | PHASE LOAD (KVA) A | | B | | C | | DESCRIPTION | BREAKER AMPS | BREAKER POLES | CIRCUIT NO. |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 20 | 1 | LIGHTING | 0.5 | 0.3 | | | | | GREENHOUSE 114 EF-1 | 15 | 3 | 2 |
| 3 | 20 | 1 | GREENHOUSE 114 CONTROL PANEL | | | 0.5 | 0.3 | | | - | - | - | 4 |
| 5 | 20 | 1 | GREENHOUSE 113 CONTROL PANEL | | | | | 0.5 | 0.3 | - | - | - | 6 |
| 7 | 20 | 1 | GREENHOUSE 114 RECS. | 0.5 | 0.3 | | | | | GREENHOUSE 114 EF-1 | 15 | 3 | 8 |
| 9 | 20 | 1 | GREENHOUSE 114 RECS. | | | 0.5 | 0.3 | | | - | - | - | 10 |
| 11 | 20 | 1 | GREENHOUSE 114 RECS. | | | | | 0.7 | 0.3 | - | - | - | 12 |
| 13 | 20 | 1 | GREENHOUSE 114 OVERHEAD RECS. | 0.5 | 0.3 | | | | | GREENHOUSE 114 EF-1 | 15 | 3 | 14 |
| 15 | 20 | 1 | GREENHOUSE 114 OVERHEAD RECS. | | | 0.5 | 0.3 | | | - | - | - | 16 |
| 17 | 20 | 1 | GREENHOUSE 114 OVERHEAD RECS. | | | | | 0.5 | 0.3 | - | - | - | 18 |
| 19 | 20 | 1 | GREENHOUSE 114 OVERHEAD RECS. | 0.5 | 0.3 | | | | | GREENHOUSE 113 EF-1 | 15 | 3 | 20 |
| 21 | 20 | 1 | GREENHOUSE 114 OVERHEAD RECS. | | | 0.4 | 0.3 | | | - | - | - | 22 |
| 23 | 20 | 1 | GREENHOUSE 114 OVERHEAD RECS. | | | | | 0.4 | 0.3 | - | - | - | 24 |
| 25 | 20 | 1 | GREENHOUSE 114 ECP SUMP PUMP | 0.5 | 0.3 | | | | | GREENHOUSE 113 EF-1 | 15 | 3 | 26 |
| 27 | 20 | 1 | GREENHOUSE 113 RECS. | | | 0.5 | 0.3 | | | - | - | - | 28 |
| 29 | 20 | 1 | GREENHOUSE 113 RECS. | | | | | 0.5 | 0.3 | - | - | - | 30 |
| 31 | 20 | 1 | GREENHOUSE 113 RECS. | 0.7 | 0.3 | | | | | GREENHOUSE 113 EF-1 | 15 | 3 | 32 |
| 33 | 20 | 1 | GREENHOUSE 113 OVERHEAD RECS. | | | 0.5 | 0.3 | | | - | - | - | 34 |
| 35 | 20 | 1 | GREENHOUSE 113 OVERHEAD RECS. | | | | | 0.5 | 0.3 | - | - | - | 36 |
| 37 | 20 | 1 | GREENHOUSE 113 OVERHEAD RECS. | 0.5 | 0.4 | | | | | GREENHOUSE 114 UH-1 | 20 | 1 | 38 |
| 39 | 20 | 1 | GREENHOUSE 113 OVERHEAD RECS. | | | 0.5 | 1.0 | | | GREENHOUSE 114 HF | 20 | 1 | 40 |
| 41 | 20 | 1 | GREENHOUSE 113 OVERHEAD RECS. | | | | | 0.4 | 0.5 | GREENHOUSE 114 ROOF VENT | 20 | 1 | 42 |
| 43 | 20 | 1 | GREENHOUSE 113 OVERHEAD RECS. | 0.4 | 0.5 | | | | | GREENHOUSE 114 SIDE VENT | 20 | 1 | 44 |
| 45 | 20 | 1 | GREENHOUSE 113 ECP SUMP PUMP | | | 0.5 | 0.4 | | | GREENHOUSE 113 UH-1 | 20 | 1 | 46 |
| 47 | 20 | 1 | SPARE | | | | | 0.0 | 1.0 | GREENHOUSE 113 HF | 20 | 1 | 48 |
| 49 | 20 | 1 | SPARE | 0.0 | 0.5 | | | | | GREENHOUSE 113 ROOF VENT | 20 | 1 | 50 |
| 51 | 20 | 1 | SPARE | | | 0.0 | 0.5 | | | GREENHOUSE 113 SIDE VENT | 20 | 1 | 52 |
| 53 | 20 | 1 | HALLWAY LIGHTING | | | | | 0.2 | 0.0 | SPARE | 20 | 1 | 54 |
| TOTAL | | | | 7.4 | | 7.7 | | 7.1 | | * GFCI BREAKER | | | |

PANEL **1GK**
LOCATION: **GREENHOUSE CORRIDOR**
VOLT: **208Y/120V, 3Ø, 4W**
BUS: **225A**
LUG LOCATION: **BOTTOM FEED**
MAIN BUS: **100A MAIN BREAKER**
MOUNTING: **SURFACE**
**NEMA 3R ENCLOSURE**
PANELBOARD SCCR RATING (A): **10,000**

| CIRCUIT NO. | BREAKER AMPS | BREAKER POLES | DESCRIPTION | PHASE LOAD (KVA) A | | B | | C | | DESCRIPTION | BREAKER AMPS | BREAKER POLES | CIRCUIT NO. |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 20 | 1 | LIGHTING | 0.5 | 0.3 | | | | | GREENHOUSE 120 EF-1 | 15 | 3 | 2 |
| 3 | 20 | 1 | GREENHOUSE 120 CONTROL PANEL | | | 0.5 | 0.3 | | | - | - | - | 4 |
| 5 | 20 | 1 | GREENHOUSE 119 CONTROL PANEL | | | | | 0.5 | 0.3 | - | - | - | 6 |
| 7 | 20 | 1 | GREENHOUSE 120 RECS. | 0.5 | 0.3 | | | | | GREENHOUSE 120 EF-1 | 15 | 3 | 8 |
| 9 | 20 | 1 | GREENHOUSE 120 RECS. | | | 0.5 | 0.3 | | | - | - | - | 10 |
| 11 | 20 | 1 | GREENHOUSE 120 RECS. | | | | | 0.7 | 0.3 | - | - | - | 12 |
| 13 | 20 | 1 | GREENHOUSE 120 OVERHEAD RECS. | 0.5 | 0.3 | | | | | GREENHOUSE 120 EF-1 | 15 | 3 | 14 |
| 15 | 20 | 1 | GREENHOUSE 120 OVERHEAD RECS. | | | 0.5 | 0.3 | | | - | - | - | 16 |
| 17 | 20 | 1 | GREENHOUSE 120 OVERHEAD RECS. | | | | | 0.5 | 0.3 | - | - | - | 18 |
| 19 | 20 | 1 | GREENHOUSE 120 OVERHEAD RECS. | 0.5 | 0.3 | | | | | GREENHOUSE 119 EF-1 | 15 | 3 | 20 |
| 21 | 20 | 1 | GREENHOUSE 120 OVERHEAD RECS. | | | 0.4 | 0.3 | | | - | - | - | 22 |
| 23 | 20 | 1 | GREENHOUSE 120 OVERHEAD RECS. | | | | | 0.4 | 0.3 | - | - | - | 24 |
| 25 | 20 | 1 | GREENHOUSE 120 ECP SUMP PUMP | 0.5 | 0.3 | | | | | GREENHOUSE 119 EF-1 | 15 | 3 | 26 |
| 27 | 20 | 1 | GREENHOUSE 119 RECS. | | | 0.5 | 0.3 | | | - | - | - | 28 |
| 29 | 20 | 1 | GREENHOUSE 119 RECS. | | | | | 0.5 | 0.3 | - | - | - | 30 |
| 31 | 20 | 1 | GREENHOUSE 119 RECS. | 0.7 | 0.3 | | | | | GREENHOUSE 119 EF-1 | 15 | 3 | 32 |
| 33 | 20 | 1 | GREENHOUSE 119 OVERHEAD RECS. | | | 0.5 | 0.3 | | | - | - | - | 34 |
| 35 | 20 | 1 | GREENHOUSE 119 OVERHEAD RECS. | | | | | 0.5 | 0.3 | - | - | - | 36 |
| 37 | 20 | 1 | GREENHOUSE 119 OVERHEAD RECS. | 0.5 | 0.4 | | | | | GREENHOUSE 120 UH-1 | 20 | 1 | 38 |
| 39 | 20 | 1 | GREENHOUSE 119 OVERHEAD RECS. | | | 0.5 | 1.0 | | | GREENHOUSE 120 HF | 20 | 1 | 40 |
| 41 | 20 | 1 | GREENHOUSE 119 OVERHEAD RECS. | | | | | 0.4 | 0.5 | GREENHOUSE 120 ROOF VENT | 20 | 1 | 42 |
| 43 | 20 | 1 | GREENHOUSE 119 OVERHEAD RECS. | 0.4 | 0.5 | | | | | GREENHOUSE 120 SIDE VENT | 20 | 1 | 44 |
| 45 | 20 | 1 | GREENHOUSE 119 ECP SUMP PUMP | | | 0.5 | 0.4 | | | GREENHOUSE 119 UH-1 | 20 | 1 | 46 |
| 47 | 20 | 1 | SPARE | | | | | 0.0 | 1.0 | GREENHOUSE 119 HF | 20 | 1 | 48 |
| 49 | 20 | 1 | SPARE | 0.0 | 0.5 | | | | | GREENHOUSE 119 ROOF VENT | 20 | 1 | 50 |
| 51 | 20 | 1 | SPARE | | | 0.0 | 0.5 | | | GREENHOUSE 119 SIDE VENT | 20 | 1 | 52 |
| 53 | 20 | 1 | SPARE | | | | | 0.0 | 0.0 | SPARE | 20 | 1 | 54 |
| TOTAL | | | | 7.4 | | 7.7 | | 6.9 | | * GFCI BREAKER | | | |

PANEL **1GM**
LOCATION: **GREENHOUSE CORRIDOR**
VOLT: **208Y/120V, 3Ø, 4W**
BUS: **225A**
LUG LOCATION: **BOTTOM FEED**
MAIN BUS: **100A MAIN BREAKER**
MOUNTING: **SURFACE**
**NEMA 3R ENCLOSURE**
PANELBOARD SCCR RATING (A): **10,000**

| CIRCUIT NO. | BREAKER AMPS | BREAKER POLES | DESCRIPTION | PHASE LOAD (KVA) A | | B | | C | | DESCRIPTION | BREAKER AMPS | BREAKER POLES | CIRCUIT NO. |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 20 | 1 | LIGHTING | 0.5 | 0.3 | | | | | GREENHOUSE 124 EF-1 | 15 | 3 | 2 |
| 3 | 20 | 1 | GREENHOUSE 124 CONTROL PANEL | | | 0.5 | 0.3 | | | - | - | - | 4 |
| 5 | 20 | 1 | GREENHOUSE 123 CONTROL PANEL | | | | | 0.5 | 0.3 | - | - | - | 6 |
| 7 | 20 | 1 | GREENHOUSE 124 RECS. | 0.5 | 0.3 | | | | | GREENHOUSE 124 EF-1 | 15 | 3 | 8 |
| 9 | 20 | 1 | GREENHOUSE 124 RECS. | | | 0.5 | 0.3 | | | - | - | - | 10 |
| 11 | 20 | 1 | GREENHOUSE 124 RECS. | | | | | 0.7 | 0.3 | - | - | - | 12 |
| 13 | 20 | 1 | GREENHOUSE 124 OVERHEAD RECS. | 0.5 | 0.3 | | | | | GREENHOUSE 124 EF-1 | 15 | 3 | 14 |
| 15 | 20 | 1 | GREENHOUSE 124 OVERHEAD RECS. | | | 0.5 | 0.3 | | | - | - | - | 16 |
| 17 | 20 | 1 | GREENHOUSE 124 OVERHEAD RECS. | | | | | 0.5 | 0.3 | - | - | - | 18 |
| 19 | 20 | 1 | GREENHOUSE 124 OVERHEAD RECS. | 0.5 | 0.3 | | | | | GREENHOUSE 123 EF-1 | 15 | 3 | 20 |
| 21 | 20 | 1 | GREENHOUSE 124 OVERHEAD RECS. | | | 0.4 | 0.3 | | | - | - | - | 22 |
| 23 | 20 | 1 | GREENHOUSE 124 OVERHEAD RECS. | | | | | 0.4 | 0.3 | - | - | - | 24 |
| 25 | 20 | 1 | GREENHOUSE 124 ECP SUMP PUMP | 0.5 | 0.3 | | | | | GREENHOUSE 123 EF-1 | 15 | 3 | 26 |
| 27 | 20 | 1 | GREENHOUSE 123 RECS. | | | 0.5 | 0.3 | | | - | - | - | 28 |
| 29 | 20 | 1 | GREENHOUSE 123 RECS. | | | | | 0.5 | 0.3 | - | - | - | 30 |
| 31 | 20 | 1 | GREENHOUSE 123 RECS. | 0.7 | 0.3 | | | | | GREENHOUSE 123 EF-1 | 15 | 3 | 32 |
| 33 | 20 | 1 | GREENHOUSE 123 OVERHEAD RECS. | | | 0.5 | 0.3 | | | - | - | - | 34 |
| 35 | 20 | 1 | GREENHOUSE 123 OVERHEAD RECS. | | | | | 0.5 | 0.3 | - | - | - | 36 |
| 37 | 20 | 1 | GREENHOUSE 123 OVERHEAD RECS. | 0.5 | 0.4 | | | | | GREENHOUSE 124 UH-1 | 20 | 1 | 38 |
| 39 | 20 | 1 | GREENHOUSE 123 OVERHEAD RECS. | | | 0.5 | 1.0 | | | GREENHOUSE 124 HF | 20 | 1 | 40 |
| 41 | 20 | 1 | GREENHOUSE 123 OVERHEAD RECS. | | | | | 0.4 | 0.5 | GREENHOUSE 124 ROOF VENT | 20 | 1 | 42 |
| 43 | 20 | 1 | GREENHOUSE 123 OVERHEAD RECS. | 0.4 | 0.5 | | | | | GREENHOUSE 124 SIDE VENT | 20 | 1 | 44 |
| 45 | 20 | 1 | GREENHOUSE 123 ECP SUMP PUMP | | | 0.5 | 0.4 | | | GREENHOUSE 123 UH-1 | 20 | 1 | 46 |
| 47 | 20 | 1 | SPARE | | | | | 0.0 | 1.0 | GREENHOUSE 123 HF | 20 | 1 | 48 |
| 49 | 20 | 1 | SPARE | 0.0 | 0.5 | | | | | GREENHOUSE 123 ROOF VENT | 20 | 1 | 50 |
| 51 | 20 | 1 | SPARE | | | 0.0 | 0.5 | | | GREENHOUSE 123 SIDE VENT | 20 | 1 | 52 |
| 53 | 20 | 1 | HALLWAY LIGHTING | | | | | 0.5 | 0.0 | SPARE | 20 | 1 | 54 |
| TOTAL | | | | 7.4 | | 7.7 | | 7.4 | | * GFCI BREAKER | | | |

PANEL **1GN**
LOCATION: **GREENHOUSE CORRIDOR**
VOLT: **208Y/120V, 3Ø, 4W**
BUS: **225A**
LUG LOCATION: **BOTTOM FEED**
MAIN BUS: **100A MAIN BREAKER**
MOUNTING: **SURFACE**
**NEMA 3R ENCLOSURE**
PANELBOARD SCCR RATING (A): **10,000**

| CIRCUIT NO. | BREAKER AMPS | BREAKER POLES | DESCRIPTION | PHASE LOAD (KVA) A | | B | | C | | DESCRIPTION | BREAKER AMPS | BREAKER POLES | CIRCUIT NO. |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 20 | 1 | LIGHTING | 0.5 | 0.3 | | | | | GREENHOUSE 126 EF-1 | 15 | 3 | 2 |
| 3 | 20 | 1 | GREENHOUSE 126 CONTROL PANEL | | | 0.5 | 0.3 | | | - | - | - | 4 |
| 5 | 20 | 1 | GREENHOUSE 125 CONTROL PANEL | | | | | 0.5 | 0.3 | - | - | - | 6 |
| 7 | 20 | 1 | GREENHOUSE 126 RECS. | 0.5 | 0.3 | | | | | GREENHOUSE 126 EF-1 | 15 | 3 | 8 |
| 9 | 20 | 1 | GREENHOUSE 126 RECS. | | | 0.5 | 0.3 | | | - | - | - | 10 |
| 11 | 20 | 1 | GREENHOUSE 126 RECS. | | | | | 0.7 | 0.3 | - | - | - | 12 |
| 13 | 20 | 1 | GREENHOUSE 126 OVERHEAD RECS. | 0.5 | 0.3 | | | | | GREENHOUSE 126 EF-1 | 15 | 3 | 14 |
| 15 | 20 | 1 | GREENHOUSE 126 OVERHEAD RECS. | | | 0.5 | 0.3 | | | - | - | - | 16 |
| 17 | 20 | 1 | GREENHOUSE 126 OVERHEAD RECS. | | | | | 0.5 | 0.3 | - | - | - | 18 |
| 19 | 20 | 1 | GREENHOUSE 126 OVERHEAD RECS. | 0.5 | 0.3 | | | | | GREENHOUSE 125 EF-1 | 15 | 3 | 20 |
| 21 | 20 | 1 | GREENHOUSE 126 OVERHEAD RECS. | | | 0.4 | 0.3 | | | - | - | - | 22 |
| 23 | 20 | 1 | GREENHOUSE 126 OVERHEAD RECS. | | | | | 0.4 | 0.3 | - | - | - | 24 |
| 25 | 20 | 1 | GREENHOUSE 126 ECP SUMP PUMP | 0.5 | 0.3 | | | | | GREENHOUSE 125 EF-1 | 15 | 3 | 26 |
| 27 | 20 | 1 | GREENHOUSE 125 RECS. | | | 0.5 | 0.3 | | | - | - | - | 28 |
| 29 | 20 | 1 | GREENHOUSE 125 RECS. | | | | | 0.5 | 0.3 | - | - | - | 30 |
| 31 | 20 | 1 | GREENHOUSE 125 RECS. | 0.7 | 0.3 | | | | | GREENHOUSE 125 EF-1 | 15 | 3 | 32 |
| 33 | 20 | 1 | GREENHOUSE 125 OVERHEAD RECS. | | | 0.5 | 0.3 | | | - | - | - | 34 |
| 35 | 20 | 1 | GREENHOUSE 125 OVERHEAD RECS. | | | | | 0.5 | 0.3 | - | - | - | 36 |
| 37 | 20 | 1 | GREENHOUSE 125 OVERHEAD RECS. | 0.5 | 0.4 | | | | | GREENHOUSE 126 UH-1 | 20 | 1 | 38 |
| 39 | 20 | 1 | GREENHOUSE 125 OVERHEAD RECS. | | | 0.5 | 1.0 | | | GREENHOUSE 126 HF | 20 | 1 | 40 |
| 41 | 20 | 1 | GREENHOUSE 125 OVERHEAD RECS. | | | | | 0.4 | 0.5 | GREENHOUSE 126 ROOF VENT | 20 | 1 | 42 |
| 43 | 20 | 1 | GREENHOUSE 125 OVERHEAD RECS. | 0.4 | 0.5 | | | | | GREENHOUSE 126 SIDE VENT | 20 | 1 | 44 |
| 45 | 20 | 1 | GREENHOUSE 125 ECP SUMP PUMP | | | 0.5 | 0.4 | | | GREENHOUSE 125 UH-1 | 20 | 1 | 46 |
| 47 | 20 | 1 | SPARE | | | | | 0.0 | 1.0 | GREENHOUSE 125 HF | 20 | 1 | 48 |
| 49 | 20 | 1 | SPARE | 0.0 | 0.5 | | | | | GREENHOUSE 125 ROOF VENT | 20 | 1 | 50 |
| 51 | 20 | 1 | SPARE | | | 0.0 | 0.5 | | | GREENHOUSE 125 SIDE VENT | 20 | 1 | 52 |
| 53 | 20 | 1 | SPARE | | | | | 0.0 | 0.0 | SPARE | 20 | 1 | 54 |
| TOTAL | | | | 7.4 | | 7.7 | | 6.9 | | * GFCI BREAKER | | | |

PANEL **1GV**
LOCATION: **GREENHOUSE CORRIDOR**
VOLT: **208Y/120V, 3Ø, 4W**
BUS: **225A**
LUG LOCATION: **BOTTOM FEED**
MAIN BUS: **100A MAIN BREAKER**
MOUNTING: **SURFACE**
**NEMA 3R ENCLOSURE**
PANELBOARD SCCR RATING (A): **10,000**

| CIRCUIT NO. | BREAKER AMPS | BREAKER POLES | DESCRIPTION | PHASE LOAD (KVA) A | | B | | C | | DESCRIPTION | BREAKER AMPS | BREAKER POLES | CIRCUIT NO. |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 20 | 1 | LIGHTING | 0.5 | 0.3 | | | | | GREENHOUSE 105 EF-1 | 15 | 3 | 2 |
| 3 | 20 | 1 | GREENHOUSE 105 CONTROL PANEL | | | 0.5 | 0.3 | | | - | - | - | 4 |
| 5 | 20 | 1 | GREENHOUSE 106 CONTROL PANEL | | | | | 0.5 | 0.3 | - | - | - | 6 |
| 7 | 20 | 1 | GREENHOUSE 105 RECS. | 0.5 | 0.3 | | | | | GREENHOUSE 105 EF-1 | 15 | 3 | 8 |
| 9 | 20 | 1 | GREENHOUSE 105 RECS. | | | 0.5 | 0.3 | | | - | - | - | 10 |
| 11 | 20 | 1 | GREENHOUSE 105 RECS. | | | | | 0.7 | 0.3 | - | - | - | 12 |
| 13 | 20 | 1 | GREENHOUSE 105 OVERHEAD RECS. | 0.5 | 0.3 | | | | | GREENHOUSE 105 EF-1 | 15 | 3 | 14 |
| 15 | 20 | 1 | GREENHOUSE 105 OVERHEAD RECS. | | | 0.5 | 0.3 | | | - | - | - | 16 |
| 17 | 20 | 1 | GREENHOUSE 105 OVERHEAD RECS. | | | | | 0.5 | 0.3 | - | - | - | 18 |
| 19 | 20 | 1 | GREENHOUSE 105 OVERHEAD RECS. | 0.5 | 0.3 | | | | | GREENHOUSE 106 EF-1 | 15 | 3 | 20 |
| 21 | 20 | 1 | GREENHOUSE 105 OVERHEAD RECS. | | | 0.4 | 0.3 | | | - | - | - | 22 |
| 23 | 20 | 1 | GREENHOUSE 105 OVERHEAD RECS. | | | | | 0.4 | 0.3 | - | - | - | 24 |
| 25 | 20 | 1 | GREENHOUSE 105 ECP SUMP PUMP | 0.5 | 0.3 | | | | | GREENHOUSE 106 EF-1 | 15 | 3 | 26 |
| 27 | 20 | 1 | GREENHOUSE 106 RECS. | | | 0.5 | 0.3 | | | - | - | - | 28 |
| 29 | 20 | 1 | GREENHOUSE 106 RECS. | | | | | 0.5 | 0.3 | - | - | - | 30 |
| 31 | 20 | 1 | GREENHOUSE 106 RECS. | 0.7 | 0.3 | | | | | GREENHOUSE 106 EF-1 | 15 | 3 | 32 |
| 33 | 20 | 1 | GREENHOUSE 106 OVERHEAD RECS. | | | 0.5 | 0.3 | | | - | - | - | 34 |
| 35 | 20 | 1 | GREENHOUSE 106 OVERHEAD RECS. | | | | | 0.5 | 0.3 | - | - | - | 36 |
| 37 | 20 | 1 | GREENHOUSE 106 OVERHEAD RECS. | 0.5 | 0.4 | | | | | GREENHOUSE 105 UH-1 | 20 | 1 | 38 |
| 39 | 20 | 1 | GREENHOUSE 106 OVERHEAD RECS. | | | 0.5 | 1.0 | | | GREENHOUSE 105 HF | 20 | 1 | 40 |
| 41 | 20 | 1 | GREENHOUSE 106 OVERHEAD RECS. | | | | | 0.4 | 0.5 | GREENHOUSE 105 ROOF VENT | 20 | 1 | 42 |
| 43 | 20 | 1 | GREENHOUSE 106 OVERHEAD RECS. | 0.4 | 0.5 | | | | | GREENHOUSE 105 SIDE VENT | 20 | 1 | 44 |
| 45 | 20 | 1 | GREENHOUSE 106 ECP SUMP PUMP | | | 0.5 | 0.4 | | | GREENHOUSE 106 UH-1 | 20 | 1 | 46 |
| 47 | 20 | 1 | SPARE | | | | | 0.0 | 1.0 | GREENHOUSE 106 HF | 20 | 1 | 48 |
| 49 | 20 | 1 | SPARE | 0.0 | 0.5 | | | | | GREENHOUSE 106 ROOF VENT | 20 | 1 | 50 |
| 51 | 20 | 1 | SPARE | | | 0.0 | 0.5 | | | GREENHOUSE 106 SIDE VENT | 20 | 1 | 52 |
| 53 | 20 | 1 | SPARE | | | | | 0.0 | 0.0 | SPARE | 20 | 1 | 54 |
| TOTAL | | | | 7.4 | | 7.7 | | 6.9 | | * GFCI BREAKER | | | |

PANEL **1GW**
LOCATION: **GREENHOUSE CORRIDOR**
VOLT: **208Y/120V, 3Ø, 4W**
BUS: **225A**
LUG LOCATION: **BOTTOM FEED**
MAIN BUS: **100A MAIN BREAKER**
MOUNTING: **SURFACE**
**NEMA 3R ENCLOSURE**
PANELBOARD SCCR RATING (A): **10,000**

| CIRCUIT NO. | BREAKER AMPS | BREAKER POLES | DESCRIPTION | PHASE LOAD (KVA) A | | B | | C | | DESCRIPTION | BREAKER AMPS | BREAKER POLES | CIRCUIT NO. |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 20 | 1 | LIGHTING | 0.5 | 0.3 | | | | | GREENHOUSE 102 EF-1 | 15 | 3 | 2 |
| 3 | 20 | 1 | GREENHOUSE 102 CONTROL PANEL | | | 0.5 | 0.3 | | | - | - | - | 4 |
| 5 | 20 | 1 | GREENHOUSE 101 CONTROL PANEL | | | | | 0.5 | 0.3 | - | - | - | 6 |
| 7 | 20 | 1 | GREENHOUSE 102 RECS. | 0.5 | 0.3 | | | | | GREENHOUSE 102 EF-1 | 15 | 3 | 8 |
| 9 | 20 | 1 | GREENHOUSE 102 RECS. | | | 0.5 | 0.3 | | | - | - | - | 10 |
| 11 | 20 | 1 | GREENHOUSE 102 RECS. | | | | | 0.7 | 0.3 | - | - | - | 12 |
| 13 | 20 | 1 | GREENHOUSE 102 OVERHEAD RECS. | 0.5 | 0.3 | | | | | GREENHOUSE 102 EF-1 | 15 | 3 | 14 |
| 15 | 20 | 1 | GREENHOUSE 102 OVERHEAD RECS. | | | 0.5 | 0.3 | | | - | - | - | 16 |
| 17 | 20 | 1 | GREENHOUSE 102 OVERHEAD RECS. | | | | | 0.5 | 0.3 | - | - | - | 18 |
| 19 | 20 | 1 | GREENHOUSE 102 OVERHEAD RECS. | 0.5 | 0.3 | | | | | GREENHOUSE 101 EF-1 | 15 | 3 | 20 |
| 21 | 20 | 1 | GREENHOUSE 102 OVERHEAD RECS. | | | 0.4 | 0.3 | | | - | - | - | 22 |
| 23 | 20 | 1 | GREENHOUSE 102 OVERHEAD RECS. | | | | | 0.4 | 0.3 | - | - | - | 24 |
| 25 | 20 | 1 | GREENHOUSE 102 ECP SUMP PUMP | 0.5 | 0.3 | | | | | GREENHOUSE 101 EF-1 | 15 | 3 | 26 |
| 27 | 20 | 1 | GREENHOUSE 101 RECS. | | | 0.5 | 0.3 | | | - | - | - | 28 |
| 29 | 20 | 1 | GREENHOUSE 101 RECS. | | | | | 0.5 | 0.3 | - | - | - | 30 |
| 31 | 20 | 1 | GREENHOUSE 101 RECS. | 0.7 | 0.3 | | | | | GREENHOUSE 101 EF-1 | 15 | 3 | 32 |
| 33 | 20 | 1 | GREENHOUSE 101 OVERHEAD RECS. | | | 0.5 | 0.3 | | | - | - | - | 34 |
| 35 | 20 | 1 | GREENHOUSE 101 OVERHEAD RECS. | | | | | 0.5 | 0.3 | - | - | - | 36 |
| 37 | 20 | 1 | GREENHOUSE 101 OVERHEAD RECS. | 0.5 | 0.4 | | | | | GREENHOUSE 102 UH-1 | 20 | 1 | 38 |
| 39 | 20 | 1 | GREENHOUSE 101 OVERHEAD RECS. | | | 0.5 | 1.0 | | | GREENHOUSE 102 HF | 20 | 1 | 40 |
| 41 | 20 | 1 | GREENHOUSE 101 OVERHEAD RECS. | | | | | 0.4 | 0.5 | GREENHOUSE 102 ROOF VENT | 20 | 1 | 42 |
| 43 | 20 | 1 | GREENHOUSE 101 OVERHEAD RECS. | 0.4 | 0.5 | | | | | GREENHOUSE 102 SIDE VENT | 20 | 1 | 44 |
| 45 | 20 | 1 | GREENHOUSE 101 ECP SUMP PUMP | | | 0.5 | 0.4 | | | GREENHOUSE 101 UH-1 | 20 | 1 | 46 |
| 47 | 20 | 1 | SPARE | | | | | 0.0 | 1.0 | GREENHOUSE 101 HF | 20 | 1 | 48 |
| 49 | 20 | 1 | SPARE | 0.0 | 0.5 | | | | | GREENHOUSE 101 ROOF VENT | 20 | 1 | 50 |
| 51 | 20 | 1 | SPARE | | | 0.0 | 0.5 | | | GREENHOUSE 101 SIDE VENT | 20 | 1 | 52 |
| 53 | 20 | 1 | SPARE | | | | | 0.0 | 0.0 | SPARE | 20 | 1 | 54 |
| TOTAL | | | | 7.4 | | 7.7 | | 6.9 | | * GFCI BREAKER | | | |

**PANEL LEGEND**

| | | |
|---|---|---|
| 1GB | 1GD | 1GF |
| 1GH | 1GK | 1GM |
| 1GN | 1GV | 1GW |


THE Johnson • Mc Adams FIRM P.A.
ARCHITECTS/ENGINEERS • PLANNING • SURVEYING • MANAGEMENT
P.O. BOX 513, GREENWOOD, MISSISSIPPI – (662) 455–4943


| NO. | DATE | BY | DESCRIPTION |
|---|---|---|---|
| | | | |
| | | | |
| | | | |

REVISIONS

BRADEN T. DUKE
LICENSED PROFESSIONAL ENGINEER
35781
STATE OF MISSISSIPPI
04/27/26

| A–E FIRM | USDA |
|---|---|
| PROJECT MANAGER BP | EPM XXX |
| DESIGNER EH | PPM XXX |
| CHECKED BY BTD | SAFETY & HEALTH XXX |
| JOB # 4825 | REAL PROPERTY XXX |

USDA

USDA Agricultural Research Service

USDA AGRICULTURAL RESEARCH SERVICE
US HORTICULTURAL RESEARCH LABORATORY
REPAIR TORNADO DAMAGE
FT. PIERCE, FL

ELECTRICAL PANEL SCHEDULES

| PROJECT NO. | AGRICULTURAL RESEARCH SERVICE | SHEET |
|---|---|---|
| XXX | | E-702 |
| DATE 04/27/2026 | FT. PIERCE, FL | 91 OF 108 |

C:\Users\EVANHE~1\AppData\Local\Temp\AcPublish_1748\E-701.dwg
Apr 27, 2026 – 9:53am




1 ED100 **DEMO - OVERALL FLOOR PLAN**
SCALE: 1/16" = 1'-0"

## GENERAL DEMOLITION NOTES

A. PRIOR TO BEGINNING WORK, SURVEY EXISTING ELECTRICAL SYSTEMS. DOCUMENT, IN WRITING, SIGNED BY THE CONTRACTING OFFICER, ANY PORTIONS OF THE EXISTING SYSTEMS THAT ARE NOT OPERATING PROPERLY BEFORE CONSTRUCTION BEGINS. ANY ELECTRICAL SYSTEMS FOUND INOPERABLE AT THE END OF THE CONSTRUCTION PROCESS THAT HAVE NOT BEEN DOCUMENTED SHALL BE REPAIRED BY THE CONTRACTOR AT HIS OWN EXPENSE.

B. PRIOR TO BEGINNING THE DEMOLITION PROCESS, CONDUCT A COMPREHENSIVE SITE SURVEY WITH THE ASSISTANCE OF THE CONTRACTING OFFICER. IDENTIFY AND MARK ALL EXISTING EQUIPMENT TO REMAIN AND ALL EXISTING RACEWAYS AND CIRCUITRY THAT ARE PRESENTLY PASSING THROUGH THE CONSTRUCTION AREA THAT ARE FEEDING EXISTING EQUIPMENT TO REMAIN.

C. REMOVE ELECTRICAL EQUIPMENT IN AREAS BEING DEMOLISHED, AND ELECTRICAL EQUIPMENT FEEDING OTHER EQUIPMENT BEING DEMOLISHED. REMOVE RACEWAYS AND CIRCUITRY BACK TO THE PANEL OF ORIGINATION. WHERE CIRCUITS ARE NOT BEING COMPLETELY DEMOLISHED, REMOVE RACEWAYS AND CIRCUITRY BACK TO A JUNCTION BOX OR OTHER COMMON CONNECTION POINT AND RECIRCUIT EXISTING ELECTRICAL EQUIPMENT TO REMAIN AS REQUIRED. WHERE NECESSARY, COMPLETELY REFEED EXISTING ELECTRICAL EQUIPMENT THAT IS TO REMAIN IF REQUIRED. IT IS THE INTENT OF THESE DOCUMENTS THAT ALL EXISTING EQUIPMENT TO REMAIN BE KEPT COMPLETELY OPERABLE DURING CONSTRUCTION AND LEFT COMPLETELY OPERABLE AT THE END OF THE CONSTRUCTION PROCESS.

D. THE ELECTRICAL EQUIPMENT SHOWN IS PROVIDED TO CONVEY THE APPROXIMATE SCOPE OF THE WORK. IT IS THE INTENT OF THESE DOCUMENTS THAT ALL ELECTRICAL EQUIPMENT, RACEWAYS, AND CIRCUITRY IN THE AREA OF WORK BE DEMOLISHED UNLESS FEEDING EXISTING EQUIPMENT TO REMAIN.

E. PERFORM DEMOLITION WORK AS FOLLOWS:
   1. DEMOLISH DEVICE OR END OF LINE EQUIPMENT.
   2. DEMOLISH RACEWAYS AND CIRCUITRY FEEDING END OF LINE EQUIPMENT (INCLUDING ALL RACEWAYS AND CIRCUITRY ASSOCIATED WITH CONTROLS).
   3. LEAVE ALL RACEWAYS AND CIRCUITRY THAT COMPLETELY PASS-THROUGH THE SPACE COMPLETELY OPERABLE BY REROUTING THE CIRCUITS AS REQUIRED.

## KEYED NOTES

1. THE EXISTING FEEDER CONDUIT AND CIRCUITRY FOR ALL GREENHOUSE PANELS IS EXISTING TO REMAIN AND SHALL BE PROTECTED THROUGHOUT DEMOLITION. SEE 2/ED101 FOR TYPICAL ELEVATION VIEW OF GREENHOUSE PANELS.
2. THE EXISTING UNDERGROUND BRANCH CIRCUIT CONDUITS AT EACH GREENHOUSE SHALL BE CUT LEVEL WITH THE SLAB AND FILLED. SEE 2/ED101 FOR TYPICAL ELEVATION VIEW OF GREENHOUSE PANELS.
3. EXISTING 3" CONDUIT ROUTED BETWEEN ELECTRICAL ROOM AND EXTERIOR OF GREENHOUSE 114 IS EXISTING TO REMAIN FOR FUTURE USE. REMOVE EXISTING CABLE BACK TO IDF #2.
4. EXISTING JUNCTION BOX, UNDERGROUND 1"C., AND CABLE ROUTED TO TELEPHONE J-BOX SHALL BE DEMOLISHED IN ITS ENTIRETY.
5. DEMOLISH EXISTING DISCONNECT AND CIRCUITRY BETWEEN DISCONNECT AND UNIT. EXISTING CIRCUITRY BETWEEN PANEL AND DISCONNECT SHALL REMAIN.
6. EXISTING CONDUIT & CIRCUITRY SHALL BE DEMOLISHED BACK TO PANEL. TURN BREAKER OFF & LABEL AS SPARE.
7. REMOVE EXISTING ACCESSIBLE DOOR OPENER AND STORE DURING DEMOLITION. REINSTALL ONCE NEW DOOR HARDWARE IS IN PLACE.
8. EXISTING ACCESS CONTROL SYSTEM SHALL BE REPLACED. SEE E-002 FOR DETAILS ON NEW SYSTEM. COORDINATE DEMO/REPLACEMENT WITH PHASING PLAN.

## BID OPTION LEGEND

BASE BID
BID OPTION #1
BID OPTION #2
BID OPTION #3



2 ED100 KEY PLAN
SCALE: N.T.S

## GRAPHIC SCALE

16' 0 8' 16'
SCALE: 1/16"= 1'-0"

| NO. | DATE | BY | DESCRIPTION |
|---|---|---|---|

REVISIONS

The Johnson + McAdams Firm P.A. ARCHITECTS/ENGINEERS • PLANNING • SURVEYING • MANAGEMENT P.O. BOX 513, GREENWOOD, MISSISSIPPI • (662) 455-4943

| A-E FIRM | USDA |
|---|---|
| PROJECT MANAGER BP | EPM XXX |
| DESIGNER EH | PPM XXX |
| CHECKED BY BTD | SAFETY & HEALTH XXX |
| JOB # 4825 | REAL PROPERTY XXX |

BRADEN T. DUKE, PROFESSIONAL ENGINEER, 35781, STATE OF MISSISSIPPI, 04/27/26

USDA Agricultural Research Service

USDA AGRICULTURAL RESEARCH SERVICE
US HORTICULTURAL RESEARCH LABORATORY
REPAIR TORNADO DAMAGE
FT. PIERCE, FL

OVERALL ELECTRICAL DEMOLITION PLAN

PROJECT NO. XXX | AGRICULTURAL RESEARCH SERVICE | SHEET ED100
DATE 04/27/2026 | FT. PIERCE, FL | 92 OF 108

J:\greenwood\2025 Jobs\4825 USDA Tornado Damage Repair Ft. Pierce FL\07 Working Folder\Elec\CAD\ED100.dwg
Apr 27, 2026 - 9:53am




1 ED101 ENLARGED TYPICAL GREENHOUSE DEMOLITION PLAN

SCALE: 1/4" = 1'-0"




NOTE: ALL EQUIPMENT SHOWN SHALL BE DEMOLISHED WITH THE EXCEPTION OF THE PANEL FEEDER CONDUIT AND CIRCUITRY (TYPICAL OF ALL GREENHOUSES).

THE CONTRACTOR SHALL TAKE EXTREME CARE AS TO NOT DAMAGE EXISTING FEEDER CONDUIT AND CONDUCTORS. IF DAMAGE OCCURS, THE CONDUIT AND/OR CONDUCTORS SHALL BE REPLACED AT NO COST TO THE GOVERNMENT.

2 ED101 TYPICAL GREENHOUSE PANEL DETAIL

SCALE: NONE

## GENERAL DEMOLITION NOTES

A. PRIOR TO BEGINNING WORK, SURVEY EXISTING ELECTRICAL SYSTEMS. DOCUMENT, IN WRITING, SIGNED BY THE CONTRACTING OFFICER, ANY PORTIONS OF THE EXISTING SYSTEMS THAT ARE NOT OPERATING PROPERLY BEFORE CONSTRUCTION BEGINS. ANY ELECTRICAL SYSTEMS FOUND INOPERABLE AT THE END OF THE CONSTRUCTION PROCESS THAT HAVE NOT BEEN SO DOCUMENTED SHALL BE REPAIRED BY THE CONTRACTOR AT HIS OWN EXPENSE.

B. PRIOR TO BEGINNING THE DEMOLITION PROCESS, CONDUCT A COMPREHENSIVE SITE SURVEY WITH THE ASSISTANCE OF THE CONTRACTING OFFICER. IDENTIFY AND MARK ALL EXISTING EQUIPMENT TO REMAIN AND ALL EXISTING RACEWAYS AND CIRCUITRY THAT ARE PRESENTLY PASSING THROUGH THE CONSTRUCTION AREA THAT ARE FEEDING EXISTING EQUIPMENT TO REMAIN.

C. REMOVE ELECTRICAL EQUIPMENT IN AREAS BEING DEMOLISHED, AND ELECTRICAL EQUIPMENT FEEDING OTHER EQUIPMENT BEING DEMOLISHED. REMOVE RACEWAYS AND CIRCUITRY BACK TO THE PANEL OF ORIGINATION. WHERE CIRCUITS ARE NOT BEING COMPLETELY DEMOLISHED, REMOVE RACEWAYS AND CIRCUITRY BACK TO A JUNCTION BOX OR OTHER COMMON CONNECTION POINT AND RECIRCUIT EXISTING ELECTRICAL EQUIPMENT TO REMAIN AS REQUIRED. WHERE NECESSARY, COMPLETELY REFEED EXISTING ELECTRICAL EQUIPMENT THAT IS TO REMAIN IF REQUIRED. IT IS THE INTENT OF THESE DOCUMENTS THAT ALL EXISTING EQUIPMENT TO REMAIN BE KEPT COMPLETELY OPERABLE DURING CONSTRUCTION AND LEFT COMPLETELY OPERABLE AT THE END OF THE CONSTRUCTION PROCESS.

D. THE ELECTRICAL EQUIPMENT SHOWN IS PROVIDED TO CONVEY THE APPROXIMATE SCOPE OF THE WORK. IT IS THE INTENT OF THESE DOCUMENTS THAT ALL ELECTRICAL EQUIPMENT, RACEWAYS, AND CIRCUITRY IN THE AREA OF WORK BE DEMOLISHED UNLESS FEEDING EXISTING EQUIPMENT TO REMAIN.

E. PERFORM DEMOLITION WORK AS FOLLOWS:
   1. DEMOLISH DEVICE OR END OF LINE EQUIPMENT.
   2. DEMOLISH RACEWAYS AND CIRCUITRY FEEDING END OF LINE EQUIPMENT (INCLUDING ALL RACEWAYS AND CIRCUITRY ASSOCIATED WITH CONTROLS).
   3. LEAVE ALL RACEWAYS AND CIRCUITRY THAT COMPLETELY PASS-THROUGH THE SPACE COMPLETELY OPERABLE BY REROUTING THE CIRCUITS AS REQUIRED.

## KEYED NOTES

1. THE EXISTING FEEDER CONDUIT AND CIRCUITRY FOR ALL GREENHOUSE PANELS IS EXISTING TO REMAIN AND SHALL BE PROTECTED THROUGHOUT DEMOLITION. SEE 2/ED101 FOR TYPICAL ELEVATION VIEW OF GREENHOUSE PANELS.

2. THE EXISTING UNDERGROUND BRANCH CIRCUIT CONDUITS AT EACH GREENHOUSE SHALL BE CUT LEVEL WITH THE SLAB AND FILLED. SEE 2/ED101 FOR TYPICAL ELEVATION VIEW OF GREENHOUSE PANELS.

## GRAPHIC SCALE

4' 0 2' 4'

SCALE: 1/4"=1'-0"

| NO. | DATE | BY | DESCRIPTION |
|---|---|---|---|

REVISIONS

The Johnson + McAdams Firm P.A.
ARCHITECTS/ENGINEERS • PLANNING • SURVEYING • MANAGEMENT
P.O. BOX 513, GREENWOOD, MISSISSIPPI • (662) 455-4943

USDA Agricultural Research Service

USDA AGRICULTURAL RESEARCH SERVICE
US HORTICULTURAL RESEARCH LABORATORY
REPAIR TORNADO DAMAGE
FT. PIERCE, FL

ENLARGED ELECTRICAL DEMOLITION PLAN

| A–E FIRM | USDA |
|---|---|
| PROJECT MANAGER BP | EPM XXX |
| DESIGNER EH | PPM XXX |
| CHECKED BY BTD | SAFETY & HEALTH XXX |
| JOB # 4825 | REAL PROPERTY XXX |

PROJECT NO. XXX

DATE 04/27/2026

AGRICULTURAL RESEARCH SERVICE

FT. PIERCE, FL

SHEET ED101

93 OF 108

J:\greenwood\2025 Jobs\4825 USDA Tornado Damage Repair Ft. Pierce FL\07 Working Folder\Elec\CAD\ED101.dwg
Apr 27, 2026 – 9:53am




BID OPTION #4 - PICO'S FARM ENLARGED GREENHOUSE DEMOLITION PLAN (1/ED102)
SCALE: 1/4" = 1'-0"




GREENHOUSE PANEL DETAIL (2/ED102)
SCALE: NONE




BID OPTION #4 - PICO'S FARM HOOPHOUSE DEMOLITION PLAN (3/ED102)
SCALE: 3/16" = 1'-0"

## KEYED NOTES

1. EXISTING PANEL, ELECTRICAL GUTTER, AND ALL CONTROL PANELS SHALL BE DEMOLISHED. THE EXISTING FEEDER CONDUIT AND CIRCUITRY SHALL REMAIN AND BE PROTECTED DURING DEMOLITION. FEEDER BREAKER IS LOCATED IN PANEL "1VC" (13,15,17) IN THE MAIN ELECTRICAL ROOM.
2. EXISTING DISCONNECT, TRANSFORMER, PANEL, UNDERGROUND CONDUIT, BRANCH CIRCUITRY, AND RECEPTACLES SHALL BE DEMOLISHED. EXISTING 480V FEEDER CONDUIT AND CONDUCTORS SHALL REMAIN AND BE PROTECTED DURING DEMOLITION. FEEDER BREAKER IS LOCATED IN PANEL "1WD" IN MAIN ELECTRICAL ROOM.

## GRAPHIC SCALE

4' 0 2' 4'
SCALE: 1/4"=1'-0"

6' 0 3' 6'
SCALE: 3/16" = 1'-0'

## GENERAL NOTES

A. PRIOR TO BEGINNING WORK, SURVEY EXISTING ELECTRICAL SYSTEMS. DOCUMENT, IN WRITING, SIGNED BY THE CONTRACTING OFFICER, ANY PORTIONS OF THE EXISTING SYSTEMS THAT ARE NOT OPERATING PROPERLY BEFORE CONSTRUCTION BEGINS. ANY ELECTRICAL SYSTEMS FOUND INOPERABLE AT THE END OF THE CONSTRUCTION PROCESS THAT HAVE NOT BEEN SO DOCUMENTED SHALL BE REPAIRED BY THE CONTRACTOR AT HIS OWN EXPENSE.

B. PRIOR TO BEGINNING THE DEMOLITION PROCESS, CONDUCT A COMPREHENSIVE SITE SURVEY WITH THE ASSISTANCE OF THE CONTRACTING OFFICER. IDENTIFY AND MARK ALL EXISTING EQUIPMENT TO REMAIN AND ALL EXISTING RACEWAYS AND CIRCUITRY THAT ARE PRESENTLY PASSING THROUGH THE CONSTRUCTION AREA THAT ARE FEEDING EXISTING EQUIPMENT TO REMAIN.

C. REMOVE ELECTRICAL EQUIPMENT IN AREAS BEING DEMOLISHED, AND ELECTRICAL EQUIPMENT FEEDING OTHER EQUIPMENT BEING DEMOLISHED. REMOVE RACEWAYS AND CIRCUITRY BACK TO THE PANEL OF ORIGINATION. WHERE CIRCUITS ARE NOT BEING COMPLETELY DEMOLISHED, REMOVE RACEWAYS AND CIRCUITRY BACK TO A JUNCTION BOX OR OTHER COMMON CONNECTION POINT AND RECIRCUIT EXISTING ELECTRICAL EQUIPMENT TO REMAIN AS REQUIRED. WHERE NECESSARY, COMPLETELY REFEED EXISTING ELECTRICAL EQUIPMENT THAT IS TO REMAIN IF REQUIRED. IT IS THE INTENT OF THESE DOCUMENTS THAT ALL EXISTING EQUIPMENT TO REMAIN BE KEPT COMPLETELY OPERABLE DURING CONSTRUCTION AND LEFT COMPLETELY OPERABLE AT THE END OF THE CONSTRUCTION PROCESS.

D. THE ELECTRICAL EQUIPMENT SHOWN IS PROVIDED TO CONVEY THE APPROXIMATE SCOPE OF THE WORK. IT IS THE INTENT OF THESE DOCUMENTS THAT ALL ELECTRICAL EQUIPMENT, RACEWAYS, AND CIRCUITRY IN THE AREA OF WORK BE DEMOLISHED UNLESS FEEDING EXISTING EQUIPMENT TO REMAIN.

E. PERFORM DEMOLITION WORK AS FOLLOWS:
   1. DEMOLISH DEVICE OR END OF LINE EQUIPMENT.
   2. DEMOLISH RACEWAYS AND CIRCUITRY FEEDING END OF LINE EQUIPMENT (INCLUDING ALL RACEWAYS AND CIRCUITRY ASSOCIATED WITH CONTROLS).
   3. LEAVE ALL RACEWAYS AND CIRCUITRY THAT COMPLETELY PASS-THROUGH THE SPACE COMPLETELY OPERABLE BY REROUTING THE CIRCUITS AS REQUIRED.




PICOS FARM KEYPLAN
SCALE: N.T.S

| NO. | DATE | BY | DESCRIPTION |
|---|---|---|---|
| | | | |

REVISIONS

The Johnson + McAdams Firm P.A. — ARCHITECTS/ENGINEERS - PLANNING - SURVEYING - MANAGEMENT

| A–E FIRM | USDA |
|---|---|
| PROJECT MANAGER BP | EPM XXX |
| DESIGNER EH | PPM XXX |
| CHECKED BY BTD | SAFETY & HEALTH XXX |
| JOB # 4825 | REAL PROPERTY XXX |

USDA Agricultural Research Service

USDA AGRICULTURAL RESEARCH SERVICE
US HORTICULTURAL RESEARCH LABORATORY
REPAIR TORNADO DAMAGE
FT. PIERCE, FL

BID OPTION #4 ELECTRICAL DEMOLITION PLAN

PROJECT NO. XXX
DATE 04/27/2026
AGRICULTURAL RESEARCH SERVICE — FT. PIERCE, FL
SHEET ED102
94 OF 108

J:\greenwood\2025 Jobs\4825 USDA Tornado Damage Repair Ft. Pierce FL\07 Working Folder\Elec\CAD\ED102.dwg
Apr 27, 2026 - 9:53am




1 ED103 BID OPTION #5 - LEESBURG FARM ENLARGED GREENHOUSE DEMOLITION PLAN

SCALE: 1/4" = 1'-0"

N

## KEYED NOTES

1. DEMOLISH EXISTING PANEL. EXISTING UNDERGROUND FEEDER CONDUIT AND CIRCUITRY SHALL BE DEMOLISHED BACK TO SWBD MDP APPROX 150' NORTH OF GREENHOUSE. TURN BREAKER OFF AND LABEL AS SPARE.

## GRAPHIC SCALE



SCALE: 1/4"=1'-0"

## GENERAL DEMOLITION NOTES

A. PRIOR TO BEGINNING WORK, SURVEY EXISTING ELECTRICAL SYSTEMS. DOCUMENT, IN WRITING, SIGNED BY THE CONTRACTING OFFICER, ANY PORTIONS OF THE EXISTING SYSTEMS THAT ARE NOT OPERATING PROPERLY BEFORE CONSTRUCTION BEGINS. ANY ELECTRICAL SYSTEMS FOUND INOPERABLE AT THE END OF THE CONSTRUCTION PROCESS THAT HAVE NOT BEEN SO DOCUMENTED SHALL BE REPAIRED BY THE CONTRACTOR AT HIS OWN EXPENSE.

B. PRIOR TO BEGINNING THE DEMOLITION PROCESS, CONDUCT A COMPREHENSIVE SITE SURVEY WITH THE ASSISTANCE OF THE CONTRACTING OFFICER. IDENTIFY AND MARK ALL EXISTING EQUIPMENT TO REMAIN AND ALL EXISTING RACEWAYS AND CIRCUITRY THAT ARE PRESENTLY PASSING THROUGH THE CONSTRUCTION AREA THAT ARE FEEDING EXISTING EQUIPMENT TO REMAIN.

C. REMOVE ELECTRICAL EQUIPMENT IN AREAS BEING DEMOLISHED, AND ELECTRICAL EQUIPMENT FEEDING OTHER EQUIPMENT BEING DEMOLISHED. REMOVE RACEWAYS AND CIRCUITRY BACK TO THE PANEL OF ORIGINATION. WHERE CIRCUITS ARE NOT BEING COMPLETELY DEMOLISHED, REMOVE RACEWAYS AND CIRCUITRY BACK TO A JUNCTION BOX OR OTHER COMMON CONNECTION POINT AND RECIRCUIT EXISTING ELECTRICAL EQUIPMENT TO REMAIN AS REQUIRED. WHERE NECESSARY, COMPLETELY REFEED EXISTING ELECTRICAL EQUIPMENT THAT IS TO REMAIN IF REQUIRED. IT IS THE INTENT OF THESE DOCUMENTS THAT ALL EXISTING EQUIPMENT TO REMAIN BE KEPT COMPLETELY OPERABLE DURING CONSTRUCTION AND LEFT COMPLETELY OPERABLE AT THE END OF THE CONSTRUCTION PROCESS.

D. THE ELECTRICAL EQUIPMENT SHOWN IS PROVIDED TO CONVEY THE APPROXIMATE SCOPE OF THE WORK. IT IS THE INTENT OF THESE DOCUMENTS THAT ALL ELECTRICAL EQUIPMENT, RACEWAYS, AND CIRCUITRY IN THE AREA OF WORK BE DEMOLISHED UNLESS FEEDING EXISTING EQUIPMENT TO REMAIN.

E. PERFORM DEMOLITION WORK AS FOLLOWS:
   1. DEMOLISH DEVICE OR END OF LINE EQUIPMENT.
   2. DEMOLISH RACEWAYS AND CIRCUITRY FEEDING END OF LINE EQUIPMENT (INCLUDING ALL RACEWAYS AND CIRCUITRY ASSOCIATED WITH CONTROLS).
   3. LEAVE ALL RACEWAYS AND CIRCUITRY THAT COMPLETELY PASS-THROUGH THE SPACE COMPLETELY OPERABLE BY REROUTING THE CIRCUITS AS REQUIRED.




LEESBURG KEYPLAN

SCALE: N.T.S

N

| NO. | DATE | BY | DESCRIPTION |
|---|---|---|---|
| | | | |
| | | | |
| | | | |

REVISIONS

THE Johnson • Mc Adams FIRM P.A.
ARCHITECTS/ENGINEERS • PLANNING • SURVEYING • MANAGEMENT
P.O. BOX 513, GREENWOOD, MISSISSIPPI – (662) 455-4943

| A–E FIRM | USDA |
|---|---|
| PROJECT MANAGER BP | EPM XXX |
| DESIGNER EH | PPM XXX |
| CHECKED BY BTD | SAFETY & HEALTH XXX |
| JOB # 4825 | REAL PROPERTY XXX |

USDA

USDA Agricultural Research Service

USDA AGRICULTURAL RESEARCH SERVICE
US HORTICULTURAL RESEARCH LABORATORY
REPAIR TORNADO DAMAGE
FT. PIERCE, FL

BID OPTION #5 ELECTRICAL DEMOLITION PLAN

| PROJECT NO. XXX | AGRICULTURAL RESEARCH SERVICE | SHEET ED103 |
|---|---|---|
| DATE 04/27/2026 | FT. PIERCE, FL | 95 OF 108 |

BRADEN T. DUKE
04/27/26
STATE OF MISSISSIPPI

J:\greenwood\2025 Jobs\4825 USDA Tornado Damage Repair Ft. Pierce FL\07 Working Folder\Elec\CAD\ED103.dwg
Apr 27, 2026 – 9:53am




2 ED104 BID OPTION #5 - LEESBURG FARM ENLARGED PUMP STORAGE DEMOLITION PLAN
SCALE: 1/4" = 1'-0"




1 ED104 BID OPTION #5 - LEESBURG FARM ENLARGED GREENHOUSE DEMOLITION PLAN
SCALE: 1/4" = 1'-0"

## KEYED NOTES

1. DEMOLISH EXISTING PANEL AND UNDERGROUND BRANCH CIRCUITS. BRANCH CIRCUIT CONDUITS SHALL BE CUT LEVEL WITH THE SLAB AND FILLED. THE EXISTING FEEDER CONDUIT AND CIRCUITRY SHALL REMAIN AND BE PROTECTED DURING DEMOLITION.
2. DEMOLISH EXISTING PANEL AND UNDERGROUND BRANCH CIRCUITS. BRANCH CIRCUIT CONDUITS SHALL BE CUT LEVEL WITH THE SLAB AND FILLED. THE EXISTING FEEDER CONDUIT SHALL BE INTERCEPTED OUTSIDE THE CONSTRUCTION ZONE AND REROUTED TO NEW PANEL LOCATION. SEE EP104.

## GRAPHIC SCALE

4' 0 2' 4'
SCALE: 1/4"=1'-0"

## GENERAL DEMOLITION NOTES

A. PRIOR TO BEGINNING WORK, SURVEY EXISTING ELECTRICAL SYSTEMS. DOCUMENT, IN WRITING, SIGNED BY THE CONTRACTING OFFICER, ANY PORTIONS OF THE EXISTING SYSTEMS THAT ARE NOT OPERATING PROPERLY BEFORE CONSTRUCTION BEGINS. ANY ELECTRICAL SYSTEMS FOUND INOPERABLE AT THE END OF THE CONSTRUCTION PROCESS THAT HAVE NOT BEEN SO DOCUMENTED SHALL BE REPAIRED BY THE CONTRACTOR AT HIS OWN EXPENSE.

B. PRIOR TO BEGINNING THE DEMOLITION PROCESS, CONDUCT A COMPREHENSIVE SITE SURVEY WITH THE ASSISTANCE OF THE CONTRACTING OFFICER. IDENTIFY AND MARK ALL EXISTING EQUIPMENT TO REMAIN AND ALL EXISTING RACEWAYS AND CIRCUITRY THAT ARE PRESENTLY PASSING THROUGH THE CONSTRUCTION AREA THAT ARE FEEDING EXISTING EQUIPMENT TO REMAIN.

C. REMOVE ELECTRICAL EQUIPMENT IN AREAS BEING DEMOLISHED, AND ELECTRICAL EQUIPMENT FEEDING OTHER EQUIPMENT BEING DEMOLISHED. REMOVE RACEWAYS AND CIRCUITRY BACK TO THE PANEL OF ORIGINATION. WHERE CIRCUITS ARE NOT BEING COMPLETELY DEMOLISHED, REMOVE RACEWAYS AND CIRCUITRY BACK TO A JUNCTION BOX OR OTHER COMMON CONNECTION POINT AND RECIRCUIT EXISTING ELECTRICAL EQUIPMENT TO REMAIN AS REQUIRED. WHERE NECESSARY, COMPLETELY REFEED EXISTING ELECTRICAL EQUIPMENT THAT IS TO REMAIN IF REQUIRED. IT IS THE INTENT OF THESE DOCUMENTS THAT ALL EXISTING EQUIPMENT TO REMAIN BE KEPT COMPLETELY OPERABLE DURING CONSTRUCTION AND LEFT COMPLETELY OPERABLE AT THE END OF THE CONSTRUCTION PROCESS.

D. THE ELECTRICAL EQUIPMENT SHOWN IS PROVIDED TO CONVEY THE APPROXIMATE SCOPE OF THE WORK. IT IS THE INTENT OF THESE DOCUMENTS THAT ALL ELECTRICAL EQUIPMENT, RACEWAYS, AND CIRCUITRY IN THE AREA OF WORK BE DEMOLISHED UNLESS FEEDING EXISTING EQUIPMENT TO REMAIN.

E. PERFORM DEMOLITION WORK AS FOLLOWS:
   1. DEMOLISH DEVICE OR END OF LINE EQUIPMENT.
   2. DEMOLISH RACEWAYS AND CIRCUITRY FEEDING END OF LINE EQUIPMENT (INCLUDING ALL RACEWAYS AND CIRCUITRY ASSOCIATED WITH CONTROLS).
   3. LEAVE ALL RACEWAYS AND CIRCUITRY THAT COMPLETELY PASS-THROUGH THE SPACE COMPLETELY OPERABLE BY REROUTING THE CIRCUITS AS REQUIRED.




LEESBURG KEYPLAN
SCALE: N.T.S

| NO. | DATE | BY | DESCRIPTION |
|---|---|---|---|

REVISIONS

The Johnson + McAdams Firm P.A. — ARCHITECTS/ENGINEERS • PLANNING • SURVEYING • MANAGEMENT — P.O. BOX 513, GREENWOOD, MISSISSIPPI

| A-E FIRM | USDA |
|---|---|
| PROJECT MANAGER BP | EPM XXX |
| DESIGNER EH | PPM XXX |
| CHECKED BY BTD | SAFETY & HEALTH XXX |
| JOB # 4825 | REAL PROPERTY XXX |

USDA — USDA Agricultural Research Service

USDA AGRICULTURAL RESEARCH SERVICE
US HORTICULTURAL RESEARCH LABORATORY
REPAIR TORNADO DAMAGE
FT. PIERCE, FL

BID OPTION #5 ELECTRICAL DEMOLITION PLAN

| PROJECT NO. XXX | AGRICULTURAL RESEARCH SERVICE | SHEET ED104 |
|---|---|---|
| DATE 04/27/2026 | FT. PIERCE, FL | 96 OF 108 |

BRADEN T. DUKE — ENGINEER — 35781 — STATE OF MISSISSIPPI — 04/27/26

J:\greenwood\2025 Jobs\4825 USDA Tornado Damage Repair Ft. Pierce FL\07 Working Folder\Elec\CAD\ED103.dwg
Apr 27, 2026 – 9:53am

J:\greenwood\2025 Jobs\4825 USDA Tornado Damage Repair Ft. Pierce FL\07 Working Folder\Elec\CAD\EL101.dwg
Apr 27, 2026 – 9:53am




1 EL101 BASE BID LIGHTING PLAN
SCALE: 3/32" = 1'-0"

## GENERAL NOTES

A. ALL FIXTURES THROUGHOUT THE GREENHOUSE SHALL BE VAPOR-TIGHT GASKETED 4' LINEAR FIXTURES.

B. ALL EMERGENCY FIXTURES SHALL BE PROVIDED WITH AN INTEGRAL 10W, 120V EMERGENCY BATTERY PACK.

C. ALL FIXTURES LOCATED IN THE GREENHOUSE CORRIDORS SHALL BE AUTOMATICALLY CONTROLLED BY MOTION SENSORS. MOTION SENSORS SHALL AUTOMATICALLY TURN LIGHTS OFF AFTER 20 MINUTES OF VACANCY.

D. ALL FIXTURES LOCATED IN THE GREENHOUSES SHALL BE MANUALLY CONTROLLED WITH WEATHERPROOF SWITCHES LOCATED OUTSIDE EACH GREENHOUSE.

E. ALL GREENHOUSE LIGHT SWITCHES SHALL BE PROVIDED WITH WEATHERPROOF COVERS.

## KEYED NOTES

1. LIGHTING FIXTURES IN THIS ROOM SHALL BE FED FROM CIRCUIT "1GW-1".
2. LIGHTING FIXTURES IN THIS ROOM SHALL BE FED FROM CIRCUIT "1GX-1".
3. LIGHTING FIXTURES IN THIS ROOM SHALL BE FED FROM CIRCUIT "1GF-1".
4. LIGHTING FIXTURES IN THIS ROOM SHALL BE FED FROM CIRCUIT "1GG-1".
5. LIGHTING FIXTURES IN THIS ROOM SHALL BE FED FROM CIRCUIT "1GH-1".
6. LIGHTING FIXTURES IN THIS ROOM SHALL BE FED FROM CIRCUIT "1GJ-1".
7. LIGHTING FIXTURES SHOWN IN THIS SECTION OF HALLWAY SHALL BE FED FROM CIRCUIT "1GH-53".

## GRAPHIC SCALE







2 EL101 KEY PLAN
SCALE: N.T.S

| NO. | DATE | BY | DESCRIPTION |
|---|---|---|---|

REVISIONS

The Johnson + McAdams Firm P.A.
ARCHITECTS/ENGINEERS • PLANNING • SURVEYING • MANAGEMENT

BRADEN T. DUKE
PROFESSIONAL ENGINEER
35781
STATE OF MISSISSIPPI
04/27/26

| A–E FIRM | USDA |
|---|---|
| PROJECT MANAGER BP | EPM XXX |
| DESIGNER EH | PPM XXX |
| CHECKED BY BTD | SAFETY & HEALTH XXX |
| JOB # 4825 | REAL PROPERTY XXX |

USDA

USDA Agricultural Research Service

USDA AGRICULTURAL RESEARCH SERVICE
US HORTICULTURAL RESEARCH LABORATORY
REPAIR TORNADO DAMAGE
FT. PIERCE, FL

BASE BID LIGHTING PLAN

| PROJECT NO. XXX | AGRICULTURAL RESEARCH SERVICE | SHEET EL101 |
|---|---|---|
| DATE 04/27/2026 | FT. PIERCE, FL | 97 OF 108 |




1 EL102 BID OPTION #1 LIGHTING PLAN
SCALE: 3/32" = 1'-0"

## GENERAL NOTES

A. ALL FIXTURES THROUGHOUT THE GREENHOUSE SHALL BE VAPOR-TIGHT GASKETED 4' LINEAR FIXTURES.

B. ALL EMERGENCY FIXTURES SHALL BE PROVIDED WITH AN INTEGRAL 10W, 120V EMERGENCY BATTERY PACK.

C. ALL FIXTURES LOCATED IN THE GREENHOUSE CORRIDORS SHALL BE AUTOMATICALLY CONTROLLED BY MOTION SENSORS. MOTION SENSORS SHALL AUTOMATICALLY TURN LIGHTS OFF AFTER 20 MINUTES OF VACANCY.

D. ALL FIXTURES LOCATED IN THE GREENHOUSES SHALL BE MANUALLY CONTROLLED WITH WEATHERPROOF SWITCHES LOCATED OUTSIDE EACH GREENHOUSE.

E. ALL GREENHOUSE LIGHT SWITCHES SHALL BE PROVIDED WITH WEATHERPROOF COVERS.

## KEYED NOTES

1. LIGHTING FIXTURES IN THIS ROOM SHALL BE FED FROM CIRCUIT "1GK-1".
2. LIGHTING FIXTURES IN THIS ROOM SHALL BE FED FROM CIRCUIT "1GL-1".
3. LIGHTING FIXTURES IN THIS ROOM SHALL BE FED FROM CIRCUIT "1GM-1".
4. LIGHTING FIXTURES IN THIS ROOM SHALL BE FED FROM CIRCUIT "1GN-1".
5. LIGHTING FIXTURES IN THIS ROOM SHALL BE FED FROM CIRCUIT "1GP-1".
6. LIGHTING FIXTURES IN THIS ROOM SHALL BE FED FROM CIRCUIT "1GQ-1".
7. LIGHTING FIXTURES IN THIS ROOM SHALL BE FED FROM CIRCUIT "1GS-1".
8. LIGHTING FIXTURES IN THIS ROOM SHALL BE FED FROM CIRCUIT "1GR-1".
9. LIGHTING FIXTURES IN THIS ROOM SHALL BE FED FROM CIRCUIT "1GT-1".
10. LIGHTING FIXTURES SHOWN IN THIS SECTION OF HALLWAY SHALL BE FED FROM CIRCUIT "1GM-53".

## GRAPHIC SCALE

10' 0 5' 10'
SCALE: 3/32" = 1'-0"




2 EL102 KEY PLAN
SCALE: N.T.S

| NO. | DATE | BY | DESCRIPTION |
|---|---|---|---|

REVISIONS

The Johnson + McAdams Firm P.A.
ARCHITECTS/ENGINEERS • PLANNING • SURVEYING • MANAGEMENT

| A-E FIRM | USDA |
|---|---|
| PROJECT MANAGER BP | EPM XXX |
| DESIGNER EH | PPM XXX |
| CHECKED BY BTD | SAFETY & HEALTH XXX |
| JOB # 4825 | REAL PROPERTY XXX |

USDA Agricultural Research Service

USDA AGRICULTURAL RESEARCH SERVICE
US HORTICULTURAL RESEARCH LABORATORY
REPAIR TORNADO DAMAGE
FT. PIERCE, FL

BID OPTION #1 LIGHTING PLAN

| PROJECT NO. XXX | AGRICULTURAL RESEARCH SERVICE | SHEET EL102 |
|---|---|---|
| DATE 04/27/2026 | FT. PIERCE, FL | 98 OF 108 |

J:\greenwood\2025 Jobs\4825 USDA Tornado Damage Repair Ft. Pierce FL\07 Working Folder\Elec\CAD\EL101.dwg
Apr 27, 2026 - 9:53am




1 EL103 BID OPTION #2 & #3 LIGHTING PLAN
SCALE: 3/32" = 1'-0"

## GENERAL NOTES

A. ALL FIXTURES THROUGHOUT THE GREENHOUSE SHALL BE VAPOR-TIGHT GASKETED 4' LINEAR FIXTURES.

B. ALL EMERGENCY FIXTURES SHALL BE PROVIDED WITH AN INTEGRAL 10W, 120V EMERGENCY BATTERY PACK.

C. ALL FIXTURES LOCATED IN THE GREENHOUSE CORRIDORS SHALL BE AUTOMATICALLY CONTROLLED BY MOTION SENSORS. MOTION SENSORS SHALL AUTOMATICALLY TURN LIGHTS OFF AFTER 20 MINUTES OF VACANCY.

D. ALL FIXTURES LOCATED IN THE GREENHOUSES SHALL BE MANUALLY CONTROLLED WITH WEATHERPROOF SWITCHES LOCATED OUTSIDE EACH GREENHOUSE.

E. ALL GREENHOUSE LIGHT SWITCHES SHALL BE PROVIDED WITH WEATHERPROOF COVERS.

## KEYED NOTES

1. LIGHTING FIXTURES IN THIS ROOM SHALL BE FED FROM CIRCUIT "1GU-1".
2. LIGHTING FIXTURES IN THIS ROOM SHALL BE FED FROM CIRCUIT "1GV-1".
3. LIGHTING FIXTURES IN THIS ROOM SHALL BE FED FROM CIRCUIT "1GA-1".
4. LIGHTING FIXTURES IN THIS ROOM SHALL BE FED FROM CIRCUIT "1GB-1".
5. LIGHTING FIXTURES IN THIS ROOM SHALL BE FED FROM CIRCUIT "1GC-1".
6. LIGHTING FIXTURES IN THIS ROOM SHALL BE FED FROM CIRCUIT "1GD-1".
7. LIGHTING FIXTURES IN THIS ROOM SHALL BE FED FROM CIRCUIT "1GE-1".
8. LIGHTING FIXTURES SHOWN IN THIS SECTION OF HALLWAY SHALL BE FED FROM CIRCUIT "1GE-41".

## GRAPHIC SCALE

10' 0 5' 10'
SCALE: 3/32"= 1'-0'

BID OPTION #2 BID OPTION #3




2 EL103 KEY PLAN
SCALE: N.T.S

| NO. | DATE | BY | DESCRIPTION |
|---|---|---|---|

REVISIONS

The Johnson + McAdams Firm P.A.
ARCHITECTS / ENGINEERS • PLANNING • SURVEYING • MANAGEMENT
P.O. BOX 513, GREENWOOD, MISSISSIPPI • (662) 455-4943

| A-E FIRM | USDA |
|---|---|
| PROJECT MANAGER BP | EPM XXX |
| DESIGNER EH | PPM XXX |
| CHECKED BY BTD | SAFETY & HEALTH XXX |
| JOB # 4825 | REAL PROPERTY XXX |

USDA Agricultural Research Service

USDA AGRICULTURAL RESEARCH SERVICE
US HORTICULTURAL RESEARCH LABORATORY
REPAIR TORNADO DAMAGE
FT. PIERCE, FL

BID OPTION #2 & #3 LIGHTING PLAN

PROJECT NO. XXX
DATE 04/27/2026
AGRICULTURAL RESEARCH SERVICE
FT. PIERCE, FL
SHEET EL103
99 OF 108

J:\greenwood\2025 Jobs\4825 USDA Tornado Damage Repair Ft. Pierce FL\07 Working Folder\Elec\CAD\EL101.dwg
Apr 27, 2026 - 9:53am




1 EL201 NORMAL LIGHTING PHOTOMETRIC PLAN (FOR REFERENCE ONLY)
SCALE: 1/16" = 1'-0"

# PHOTOMETRIC CALCULATIONS

| ROOM NUMBER | ROOM NAME | AVERAGE | MAXIMUM | MINIMUM | AVG/MIN | MAX/MIN |
|---|---|---|---|---|---|---|
| 121 | GREENHOUSE BAY | 14 | 27 | 4 | 3.7 | 6.8 |
| X | HALLWAY | 9 | 26 | 2 | 4.5 | 13 |
| 130 | SMALL GH BAY | 18 | 21 | 14 | 1.3 | 1.5 |




2 EL201 KEY PLAN
SCALE: N.T.S

THE Johnson • Mc Adams FIRM P.A.
ARCHITECTS/ENGINEERS • PLANNING • SURVEYING • MANAGEMENT
P.O. BOX 513, GREENWOOD, MISSISSIPPI – (662) 455–4943

| NO. | DATE | BY | DESCRIPTION |
|---|---|---|---|

REVISIONS

| A–E FIRM | USDA |
|---|---|
| PROJECT MANAGER BP | EPM XXX |
| DESIGNER EH | PPM XXX |
| CHECKED BY BTD | SAFETY & HEALTH XXX |
| JOB # 4825 | REAL PROPERTY XXX |

USDA

USDA Agricultural Research Service

USDA AGRICULTURAL RESEARCH SERVICE
US HORTICULTURAL RESEARCH LABORATORY
REPAIR TORNADO DAMAGE
FT. PIERCE, FL

NORMAL LIGHTING CALCULATIONS

| PROJECT NO. XXX | AGRICULTURAL RESEARCH SERVICE | SHEET EL201 |
|---|---|---|
| DATE 04/27/2026 | FT. PIERCE, FL | 100 OF 108 |

J:\jgreenwood\2025 Jobs\4825 USDA Tornado Damage Repair Ft. Pierce FL\07 Working Folder\Elec\CAD\not used\EL201.dwg
Apr 27, 2026 – 9:53am




N
1 EL202 EMERGENCY LIGHTING PHOTOMETRIC PLAN (FOR REFERENCE ONLY)
SCALE: 1/16" = 1'-0"

## PHOTOMETRIC CALCULATIONS

| ROOM NUMBER | ROOM NAME | AVERAGE | MAXIMUM | MINIMUM | AVG/MIN | MAX/MIN |
|---|---|---|---|---|---|---|
| 121 | GREENHOUSE BAY | 1 | 6 | 0.14 | 8.3 | 40 |
| X | HALLWAY | 1 | 9 | 0.10 | 47 | 350 |
| 130 | SMALL GH BAY | 3 | 6 | 0.4 | 6.8 | 13.5 |




N
2 EL202 KEY PLAN
SCALE: N.T.S

The Johnson + McAdams Firm P.A.
ARCHITECTS/ENGINEERS - PLANNING - SURVEYING - MANAGEMENT

| NO. | DATE | BY | DESCRIPTION |
|---|---|---|---|

REVISIONS

| A-E FIRM | USDA |
|---|---|
| PROJECT MANAGER BP | EPM XXX |
| DESIGNER EH | PPM XXX |
| CHECKED BY BTD | SAFETY & HEALTH XXX |
| JOB # 4825 | REAL PROPERTY XXX |

USDA Agricultural Research Service

USDA AGRICULTURAL RESEARCH SERVICE
US HORTICULTURAL RESEARCH LABORATORY
REPAIR TORNADO DAMAGE
FT. PIERCE, FL

EMERGENCY LIGHTING CALCULATIONS

PROJECT NO. XXX
DATE 04/27/2026
AGRICULTURAL RESEARCH SERVICE
FT. PIERCE, FL
SHEET EL202
101 OF 108

J:\greenwood\2025 Jobs\4825 USDA Tornado Damage Repair Ft. Pierce FL\07 Working Folder\Elec\CAD\not used\EL202.dwg
Apr 27, 2026 - 9:53am

LUMINAIRE REQUIREMENTS:

1. HOUSING - ONE-PIECE 5VA FIBERGLASS HOUSING WITH INTERGRAL PERIMETER CHANNEL UTILIZING CONTINUOUS POURED-IN-PLACE NEMA 4X GASKET. APPROVED FOR THROUGH WIRING. CAPTIVE POLYMERIC LATCHES. FROSTED, LOW PROFILE, POLYCARBONATE LENSE.
2. LIGHT SOURCE - 4000K COLOR TEMPERATURE, MINIMUM EFFICACY OF 100 LUMENS/WATT, WITH A MINIMUM CRI OF 80.
   - TYPE "A1 & A1E" FIXTURE WITH A 4,000 LUMEN PACKAGE.
3. DRIVER - OPERATING VOLTAGE OF 120-277V. DIMMABLE TO 10%. (0-10 VOLT DIMMING)
4. CERTIFICATION - CSA CERTIFIED TO UL STANDARDS. SUITABLE FOR WET LOCATION. IP65, IP66, IP67 RATED. NSF SPLASH ZONE 2 AND NON-FOOD RATED. NEMA 4X RATED.
5. MOUNTING - SURFACE MOUNT.
6. THIS SKETCH IS A NON-PROPRIETARY GRAPHIC REPRESENTATION OF A LUMINAIRE THAT MAY MEET THE SPECIFICATION REQUIREMENTS. IT IS NOT INTENDED TO INDICATE A CERTAIN MANUFACTURER OR PREFERENCE.
7. EMERGENCY PACK - FIXTURES "A1E" SHALL HAVE AN EMERGENCY SELF-DIAGNOSTIC BATTERY PACK, 10W CONSTANT POWER, CERTIFIED IN CA TITLE 20.

4' LED GASKETED STRIP FIXTURE

| LEGEND: | FIXTURE TYPE: A1, A1E |
|---|---|


LUMINAIRE REQUIREMENTS:

1. HOUSING - DIE-CAST ALUMINUM CONSTRUCTION - COMPACT HOUSING. FULLY OVERLAPPING LIGHT SEAL TO PREVENT LIGHT LEAKS. UNIVERSAL DIRECTIONAL CHEVRON KNOCKOUTS.
   - X1 - SINGLE SIDED CHEVRON SIGN.
2. LIGHT SOURCE - LED'S MOUNTED ON PRINTED CIRCUIT BOARD. 10 YEARS WARRANTY.
3. LETTERS/CHEVRONS - MINIMUM 6" HIGH WITH 3/4" STROKE. RED LETTERS AS INDICATED. PROVIDE CHEVRONS AS INDICATED EITHER LEFT, RIGHT OR BOTH DIRECTIONS AS INDICATED. CHEVRONS PUNCHED OUT THROUGH HOUSING AS REQUIRED.
4. EMERGENCY PACK - SOLID-STATE, CONSTANT-CURRENT TYPE BATTERY CHARGER WITH MAINTENANCE-FREE, NICKEL-CADMIUM BATTERY, AC-ON INDICATOR LAMP AND TEST SWITCH.
5. MOUNTING - UNIVERSAL MOUNTING KIT FOR CEILING, WALL OR END-OF-FIXTURE MOUNTING.
6. ILLUMINATION - PROVIDED BY RED HIGH-OUTPUT LEDS INSIDE OF FIXTURE HOUSING. PROVIDE POLYSTYRENE DIFFUSER IN COLOR INDICATED WITH FREQUENCY-MATCHED SILKSCREEN COATING FOR MAXIMUM LED LIGHT OUTPUT.
7. VOLTAGE - OPERATING VOLTAGE OF 120-277V.
8. NOM. DIMENSIONS: (L=11.75" X W=8.25" X D=2").

| LEGEND: | FIXTURE TYPE: X1 |
|---|---|

NOTE: SUPPORT THE LIGHT FIXTURES AT ALL FOUR CORNERS OF THE FIXTURE.




1 EL501 FIXTURE CONNECTION DETAIL

SCALE: NONE

NOTE: ALL CEILING MOUNTED OCCUPANCY SENSORS LOCATED IN THE GREENHOUSE CORRIDORS SHALL BE WET/DAMP LOCATION RATED




2 EL501 TYPICAL CEILING MOUNTED OCCUPANCY SENSOR ON/OFF

SCALE: NONE

# LUMINAIRE SCHEDULE

| FIXTURE NAME | SYMBOL | MODEL | DESCRIPTION | VOLTS | INPUT VA | TOTAL LUMENS | NOTE 1 |
|---|---|---|---|---|---|---|---|
| A1 | | 4' LINEAR LED STRIP | 4000 K, MEDIUM DISTRIBUTION, WHITE, SURFACE | 120V 1P 2W | 28.2 | 4000 | 4' VAPOR TIGHT FIXTURE. |
| A1E | | 4' LINEAR LED STRIP EMERGENCY | 4000 K, MEDIUM DISTRIBUTION, WHITE, SURFACE | 120V 1P 2W | 28.2 | 4000 | 4' VAPOR TIGHT FIXTURE. PROVIDE WITH INTEGRAL EMERGENCY BATTERY. |
| X1E | | EXIT SIGN | WET LOCATION RATED EXIT SIGN | 120V 1P 2W | | | SELF DIAGNOSTICS AND INTEGRAL EMERGENCY BATTERY. |


THE Johnson • Mc Adams FIRM P.A.
ARCHITECTS/ENGINEERS - PLANNING • SURVEYING • MANAGEMENT
P.O. BOX 513, GREENWOOD, MISSISSIPPI – (662) 455-4943


| NO. | DATE | BY | DESCRIPTION |
|---|---|---|---|
| | | | |
| | | | |
| | | | |

REVISIONS

| A-E FIRM | USDA |
|---|---|
| PROJECT MANAGER BP | EPM XXX |
| DESIGNER EH | PPM XXX |
| CHECKED BY BTD | SAFETY & HEALTH XXX |
| JOB # 4825 | REAL PROPERTY XXX |

USDA

USDA Agricultural Research Service

USDA AGRICULTURAL RESEARCH SERVICE
US HORTICULTURAL RESEARCH LABORATORY
REPAIR TORNADO DAMAGE
FT. PIERCE, FL

FIXTURE SCHEDULE & DETAILS

| PROJECT NO. XXX | AGRICULTURAL RESEARCH SERVICE | SHEET EL501 |
|---|---|---|
| DATE 04/27/2026 | FT. PIERCE, FL | 102 OF 108 |




1 EP101 **OVERALL SITE POWER PLAN**

SCALE: 1/16" = 1'-0"

## GENERAL NOTES

A. ALL CONDUIT ASSOCIATED WITH THE GREENHOUSES SHALL BE UV RESISTANT, SCHEDULE 80 PVC.

B. ALL CIRCUITRY SHALL BE XHHW-2.

C. ALL JUNCTION BOXES ASSOCIATED WITH THE GREENHOUSES SHALL BE WATER-TIGHT POLYCARBONATE BOXES WITH WEATHERPROOF GASKETS AND FITTINGS.

D. ALL RECEPTACLES SHALL HAVE A WEATHERPROOF COVER AND BE GFI TYPE OR FED WITH A GFI BREAKER.

E. REFER TO ARCHITECTURAL PLANS FOR DEMOLITION AND NEW CONSTRUCTION PHASING PLAN. ALL EQUIPMENT NOT UNDER CONSTRUCTION SHALL REMAIN IN OPERATION THROUGHOUT THE ENTIRETY OF THE PROJECT.

F. ALL BREAKERS FOR EQUIPMENT SHALL BE LOCKABLE IN THE OPEN POSITION.

## KEYED NOTES

1. SEE ACCESS CONTROL DETAIL ON SHEET E-002 FOR REQUIRED DEVICES AND MORE INFORMATION.
2. SEE TYPICAL DOUBLE GREENHOUSE PANEL AND MICROGROW CONTROLLER LAYOUT DETAIL 4/E-002 FOR MORE INFORMATION.
3. SEE TYPICAL SINGLE GREENHOUSE PANEL AND MICROGROW CONTROLLER LAYOUT DETAIL 5/E-002 FOR MORE INFORMATION.
4. DAC-1: AIR CURTAIN. 1500W, 120V, 1Ø, PROVIDE 30/1 BREAKER IN PANEL AS INDICATED.
5. ACCESS CONTROL PANEL. UTILIZE SPARE 20/1 BREAKER IN PANEL 1GE FOR 120V POWER.
6. RECONNECT DOOR CONTROL PUSH BUTTON CIRCUITRY AFTER NEW DOOR INSTALLATION.

## GRAPHIC SCALE

16' 0 8' 16'

SCALE: 1/16" = 1'-0'

## BID OPTION LEGEND

- BASE BID
- BID OPTION #1
- BID OPTION #2
- BID OPTION #3



2 EP101 KEY PLAN

SCALE: N.T.S

| NO. | DATE | BY | DESCRIPTION |
|---|---|---|---|

REVISIONS

Johnson + McAdams

| A-E FIRM | USDA |
|---|---|
| PROJECT MANAGER BP | EPM XXX |
| DESIGNER EH | PPM XXX |
| CHECKED BY BTD | SAFETY & HEALTH XXX |
| JOB # 4825 | REAL PROPERTY XXX |

USDA Agricultural Research Service

USDA AGRICULTURAL RESEARCH SERVICE
US HORTICULTURAL RESEARCH LABORATORY
REPAIR TORNADO DAMAGE
FT. PIERCE, FL

OVERALL SITE POWER PLAN

| PROJECT NO. XXX | AGRICULTURAL RESEARCH SERVICE | SHEET EP101 |
|---|---|---|
| DATE 04/27/2026 | FT. PIERCE, FL | 103 OF 108 |

J:\greenwood\2025 Jobs\4825 USDA Tornado Damage Repair Ft. Pierce FL\07 Working Folder\Elec\CAD\EP101.dwg
Apr 27, 2026 – 9:53am




1 EP102 **BID OPTION #4 - PICO'S FARM ENLARGED GREENHOUSE ELECTRICAL PLAN**

SCALE: 1/4" = 1'-0"

| PANEL | LOCATION: | GREENHOUSE CORRIDOR | LUG LOCATION: | BOTTOM FEED | |
|---|---|---|---|---|---|
| 1GY | VOLT: | 208Y/120V, 3Ø, 4W | MAIN BUS: | 100A MAIN BREAKER | NEMA 3R ENCLOSURE |
| | BUS: | 100A | MOUNTING: | SURFACE | PANELBOARD SCCR RATING (A): 10,000 |

| CIRCUIT NO. | BREAKER AMPS | BREAKER POLES | DESCRIPTION | PHASE LOAD (KVA) A | | B | | C | | DESCRIPTION | BREAKER AMPS | BREAKER POLES | CIRCUIT NO. |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 20 | 1 | LIGHTING | 0.2 | 0.5 | | | | | ECP SUMP PUMP REC. | 20 | 1 | 2 |
| 3 | 20 | 1 | GENERAL USE RECS. | | | 0.5 | 0.3 | | | EF-2 (1/2 HP) | 15 | 2 | 4 |
| 5 | 20 | 1 | GENERAL USE RECS. | | | | | 0.5 | 0.3 | - | - | - | 6 |
| 7 | 20 | 1 | GENERAL USE RECS. | 0.5 | 0.3 | | | | | EF-2 (1/2 HP) | 15 | 2 | 8 |
| 9 | 20 | 1 | GENERAL USE RECS. | | | 0.4 | 0.3 | | | - | - | - | 10 |
| 11 | 20 | 1 | OVERHEAD RECS. | | | | | 0.7 | 1.0 | UH-2 | 20 | 3 | 12 |
| 13 | 20 | 1 | OVERHEAD RECS. | 0.7 | 1.0 | | | | | - | - | - | 14 |
| 15 | 20 | 1 | OVERHEAD RECS. | | | 0.7 | 1.0 | | | - | - | - | 16 |
| 17 | 20 | 1 | SPARE | | | | | 0.0 | 1.0 | UH-2 | 20 | 3 | 18 |
| 19 | 20 | 1 | SPARE | 0.0 | 1.0 | | | | | - | - | - | 20 |
| 21 | 20 | 1 | SPARE | | | 0.0 | 1.0 | | | - | - | - | 22 |
| 23 | 20 | 1 | SPARE | | | | | 0.0 | 0.2 | HF FAN | 15 | 1 | 24 |
| 25 | 20 | 1 | SPARE | 0.0 | 0.2 | | | | | HF FAN | 15 | 1 | 26 |
| 27 | 20 | 1 | SPARE | | | 0.0 | 0.5 | | | GREENHOUSE CONTROLS | 20 | 1 | 28 |
| 29 | 20 | 1 | SPARE | | | | | 0.0 | 1.5 | DAC-1 | 30 | 1 | 30 |
| 31 | 20 | 1 | SPARE | 0.0 | 0.0 | | | | | SPARE | 20 | 1 | 32 |
| 33 | 20 | 1 | SPARE | | | 0.0 | 0.0 | | | SPARE | 20 | 1 | 34 |
| 35 | 20 | 1 | SPARE | | | | | 0.0 | 0.0 | SPARE | 20 | 1 | 36 |
| TOTAL | | | | 4.4 | | 4.6 | | 5.2 | | * GFCI BREAKER | | | |

| PANEL | LOCATION: | EXTERIOR | LUG LOCATION: | BOTTOM FEED | |
|---|---|---|---|---|---|
| L1 | VOLT: | 240/120V, 1Ø, 3W | MAIN BUS: | 70A MAIN BREAKER | NEMA 3R ENCLOSURE |
| | BUS: | 100A | MOUNTING: | SURFACE | PANELBOARD AIC RATING (A): 10,000 |

| CIRCUIT NO. | BREAKER AMPS | BREAKER POLES | DESCRIPTION | PHASE LOAD (KVA) L1 | | L2 | | DESCRIPTION | BREAKER AMPS | BREAKER POLES | CIRCUIT NO. |
|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 20 | 1 | LIGHTING | 0.3 | 0.3 | | | EF-2 (1/2 HP) | 15 | 2 | 2 |
| 3 | 20 | 1 | GENERAL USE RECS. | | | 0.4 | 0.3 | - | - | - | 4 |
| 5 | 30 | 1 | SPECIAL USE RECS. | 1.8 | 0.3 | | | EF-2 (1/2 HP) | 15 | 2 | 6 |
| 7 | 30 | 1 | SPECIAL USE RECS. | | | 1.8 | 0.3 | - | - | - | 8 |
| 9 | 20 | 1 | SPARE | 0.0 | 0.5 | | | SPARE | 20 | 1 | 10 |
| 11 | 20 | 1 | SPARE | | | 0.0 | 0.5 | SPARE | 15 | 1 | 12 |
| 13 | 20 | 1 | SPARE | 0.0 | 0.0 | | | SPARE | 20 | 1 | 14 |
| 15 | 20 | 1 | SPARE | | | 0.0 | 0.0 | SPARE | 20 | 1 | 16 |
| 17 | 20 | 1 | SPARE | 0.0 | 0.0 | | | SPARE | 20 | 1 | 18 |
| 19 | 20 | 1 | SPARE | | | 0.0 | 0.0 | SPARE | 20 | 1 | 20 |
| 21 | 20 | 1 | SPARE | 0.0 | 0.0 | | | SPARE | 20 | 1 | 22 |
| 23 | 20 | 1 | SPARE | | | 0.0 | 0.0 | SPARE | 20 | 1 | 24 |
| TOTAL | | | | 3.1 | | 3.2 | | * GFCI BREAKER | | | |




2 EP102 **BID OPTION #4 - PICO'S FARM HOOPHOUSE ELECTRICAL PLAN**

SCALE: 3/16" = 1'-0"

## GENERAL NOTES

A. ALL CONDUIT MOUNTED OVERHEAD SHALL BE UV RESISTANT, SCHEDULE 80 PVC CONDUIT.

B. ALL BRANCH CIRCUITS SHALL BE XHHW-2 CONDUCTORS.

C. ALL RECEPTACLES SHALL BE MOUNTED TO UNISTRUT IN THE HOOP STYLE GREENHOUSE.

D. ALL JUNCTION BOXES ASSOCIATED WITH THE GREENHOUSES SHALL BE WATER-TIGHT POLYCARBONATE BOXES WITH WEATHERPROOF GASKETS AND FITTINGS.

E. ALL RECEPTACLES SHALL HAVE A WEATHERPROOF COVER AND BE GFI TYPE OR FED WITH A GFI BREAKER.

F. THE CONTRACTOR SHALL REPAIR THE EXISTING SAGGING CONDUIT AT THE PUMP FILTRATION STATION. SEE ARCHITECTURAL PLANS FOR LOCATION.

G. RECEPTACLES ARE TO BE MOUNTED ABOVE TABLES, APPROX. 48" A.F.F.

## X KEYED NOTES

1. THE CONTRACTOR SHALL PROVIDE A FUSED DISCONNECT (60/2/3R, F-40), 15kVA NEMA 3R DRY TYPE TRANSFORMER (480V:240/120V) MOUNTED ON A CONCRETE PAD, AND PANEL 'L1'. MOUNT EQUIPMENT ON GALVANIZED STRUT RACK. SEE PANEL SCHEDULE FOR MORE INFORMATION.
2. NEMA 5-20R RECEPTACLE MOUNTED IN WEATHERPROOF BOX W/ A WEATHERPROOF WHILE-IN-USE COVERPLATE.
3. NEMA 5-30R RECEPTACLE MOUNTED IN WEATHERPROOF CAST ALUMINUM BOX W/ A WEATHERPROOF WHILE-IN-USE COVERPLATE.
4. THE CONTRACTOR SHALL PROVIDE (2) 3/4" x 10' COPPER CLAD DRIVEN GROUND RODS DRIVEN. BOND TO GROUND BAR OF PANEL WITH #4 CU.
5. DAC-1: AIR CURTAIN. 1500W, 120V, 1Ø, PROVIDE 30/1 BREAKER IN PANEL AS INDICATED.
6. LIGHTING FIXTURES WITHIN THIS ROOM SHALL BE SERVED FROM "1GY-1".
7. LIGHTING FIXTURES WITHIN THIS ROOM SHALL BE SERVED FROM "L1-1".

## GRAPHIC SCALE

4' 0 2' 4'

SCALE: 1/4"=1'-0"

6' 0 3' 6'

SCALE: 3/16" = 1'-0'




PICOS FARM KEYPLAN

SCALE: N.T.S

| NO. | DATE | BY | DESCRIPTION |
|---|---|---|---|
| | | | |

REVISIONS

The Johnson + McAdams Firm P.A. ARCHITECTS/ENGINEERS - PLANNING - SURVEYING - MANAGEMENT P.O. BOX 513, GREENWOOD, MISSISSIPPI

| A–E FIRM | USDA |
|---|---|
| PROJECT MANAGER BP | EPM XXX |
| DESIGNER EH | PPM XXX |
| CHECKED BY BTD | SAFETY & HEALTH XXX |
| JOB # 4825 | REAL PROPERTY XXX |

BRADEN T. DUKE REGISTERED PROFESSIONAL ENGINEER 35781 STATE OF MISSISSIPPI 04/27/26

USDA Agricultural Research Service

USDA AGRICULTURAL RESEARCH SERVICE
US HORTICULTURAL RESEARCH LABORATORY
REPAIR TORNADO DAMAGE
FT. PIERCE, FL

**BID OPTION #4 ELECTRICAL PLAN**

| PROJECT NO. XXX | AGRICULTURAL RESEARCH SERVICE | SHEET EP102 |
|---|---|---|
| DATE 04/27/2026 | FT. PIERCE, FL | 104 OF 108 |

J:\greenwood\2025 Jobs\4825 USDA Tornado Damage Repair Ft. Pierce FL\07 Working Folder\Elec\CAD\EP102.dwg Apr 27, 2026 – 9:53am




1 EP103 BID OPTION #5 - LEESBURG FARM ENLARGED GREENHOUSE ELECTRICAL PLAN
SCALE: 1/4" = 1'-0"




2 EP103 BID OPTION #5 - LEESBURG FARM ENLARGED PESTICIDE STORAGE ELECTRICAL PLAN
SCALE: 1/4" = 1'-0"

| PANEL G1 | LOCATION: | EXTERIOR | LUG LOCATION: | BOTTOM FEED | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| | VOLT: | 208/120V, 1Ø, 3W | MAIN BUS: | 100A MAIN BREAKER | NEMA 3R ENCLOSURE | | | | |
| | BUS: | 100A | MOUNTING: | SURFACE | PANELBOARD AIC RATING (A): | 10,000 | | | |

| CIRCUIT NO. | BREAKER AMPS | BREAKER POLES | DESCRIPTION | PHASE LOAD (KVA) L1 | | PHASE LOAD (KVA) L2 | | DESCRIPTION | BREAKER AMPS | BREAKER POLES | CIRCUIT NO. |
|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 20 | 1 | LIGHTING | 0.1 | 0.3 | | | EF-2 (1/2 HP) | 15 | 2 | 2 |
| 3 | 20 | 1 | GENERAL USE RECS. | | | 0.5 | 0.3 | - | - | - | 4 |
| 5 | 20 | 1 | GENERAL USE RECS. | 0.5 | 0.3 | | | EF-2 (1/2 HP) | 15 | 2 | 6 |
| 7 | 20 | 1 | OVERHEAD RECS. | | | 0.7 | 0.3 | - | - | - | 8 |
| 9 | 20 | 1 | ECP SUMP PUMP REC. | 0.5 | 0.5 | | | UH-3 | 20 | 1 | 10 |
| 11 | 20 | 1 | ECP SUMP PUMP REC. | | | 0.5 | 0.5 | HF FAN | 15 | 1 | 12 |
| 13 | 20 | 1 | OVERHEAD RECS. | 0.7 | 0.0 | | | SPARE | 15 | 2 | 14 |
| 15 | 20 | 1 | SPARE | | | 0.0 | 0.0 | - | - | - | 16 |
| 17 | 20 | 1 | SPARE | 0.0 | 0.0 | | | SPARE | 20 | 1 | 18 |
| 19 | 20 | 1 | SPARE | | | 0.0 | 0.0 | SPARE | 20 | 1 | 20 |
| 21 | 20 | 1 | SPARE | 0.0 | 0.0 | | | SPARE | 20 | 1 | 22 |
| 23 | 20 | 1 | SPARE | | | 0.0 | 0.0 | SPARE | 20 | 1 | 24 |
| TOTAL | | | | 2.9 | | 2.8 | | * GFCI BREAKER | | | |

| PANEL S1 | LOCATION: | EXTERIOR | LUG LOCATION: | BOTTOM FEED | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| | VOLT: | 208/120V, 1Ø, 3W | MAIN BUS: | 100A MAIN BREAKER | NEMA 3R ENCLOSURE | | | | |
| | BUS: | 100A | MOUNTING: | SURFACE | PANELBOARD AIC RATING (A): | 10,000 | | | |

| CIRCUIT NO. | BREAKER AMPS | BREAKER POLES | DESCRIPTION | PHASE LOAD (KVA) L1 | | PHASE LOAD (KVA) L2 | | DESCRIPTION | BREAKER AMPS | BREAKER POLES | CIRCUIT NO. |
|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 20 | 1 | LIGHTING | 0.1 | 0.0 | | | SPARE | 20 | 2 | 2 |
| 3 | 20 | 1 | GENERAL USE RECS. | | | 0.4 | 0.0 | - | - | - | 4 |
| 5 | 20 | 1 | SPARE | 0.0 | 0.0 | | | SPARE | 20 | 1 | 6 |
| 7 | 20 | 1 | SPARE | | | 0.0 | 0.0 | SPARE | 20 | 1 | 8 |
| 9 | 20 | 1 | SPARE | 0.0 | 0.0 | | | SPARE | 20 | 1 | 10 |
| 11 | 20 | 1 | SPARE | | | 0.0 | 0.0 | SPARE | 20 | 1 | 12 |
| 13 | 20 | 1 | SPARE | 0.0 | 0.0 | | | SPARE | 20 | 1 | 14 |
| 15 | 20 | 1 | SPARE | | | 0.0 | 0.0 | SPARE | 20 | 1 | 16 |
| 17 | 20 | 1 | SPARE | 0.0 | 0.0 | | | SPARE | 20 | 1 | 18 |
| 19 | 20 | 1 | SPARE | | | 0.0 | 0.0 | SPARE | 20 | 1 | 20 |
| 21 | 20 | 1 | SPARE | 0.0 | 0.0 | | | SPARE | 20 | 1 | 22 |
| 23 | 20 | 1 | SPARE | | | 0.0 | 0.0 | SPARE | 20 | 1 | 24 |
| TOTAL | | | | 0.1 | | 0.4 | | * GFCI BREAKER | | | |

## GENERAL NOTES

A. ALL CONDUIT MOUNTED OVERHEAD SHALL BE UV RESISTANT, SCHEDULE 80 PVC CONDUIT.

B. ALL BRANCH CIRCUITS SHALL BE XHHW-2 CONDUCTORS.

C. ALL SHALL BE MOUNTED TO UNISTRUT IN THE HOOP STYLE GREENHOUSE.

D. ALL JUNCTION BOXES ASSOCIATED WITH THE GREENHOUSES SHALL BE WATER-TIGHT POLYCARBONATE BOXES WITH WEATHERPROOF GASKETS AND FITTINGS.

E. ALL MOUNTED RECEPTACLES SHALL BE GFI TYPE OR FED WITH A GFI BREAKER.

## X KEYED NOTES

1. RECONNECT EXISTING CIRCUITRY TO NEW PANEL. SEE PANEL SCHEDULE FOR EXACT INFORMATION. MOUNT PANEL IN MANNER AS NOT TO DAMAGE GREENHOUSE SIDE PANELING. COORDINATE GREENHOUSE CONTROLLER LOCATION PRIOR TO ROUGH-IN PROVIDE NEMA 4X BOX FOR CONTROLLER AND CONTACTORS.
2. WATER-TIGHT JUNCTION BOX, SOW CORD, AND WATER-TIGHT L5-20R RECEPTACLE. SEE DETAIL 3/E-002. (TYPICAL OF ALL OVERHEAD MOUNTED RECEPTACLES)
3. APPROX. LOCATION OF NEW PANEL S1. COORDINATE EXACT LOCATION PRIOR TO INSTALLATION. PANEL SHALL BE MOUNTED ON GALVANIZED METAL STRUT FRAME. EXTEND EXISTING CONDUIT AND CIRCUITRY TO NEW PANEL LOCATION. UTILIZE UL LISTED POLARIS LUGS AS REQUIRED.
4. LIGHTING FIXTURES WITHIN THIS ROOM SHALL BE SERVED FROM "S1-1".
5. LIGHTING FIXTURES WITHIN THIS ROOM SHALL BE SERVED FROM "G1-1".

## GRAPHIC SCALE

4' 0 2' 4'
SCALE: 1/4"=1'-0"




KEY PLAN
SCALE: N.T.S

| NO. | DATE | BY | DESCRIPTION |
|---|---|---|---|

REVISIONS

THE Johnson • Mc Adams FIRM P.A.
ARCHITECTS/ENGINEERS • PLANNING • SURVEYING • MANAGEMENT
P.O. BOX 513, GREENWOOD, MISSISSIPPI – (662) 455-4943

| A–E FIRM | USDA |
|---|---|
| PROJECT MANAGER BP | EPM XXX |
| DESIGNER EH | PPM XXX |
| CHECKED BY BTD | SAFETY & HEALTH XXX |
| JOB # 4825 | REAL PROPERTY XXX |

USDA

USDA Agricultural Research Service

USDA AGRICULTURAL RESEARCH SERVICE
US HORTICULTURAL RESEARCH LABORATORY
REPAIR TORNADO DAMAGE
FT. PIERCE, FL

BID OPTION #5 ELECTRICAL PLAN

| PROJECT NO. XXX | AGRICULTURAL RESEARCH SERVICE | SHEET EP103 |
|---|---|---|
| DATE 04/27/2026 | FT. PIERCE, FL | 105 OF 108 |

J:\rgreenwood\2025 Jobs\4825 USDA Tornado Damage Repair Ft. Pierce FL\07 Working Folder\Elec\CAD\EP103.dwg
Apr 27, 2026 – 9:53am




1 EP401 ENLARGED TYPICAL GREENHOUSE POWER PLAN

SCALE: 1/4" = 1'-0"




2 EP401 ENLARGED AIR CONDITIONED GREENHOUSE POWER PLAN

SCALE: 1/4" = 1'-0"

## GENERAL NOTES

A. ALL CONDUIT ASSOCIATED WITH THE GREENHOUSES SHALL BE UV RESISTANT, SCHEDULE 80 PVC.

B. ALL CIRCUITRY SHALL BE XHHW-2.

C. ALL JUNCTION BOXES ASSOCIATED WITH THE GREENHOUSES SHALL BE WATER-TIGHT POLYCARBONATE BOXES WITH WEATHERPROOF GASKETS AND FITTINGS.

D. ALL RECEPTACLES SHALL HAVE A WEATHERPROOF COVER AND BE GFI TYPE OR FED WITH A GFI BREAKER.

E. BREAKERS SERVING EQUIPMENT SHALL BE CAPABLE OF BEING LOCKED IN THE OPEN POSITION.

## (X) KEYED NOTES

1. SEE GREENHOUSE PANEL DETAILS ON SHEET E-002 FOR TYPICAL PANEL AND MICROGROW CONTROLLER LAYOUTS.
2. PROVISIONS FOR OWNER PROVIDED GROW LIGHTS. THE CONTRACTOR SHALL PROVIDE WATER-TIGHT JUNCTION BOX, SOW CORD, AND WATER-TIGHT L5-20R RECEPTACLE. SEE DETAIL 3/E-002. (TYPICAL OF ALL OVERHEAD MOUNTED RECEPTACLES)
3. NEMA 3R MOTOR-RATED SWITCH AS LOCAL DISCONNECT. MOUNT ADJACENT TO UNIT. (TYPICAL)

## GRAPHIC SCALE

4' 0 2' 4'

SCALE: 1/4"=1'-0"




KEY PLAN

SCALE: N.T.S

| NO. | DATE | BY | DESCRIPTION |
|---|---|---|---|

REVISIONS

Johnson + McAdams

| A–E FIRM | USDA |
|---|---|
| PROJECT MANAGER BP | EPM XXX |
| DESIGNER EH | PPM XXX |
| CHECKED BY BTD | SAFETY & HEALTH XXX |
| JOB # 4825 | REAL PROPERTY XXX |

USDA Agricultural Research Service

USDA AGRICULTURAL RESEARCH SERVICE
US HORTICULTURAL RESEARCH LABORATORY
REPAIR TORNADO DAMAGE
FT. PIERCE, FL

ENLARGED GREENHOUSE POWER PLAN

| PROJECT NO. XXX | AGRICULTURAL RESEARCH SERVICE | SHEET EP401 |
|---|---|---|
| DATE 04/27/2026 | FT. PIERCE, FL | 106 OF 108 |

J:\jgreenwood\2025 Jobs\4825 USDA Tornado Damage Repair Ft. Pierce FL\07 Working Folder\Elec\CAD\EP401.dwg Apr 27, 2026 – 9:53am




1 EP402 ENLARGED MAINTENANCE GARAGE POWER PLAN
SCALE: 1/8" = 1'-0"




2 EP402 MAINTENANCE GARAGE SINGLE LINE DIAGRAM
SCALE: NONE

| PANEL ML2 | LOCATION: MAINTENANCE SHOP | | | VOLT: 208Y/120V, 3Ø, 4W | BUS: 100A | LUG LOCATION: TOP FEED | MAIN BUS: 100A MAIN BREAKER | MOUNTING: SURFACE | | PANELBOARD SCCR RATING (A): 10,000 | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| CIRCUIT NO. | BREAKER AMPS | BREAKER POLES | DESCRIPTION | PHASE LOAD (KVA) A | | B | | C | | DESCRIPTION | BREAKER AMPS | BREAKER POLES | CIRCUIT NO. |
| 1 | 30 | 3 | AHU-1 | 0.7 | 0.0 | | | | | SPARE | 30 | 3 | 2 |
| 3 | - | - | - | | | 0.7 | 0.0 | | | - | - | - | 4 |
| 5 | - | - | - | | | | | 0.7 | 0.0 | - | - | - | 6 |
| 7 | 30 | 3 | AHU-2 | 0.7 | 0.0 | | | | | SPARE | 35 | 3 | 8 |
| 9 | - | - | - | | | 0.7 | 0.0 | | | - | - | - | 10 |
| 11 | - | - | - | | | | | 0.7 | 0.0 | - | - | - | 12 |
| 13 | 70 | 3 | AC-1 | 7.1 | 0.0 | | | | | SPARE | 15 | 3 | 14 |
| 15 | - | - | - | | | 7.1 | 0.0 | | | - | - | - | 16 |
| 17 | - | - | SPARE | | | | | 0.0 | 0.0 | - | - | - | 18 |
| 19 | 20 | 1 | SPARE | 0.0 | 0.0 | | | | | SPARE | 20 | 1 | 20 |
| 21 | 20 | 1 | SPARE | | | 0.0 | 0.0 | | | SPARE | 20 | 1 | 22 |
| 23 | 20 | 1 | SPARE | | | | | 0.0 | 0.0 | SPARE | 20 | 1 | 24 |
| 25 | 20 | 1 | SPARE | 0.0 | 0.0 | | | | | SPARE | 20 | 1 | 26 |
| 27 | 20 | 1 | SPARE | | | 0.0 | 0.0 | | | SPARE | 20 | 1 | 28 |
| 29 | 20 | 1 | SPARE | | | | | 0.0 | 0.0 | SPARE | 20 | 1 | 30 |
| 31 | 20 | 1 | SPARE | 0.0 | 0.0 | | | | | SPARE | 20 | 1 | 32 |
| 33 | 20 | 1 | SPARE | | | 0.0 | 0.0 | | | SPARE | 20 | 1 | 34 |
| 35 | 20 | 1 | SPARE | | | | | 0.0 | 0.0 | SPARE | 20 | 1 | 36 |
| 37 | 20 | 1 | SPARE | 0.0 | 0.0 | | | | | SPARE | 20 | 1 | 38 |
| 39 | 20 | 1 | SPARE | | | 0.0 | 0.0 | | | SPARE | 20 | 1 | 40 |
| 41 | 20 | 1 | SPARE | | | | | 0.0 | 0.0 | SPARE | 20 | 1 | 42 |
| TOTAL | | | | 8.5 | | 8.5 | | 1.4 | | * GFCI BREAKER | | | |

## KEYED NOTES

1. REUSE EXISTING CIRCUITRY MADE AVAILABLE DURING DEMOLITION. PROVIDE NEW DISCONNECT AND EXTEND CONDUIT AND CIRCUITRY TO UNIT.
2. PROVIDE A 35/3 BREAKER IN EXISTING PANEL ML1 (CKT 31,33,35). UTILIZE EXISTING CONDUIT AND 3#10, #10(G).
3. PROVIDE NEW CONDUIT AND CIRCUITRY FROM PANEL ML2.
4. REPLACE EXISTING 25/2 BREAKER IN PANEL PL1 (CKT 19, 21) WITH A 20/2 BREAKER. REUSE EXISTING CONDUIT AND CIRCUITRY.
5. REPLACE EXISTING 35/3 BREAKER IN PANEL PL1 (CKT 25, 27, 29) WITH A 20/2 BREAKER AND (1) SPACE. UTILIZE EXISTING CONDUIT AND 2#12, #12(G).
6. REPLACE EXISTING 35/3 BREAKER IN PANEL PL1 (CKT 31, 33, 35) WITH A 30/3. UTILIZE EXISTING CONDUIT AND CIRCUITRY.
7. PROVIDE A NEW 15/2 BREAKER IN PANEL PL3. UTILIZE 2#12, #12(G), 3/4"C.
8. REPLACE EXISTING 30/2 BREAKER IN PANEL PL1 (CKT 1,3) WITH A 15/2 BREAKER. REUSE EXISTING CONDUIT AND CIRCUITRY.

## GRAPHIC SCALE







KEY PLAN
SCALE: N.T.S

| NO. | DATE | BY | DESCRIPTION |
|---|---|---|---|

REVISIONS

The Johnson + McAdams Firm P.A.
ARCHITECTS/ENGINEERS • PLANNING • SURVEYING • MANAGEMENT

A-E FIRM | USDA

| | |
|---|---|
| PROJECT MANAGER: BP | EPM: XXX |
| DESIGNER: EH | PPM: XXX |
| CHECKED BY: BTD | SAFETY & HEALTH: XXX |
| JOB #: 4825 | REAL PROPERTY: XXX |

USDA Agricultural Research Service

USDA AGRICULTURAL RESEARCH SERVICE
US HORTICULTURAL RESEARCH LABORATORY
REPAIR TORNADO DAMAGE
FT. PIERCE, FL

ENLARGED MAINTENANCE GARAGE POWER PLAN

PROJECT NO. XXX
DATE 04/27/2026
AGRICULTURAL RESEARCH SERVICE
FT. PIERCE, FL
SHEET EP402
107 OF 108

BRADEN T. DUKE PROFESSIONAL ENGINEER 35781 STATE OF MISSISSIPPI 04/27/26

J:\greenwood\2025 Jobs\4825 USDA Tornado Damage Repair Ft. Pierce FL\07 Working Folder\Elec\CAD\EP402.dwg
Apr 27, 2026 - 9:54am




1 EY101 LIGHTNING PROTECTION PLAN
SCALE: 1/16" = 1'-0"

## BID OPTION LEGEND

- BASE BID
- BID OPTION #1
- BID OPTION #2
- BID OPTION #3



3 EY101 KEY PLAN
SCALE: N.T.S

## GENERAL NOTES

A. LIGHTNING PROTECTION SYSTEM SHALL COMPLY WITH NFPA 780 AND SPECIFICATION 26 41 00.

B. LIGHTNING AIR TERMINALS SHALL BE BONDED DIRECTLY TO ALUMINUM FRAME, ON TOP OF ROOF RIDGE.

C. BOND ALUMINUM FRAME OF EACH GREENHOUSE TO A 3/4" x 10' COPPER CLAD GROUND ROD WITH A #1/0 AL DOWN CONDUCTOR PER NFPA 780.

D. BOND ALUMINUM DOWN CONDUCTORS, ALUMINUM GREENHOUSE FRAME, AND EXISTING REBAR IN CONCRETE SLAB TO GROUND RODS PER NFPA 780.

E. BOND LIGHTNING PROTECTION SYSTEM TO THE EXISTING GROUNDING ELECTRODE SYSTEM PER NFPA 780.

F. EQUIPMENT AND ASSOCIATED WORK IN AREAS WILL BE DEFINED BY BID OPTION NUMBER SHOWN IN LEGEND AND KEY PLAN.

G. COORDINATE WITH THE GREENHOUSE MANUFACTURER ON THE LOCATION AND MOUNTING METHOD OF AERIALS TO AVOID CONFLICT WITH THE OPERABLE VENTS.

## GRAPHIC SCALE

16' 0 8' 16'
SCALE: 1/16"= 1'-0'




2 EY101 AIR TERMINAL MOUNTING DETAIL
SCALE: NONE

| NO. | DATE | BY | DESCRIPTION |
|---|---|---|---|
| | | | |
| | | | |
| | | | |

REVISIONS

THE Johnson • Mc Adams FIRM P.A.
ARCHITECTS/ENGINEERS • PLANNING • SURVEYING • MANAGEMENT
P.O. BOX 513, GREENWOOD, MISSISSIPPI – (662) 455-4943

04/27/26

| A–E FIRM | USDA |
|---|---|
| PROJECT MANAGER BP | EPM XXX |
| DESIGNER EH | PPM XXX |
| CHECKED BY BTD | SAFETY & HEALTH XXX |
| JOB # 4825 | REAL PROPERTY XXX |

USDA

USDA Agricultural Research Service

USDA AGRICULTURAL RESEARCH SERVICE
US HORTICULTURAL RESEARCH LABORATORY
REPAIR TORNADO DAMAGE
FT. PIERCE, FL

LIGHTNING PROTECTION PLAN

| PROJECT NO. XXX | AGRICULTURAL RESEARCH SERVICE | SHEET |
|---|---|---|
| DATE 04/27/2026 | FT. PIERCE, FL | EY101 108 OF 108 |

J:\greenwood\2025 Jobs\4825 USDA Tornado Damage Repair Ft. Pierce FL\07 Working Folder\Elec\CAD\EY101.dwg
Apr 27, 2026 – 9:54am