SUPPLEMENTAL QUALITY ASSURANCE PROVISION (SQAP)

Prescribed by: eSOP 4155.05-001
Sponsor: J3

REVISIONS

REV	DESCRIPTION	DATE	APPROVED
1	ENERGY QAP C16.23	08/15/2025	

C16.23 FUEL, NAVAL DISTILLATE (F-76) (DLA ENERGY AUG 2025)

National Stock Number:	Product Nomenclature:	DLA Energy Product Code:
9140-00-273-2377	Fuel, Naval Distillate	F76

(a) Naval Distillate Fuel (F-76) shall conform to the requirements of Military specification MIL-DTL-16884R dated 03 Jan 2025. Nomenclature for Naval Distillate Fuel (F-76) is shown above.

(b) SPECIFICATION MODIFICATIONS:

(1) PROPERTIES: The F-76 supplied under this contract shall not contain un-hydrotreated light cycle oils or contain any stabilizer additives, or any other additive or material not explicitly allowed per section 3.2 of MIL-DTL-16884R.

(i). For F-76 containing a synthetic component, the synthetic component shall be certified to Tables A-I and A-II of MIL-DTL-16884R; for synthesized iso-paraffins, the synthetic component shall be certified to Tables B-I and B-II of MIL-DTL-16884R. It is not necessary to analyze each batch of the synthetic component for compliance with Table A-II (or Table B-II, as applicable) once it is demonstrated that the process scheme is adequately controlled and if no significant changes to existing production operations have been made, such as a turnaround event on a refinery unit used to produce the synthetic component or a change in feedstock material. The signed F-76 synthetic component certification page shall be supplied for each shipment which includes synthetic paraffinic materials, attesting that no changes to the production process have been made, and certifying that the last certificate of analysis, dated and including Table A-II (or Table B-II, as applicable) results, is still valid.

(2) TEST MODIFICATIONS:

(i). Flash Point: All batches of F-76 that are presented for Government acceptance at origin shall meet a minimum flash point requirement of 62.5 degrees Celsius (°C).

(ii). FAME: F-76 offered from a location other than where refined (excludes synthesized material as defined in section 3.2.2 and 3.2.3 of MIL- DTL-16884R) requires testing for FAME content by the latest revisions of test methods ASTM D7963, BS EN 14078, or IP 579. The latest revision of ASTM D7963 is considered to be the referee test method.

(3) LOCATION:
(i). In Australia, all deliveries of F-76 shall have a minimum Flash Point of 62.5°C at the custody transfer point.

(c) ADDITIVES:

(1) Lubricity Improver Additive (LIA) - Lubricity additives are allowed in F-76. The LIA additive(s) used shall conform to MIL-PRF-32490A, Performance Specification, Additive, Lubricity Improver, Distillate Fuel, dated 24 May 2019 and found in ASSIST and shall be listed in the electronic Qualified Products List (QPL)-32490, located in the Qualified Products Database (QPD) found at https://assist.dla.mil/ (or http://quicksearch.dla.mil) . Instructions on how to use ASSIST are located in QAP C1.02. Either Grade A, Grade B, or Grade C material is suitable for treatment of desulfurized F-76. Additive concentration shall not exceed the maximum allowable concentration applicable to the specific additive selected for inclusion in finished F-76.

(i). For pipeline deliveries only. Most pipelines do not allow the addition of diesel lubricity additives to be shipped via their system; therefore, the following guidelines apply:

REVISIONS

REV	DESCRIPTION	DATE	APPROVED
1	ENERGY QAP C16.23	08/15/2025	

• For F-76 shipped via pipeline that does not allow LIA, no LIA is to be added to the fuel. Lubricity shall not be a criterion for acceptance in this scenario. Lubricity improver will be injected into the fuel upon receipt.

(ii). Information pertaining to qualification of additives not currently listed on QPL-32490 may be obtained from Commander, Naval Sea Systems Command, ATTN: SEA 05S, 1333 Isaac Hull Avenue, SE, Stop 5160, Washington Navy Yard, DC 20376-5160, USA, or by e-mailing CommandStandards@navy.mil.

(d) DYES AND MARKERS:

(1) Red dye required in off-highway diesel fuel in accordance with 40 CFR Part 80 as modified by the Environmental Protection Agency's interim final rule published in the Federal Register dated July 14, 1994 shall not be added to F-76. The finished product shall show no visual evidence of red dye. This F-76 product is for military, off-highway use only and must be segregated at all times from any diesel fuel used on-highway. NOTE: Red dye does not apply to Atlantic/Europe/Mediterranean or Western Pacific Overseas Bulk purchase programs unless offering refinery is located in the United States or one of its possessions.

(e) OTHER REQUIREMENTS:

(1) Unless otherwise indicated by the Contractor in writing, prior to award, the product offered shall be required to fully meet all applicable specifications. The supplier shall provide to the receiving vessel a “Statutory Sample” of at least 400 mL in volume, taken from the receiving vessel's inlet bunker manifold, together with a Bunker Delivery Note (BDN). This sample will be sealed and carry a sample tag that provides the documentation required per MARPOL 73/78, Annex VI Regulation 18.

(2) ADDITIONAL SAMPLING:

(i). The government may request a sample of F-76 during each quarter of contract performance not to exceed 5 gallons. Samples shall be shipped in a 5-gallon epoxy lined can (preferred) or five 1-gallon epoxy lined cans. (NOTE: These samples are in addition to those required in accordance with Quality Assurance Provision (QAP) E1). The sample shall be shipped to:

Naval Air Station HAZMART
5-gallon TEST
SAMPLE
22680 Hammond
Road Bldg. 2385
Patuxent River, MD
20670
Attn: Terrence Dickerson, AB44100 Fuels & Lubricants
Phone: (301) 757-0447; Email: terrence.w.dickerson.civ@us.navy.mil

The paperwork provided with these samples shall include the following information:

Contract Number
Contractor's
Name
Product
Refinery
Location
Quantity of
Tank/Batch
Full-Specification Test Report

REVISIONS

REV	DESCRIPTION	DATE	APPROVED
1	ENERGY QAP C16.23	08/15/2025	

(3) BATCH SAMPLING: The Contractor shall provide one 20 mL sample per each individual tank in a procurement batch upon completion. The Sample shall be shipped within 30 days of the procurement batch delivery. A batch is defined as: A specific quantity of product that is processed or utilized as a single unit and tested to meet test criteria and specifications.

(i). For each 20 mL sample provided by the Contractor, the Contractor shall also submit a Refinery Certificate of Quality (RCQ), or Certificate of Analysis (CoA), as applicable, with the F-76 sample when submitting to the US Naval Air Station. The RCQ or CoA for each individual tank shall be representative of Level A testing for the F-76 product.

NOTE: This sample is in addition to those required in accordance with Quality Assurance Provision (QAP) E1

The sample from each tank/batch shall be either an all-level sample or a composite of upper, middle, and lower samples. A copy of the full-specification test report shall accompany each sample. The sample container will be any 20 mL amber borosilicate vial with a polytetrafluoroethylene (PTFE) lined screw cap. A tracking number for the samples shall be provided to: Terrence Dickerson at terrence.w.dickerson.civ@us.navy.mil or (301) 757-0447. Samples shall be shipped to:

Naval Air Station HAZMART
20mL TEST SAMPLE
22680 Hammond Road Bldg. 2385 Patuxent River, MD 20670
Attn: Terrence Dickerson, AB44100 Fuels & Lubricants

The paperwork provided with these samples shall include the following information:

Contract Number
Contractor's Name Product
Refinery Location Quantity of Tank/Batch
Full-Specification Test Report

For samples containing synthetic components, include the following additional information:

Manufacturer of synthetic component
Batch Number Date of Test Report
Quantity of Tank/Batch
Percent Composition
Production Process of Synthetic Component Feedstock
Full-Specification Test Report

(4) TRACEABILITY:

(i). F-76 fuel supplied under this contract shall maintain traceability with respect to additives and materials, which is defined as the ability to trace the individual batch of fuel back to the original point of manufacture through documentation.

(ii). All traceability documentation shall be sufficient to guarantee that at no point any unauthorized materials or additives have been blended into the final product or any of its associated blend components per section 3.2 Material of MIL-DTL-16884R.

(iii). For all F-76 supplied, the traceability documentation shall consist of statement(s) attesting to the materials composition, which includes materials derived from non-petroleum sources, additives and their concentration levels. Additives and concentrations to be reported include LIAs outlined in section d.1 above and any trace additives resulting from existing tank heels, product trail-back in a multiproduct system, all product blending operations, etc.

REVISIONS

REV	DESCRIPTION	DATE	APPROVED
1	ENERGY QAP C16.23	08/15/2025	

(iv). If F-76 is produced by means of blending, the traceability requirement and documentation for additives and materials shall apply to each blending component used from the point of manufacture through the blend operation. Materials composition, additives and their concentration levels shall be included. The requirement and intent of traceability for blend components is not to obtain full certificates of analysis of each individual blend component, but for certification that no unapproved additives or materials are present in blend components used.

(v). The form titled: "F-76 Traceability Signature Page" (attached below) shall be used to document conformance with the provisions of this traceability paragraph. The offeror/supplier shall comply with this requirement utilizing one of the three options below and notification shall be provided to both the contracting office and QT@dla.mil during the pre-award phase which option was chosen for compliance. Documents provided in conjunction with individual shipments shall be uploaded into Wide Area Work Flow as attachments under the quality tab.

• OPTION 1 - As part of the offeror submission package the offeror shall provide the traceability signature page from each entity in the supply chain providing and/or handling F-76 product and/or blending components all the way back to the point of manufacture. For each individual shipment, the supplier will submit a traceability page signed only by the awardee.

• OPTION 2 - As part of the offer submission package the offeror shall provide the traceability signature page, signed only by the offeror. Upon award and prior to the first shipment the awardee shall provide the signed traceability signature page from each entity in the supply chain providing and/or handling F-76 product and/or blending components all the way back to the point of manufacture. For each individual shipment, the supplier will submit a traceability page signed only by the awardee.

• OPTION 3 - As part of the offeror submission package, the offeror shall provide the traceability signature page, signed only by the offeror. For each individual shipment, the awardee shall provide the signed traceability signature page from each entity in the supply chain providing and/or handling F-76 product and/or blending components all the way back to the point of manufacture.

iii. Regardless of the option chosen, the traceability sheet signed by offeror shall be submitted to both the contracting office and to QT@dla.mil during pre-award phase.

iv. For OPTION 1 or OPTION 2, the purpose of the awardee submitting a signed traceability page with each shipment is to confirm that the initial traceability certification is still valid at the time of F-76 product shipment.

• If at any point during the contract period the traceability information provided under OPTION 1 or OPTION 2 becomes invalid (i.e. the supply chain is altered or the source of F-76 product or a blending component changes), the supplier shall notify both the contracting office and QT@dla.mil and updated documentation shall be provided.

C16.23 FUEL, NAVAL DISTILLATE (F-76) (DLA ENERGY AUG 2025)

F-76 Traceability Signature Page

Contract or Solicitation Number:	
CLIN:	
Order Number:	
Shipment Number:	

Traceability OPTION selected per paragraph (4).(v) (circle or otherwise indicate which one of the three options is chosen): OPTION 1 OPTION 2 OPTION 3

F-76 fuel supplied under the above contract, CLIN, order number and shipment number maintains traceability with respect to the materials composition, additives and their concentration levels. This signed statement certifies that at no point have any unauthorized un- hydrotreated light cycle oils, other unauthorized materials, or additives been blended into the final product or any of its associated blend components per the most recent revision of MIL-DTL-16884 at date of contract award. All materials and additives are listed below. The percentage of each material as defined in sections 3.2, 3.2.2, and 3.2.3 (i.e. refined hydrocarbon distillate fuel, Fischer-Tropsch, Hydroprocessed Renewable Diesel, etc.) and the concentration level for each additive are also shown. For the purposes of the offeror submission this signed statement attests that no unapproved additives or materials will be added to batches or components of batches of F-76 for delivery under government contracts.

Signature:	
Printed Name:	
Title:	
Company Name:	
Date:	

Material	Percent

Additive	Concentration	Responsible Party for Injection

F-76 Synthetic Component Certification

Contract or Solicitation Number:	
CLIN:	
Order Number:	
Shipment Number:	

Synthetic paraffinic materials supplied as indicated with the above contract, CLIN, order number, and shipment number is derived from either Fischer-Tropsch (FT) or Hydroprocessed Renewable Diesel (HRD) methods. This signed statement certifies that since the last certificate of analysis (COA), including table A-II or B-II results of MIL-DTL-16884P, Appendix A or B, no changes, including feedstock material, production location, or production processes have been made. In addition, no turnaround events have been executed on any units utilized to produce the synthetic paraffinic materials since the last COA, including table A-II or B-II, properties were tested. Please supply the date of the most recent COA and an identifying number for that report in the space provided below.

DATE OF COA:_____

LAB REPORT ID NUMBER_____

Signature:	
Printed Name:	
Title:	
Company Name:	
Date:	