

MSFC ST12 requires machining of the following parts:

- 2 ea. RDSX-102-001 FRONT APERTURE.STEP
- 2 ea. RDSX-154 REAR APERTURE.STEP

Requirements:

- Work must be completed within 35 business days or less to maintain project schedule ahead of launch.
- Meet geometric dimensional and tolerance called out in drawings
- Customer supplied 17-4 PH stainless steel alloy in the H1150 heat treat condition
- Stress relief heat treat per SAE AMS2759/11
- Smallest Roughness: 125uin/3.2um Ra
- Bag and Tag
- **Inspection:** Formal Inspection with Dimensional Report
- **Certificates and Supplier Qualifications:** ITAR/EAR Registration, Finishing Certification, Certificate of Conformance
- EDM work to be done by customer. part is to be finish machined less windows at .125" stock
- Print exception, note 6: part to be machined to .125" before stress relief
- Print exception, note 9: no passivation
- Print exception, note 11, lap, to be done by customer

CAD and mechanical drawing files will be provided upon request. To receive CAD and mechanical drawings files, vendor representative must have a box.com account, verify that they are a US Person (US Citizen or Permanent Resident Card holder), and provide the full name and email of the person associated with the box.com account. Information must be provided to the POC in the RFQ.