

REV:	ENGINEERING DATA REQUIREMENTS (ATTACHMENT "A")	
NOTE: MILITARY SPECIFICATIONS / STANDARDS WILL NOT BE FURNISHED IN THE BID SET.		
1. THE FOLLOWING INSTRUCTIONS ARE FURNISHED FOR THE MANUFACTURE OF: MOTOR ALTERNATING		
2. PART NUMBER: 252UF12	3. NATIONAL STOCK NUMBER: 6105-01-036-5479LE	

4. THE FOLLOWING SPECIFICATIONS/STANDARDS, ETC., WILL BE USED IN LIEU OF THE DATA INDICATED. THE SUPERSEDED DATA WILL NOT BE FURNISHED UNLESS SO INDICATED.

5. OO-ALC LANDING GEAR ENGINEERING RETAINS ALL RIGHTS TO REVIEW AND ACCEPT MATERIAL REVIEW BOARD (MRB'S) DISPOSITIONS PRIOR TO SHIPMENT OF DISCREPANT ITEM. ALL DEVIATIONS, MINOR AND MAJOR, FROM THE ENGINEERING DRAWING PACKAGE SHALL BE SUBMITTED FOR MRB DISPOSITION.

6. PRIOR TO CONTRACT AWARD, THE CONTRACTOR SHALL CERTIFY TO THE GOVERNMENT IN WRITING FULL COMPLIANCE WITH MANUALS, SPECIFICATIONS, AND STANDARDS CALLED OUT AND REQUIRED FOR THE MANUFACTURE OF THIS CONTRACTED LANDING GEAR COMPONENT/ASSEMBLY. CONTRACTOR IS RESPONSIBLE TO COMPLETELY SEARCH THESE MANUAL, SPECIFICATIONS, AND STANDARDS AND FULLY UNDERSTAND THE REQUIREMENTS NECESSARY TO MANUFACTURE LANDING GEAR COMPONENTS. ANY QUESTIONS CAN BE FORWARDED TO OO-ALC LANDING GEAR ENGINEERING.

7. **TESA TAPE LABEL APPLIED DIRECTLY TO PART AND HRI ETCHED DIRECTLY ON PART:**

UNIQUE IDENTIFICATION (UID) SHALL BE APPLIED TO EACH PART PER MIL-STD-130. THE UID SHALL CONTAIN HUMAN-READABLE INFORMATION (HRI) AND MACHINE-READABLE INFORMATION (MRI) MARKINGS. QUALITY AND TECHNICAL REQUIREMENTS FOR BOTH THE MRI AND HRI SHALL BE IN ACCORDANCE WITH SAE AS9132. THE METHOD OF MARKING FOR THE HRI SHALL BE LIMITED TO ELECTRO-CHEMICAL ETCHING, DOT PEEN, VIBRO PEEN, OR MICRO-MILL. THE DEPTH OF EACH MARK SHALL BE FROM .003 - .005 INCHES. THE HRI MARK THE HRI SHALL INCLUDE BOTH THE PART NUMBER AND THE SERIAL NUMBER. THE SERIAL NUMBER WILL BE LIMITED TO 16 ALPHANUMERIC CHARACTERS INCLUDING THE VENDOR CAGE (FSCM) OF THE CONTRACTOR NAMED ON THE CONTRACT, DATE OF MANUFACTURE IN THE FORMAT MMY, AND A UNIQUE 4-DIGIT NUMBER STARTING WITH 0001 IN NUMERICAL ORDER OF MANUFACTURE. THE HRI SHALL APPEAR AS "SN 9874701040001". THE HEIGHT OF EACH ALPHANUMERIC CHARACTER IN THE HRI SHALL BE A MAXIMUM OF .125 INCHES. THE METHOD OF MARKING FOR THE MRI SHALL IN ACCORDANCE WITH DRAWING 200827953-05 APPLY TWO TOPCOATS POLYURETHANE OVER LABEL PER MIL-PRF-85285, TYPE I, CLEAR PER FED-STD-595. THE LOCATION OF THE UID SHALL BE IDENTIFIED ON THE DRAWING. TESATAPE LABEL SHALL ONLY BE PLACED ON THE TOP COAT OF THE PAINTED COMPONENTS.

PREPARED BY: ROBERT YOUNG	OFFICE SYMBOL: 417 SCMS/GUEA	DATE: 7/13/2011
------------------------------	---------------------------------	--------------------