

Spec Sheet for 125HP AG Tractor

Flint Hills National Wildlife Refuge

530 W Maple Ave

Hartford, KS 66854

Contact

TJ Cooper

620-392-5553

TJ_Cooper@fws.gov

Base Machine Weight

- At least 13,779 LBS.

Engine Performance

- Diesel Engine
- Minimum Engine Horsepower 125 HP
- Minimum PTO Horsepower 97 HP
- Maximum PTO Power 116 HP
- Rated speed of at least 2100 RPM
- Emissions after-treatment system meeting EPA Final Tier 4 requirements, including DOC, SCR/DEF, and/or equivalent manufacturer-certified technology
- Turbocharged diesel engine capable of maintaining performance under varying load conditions
- EPA Final Tier 4 compliant emissions system

Transmission

- Minimum 16 forward/16 reverse transmission with clutchless power shifting capability or equivalent performance transmission suitable for agricultural field operations and loader work.

Hydraulic System/Pump

- Hydraulic Pump 80 L/Min
- Minimum 3 Mechanical SCVs

Rear PTO

- An independent, 2-Speed manually shifted rear PTO (540/1000)
- Torque rise 40%
- Electro hydraulically operated, oil cooled, Multi disc design
- In-Cab Switch
- External fender-mounted remote control

Alternator/Electric system

- Battery Circuit Breaker
- At least 14 volts/170 AMP

Cab

- Standard Cab with Right hand Console
- Standard Cab with Right hand Console
- Premium seat
- Telescopic Mirrors
- Premium Radio

Axle/Wheels/Clutch/Brakes

- Rack and Pinon Axle of at least 3.62 inches x 100.4 inches
- Three planetary gear reduction

- Primary and Secondary Brakes
- Parking Brake
- Front wheel drive brakes
- Electrohydraulically oil clutch for Rear Differential Lock
- Rear Cast Wheels
- Rear Wheels 480/70R24
- 4WD Front Axle Unsuspended
- Adjustable Steel Wheels
- Front Wheels 420/70R24

Steering

- Dynamic Load Sensing
- Hydrostatic
- Flow metering

Capacities/Fuel Tank

- At least 46.2 gallons of fuel or more
- Diesel Exhaust Fluid 5 gallons for more
- Fuel Tank Bottom Guard

Connected Support

- Help monitor alerts from the machine remotely
- Monitor engine hours and utilization
- View machine location and get driving directions to the site
- Monitor fuel Level and idle time
- Dealers can monitor alerts coming from machine
- Remote connect to the machine for real-time diagnosis
- Perform software updates from the dealership
- Dealer can remotely assist us with in-cab display setup and adjustments for optimal machine performance

Hitch/Drawbar

- Rear Hitch Maximum lift Capacity behind lift points 12,023 lbs or more
- Draft links with Telescopic Ball Ends Category 2
- Center Link with Ball end Category 2
- Sway blocks

External Features

- Front Base weight of At least 132 lbs
- Front Suitcase weights X8 At least 758 pounds
- Front Fenders 4WD Turn able
- Rear Fender Extensions adjusted to Tire Size
- Cold Start Package
- Fuel Tank Bottom Guard
- Tool Box

Factory Base Warranty

- At least 2 years/ 2000 hours
- Station is allowed to purchase extended warranty within a year from delivery
- 1 English owners/operator Manuel

Trade must be picked up within a month from delivery and contact Delivery Station a week before or more before delivery and pick up of Trades.

Delivery Address

Flint Hills National Wildlife Refuge
530 W Maple Ave
Hartford, KS 66854

Trade IN:

2014 John Deere 6125R Serial # 1L06125RAEH803799 see attachments for information and photos