

SPECIAL PACKAGING INSTRUCTION

Form Approved
OMB No. 0704-0188

XTH

The public reporting burden for this collection of information is estimated to average 30 days per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing the burden, to the Department of Defense, Executive Services Directorate (0704-0188). Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number

PLEASE DO NOT RETURN YOUR COMPLETED FORM TO THE ABOVE ORGANIZATION.

1. PART OR DRAWING NO. (CAGE) NOMENCLATURE PSOC-205-HDB-231463 (3D6E9) AXLE			2. CAGE 19207		3. SPI NO. AK14395441	
4. NATIONAL STOCK NO. 2520-01-439-5441			5. DATE 08/09/2022		6. REVISION A	
7. QUP 1 EACH	8. ICQ 000	9. UNIT PACK WT (LB.) 2000.0*	10. UNIT PACK CU (CU. FT.) 112.000*		11. UNIT PACK SIZE (INCHES) 96.0 X 48.0 X 42.0*	
12. MILITARY PRESERVATION MIL-STD-2073-1, METHOD 20		18. STEPS	19. REQD	20. DESCRIPTION		
13. CLEANING MIL-STD-2073-1 AND NOTE B		1C		PRESERVATIVE : MIL-PRF-10924		
		2D		PRESERVATIVE: SEE NOTES		
14. DRYING MIL-STD-2073-1 AND NOTE B		3E		CAPS/PLUGS : NAS846 CAPS/PLUGS: NAS847		
		4F		PRIMER : A-A-52465		
15. PACKING		5G		PRESERVATIVE : MIL-PRF-16173, GR 4		
		6H	1	CONTAINER : ASTM-D6256		
a. LEVEL A MIL-STD-2073-1 AND NOTE H						
b. LEVEL B NOT APPLICABLE						
16. MARKING MIL-STD-129						

17. NOTES/ DRAWING

- A. PRESERVATION AND PACKAGING SHALL BE INSPECTED IN ACCORDANCE WITH MIL-STD-2073-1D AND ANY APPLICABLE CONTAINER SPECIFICATIONS.
- B. CLEAN AND DRY ITEM BY ANY SUITABLE PROCESS BEFORE APPLICATION OF PRESERVATIVE AND PACKAGING MATERIALS.
- C. APPLY GREASE THROUGH GREASE FITTINGS.
- D. PRESERVE INTERNALLY WITH OPERATIONAL FLUID.
- E. SEAL ALL OPENINGS WITH CAPS/PLUGS OF THE APPROPRIATE SIZE.
- F. PRIMER APPLICATION ON NONMETALLIC SURFACES SHALL BE HELD TO A MINIMUM. INTERIOR OF BRAKE DRUMS, BRAKE DISKS, CALIPERS, SHOES, AND RELATED BARE FERROUS METAL PARTS SHALL BE COATED WITH PRIMER.
- G. APPLY PRESERVATIVE TO BARE UNPAINTED METAL SURFACES.
- H. BLOCKING, BRACING, CUSHIONING, AND IMMOBILIZATION OF ITEM INSIDE CONTAINER IAW MIL-STD-2073-1 USING MIL-STD-1186 AS GUIDANCE.
- I. THE UNIT CONTAINER IS THE SHIPPING CONTAINER

*UNIT PACK WEIGHT, CUBE, AND DIMENSIONS ARE ESTIMATED FOR GOVERNMENT PLANNING PURPOSES ONLY.