

REV:	ENGINEERING DATA REQUIREMENTS (ATTACHMENT "A")	
NOTE: MILITARY SPECIFICATIONS / STANDARDS WILL NOT BE FURNISHED IN THE BID SET.		
1. THE FOLLOWING INSTRUCTIONS ARE FURNISHED FOR THE MANUFACTURE OF: DOOR ASSY, ENGINE ACCESS-FS 345.20 TO FS389.80, LH		
2. PART NUMBER: 16B6514-681	3. NATIONAL STOCK NUMBER: 1560-01-263-4414WF	

4. THE FOLLOWING SPECIFICATIONS/STANDARDS, ETC., WILL BE USED IN LIEU OF THE DATA INDICATED. THE SUPERSEDED DATA WILL NOT BE FURNISHED UNLESS SO INDICATED.
5. THE SOURCE/MATERIAL IF LISTED ON THE STANDARDS, SPECIFICATION AND DRAWINGS ARE THE ONLY SOURCE/MATERIALS FOR THOSE ITEMS. SUBSTITUTIONS SHALL HAVE PRIOR APPROVAL BY THE COGNIZANT ENGINEERING ACTIVITY.
6. DEVIATIONS FROM SPECIFICATIONS IDENTIFIED IN CONTROL DRAWINGS ARE NOT AUTHORIZED WITHOUT PRIOR APPROVAL BY THE COGNIZANT ENGINEERING.
7. UNIQUE IDENTIFICATION (UID) SHALL BE APPLIED PER MIL-STD-130 IN LIEU OF FPS-3008:
- A. Minimum 1/8th inch on Human readable to include:
 - 1. CAGE (17V)
 - 2. P/N (1P)
 - 3. Serial Number (1S)
 - B. Minimum 1/4 inch square on Machine Readable 2D Matrix – construct 2 – to include
 - 1. CAGE (17V)
 - 2. P/N (1P)
 - 3. Serial Number (1S)
 - C. Label shall contain all data on existing label, if existing label is to be replaced.
 - D. Same Label Material shall be used as specified in drawing for existing label.
 - E. MIL-STD-130, ANSI/AIM BCII, ISO 15434, ISO 15415, and ISO 15418

PREPARED BY: DONALD WILLMOTH	OFFICE SYMBOL: 416 SCMS/GUEAA	DATE: 20200929
--	---	--------------------------