

Brand Name or Equal Worksheet (“Salient Characteristics”) v 2.0

Brand Name or Equal Item:

Armstrong DRV80 Digital Recirculation Valve

Model:

Protection NEMA 3S, IPX4

Ambient Temperature Minimum Ambient Temperature: 35°F (2°C) Maximum Ambient Temperature: 122°F (50°C)

Ambient Humidity 95% Non-Condensing

Installation Environment Suitable for indoor use only

Materials Valve: Stainless Steel, Electronics Module: PC / ABS

Safety Seven fail-safe cold triggers supported by integral self-diagnostics and a programmable over-temp limit

Connections

Inlet and Outlet Connections 3” NPT Female Connections

Pressures

Inlet Supply Pressures Maximum Pressure: 200 psi / 1379 kPa = 13.8 bar Minimum Pressure: 20 psi / 138 kPa = 1.5 bar

Supply Pressure Differential Nominally equal

Temperatures

Hot Water Supply Temperature Maximum Inlet Hot Supply Temperature: 185°F (85°C) Minimum Inlet Hot Supply Temperature: 5°F (2°C)

above DRV set point

Cold Water Supply Temperature Minimum Inlet Cold Supply Temperature: 35.6°F (2°C)

Min. Recirculation Temperature Loss 1°F (< 1°C)

Min. Continuous Recirculation Flow 10 GPM (38 LPM)

Recirculation Circuit

Minimum Distance to First Outlet 25 ft (7.6 m)

Electrical

Power Supply 120 - 240V AC - 50/60 Hz

Supply Fuse / Circuit Breaker Grounding required (Switched Type 3 Amp - no plug; 15 Amp Grounding-type receptacle - plug)

Battery Qty (2) CR - P2 6V

Configurable Settings

Set Point Range 81°F to 158°F (27°C to 70°C)

Brand Name or Equal Worksheet (“Salient Characteristics”) v 2.0

High Temperature Alert Minimum of 2°F (1°C) above DRV set point

High Temperature Error 5°F (2°C) above DRV set point

Thermal Disinfection Temperature Programmable range of 158°F to 185°F (70°C to 85°C)

Thermal Disinfection Set-Up Disinfection Duration: < 100 minutes Disinfection Cool Down Duration: < 30 hours

Units of Measure Degrees Fahrenheit (°F) or Degrees Celsius (°C)

Connectivity

Bluetooth® On board with SAGE® mobile application (available in the Apple App Store and Google Play)

BACnet MSTP On board for connection to building automation system (BAS) operating on BACnet MSTP protocol

Modbus RTU RS-485 port for connection to building automation systems (BAS) operating on Modbus RTU protocol

SAGE® Module

RS-485 port for connection to SAGE® module with Modbus TCP, BACnet TCP/IP, BACnet MSTP, or LonWorks processor

Note: Processors for other BAS protocols may be available upon request

SAGE® Subscription Real-time monitoring, recording, and documentation dashboard for Armstrong Hot Water Systems

Per VAAR 811.104 and 811.105, I certify the following regarding the above information:

- The salient characteristics listed above are essential to the Government’s requirements.
- To my knowledge, the restrictions listed above will not limit the acquisition to an item peculiar to one manufacture.