

ORDERING DATA SHEET – GENERAL

NOUN NAME: PRESSURE GAGE

DESCRIPTION: 8-1/2", RANGE: 0-3000 PSIG, ACCURACY: 0.10% WITH 0.1% HYSTERESIS, (350° POINTER TRAVEL), SCALE GRADUATION: 5.0 PSI, BOTTOM CONN. (7/16-20/M) TEMP COMP 0.10% ACCU, TEMP RATING -25 TO 125F, AL CASE, SOLID FRONT, SAFETY GLASS LENS, SLOTTED LINK AND SPECIAL CLEANING

SPEC: MS33656-4

MATERIAL: 403SS BOURDON TUBE, SKT & MVT

MANUFACTURER/VENDOR P/N: HEISE MODEL A4A CM HAS BEEN FOUND TO MEET TECHNICAL REQUIREMENTS OF THE GOVERNMENT.

QUANTITY: 6 EACH

ADDITIONAL NOTES: SOURCE: ASHCROFT INC, Phone Number: 203-378-8281, Cage Code: 049X3

CERTIFICATE OF COMPLIANCE REQUIRED

Changes to specification or other technical requirements are not allowed without Shipyard approval via the Administrative Contracting Officer (ACO).

JOB ORDER
88MSM00001

KEY OP
000

KO ITEM
000

REV
-

IDN
5363-7195

IDN REV
4

PAGE 1 OF 1