

STATEMENT OF WORK

1. Objective/Requirements

The NASA Marshall Space Flight Center (MSFC) requires the purchase of twenty-seven (27) CIS Secure TSG Class A Approved Cisco 8851 Fiber VOIP with 28 Key Expansion Module (KEM) Microphone Removed because they are NASA APL-approved, already deployed within the Building 4203 SCIF, and fully integrated with the existing Cisco Systems call control and network infrastructure.

2. Characteristics, Scope, and Specs

Quantity	OEM Part #	Product Description
27	DTD-8851-01D1A-SD	CIS Secure TSG Class A Approved Cisco 8851 Fiber VOIP with 28 Key Expansion Module (KEM) Microphone Removed Description: TSG Class A Approved Cisco 8851 Fiber VOIP with 28 Key Expansion Module (KEM) Microphone Removed, and Speakerphone Disabled. Supports Session Initiation Protocol (SIP) for signaling, Session Description Protocol (SDP), and IPv4 and IPv6. The CNSS defined Positive Disconnect feature disengages manually, provides a clear illuminated indication of when the phone audio is active, and re-engages automatically when the phone is hung up. LAN port: 1GB SC Fiber. PC port: RJ45 10/100/1000MB. The required DTD-VOIP-PI-02 power injector for Class A compliance is included and must be plugged in to a grounded AC outlet at all times. License is not included. TSG Approval Number: XXX. Class A device. One Year Warranty

3. Place of Performance

AEGIS/NASA Marshall Space Flight Center (MSFC)
Rideout Road
Building 4723 Room 113
Huntsville, AL 35812

4. Period of Performance

30 Days ARO