

SPECIAL PACKAGING INSTRUCTION			CODE ID 98747	SPI NO. (TPD) F01-664-9140 SHEET 1 OF 4
PART OR DRAWING NO. 2218390-001	NATIONAL STOCK NO. 5895-01-644-9140 WF	CURRENT REV B	ILL. K. KNIGHTON P.S. K. RESTORFF CHK. S. LUCERO AUTH. J. BURLEIGH	
ITEM NOMENCLATURE THEODOLITE, SURVEYING		ORIGINAL DATE 16061		

MILITARY PRESERVATION IAW MIL-STD-2073-1

SERVICEABLE METHOD: 10

UNSERVICEABLE METHOD: 10

QUP 001

ICQ 000

CLEANING & DRYING: IAW MIL-STD-2073-1

PRESERVATIVE: N/A

MARKING IAW MIL-STD-129

SPECIAL MARKINGS:

A) SPI NO. F01-664-9140
MARK THE SPI NUMBER ON THE IDENTIFICATION SIDE OF CONTAINER.

B) REUSABLE CONTAINER & DUNNAGE DO NOT DESTROY.

C) NOT FOR OUTSIDE STORAGE

CLOSURE

LEVEL A: IAW: ASTM D6251

LEVEL B: IAW: ASTM D6251

PACKING AS SPECIFIED BELOW AND BILL OF MATERIALS

LEVEL	SPEC	STYLE	TYPE	CL	VRTY	GR	TR
A	ASTM D6251	A	III	2			B
B	ASTM D6251	A	III	2			B

	LEVEL A	LEVEL B
GROSS CU FT	15.180	15.180
GROSS WT LBS	140	140
DESIGN FRAGILITY G	60	60

	LENGTH	WIDTH	DEPTH
CNTR I.D.			
LEVEL A:	29	28	22
LEVEL B:	29	28	22
CNTR O.D.			
LEVEL A:	31 1/4	30 1/4	27 3/4
LEVEL B:	31 1/4	30 1/4	27 3/4
ITEM DIM	24	23	17
ITEM WT.	87 LBS		

REVISIONS		
LTR	DESCRIPTION	DATE
B	ADDED CUI MARKINGS AND UPDATED O.D.	23080

DISTRIBUTION STATEMENT D: DISTRIBUTION AUTHORIZED TO DOD AND U.S. DOD CONTRACTORS ONLY, ADMINISTRATIVE OR OPERATIONAL USE, 10 SEPTEMBER 2020. OTHER REQUESTS FOR THIS DOCUMENT SHALL BE REFERRED TO 406 SCMS/GULAA, (PACKAGING DIVISION), HILL AFB, UTAH 84056.

DESTRUCTION NOTICE: IAW DoDI 5200.48 4.5.a; MUST DO SO IN A MANNER MAKING IT UNREADABLE, INDECIPHERABLE, AND IRRECOVERABLE.

SPI NO. F01-664-9140

SPECIAL PACKAGING INSTRUCTION				CODE ID 98747	SPI NO. (TPD) F01-664-9140
ITEM NOMENCLATURE THEODOLITE, SURVEYING					SHEET 2 OF 4
-5	1	WRAP	82 X 43	A-A-3174 TYPE I, CL. 1, GR. A, FIN. 1	
-4	2	CUSHIONING, END	24 X 18 X 2	A-A-59136 CLASS 2, GRADE A	
-3	2	CUSHIONING, SIDE	29 X 18 X 2	A-A-59136 CLASS 2, GRADE A	
-2	2	CUSHIONING, TOP & BOTTOM	29 X 28 X 2	A-A-59136 CLASS 2, GRADE A	
-1	2	SKID	4 X 4 (NOM) X 30 1/4	ASTM D6199 CLASS 2	
P/N	QTY REQD	NOMENCLATURE OR DESCRIPTION	SIZE: (INCHES UNLESS SPECIFIED) TOLERANCES ON FRAC. $\pm \frac{1}{8}$, DECIMAL $\pm .10$, ANGLES $\pm 1^\circ$	MATERIAL SPECIFICATION	

SPECIAL PACKAGING INSTRUCTION	CODE ID 98747	SPI NO. (TPD) F01-664-9140
ITEM NOMENCLATURE THEODOLITE, SURVEYING		SHEET 3 OF 4

CAUTION NOTICES

NOTICE 1: ASSETS PACKAGED IN ACCORDANCE WITH PREVIOUS EDITIONS OF THIS SPI DO NOT REQUIRE REPACKAGING IF THE INTEGRITY OF THE SPI IS MAINTAINED.

NOTICE 2: SEE SPIRES FOR A COMPLETE LISTING OF NSN's ASSIGNED TO THIS SPI.

NOTICE 3: PACKAGING MATERIAL MAY BE SUBSTITUTED IF IT MEETS THE REQUIREMENTS OF MIL-STD-2073, PROVIDES EQUAL OR BETTER PROTECTION AND THERE IS NO INCREASED COST TO THE GOVERNMENT.

NOTICE 4: LEVEL A PROTECTION REQUIRED TO MEET THE MOST SEVERE WORLDWIDE SHIPMENT, HANDLING, AND STORAGE CONDITIONS. EXAMPLES OF SITUATIONS ARE: WAR RESERVE MATERIAL, MOBILIZATION, STRATEGIC AND THEATER DEPLOYMENT, OPEN STORAGE AND DECK LOADING. SECURITY ASSISTANCE ITEMS, INCLUDING FMS, ARE ESPECIALLY SUSCEPTIBLE TO DAMAGE DUE TO UNKNOWN AND UNFAVORABLE TRANSPORTATION, CLIMATIC, AND STORAGE CONDITIONS. PROVIDE LEVEL B PACKING UNLESS OTHERWISE DIRECTED BY THE PROCURING COUNTRY.

INTERNATIONAL STANDARDS FOR PHYTOSANITARY MEASURES**REVISION OF ISPM NO. 15****REVISION OF WOOD PACKAGING MATERIAL FOR INTERNATIONAL TRADE**

THE FOLLOWING STATEMENT IS IN COMPLIANCE WITH THE UNITED NATIONS-IMPLEMENTED RESTRICTIONS ON WOOD PACKAGING MATERIAL (WPM). THIS REQUIREMENT IS SPECIFICALLY CONCERNED WITH INVASIVE SPECIES SUCH AS THE PINEWOOD NEMATODE. WPM IS DEFINED AS WOOD PALLETS, SKIDS, LOAD BOARDS, PALLET COLLARS, WOODEN BOXES, REELS, DUNNAGE, CRATES, FRAMES, AND CLEATS. THE STATEMENT BELOW CITES THE REQUIREMENTS IN DETAIL AND COVERS LUMBER FOR BUILDING CONTAINERS AND PALLETS USED FOR DELIVERIES, RESULTING IN SHIPMENTS WORLDWIDE (DIRECT, OR THROUGH AIR LOGISTICS CENTERS (ALC), CONTAINER CONSOLIDATION POINTS (CCP), OR OTHER BASES).

WOODEN LUMBER, WOODEN PALLET AND PACKAGING/CONTAINER STATEMENT:

ALL WOODEN LUMBER, WOODEN PALLETS, AND WOODEN CONTAINERS PRODUCED ENTIRELY OR IN PART OF WOOD PACKAGING MATERIAL (WPM) SHALL BE CONSTRUCTED FROM DEBARKED WOOD IN ADDITION TO THE APPLICATION OF HEAT-TREATED (HT) MATERIAL (HT TO 56 DEGREES CENTIGRADE OR 133 DEGREES FAHRENHEIT FOR 30 MINUTES). CERTIFICATION/MARKING IS REQUIRED BY AN ACCREDITED AGENCY RECOGNIZED BY THE AMERICAN LUMBER STANDARDS COMMITTEE (ALSC). FOR REFERENCE DOCUMENTATION, SEE LATEST REVISION OF "INTERNATIONAL STANDARDS FOR PHYTOSANITARY MEASURES (ISPM NO. 15), "REGULATION OF WOOD PACKAGING MATERIAL IN INTERNATIONAL TRADE."

NOTES

1. THE HARD PLASTIC CASE **IS NOT** AN APPROVED SHIPPING CONTAINER AND **MUST BE** OVERBOXED AS SHOWN ON PAGE 4 OF THIS INSTRUCTION.

SPECIAL PACKAGING INSTRUCTION

CODE ID
98747SPI NO. (TPD)
F01-664-9140ITEM NOMENCLATURE
THEODOLITE, SURVEYING

SHEET 4 OF 4

