

Performance Work Statement
CLEAN, COAT AND PAINT METAL PARTS

BASE YEAR: Starts at time of award

Option Year: The year following the base year.

The contractor shall clean and coat all parts in accordance with the drawings and specifications provided. Only the coating sections of the drawings provided will be completed by the contractor. This will be an as needed service with deliveries spread out over the life of the contract. Six parts total will require treatment but could be sent in batches of a single part number (listed in Table 1) or, could be shipped in batches of six part numbers. Prior arrangement with the contractor will be made in advance of each shipment.

Paint color for part numbers 5-19-7355 Cap, Filter Inlet and 5-19-7437 Filter Body and Outlet Assembly, shall be:

Green 383 CAMO, Color Number 34094 per FED-STD-595 or

Tan 686A CAMO, Color Number 33446 per FED-STD-595.

Pine Bluff will give guidance to the contractor, in advance of shipment, as to the color required, if painting is required.

CLIN Structure

BASE YEAR		MIN QTY.	MAX QTY
CLIN 1	5-19-7355 Cap, Filter Inlet. Chromate Only	1,000	2,546
CLIN 2	5-19-7355 Cap, Filter Inlet Chromate and Paint (Green)	1	2,269
CLIN 3	5-19-7355 Cap, Filter Inlet Chromate and Paint (Tan)	1	277
CLIN 4	5-19-7437 Filter Body, Outlet Chromate only	1,000	2,546
CLIN 5	5-19-7437 Filter Body, Outlet Chromate and Paint (Green)	1	2,269
CLIN 6	5-19-7437 Filter Body Outlet Chromate and Paint (Tan)	1	277
CLIN 7	5-19-7443 Outer Mesh Assy. Chromate Only	1,000	1,832
CLIN 8	5-19-7440 Inner Mesh Assy. Chromate Only	1,000	1,832
CLIN 9	5-19-7444 Outer Gas Mesh Assy.	1,000	1,832
CLIN 10	5-19-7236 Channel, treat per drawing.	1	1,832

Option Year 1

MIN QTY MAX QTY

CLIN 1	5-19-7355 Cap, Filter Inlet. Chromate Only	1	2000
CLIN 2	5-19-7355 Cap, Filter Inlet Chromate and Paint (Green)	1	2000
CLIN 3	5-19-7355 Cap, Filter Inlet Chromate and Paint (Tan)	1	2000
CLIN 4	5-19-7437 Filter Body, Outlet Chromate only	1	2000
CLIN 5	5-19-7437 Filter Body, Outlet Chromate and Paint (Green)	1	2000
CLIN 6	5-19-7437 Filter Body Outlet Chromate and Paint (Tan)	1	2000
CLIN 7	5-19-7443 Outer Mesh Assy. Chromate Only	1	2000
CLIN 8	5-19-7440 Inner Mesh Assy. Chromate Only	1	2000
CLIN 9	5-19-7444 Outer Gas Mesh Assy.	1	2000
CLIN 10	5-19-7236 Channel	1	2000

TABLE 1

Part # and Nomenclature and Drawing Number to be referenced	SPECIFICATION	Minimum Quantity Per Shipment
5-19-7443 Outer Mesh Assy.	7.3.1 Mil-Std-171 (Note 5 on Drawing)	250
5-19-7440 Inner Mesh Assy.	7.3.1 Mil-Std-171 (Note 5 on Drawing)	250
5-19-7236 Channel	Finish 1.9.2.1 or 1.1.2.2 of Mil-Std-171 (Note 3 on Drawing)	250
5-19-7444 Outer Gas Mesh Assy.	7.3.1 Mil-Std-171 (Note 5 on Drawing)	250
5-19-7355 Cap, Filter Inlet	7.3.1 Mil-Std-171 (Note 12 on Drawing) No Vacuum Impregnation 20.24 of MIL-STD-171, Color per table 1, Exterior Surfaces only (Notes 12 on Drawing) Area to be free of paint (note 14 of drawing)	250
5-19-7437 Filter Body and Outlet Assembly	7.3.1 Mil-Std-171 (Note 4 on Drawing) 20.24 of MIL-STD-171, Color per table 1, Exterior Surfaces only (Notes 5 on Drawing) Area to be free of paint (note 6 of drawing)	250

SALT FOG REQUIREMENT

Verify corrosion resistance requirements by salt fog testing in accordance with Method 509.5 of MIL-STD-810, except the total duration shall be two 96-hour exposure cycles. Each 96-hour exposure cycle consists of four 24-hour periods of alternating salt fog challenge and drying periods. After the two 96-hour exposure cycles, rinse the external surfaces with clearwater if desired, dry, and inspect filter (inside and outside) for evidence of damage and corrosion. There shall be no deformation, cracking or flaking of the final coating can be removed by fingernail or knife. Discoloration of the material is acceptable.