

**SALIENT CHARACTERISTICS
FOR
BRAND NAME
Raymond 9600-CSR30T Swing-reach very narrow rail guided turret forklift**

March 2026

**Salient Characteristics
For
BRAND NAME
Raymond Forklift Truck
Fairchild AFB, WA**

1. BACKGROUND: LRS requires the ability to safely access parts and materials stored in aisle locations that require a swing-lift to place in location while safely and efficiently moving Fairchild Air Force Base assets.

2. OBJECTIVES: Maintain safe and efficient operation of warehouse by obtaining and utilizing forklift trucks.

3. REQUIREMENTS: The contractor shall provide one new BRAND NAME Raymond 9600-CSR30T Swing-reach very narrow rail guided turret forklift with the following minimum salient characteristics:

- Rated capacity 3000-lbs to 240", 2900-lbs to 250 & 2200-lbs to 274"
 - Base legs 40" wide Forks 42" long
 - Travel alarm – forward & reverse.
 - Guide roller with auto center steering (set for Current Guide Rails)
 - Safety amber strobe light
 - Lift limit switch with override button
 - Speed reduced over 24" of lift
 - Full body harness and retractable type tether
 - Fire Extinguisher
 - Side-gate power cut-off switches
 - Forward & reverse lights; aisle & work area LED
 - Manuals: operator/ parts/ maintenance. English. One paper copy
 - Operator Compartment Fan
 - Operator compartment dome light
 - Weight & Height limit display
 - UL "E" Safety rating
 - Delivery, set-up, prep, testing and 90 day follow-up visit.
- Add-ons:**
- Qty. (1) new M250-1212515-BRAY, rated at 875-Ah, 24-volt, lead-acid type battery. Weight 1775, includes single point watering system and electrolyte level indicator light
 - Qty. (1) X7MV48-480-0207-BRAY, AC power: 480-V, 3-Ph. Includes floor stand and cable retractor pole.

4. DELIVERY: FOB Destination