

Grissom ARB Bio Identification and Notification

Contractors are required to provide a list of any toxic chemicals or materials to be used, to include any OSHA expanded standard chemicals. The list is attached, starting on page 2 of this document.

Contractors are also required to notify the Contracting Officer if any lasers or radioactive material will be used, prior to entering Grissom Air Reserve Base.

Corresponding Expanded Standards Requirements - Crosswalk	Permissible Exposure Limit	Supplementary OEEL	Training	Refresher Training	Medical Surveillance	Periodic Examinations	Initial Monitoring	Routine Monitoring	Special respiratory requirements	Written Compliance Program	Written Housekeeping Plan	Air Monitoring Notification limit	Regulated Areas	Medical Removal Protection	Change Rooms	Shower provided	Worker Rotation	Written Emergency Action Plan
1. 1,2-dibromo-3-chloropropane	0.001 ppm	None	Any	None	Enter regulated areas	YR	Yes	6 mon	No	Yes	No	15 WD	Yes-PEL	No	Yes	Yes	No	Yes
2. 1, 3 Butadiene	1 ppm	0.5 ppm (AL) 5 ppm (STEL)	AL	YR	AL-30	YR	Yes	YR	No	Yes	No	15 WD	Yes-PEL	No	No	No	No	Yes
3. Acrylonitrile	2 ppm	1 ppm (AL) 10 ppm (C)	AL	YR	AL	YR	Yes	6 mon	No	Yes	No	15 WD	Yes-PEL	No	Yes	Yes	No	Yes
4. Arsenic	0.01 mg/m ³	0.005 mg/m ³ (AL)	AL	YR	AL-30	YR	Yes-8hr	6 mon	Yes	Yes	Yes	15 WD	Yes-PEL	No	Yes	Yes	No	No
5. Asbestos (General Industry- i.e. vehicle brake maintenance)	0.1 f/cc	1 f/cc - 30 min (EL)	PEL	YR	PEL	YR	Yes*	6 mon	No	Yes	No	15 WD	Yes-PEL	No	Yes	Yes	No	No
6. Asbestos (Construction Industry- i.e., maintenance small scale abatement)	0.1 f/cc	1 f/cc - 30 min (EL)	Yes**	YR	Yes*	YR*	Yes	6 mon NEA option	Yes	No	No	10 WD	Yes-PEL	No	Yes	Yes	No	No
7. Benzene	1 ppm	0.5 ppm (AL) 5 ppm (STEL)	Any	AL-YR	AL-30	YR	Yes	6 mon	No	Yes-PEL	No	15 WD	Yes-PEL	Yes	No	No	No	No
8. Beryllium 29 CFR 1910.1024, 9 Jan 2017	0.2 µg/m ³	0.1 µg/m ³ (AL) 2.0 µg/m ³ (STEL)	Yes	YR	Yes	2 YR	Yes	AL -6 mon PEL -3 mon	Yes	Yes-PEL	Yes	15 WD	Yes-PEL	No	Yes	No	No	No
9. Cadmium	0.005 mg/m ³	0.0025 mg/m ³ (AL)	Any	Any-YR	AL-30	YR	Yes	PEL -6 mon	No	Yes-PEL	Yes	15 WD	Yes-PEL	Yes	Yes	Yes	No	Yes
10. Ethylene Oxide	1 ppm	0.5 ppm (AL) 5 ppm (EL)	AL	YR	AL-30	YR-30	Yes	6 mon	No	Yes-PEL	No	15 WD	Yes-PEL	No	No	No	No	Yes
11. Formaldehyde	0.75 ppm	0.5 ppm (AL) 2 ppm (STEL)	>.1ppm	YR	AL	YR-AL exp	Yes	6 mon	Yes	No	No	15 WD	Yes-PEL	Yes	Yes	No	No	No
12. Chromium (VI) Hexavalent	0.005 mg/m ³	0.0025 mg/m ³ (AL)	No**	No	AL-30	YR	Yes	AL- 6 mon	No	No	No	15 WD	Yes-PEL	No	Yes	No	No	No
13. Lead (General Industry- i.e., brakes, lab compounds, lead bricks, bullets, CATM activities, blasting/sanding lead paint)	0.05 mg/m ³	0.03 mg/m ³ (AL)	AL or skin/eye	YR	AL-30	YR-AL exp	Yes, 7 hr	6 mon – NEA option	No	Yes-PEL	No	15 WD	No	Yes	Yes	Yes	Yes	No
14. Lead (Construction- i.e., lead seals, lead paint remediation	0.05 mg/m ³	0.03 mg/m ³ (AL)	AL	YR	AL	YR if AL-30	Yes-AL	6 mon	No	Yes	Yes ☯	5 WD	No	Yes	Yes	Yes	Yes	No

stripping for construction & maintenance activities)																		
15. Methylene Chloride	25 ppm	12.5 ppm (AL) 125 ppm (STEL)	Any	YR	AL-30 dermal-15	YR	Yes	6 mon	No	Yes	No	15 WD	Yes-PEL	Yes	No	No	No	Yes
16. Methylenedianiline (MDA)	0.01 ppm	0.005 ppm (AL) 0.1 ppm (STEL)	Any	YR	AL-30 Dermal-15	YR	Yes	3 mon	No	Yes	No	15 WD	Yes-PEL & Dermal	Yes	Yes	Yes	No	Yes
17. Vinyl Chloride	1 ppm	0.5 ppm (AL) 5 ppm (EL)	Any	YR	AL	YR*	Yes - AL	6 mon	No	No	No	15 WD	Yes-PEL	No	No	No	No	Yes
18. 1910.1003 -1910.1016 (Group of 13 Carcinogens)	None	None	Enter regul areas	YR	Enter regulated areas	YR	No	No	Yes	No	No	None	Yes-Any	No	Yes	Yes	No	Yes
19. Respirable Crystalline Silica	0.05 mg/m ³	0.025 mg/m ³ (AL)	AL	No**	AL-30	3 yrs	Yes, 8 hr	AL-6 mon PEL-3 mon	No	Yes-AL	Yes-AL	15 WD	Yes-PEL	No	No	No	No	No

Legend	WD: Working Days 6 mon: every six months if AL is exceeded, but annually if no exposures at PEL or greater No**(but mention in HazCom training.) Yes* 1926.1101(m)(2)(i)(A) Prior to assignment of the employee to an area where negative-pressure respirators are worn; 1926.1101(m)(2)(i)(B) When the employee is assigned to an area where exposure to asbestos may be at or above the permissible exposure limit for 30 or more days per year, or engage in Class I, II, or III work for a combined total of 30 or more days per year, a medical examination must be given within 10 working days following the thirtieth day of exposure; Yes** 1926.1101(o)(4)(i) For Class I and II asbestos work the competent person shall be trained in all aspects of asbestos removal and handling, including: abatement, installation, removal and handling; the contents of this standard; the identification of asbestos; removal procedures, where appropriate; and other practices for reducing the hazard. Such training shall be obtained in a comprehensive course for supervisors that meets the criteria of EPA's Model Accredited Plan (40 CFR part 763, subpart E, Appendix C), such as a course conducted by an EPA-approved or state-approved training provider, certified by EPA or a state, or a course equivalent in stringency, content, and length. 1926.1101(o)(4)(ii) For Class III and IV asbestos work, the competent person shall be trained in aspects of asbestos handling appropriate for the nature of the work, to include procedures for setting up glove bags and mini-enclosures, practices for reducing asbestos exposures, use of wet methods, the contents of this standard, and the identification of asbestos. Such training shall include successful completion of a course that is consistent with EPA requirements for training of local education agency maintenance and custodial staff as set forth at 40 CFR 763.92(a)(2), or its equivalent in stringency, content, and length. Competent persons for Class III and IV work, may also be trained pursuant to the requirements of paragraph (o)(4)(i) of this section. YR* Does not apply to Class IV training. Yes†; 1926.62 Appendix B (Employee Standard Summary) EL: Excursion Limit AL: Action Level STEL: Short-Term Exposure Limit as determined by any 15-minute sample period C: Ceiling Limit																	
--------	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

Updated: 7 February 2017 - This document now includes 29 CFR 1910.1024 Beryllium Expanded Standard final rule and is a summation of the requirements from this date. Users should always verify the 29 CFR 1910 OSHA regulatory requirements prior to using this document for publication or official reference.