

SALIENT CHARACTERISTICS

Heavy Equipment Attachments for Rapid Airfield Damage Repair (ADR)

1.0 BACKGROUND: The 161st Engineer Support Company (161 ESC), 20th Engineer Brigade, requires commercial heavy equipment attachments to modernize its Airfield Damage Repair (ADR) capabilities. The equipment is essential for decreasing runway repair times in contested environments by enabling operators to rapidly cut dense, reinforced concrete. The following characteristics are considered essential to meet the Government's minimum needs.

2.0 CLIN STRUCTURE AND ITEM DESCRIPTIONS: The contractor shall provide the following equipment. All quoted equipment must be new and meet the structural and performance specifications outlined below:

CLIN	Item Description	Detailed Description	Qty	Unit
0001	Saw Package	Complete Saw Package configured for M400T Skid Steer Loader and IHMEE.	1	EA
0001AA	Skid Steer Attachment	Saw Attachment compatible with M400T Skid Steer Loader and IHMEE	1	EA
0001AB	Army 24 Volt / Standard Flow Modifications	Saw modifications to include: New 24-Volt Electrical System; 60cc Motor for Standard Flow; Auxiliary Power Receptacle added for powering electrical components; External Hand Controls for operating saw	1	EA
0001AC	42" Guard for Package	42-inch Guard Assembly compatible with Saw Attachment	1	EA
0001AD	Pillow Block Assembly (Steel)	Steel Pillow Block Assembly compatible with Saw Attachment	1	EA
0001AE	Hose Kit	Hydraulic Hose Kit compatible with Saw Attachment	1	EA
0001AF	36" x .200 FSXP2CM Concrete Blade	36-inch x .200 Diamond Concrete Cutting Blade	1	EA
0001AG	36" x .220 Asphalt/Concrete Blade	36-inch x .220 Diamond Asphalt/Concrete Cutting Blade	1	EA
0001AH	42" x .200 Concrete Blade	42-inch x .200 Diamond Concrete Cutting Blade	1	EA
0002	Shipping	Shipping and Delivery FOB Destination to Fort Bragg, NC 28310	1	LO

3.0 PERFORMANCE AND TECHNICAL REQUIREMENTS

3.1 Primary Saw Attachment (CLIN 0001AA - 0001AB)

Cutting Capacity: The complete saw package must possess the ability to cut up to 18-inch-thick reinforced concrete.

Platform Compatibility: Must physically and hydraulically mount and integrate seamlessly with both the M400T Loader Skid Steer (LIN: L77147) and the IHMEE Tractor Wheeled Individual (LIN: H53576).

Note: The vendor must include all necessary interchangeable mounting brackets, adapter plates, and hydraulic hose/coupler configurations required to operate the attachment interchangeably on both machines.

Electrical/Hydraulic Integration: Must include the specified 60cc Motor for Standard Flow and fully integrate with existing Army 24-volt electrical systems via the modified auxiliary power receptacle and external hand controls (as defined in CLIN 0001AB).

Durability: Equipment must provide reliable operation under austere field conditions.

3.2 Components and Consumables (CLIN 0001AC - 0001AH)

All guards, pillow block assemblies, and hose kits must be OEM-compatible or seamlessly integrate with the primary saw attachment without further modification by the Government.

Blades provided (36-inch and 42-inch) must be diamond-tipped, heavy-duty commercial grade, and specifically rated for the materials identified (reinforced concrete and asphalt/concrete mix).

4.0 DELIVERY AND GENERAL REQUIREMENTS

Condition: All equipment must be strictly new and in original condition. Remanufactured, refurbished, or "gray market" items are not acceptable.

Manuals: Standard commercial operator and maintenance manuals shall be provided with the equipment.

Warranty: A standard commercial manufacturer warranty must be included and take effect upon Government acceptance of the equipment.

Delivery Date: All items must be delivered FOB Destination and ready for use no later than 01 June 2026.