

PRESOLICITATION NOTICE

Portable Light Towers

From: 700 CONS/PKA

Bldg 2767, Kapaun Air Station
D-67661, Kaiserslautern

POCs:

Contracting Specialist: Ms. Cevonia Joshua

E-mail: cevonia.joshua.1@us.af.mil
TEL: 0631 536 8444

Contracting Officer: Mr. Autry Fontenot

E-mail: autry.fontenot.2@us.af.mil
TEL: 0631 536 6787

Notice to Offeror(s)/Supplier(s):

Funds are presently available for this effort. An award will be made based on acceptable and conforming offeror. The Government reserves the right to cancel this solicitation, either before or after the closing date. In the event the Government cancels this solicitation, the Government has no obligation to reimburse an offeror for any costs.

Anticipated award date 08 May 2026

Due to the overseas location of this requirement, no set-aside will be used in accordance with RFO 19.000(b)(1)(ii). The North American Industry Classification System (NAICS) code associated with this requirement is **423810**. The Product Service Code (PSC) is **3990**. Evaluation of commercial items in accordance with RFO 52.212-2 will be utilized using most advantageous to the government.

Once solicited, all responsible sources may submit a quotation, bid, or proposal, as appropriate, which will be considered by the agency subject to the World Trade Organization. IAW RFO 52.225-5, Trade Agreements, one or more of the items under this acquisition is subject to the World Trade Organization Government Procurement Agreement and Free Trade Agreements.

Description of Requirement:

4 Portable Light Towers

The requirement consists of a mobile, diesel-powered, trailer-mounted lighting system designed for durability and ease of transport. The system must be equipped with four or more high efficiency 320W LED floodlights, capable of producing a minimum total luminous flux of over 211,000 lumens and illuminating an area of at least 9,200 square meters.

The system must feature a hydraulic vertical mast with a rotation capability of approximately 340 degrees to allow for precise light positioning. For operational flexibility, the unit must provide auxiliary power through an integrated alternator delivering at least 4.2kVA at 240V, complete with an external 16A outlet socket to power ancillary equipment. The entire system shall be mounted on a road-ready trailer that includes a foldable drawbar to minimize its footprint for storage and transport.

Interested offerors are encouraged to provide a tech sheet and/or photos of the item you intend to quote.