

SPECIAL PACKAGING INSTRUCTION			CODE ID 98747	SPI NO. (TPD) F01-038-5126 SHEET 1 OF 4
PART OR DRAWING NO. 9550616-1LC	NATIONAL STOCK NO. 1630-01-038-5126 LE	CURRENT REV G	ILL. K. KNIGHTON P.S. D. GIBSON CHK. S. LUCERO AUTH. J. BURLEIGH	
ITEM NOMENCLATURE WHEEL, LANDING GEAR		ORIGINAL DATE 89341		

MILITARY PRESERVATION IAW MIL-STD-2073-1

SERVICEABLE METHOD: 20

UNSERVICEABLE METHOD: 20

QUP 001

ICQ 000

CLEANING & DRYING: IAW MIL-STD-2073-1

PRESERVATIVE: MIL-PRF-81322G OR EQUAL

MARKING IAW MIL-STD-129

SPECIAL MARKINGS:

A) SPI NO. F01-038-5126
MARK THE SPI NUMBER ON THE IDENTIFICATION SIDE OF CONTAINER.

B) REUSABLE CONTAINER & DUNNAGE DO NOT DESTROY.

CLOSURE

LEVEL A: IAW: ASTM D6251 (UNNAILED CLOSURE)

LEVEL B: IAW: ASTM D6251 (UNNAILED CLOSURE)

PACKING AS SPECIFIED BELOW AND BILL OF MATERIALS

LEVEL	SPEC	STYLE	TYPE	CL	VRTY	GR	TR
A	ASTM D6251	III	2				B
B	ASTM D6251	III	2				A

	LEVEL A	LEVEL B
GROSS CU FT	10.871	10.871
GROSS WT LBS	196	196
DESIGN FRAGILITY G	110	110

	LENGTH	WIDTH	DEPTH
CNTR I.D.			
LEVEL A:	24 1/2	24 1/2	21 1/4
LEVEL B:	24 1/2	24 1/2	21 1/4

	LENGTH	WIDTH	DEPTH
CNTR O.D.			
LEVEL A:	26 3/4	26 3/4	26 7/8
LEVEL B:	26 3/4	26 3/4	26 7/8

ITEM DIM	24	24	18 5/8
ITEM WT.	151 LBS		

REVISIONS		
LTR	DESCRIPTION	DATE
G	CHANGED O.D. UPDATED B.O.M.	25126

SPI PACKS PRIOR TO REVISION D MUST BE REPACKED

WARNING/NOTE:

THE PACKAGER/SHIPPER HAS THE RESPONSIBILITY TO VERIFY THE REVISION OF THE EXISTING CONTAINER AND ENSURE THE CONTAINER MEETS THE CURRENT STANDARDS. IF UNABLE TO CONFIRM PROPER PACKAGING THEN CONTACT THE PACKAGING SPECIALIST ASSIGNED TO THE SPI.

CONTROLLED BY: 406 SCMS

CONTROLLED BY: GULAA-HILL AFB

CONTROLLED BY: CUI/SP-CTI

DISTRIBUTION/DISSEMINATION CONTROL: FEDCON

POC: 406SCMS.GULAA.CONTRACTSHILL@US.AF.MIL

SPI NO. F01-038-5126

SPECIAL PACKAGING INSTRUCTION				CODE ID 98747	SPI NO. (TPO) F01-038-5126
ITEM NOMENCLATURE WHEEL, LANDING GEAR					SHEET 2 OF 4
-7	2	STRAPPING, STEEL	5/8 X .020 X AS REQUIRED	ASTM D3953 TYPE 1, RD, FINISH A	
-6	A/R	TAPE, MASKING	1 X AS REQUIRED	ASTM D6123 TYPE I OR II	
-5	1	RACE COVER	AS REQUIRED	MIL-PRF-121 TYPE I	
-4	1	WRAP	82 X 42	A-A-3174 TYPE I, CLASS 1, GRADE A, FIN. 1	
-3	4	LINER, SIDE & END	24 1/4 X 20 1/4 X 1/8	ASTM D4727 CF, DOM, SW, GR 200	
-2	2	PAD, TOP & BOTTOM	23 7/8 X 23 7/8 X 1/8	ASTM D4727 CF, DOM, SW, GR 200	
-1	2	SKID	4 X 4 (NOM) X 26 3/4	ASTM D6199 CLASS 2	
P/N	QTY REQD	NOMENCLATURE DESCRIPTION	SIZE: (INCHES UNLESS SPECIFIED) TOLERANCES ON FRAC. $\pm \frac{1}{8}$, DECIMAL $\pm .01$, ANGLES $\pm 1^\circ$	MATERIAL SPECIFICATION	

SPECIAL PACKAGING INSTRUCTION	CODE ID 98747	SPI NO. (TPO) F01-038-5126
ITEM NOMENCLATURE WHEEL, LANDING GEAR		SHEET 3 OF 4

CAUTION NOTICES

NOTICE 1: ASSETS PACKAGED IN ACCORDANCE WITH THE PREVIOUS EDITION OF THIS SPI DO NOT REQUIRE REPACKAGING IF THE INTEGRITY OF THE SPI IS MAINTAINED.

NOTICE 2: SEE SPIRES FOR A COMPLETE LISTING OF NSN's ASSIGNED TO THIS SPI.

NOTICE 3: PACKAGING MATERIAL MAY BE SUBSTITUTED IF IT MEETS THE REQUIREMENTS OF MIL-STD-2073-1, PROVIDES EQUAL OR BETTER PROTECTION AND THERE IS NO INCREASED COST TO THE GOVERNMENT.

NOTICE 4: LEVEL A PROTECTION REQUIRED TO MEET THE MOST SEVERE WORLDWIDE SHIPMENT, HANDLING, AND STORAGE CONDITIONS. EXAMPLES OF SITUATIONS ARE: WAR RESERVE MATERIAL, MOBILIZATION, STRATEGIC AND THEATER DEPLOYMENT, OPEN STORAGE AND DECK LOADING. SECURITY ASSISTANCE ITEMS, INCLUDING FMS, ARE ESPECIALLY SUSCEPTIBLE TO DAMAGE DUE TO UNKNOWN AND UNFAVORABLE TRANSPORTATION, CLIMATIC, AND STORAGE CONDITIONS. PROVIDE LEVEL B PACKING UNLESS OTHERWISE DIRECTED BY THE PROCURING COUNTRY.

INTERNATIONAL STANDARDS FOR PHYTOSANITARY MEASURES**REVISION OF ISPM NO. 15****REVISION OF WOOD PACKAGING MATERIAL FOR INTERNATIONAL TRADE**

THE FOLLOWING STATEMENT IS IN COMPLIANCE WITH THE UNITED NATIONS-IMPLEMENTED RESTRICTIONS ON WOOD PACKAGING MATERIAL (WPM). THIS REQUIREMENT IS SPECIFICALLY CONCERNED WITH INVASIVE SPECIES SUCH AS THE PINWOOD NEMATODE. WPM IS DEFINED AS WOOD PALLETS, SKIDS, LOAD BOARDS, PALLET COLLARS, WOODEN BOXES, REELS, DUNNAGE, CRATES, FRAMES, AND CLEATS. THE STATEMENT BELOW CITES THE REQUIREMENTS IN DETAIL AND COVERS LUMBER FOR BUILDING CONTAINERS AND PALLETS USED FOR DELIVERIES, RESULTING IN SHIPMENTS WORLDWIDE (DIRECT, OR THROUGH AIR LOGISTICS CENTERS (ALC), CONTAINER CONSOLIDATION POINTS (CCP), OR OTHER BASES).

WOODEN LUMBER, WOODEN PALLET AND PACKAGING/CONTAINER STATEMENT:

ALL WOODEN LUMBER, WOODEN PALLETS, AND WOODEN CONTAINERS PRODUCED ENTIRELY OR IN PART OF WOOD PACKAGING MATERIAL (WPM) SHALL BE CONSTRUCTED FROM DEBARKED WOOD IN ADDITION TO THE APPLICATION OF HEAT-TREATED (HT) MATERIAL (HT TO 56 DEGREES CENTIGRADE OR 133 DEGREES FAHRENHEIT FOR 30 MINUTES). CERTIFICATION/MARKING IS REQUIRED BY AN ACCREDITED AGENCY RECOGNIZED BY THE AMERICAN LUMBER STANDARDS COMMITTEE (ALSC). FOR REFERENCE DOCUMENTATION, SEE LATEST REVISION OF "INTERNATIONAL STANDARDS FOR PHYTOSANITARY MEASURES (ISPM NO. 15), "REGULATION OF WOOD PACKAGING MATERIAL IN INTERNATIONAL TRADE."

NOTES

1. APPLY PRESERVATIVE MIL-PRF-81322G OR EQUAL TO THREADS AND METAL REQUIRED.
2. PLACE PADS, REF.-2 ON TOP, AND BOTTOM.
3. WHEN HEAT SHIELD PROTRUDES PAST THE TOP OF THE WHEEL, MAKE 'CUTOUT' IN LINER, REF.-2, TO ALLOW RECESS FOR PROTECTION OF SHIELD.

SPECIAL PACKAGING INSTRUCTION

CODE ID
98747SPI NO. (TPO)
F01-038-5126ITEM NOMENCLATURE
WHEEL, LANDING GEAR

SHEET 4 OF 4

