

Salient Characteristics

Overall Requirements: Low Speed Vehicle Specs, must be gasoline type, must not exceed 19 MPH max speed and cannot weigh more the 3K lbs.

- Gas-assist dump box makes unloading heavy loads from the cargo box quick and easy.
- Steering Tilt adjustment

Suspension:

- Front Suspension Dual A-arm
- Rear Suspension Dual A-arm
- Front Travel (in./cm.)10" (25.4 cm)
- Rear Travel (in./cm.)10" (25.4 cm)

Brakes:

- Front braking system4-wheel hydraulic disc with dual-bore front and rear calipers
- Rear braking system4-wheel hydraulic disc with dual-bore front and rear calipers
- Parking BrakePark in-transmission
- **Wheels & Tires:**
- Industrial heavy-duty tires, Wheels12" steel
- Front Tire 25 x 10-12; Carlstar 489
- Rear Tire 25 x 11-12; Carlstar 489

Dimensions:

- Bed Box Dimensions (LxWxH)36.7 x 54.2 x 12.5" (93 x 138 x 32 cm)
- Ground Clearance12" (30.5 cm)
- Overall Vehicle Size (LxWxH)120 x 62.5 x 76" (305 x 159 x 191 cm)
- Wheelbase 81" (206 cm)
- Hitch/Type Standard 2" (5 cm) receiver
- Turning Radius13.3' (4 m)

Capacities:

- Fuel Capacity at a minimum: 11.35 gal (43 L)
- Towing Capacity 2,500 lbs. (1,134 kg)
- Payload Capacity 1,500 lbs. (680 kg) CA Models: 1,100 lbs, (499 kg)
- Seating Capacity 3- no less than 2 with 3-point harness/safety belt

Weights:

- Estimated Dry Weight (lbs./kgs.) 1,487 lbs. (674 kg) // no heavier than 3K lbs.
- Curb Weight 1,612 lbs. (731 kg)

Lights and Safety:

- Lighting Halogen headlights, 55-W low beam, 60-W high beam, dual LED taillights

Features:

- Cargo System Gas-assist dump box with Lock & Ride accessory integration
- Seat Type 3-person bench seat
- Features Doors: Cab Nets- at a minimum
- speedometer, odometer, tripmeter, gear indicator, fuel gauge, coolant temperature, voltmeter, seat belt reminder
- Must have wind shield & roof