

Specifications: Lochinvar Armor® AWH0650NPM

Performance & Efficiency

- BTU Input: 650,000 BTU/hr
 - Thermal Efficiency: 98%
 - AFUE Rating: 98%
 - Turndown Ratio: 10:1 (Modulating burner)
 - Recovery Rate: 772 Gallons Per Hour (GPH) at a 100°F temperature rise
 - Working Pressure: 160 psi (ASME Section IV "HLW" Stamp certified)
 - Fuel Type: Natural Gas (Standard)
 - Low NOx Operation: Meets green technology and environmental standards
-

Physical Dimensions & Weight

- Height: 45 inches
 - Width: 24 inches
 - Depth: 41 inches
 - Shipping Weight: 424 lbs
 - Clearance: Approved for zero clearance to combustible materials and combustible floor installation
-

Connections & Venting

- Gas Connection Size: 1-1/4 inch
- Water Connection Size: 2 inch
- Air Inlet Size: 4 inch
- Vent Size: 4 inch (Supports up to 150 equivalent feet of venting)

- Venting Materials: Approved for PVC, CPVC, Polypropylene, or AL29-4C stainless steel
 - Venting Type: Direct Vent / Sealed Combustion (Pump Supplied)
 - Pump Specifications: All-bronze circulating pump (1/2 HP, 120V, 1 PH, 60 Hz)
-

Smart Technology & Controls

- Control System: SMART TOUCH™ full-color touchscreen LCD display
 - Remote Monitoring: CON·X·US® mobile communication platform (integrated)
 - Building Automation: Standard integration with 0-10 VDC input; optional Modbus or BACnet MSTP/IP communications
 - Sequencing: Built-in cascading sequencer for up to 8 water heaters
 - Safety Features:
 - Low water flow safety control and indication
 - Freeze protection
 - High/Low gas pressure switches with manual reset
 - Direct-spark ignition
 - Inlet and outlet temperature sensors
-

Construction & Maintenance

- Heat Exchanger: 316L Stainless Steel (Gasketless design)
- Serviceability: Features a slide-out door for improved access to the burner and heat exchanger
- Installation: Indoor/Outdoor convertible (Requires field conversion kit for outdoor use)
- Warranty: 5-year limited heat exchanger warranty; 1-year parts warranty