

HD 1-1/4" Extruded tongue and groove aluminum flooring – **Only Aluminum tread plate overlay available is that acceptable?**

- Not Acceptable (need smooth surface for rolling gear and other wheeled items)

Extruded bedrail and roof rail. Extruded 1" x 2 1/2" wall posts spaced at 16" OC – **Only 1" x 1 1/4" available is that acceptable?**

- Acceptable based on load rating

2 5/16" adjustable ball coupler, safety chains, breakaway switch, San-pa jack – **Not finding a 2 5/16" adjustable ball coupler. Is a fixed ball coupler acceptable?**

- Need tongue load rating for 2500lbs – adjustable not important

Generator system with vented storage breaker panel 12V inverter 2- 110V outlets above work bench and 2110V outlets in rear corners of trailer and through wall shore power plug ALL outlets must have water covers – **Is the generator to be included & installed with the trailer build? What size of generator is needed? Is the end user providing the generator? If the generator is not to be supplied by us, what are the dimensions of the generator door?**

- The generator is to be included & installed with the trailer build and sits on trailer tongue
- 5KW generator with housing large enough to contain and access for maintenance

AC with heat on roof – **Does the heat need to be ducted or just a heat strip in the A/C unit itself?**

- Ducted is not necessary, however a second A/C would suffice on the rear half

65 Gallon water tank with fill intake door and vent with drain plug – **Is this for a Fresh water dip tank for cleaning and rinsing gear? Does it need to be open at the top?**

- This is fresh water as it is for rinsing gear and needs to have a pump and valve for using a hose
- Needs to have an opening to fill tank from exterior of trailer

slide master for air compressor unit in rear DS -slides out roll-up door – **What are the dimensions of the compressor so we can design the master compartment?**

- roll-upside door 48"wide open by 66" Tall with a slide out tray supporting 1k lbs