

SPECIAL PACKAGING INSTRUCTION			CODE ID 98747	SPI NO. (TPD) F00-596-9637	
			SHEET 1 OF 4		
PART OR DRAWING NO. 160C136201-1	NATIONAL STOCK NO. 1630-00-596-9637 LE	CURRENT REV F	ILL. K. KNIGHTON P.S. B. TALBOT CHK. W. MONSON AUTH. J. BURLEIGH		
ITEM NOMENCLATURE WHEEL, LANDING GEAR		ORIGINAL DATE 97365			
MILITARY PRESERVATION IAW MIL-STD-2073			PACKING AS SPECIFIED BELOW AND BILL OF MATERIALS		
SERVICEABLE METHOD: 20		LEVEL	SPEC	STYLE	TYPE CL VRTY GR TR
UNSERVICEABLE METHOD: 20		A	ASTM D6251	A	III 2 B
QUP 001		B	ASTM D5118	RSC	V3c
ICQ 000				LEVEL A	LEVEL B
CLEANING & DRYING: IAW MIL-STD-2073		GROSS CU FT		1.712	0.967
PRESERVATIVE: MIL-PRF-81322 CODE 12 ▶		GROSS WT LBS		35	22
		DESIGN FRAGILITY G		110	110
MARKING IAW MIL-STD-129			LENGTH WIDTH DEPTH		
SPECIAL MARKINGS:			CNTR I.D.		
A) SPI NO. F00-596-9637			LEVEL A:		
MARK THE SPI NUMBER ON THE IDENTIFICATION SIDE OF CONTAINER.			LEVEL B:		
B) REUSABLE CONTAINER & DUNNAGE DO NOT DESTROY.			CNTR O.D.		
CLOSURE			LEVEL A:		
LEVEL A: IAW: ASTM D6251			LEVEL B:		
LEVEL B: IAW: ASTM D1974			ITEM DIM		
			ITEM WT.		
REVISIONS					
LTR	DESCRIPTION				DATE
F	ADDED DISTRIBUTION STATEMENT AND DESTRUCTION NOTICE, UPDATED DIMENSIONS AND BOM				21181
DISTRIBUTION STATEMENT D: DISTRIBUTION AUTHORIZED TO DOD AND U.S. DOD CONTRACTORS ONLY, ADMINISTRATIVE OR OPERATIONAL USE, 30 JUNE 2021. OTHER REQUESTS FOR THIS DOCUMENT SHALL BE REFERRED TO 406 SCMS/GULAA, (PACKAGING DIVISION), HILL AFB, UTAH 84056.					
DESTRUCTION NOTICE: FOLLOW THE PROCEDURES IN DOD 5220.22-M, NATIONAL INDUSTRIAL SECURITY PROGRAM OPERATING MANUAL (NISPO), SECTION 5-705, OR DOD 5200.1-R, INFORMATION SECURITY PROGRAM, CHAPTER VI. FOR UNCLASSIFIED, LIMITED DOCUMENTS, DESTROY BY ANY METHOD THAT WILL PREVENT DISCLOSURE OF CONTENTS OR RECONSTRUCTION OF THE DOCUMENT.					

SPI NO. F00-596-9637

SPECIAL PACKAGING INSTRUCTION	CODE ID 98747	SPI NO. (TPD) F00-596-9637
ITEM NOMENCLATURE WHEEL, LANDING GEAR		SHEET 3 OF 4

CAUTION NOTICES

NOTICE 1: ASSETS PACKAGED IN ACCORDANCE WITH PREVIOUS EDITIONS OF THIS SPI DO NOT REQUIRE REPACKAGING IF THE INTEGRITY OF THE SPI IS MAINTAINED.

NOTICE 2: SEE SPIRES FOR A COMPLETE LISTING OF NSN's ASSIGNED TO THIS SPI.

NOTICE 3: PACKAGING MATERIAL MAY BE SUBSTITUTED IF IT MEETS THE REQUIREMENTS OF MIL-STD-2073, PROVIDES EQUAL OR BETTER PROTECTION AND THERE IS NO INCREASED COST TO THE GOVERNMENT.

NOTICE 4: LEVEL A PROTECTION REQUIRED TO MEET THE MOST SEVERE WORLDWIDE SHIPMENT, HANDLING, AND STORAGE CONDITIONS. EXAMPLES OF SITUATIONS ARE: WAR RESERVE MATERIAL, MOBILIZATION, STRATEGIC AND THEATER DEPLOYMENT, OPEN STORAGE AND DECK LOADING. SECURITY ASSISTANCE ITEMS, INCLUDING FMS, ARE ESPECIALLY SUSCEPTIBLE TO DAMAGE DUE TO UNKNOWN AND UNFAVORABLE TRANSPORTATION, CLIMATIC, AND STORAGE CONDITIONS. PROVIDE LEVEL B PACKING UNLESS OTHERWISE DIRECTED BY THE PROCURING COUNTRY.

NOTICE 5: FOR LEVEL A PACKAGING REQUIREMENTS, LEVEL B PACKS SHALL BE OVERBOXED IN A LEVEL A SPECIFIED CONTAINER SHOWN ON PAGE 1 UNDER PACKAGING LEVEL A.

INTERNATIONAL STANDARDS FOR PHYTOSANITARY MEASURES

REVISION OF ISPM NO. 15

REVISION OF WOOD PACKAGING MATERIAL FOR INTERNATIONAL TRADE

THE FOLLOWING STATEMENT IS IN COMPLIANCE WITH THE UNITED NATIONS-IMPLEMENTED RESTRICTIONS ON WOOD PACKAGING MATERIAL (WPM). THIS REQUIREMENT IS SPECIFICALLY CONCERNED WITH INVASIVE SPECIES SUCH AS THE PINEWOOD NEMATODE. WPM IS DEFINED AS WOOD PALLETS, SKIDS, LOAD BOARDS, PALLET COLLARS, WOODEN BOXES, REELS, DUNNAGE, CRATES, FRAMES, AND CLEATS. THE STATEMENT BELOW CITES THE REQUIREMENTS IN DETAIL AND COVERS LUMBER FOR BUILDING CONTAINERS AND PALLETS USED FOR DELIVERIES, RESULTING IN SHIPMENTS WORLDWIDE (DIRECT, OR THROUGH AIR LOGISTICS CENTERS (ALC), CONTAINER CONSOLIDATION POINTS (CCP), OR OTHER BASES).

WOODEN LUMBER, WOODEN PALLET AND PACKAGING/CONTAINER STATEMENT:

ALL WOODEN LUMBER, WOODEN PALLETS, AND WOODEN CONTAINERS PRODUCED ENTIRELY OR IN PART OF WOOD PACKAGING MATERIAL (WPM) SHALL BE CONSTRUCTED FROM DEBARKED WOOD IN ADDITION TO THE APPLICATION OF HEAT-TREATED (HT) MATERIAL (HT TO 56 DEGREES CENTIGRADE OR 133 DEGREES FAHRENHEIT FOR 30 MINUTES). CERTIFICATION/MARKING IS REQUIRED BY AN ACCREDITED AGENCY RECOGNIZED BY THE AMERICAN LUMBER STANDARDS COMMITTEE (ALSC). FOR REFERENCE DOCUMENTATION, SEE LATEST REVISION OF "INTERNATIONAL STANDARDS FOR PHYTOSANITARY MEASURES (ISPM NO. 15), "REGULATION OF WOOD PACKAGING MATERIAL IN INTERNATIONAL TRADE."

NOTES

1. APPLY P12 TO BEARING CUP AND RACES. COVER WITH REF.-3, SECURE IN PLACE WITH TAPE, REF.-4.
2. PLACE PAD, REF.-1, IN BOTTOM OF CONTAINER AND FULLY ENCAPSULATE WHEEL IN REF.-5.
3. PLACE WHEEL INSIDE CONTAINER, INSERT LINERS, REF.-2, AND PLACE REMAINING PAD, REF.-1, ON TOP OF WHEEL.
4. USE EXTRA PADS, REF.-1 OR REF.-2, TO ENSURE A SNUG FIT.

SPECIAL PACKAGING INSTRUCTION

CODE ID
98747

SPI NO. (TP)
F00-596-9637

ITEM NOMENCLATURE
WHEEL, LANDING GEAR

SHEET 4 OF 4

