

SCOPE OF WORK

PROJECT: Supply and Deliver new Elation LED Automated Lighting Fixtures, and associated accessories.

LOCATION: United States Military Academy
Bldg. 655 / Eisenhower Hall Theatre
655 Pitcher Road
West Point, NY 10996

The Contractor shall supply and deliver the following items **(Brand Name – or Equal)**.

1. Elation Paragon M – 900W Variable CRI LED IP Framing Profile Fixture with CMY - (Brand Name – or – Equal)

MFR: Elation

P/N#: PAR112

ITEM: 900W Variable CRI LED IP Framing Profile Fixture with CMY

QTY: 14 each

Features and Specifications

SOURCE

High Efficiency 900W 6,500K Variable CRI White LED Engine

30,000 Hour Average LED Life*

*Test lab conditions. May vary depending on several factors including but not limited to:

Environmental Conditions, Power/Voltage, Usage Patterns (OnOff Cycling), Control, and Dimming.

PHOTOMETRIC DATA

37200 Total Lumen Fixture Output @ CRI 80

TruTone variable CRI up to CRI 93

Front Lens 6.3" (160mm)

Profile Lens (standard)

Zoom Range 4.5° - 52°

Beam Angle 4° - 48.6°

Field Angle 4.4° - 52°

Cutoff Angle 4.5° - 54.2°

PC Lens (optional)

Zoom Range 6° - 50°

Beam Angle 3.7° - 44.5°

Field Angle 5.8° - 50.2°

Cutoff Angle 6.7° - 52.1°

Fresnel Lens (optional)

Zoom Range 9° - 55°

Beam Angle 4.5° - 46.8°

Field Angle 8.9° - 54°

Cutoff Angle 13.4° - 60.4°

EFFECTS

Motorized Zoom

4 Full Blackout Framing Blades, +/-45° Index

+/-120° Framing Index

Full 360° Bi-Directional Animation Wheel

4-Facet Round and Linear Rotating Prisms

2 Variable Frost Filters (Light and Wash)

Motorized Iris with Variable Pulse Effects

Variable 16-bit Dimming Curve Modes

High Speed Electronic Shutter and Strobe

DMX Controllable LED Refresh Rate

Pan Angle: 540°

Tilt Angle: 260°

COLOR

CMY Color Mixing

Linear CTO Color Correction 6500K - 2600K

6 Dichroic Colors including UV Filter, Quad Color

TruTone variable CRI 73-93

GOBOS

2x 7 Rotating / Indexing Interchangeable Glass Gobos

CONTROL / CONNECTIONS

2 DMX Channel Modes (43/65)

16-bit Pan, Tilt and Dimming Control

5 Fan modes for ultra quiet operation

DMX, RDM, Art-NET, sACN Protocol Support

(4) Button Touch Control Panel

Full Color 180° Reversible LCD Menu Display

NFC on bottom and front of fixture base

Hibernation Mode (Power Save)

IP65 Locking 5pin XLR In/Out

IP65 Locking RJ45 Ethernet In/Out

IP65 Locking Power In

SIZE / WEIGHT

Length: 17.5 in (444mm)

Width: 12.4 in (315mm)
Height: 26.6 in (680 mm)
Center-to-Center Distance: 25.1 in (638mm)
Weight: 70.5 lbs. (32 kg)

MOUNTING

2x 180mm Omega Bracket
2x M12 Screw Hole
Fixture can be mounted in any orientation

ELECTRICAL

AC 100-240V 50/60Hz
Max Power Consumption 1400W
-4°F to 113°F (-20°C to 45°C)

INCLUDED ITEMS

Omega Brackets (x2)
IP65 Rated Locking Power Cable
Stainless Steel Safety Wire
Foam Inlay

APPROVALS / RATINGS

CE | cETLus | FCC | UKCA | IP54

2. Elation SOL I Blinder, 250W RGBLAW LED Modular Blinder, IP65 (Brand Name – or Equal)

MFR: Elation

P/N#: SOL001

ITEM: 250W RGBLAW LED Modular Blinder

QTY: 30 each

Features and Specifications

SOURCE

250W RGBLAW LED

30,000 Hour Average LED Life*

*Test lab conditions. May vary depending on several factors including but not limited to: Environmental Conditions, Power/Voltage, Usage Patterns (On-Off Cycling), Control, and Dimming.

PHOTOMETRIC DATA

Total Lumen Output

9128 (Integrating Sphere)

CRI TBA

Compound Lens

Beam Angle: 46°
Field Angle: 85°
No Lens Beam Angle: 52°
Field Angle: 95°

EFFECTS

Variable Strobe Rate: 1- 20kHz
Dim-to-Warm/ Red Shift Emulation
Variable 16-bit Dimming Modes and Curves
High Output Blinder Mode or Constant Output
Mode Options

COLOR

RGBLAW Color Array
CMY Emulation
Variable CCT 1800K - 8500K
Virtual Gel Swatch Book

CONTROL / CONNECTIONS

12 DMX Channel Modes (1ch, 2ch, 3ch, 4ch, 6ch, 7ch, 13ch, 21ch, 10ch, 15ch, 10ch & 15ch)
Simple 'Array Mode' Addressing System
Manual and DMX Controlled Dimmer and Color
4 Button Control Panel, LED Display
Aria x2 Wireless Device Management
RDM (Remote Device Management)
5pin DMX and IP65 Locking Power Cable In/Out

SIZE / WEIGHT (Without Accessories)

Length: 7.28" (185mm)
Width: 4.48" (114mm)
Vertical Height: 4.48" (114mm)
Weight (Fixture Only): 5.5 lbs (2.9 kg)
Weight (With Floor Stand/Yoke): 9.25 lbs (4.2 kg)

ELECTRICAL / THERMAL

AC 100-240V - 50/60Hz
285W Max Power Consumption
5°F to 113°F (-15°C to 45°C)
BTU/hr (+/- 10%) 972

INCLUDED ITEMS

Fixture Yoke / Floor Stand
Fixture Interconnect Adapter
Safety Cable

IP65 Locking Power Cable

OPTIONAL ITEMS

SÖL I Interconnect (SOL1IC)
SÖL I M10 Connect (SOL1M10C)
SÖL I Rear Mount Bracket (SOL1RMB)
SÖL I Heavy Duty Yoke (SOL1Y)
SÖL I Blinder Frame Kit (SOL1BFK)
) SÖL Fresnel Lens (SOLFL)
SÖL Frosted Lens (SOLFRO)
SÖL Bowens Adapter (SOLBA)
SÖL Dome Lens (SOLDL)
SÖL Blackout Lens (SOLBL)
SÖL Gel Frame Holder Kit (SOLGFHK)
SÖL Barndoor (SOLBD)
SÖL Power & DMX Jumper Cable (PDJ112)
8050000053 - Omega Bracket

APPROVALS / RATINGS

CE | cETLus | IP65 | FCC | UKCA

3. The Light Source MWB, Mega Claw Pipe Clamp - (Brand Name – or -Equal)

MFR: The Light Source

P/N#: MWB

ITEM: Mega Claw Pipe Clamp

QTY: 58 Each

Features and Specifications

- Minimum Size: 1.5" pipe, 1.90" OD pipe
- Maximum Size: 2" OD truss tube
- Safe Vertical Working Load: 1,100 lb (500kg)
- Hardware:
 - 1/2"-13 x 1" grade 5 hex head fixture mounting bolt with 1" diameter 600 pound belleville spring washer for tensioning.
 - 1/2"-13 x 4" trapazoidal head bolt for securing link to pipe.
- Dimensions (HxWxD): 4.375" x 6" x 2"
- Weight: 2 lb (0.9kg)

4. Leviton Locking Plug, 20Amp, 125 Volt, Industrial Grade, Black (Brand Name – or – Equal)

MFR: Leviton

P/N#: 2311-B

ITEM: 20Amp, 125Volt, NEMA L5-20P, 2P, 3W, Locking Plug, Industrial Grade Plug
QTY: 44 each

Features and Specifications

Color: Black

NEMA: L5-20P

Amperage: 20A

Twist-Lock Design

5. Eisenhower Hall Theater has a backstage loading dock for deliveries. The loading dock is at standard truck height. Dock plates are available for unloading.

6. The **PERIOD OF PERFORMANCE** for this procurement will begin on the date the contract is awarded or 30 day ARO (After Receipt of Order).