

**Specifications
Polymers and Liquid Aluminum Sulfate IDIQ
Yosemite National Park**

Objective:

The Utilities Branch at Yosemite National Park is soliciting for multiple types of polymer and liquid aluminum sulfate to aid in the process of water and wastewater treatment. The intent is to contract for materials that will improve plant operation and reduce total costs. These two facilities are located in El Portal on Highway 140 just east of Mariposa, and Wawona on Highway 41 at the south end of Yosemite National Park. Utilities Branch at Yosemite National Park is looking for a one-year contract with 4 option years, or a total of 5-year contract.

Background:

The El Portal Wastewater Treatment Plant (EPWWTP), 5083 Foresta Road, El Portal, CA 95318 is located on CA Route 140 and is at 2,000 feet elevation. Summer months are dry and very warm, winter months can produce snow. Delivery of goods during winter months may require chains on the delivery vehicle. There is a 45-foot maximum vehicle length limit, on CA Route 140. This plant has the ability to treat up to One Million Gallons per Day (1 MGD) of wastewater.

The EPWWTP is soliciting for three (3) types of polymer:

First, is a liquid Polyaluminum Chloride (PAC) polymer used in the tertiary treatment process. This product must reduce tertiary influent nephelometric turbidity unit (NTU) of 2 or lower and tertiary effluent average NTU of 0.10 or lower. This product must meet phosphorus influent of 2-3 mg/L and effluent of .20 mg/L. Must be National Science Foundation (NSF) 60/61 approved and must not change effluent characteristics which would cause failure to meet National Pollutant Discharge Elimination System (NPDES) requirements. This is to be delivered in totes of 275 gallons and 2 totes per delivery. Average usage is expected to be approximately 1,650 gallons/year, with delivery, 3 times per year. Any new or proposed PAC may not increase the conductivity of the final effluent above current levels with existing dosage.

Second, is a dry anionic polymer used in the secondary clarifier. This product must meet an influent 2-5 NTU and effluent of 1.0 NTU or lower. This dry polymer is to be delivered in 50-pound waterproof containers on pallet of 50. All containers and additives must be NSF 60/61 approved and must not change effluent characteristics which would cause failure to meet NPDES requirements. The expected annual procurement is 100 containers.

Third, is a liquid polymer used to centrifuge anaerobic digester solids. This product must consistently produce 24% or better total solids centrifuge discharge and produce visually clear centrate. The centrate cannot interfere with primary clarifier settling or decrease total solids to <2.5%. The polymer is to be delivered in returnable 275-gallon palletized totes and movable

with forklift or pallet jack (55-gallon drums are not acceptable, and vendor is required to remove empty totes with each delivery)

EPWWTP Liquid Aluminum Sulfate:

Liquid Aluminum Sulfate is used in the secondary wastewater treatment process to lower phosphorus and turbidity. This product must meet phosphorus influent of 2-3 mg/L and effluent of .20 mg/L. Must be NSF 60/61 approved and must not change effluent characteristics which would cause failure to meet NPDES requirements. This is to be delivered in bulk of up to 4,500 gallons per delivery. Average usage is expected to be approximately 22,500 gallons/year, with delivery quantities of 4,500 gallons, 5 times per year. Vendor shall pump bulk amount into existing aboveground tank. Any new or proposed PAC may not increase the conductivity of the final effluent above current levels with existing dosage.

Background:

The Wawona Wastewater Plant located at 4004 Chilnualna Falls Road, Wawona, CA 95389, and the Wawona Water Treatment Plant located at 2840 Gordon Way, Wawona, CA 95389, are both on CA Route 41 are at 4,000 feet elevation. Summer months are dry and very warm, but winter months produce snow, sometimes up to 4 feet at a time. Delivery of goods during winter months may require chains on the delivery vehicle. The Wawona Wastewater Plant has the ability to treat up to 100,000 Gallons per Day (GPD), Wawona Water Plant has the ability to treat 400,000 GPD.

The Wawona District is soliciting for two types of polymer:

The Wawona Wastewater Plant currently uses a liquid PAC polymer. This product must reduce tertiary filter influent of up to 15 NTU to a tertiary effluent average of 0.5 NTU or lower. This product must meet phosphorus influent of 2-3 mg/L and effluent of .20 mg/L and must be NSF 60/61 approved. This PAC is to be delivered in 275 Gallon Totes. The Wawona Wastewater Plant uses approximately 5,000 gallons per year. PAC must not change wastewater characteristics where a violation of Federal, State, or local water quality regulations would occur.

The Wawona Potable Water Plant currently uses a liquid PAC polymer. This product must reduce tertiary influent of 0.50 NTU or lower and to a tertiary effluent average of 0.10 NTU or lower. Product must be NSF 60/61 approved. This PAC is to be delivered in 275 Gallon Totes. The Wawona Potable Water Plant uses approximately 1,200 gallons per year. PAC must not change water characteristics where a violation of Federal, State, or local water quality regulations would occur.

Performance of Vendor:

1. The Utilities Branch at Yosemite National Park is soliciting vendors to deliver polymer samples (or mail 100ml sample) that meet the above chemical makeup criteria and NPS staff will perform jar testing on site.
2. Interested vendors shall reply to solicitation and will be contacted by NPS to send or deliver polymer samples for jar testing by NPS personnel.
3. After the jar tests are performed and completed, the vendor shall submit chemical make-up results to NPS, as well as a cost per 1,000 gallons treated within 72 hours.

4. If NPS deems product and price reasonable, vendor shall provide a 5-day supply of recommended polymer for a full-scale treatability run at a cost to the Government within 15 days of completion of numbers 1, 2 and 3 listed above. This purchase is not a contractual obligation and will be made by charge card.
5. All vendors must supply estimated cost per 1,000 gallons of water and wastewater treated after jar testing results along with test results and calculations.
6. Containers used to deliver the product must be removed by vendor at each delivery.
7. Product that has shelf life must be noted; expired product must be picked up by vendor at no charge to Government.
8. Multiple vendors may be selected to perform full scale test, by NPS personnel.
9. Plant operation records will be made available if requested.
10. All materials will be awarded to one vendor for both facility locations.

Delivery:

NPS will award contract to vendor no later than July 1st, 2026. Delivery orders will be placed by contracting officer as needed at plant operations. Delivery orders shall be made within 10 days of notice to proceed and delivered directly to EPWWTP and Wawona Plants, as applicable.

Vehicle length restriction on Hwy 140 maximum 45 feet total length**