

Model	Description
SCZII-61RD-38FX-EFI	61" Velocity Plus™ Rear Discharge Cutter Deck, 38 HP Kawasaki® FX Series EFI – electronic fuel injection
Product Dimensions	
Length	87"-91.25"
Width (chute down)	73.5"
Width (chute in transport position)	62.75"
Height (ROPS down)	49.5"
Height (ROPS up)	67"
Weight	1,364-1,392 lb
GENERAL	
Total Fuel Capacity	13 gallons
Drive Tires	24" x 12" - 12"
Caster Tires	13" x 6.5" - 6"
Seat	4-point iso-mounted mid-back mounted on operator-suspension platform
DRIVE SYSTEM	
Drive System Type	Hydro-Gear ZT5400 Transaxle. Two-Speed
Pumps	Internal Pump: 16 cc
Motors	Internal Motor: 21 cc
Forward Ground Speed	16 mph (high-speed) 12 mph (low-speed)
Reverse Ground Speed	8 mph (high-speed) 5 mph (low-speed)
Parking Brake	Foot-operated pedal
DECK	
Cutting Widths	61"
Type	Velocity Plus™
Cutting Height	1.25" to 5" in .25" increments
Deck Lift	Adjustable foot-operated pedal
Construction	Tri-plate cutter deck constructed of 3 steel plates totaling nearly 1/2" of steel. Reinforcement plates at cutter deck spindles.
Spindles	Cast-iron housing with tapered roller bearings.
Blade Engagement	Ogura GT5 (350 ft lb) Adjustable air-gap for extended life.



FEATURES

REAR-DISCHARGE VELOCITY PLUS CUTTER DECKS

VELOCITY PLUS REAR-DISCHARGE

The industry-leading 61" Velocity Plus™ Cutter Deck is also available in rear discharge (RD) on the Scag® Cheetah™ II. Same tough spindles and Tri-Plate deck top. Same Scag toughness built in.

Versatility — The Velocity Plus rear-discharge deck is ideal for cemeteries, roadsides, medians and parking lots, or any other location in which side discharging is not allowed or is undesirable.

Strength — Scag's tough cutter-blade spindles and Tri-Plate construction ensure solid performance and long life. Replaceable trim-side wear pads on both the left and right sides of the deck protect the deck and landscape from damage.

Productivity — An extra-large rear-discharge opening enhances discharge for even clipping dispersal.

Flexibility — The Velocity Plus cuts everything from fine grasses to tough weeds.



TIGER EYE ADVANCED MONITORING SYSTEM

The on-board Tiger Eye™ Advanced Monitoring System keeps a constant, real-time “eye” on important system functions on your Scag® mower.

Depending on the mower model and engine selection, a wide variety of systems are monitored in real-time, giving you valuable information in just a glance, right from the operator's seat. The backlit panel makes viewing easy, even in low light, while still easy to read in direct sunlight.

Real-time monitoring of the following systems:*

- Hour Meter
- Volt Meter / Charging System
- Engine Water Temperature (on liquid-cooled models)
- Engine Oil Pressure (on select models)
- Glow Plug Indicator (on diesel models)
- Air Filter Condition**
- Control Lever Circuit
- PTO Circuit
- Parking Brake Circuit
- Seat Switch Circuit
- Safety Interlock Module

OGURA PTO CLUTCH BRAKE

Other manufacturers opt for less expensive, smaller-capacity, nonadjustable, “disposable” clutches. Not Scag®. Scag PTO clutch brakes are manufactured by Ogura, the world's best manufacturer of electromagnetic clutches, providing smooth blade engagements and fast blade stops.

All Ogura clutches feature an adjustable air gap. What does that mean to you? It means that when most clutches are worn out and must be replaced at a significant cost to YOU, the Ogura clutch can be easily adjusted to bring it back into specification (your Scag dealer can perform this adjustment).

These clutches also feature industry-leading torque values (the holding power that links the engine to the cutter-deck drive system) to ensure solid drive to the cutter deck and no slipping in heavy conditions.