


TASK GROUP INSTRUCTION
AIM REV 20.11.4.0 (OCTOBER 2020)

TGI NO.:	COMPONENT NAME:	TYPE:	PHASE:	REPEAT:	CHANGE:
	AFT UPTAKE SPACE	AY	A	0	0
SHIP/HULL NO.:	SHIP/HULL NAME:	SYSTEM:	PROJ/WO NO:	CASREP CAT:	
DDG-76	USS HIGGINS		KB3		
CU PHASE TITLE:					
F/O - INSPECT, REPAIR, AND PRESERVE AFT UPTAKE SPACE					
PREPARING ACTIVITY:					
PREPARED BY:	CODE	PHONE	DATE		
KAZUMI WATANABE	231A	315-243-4518	19-DEC-2025		
APPROVED BY:	CODE	PHONE	DATE		
YUJI NAKAMURA	231A	315-243-6041	19-DEC-2025		
CONCURRED BY:	CODE	PHONE	DATE		
CONCURRED BY:	CODE	PHONE	DATE		
CONCURRED BY:	CODE	PHONE	DATE		
CONCURRED BY:	CODE	PHONE	DATE		
REASON FOR WORK/NEED FOR CHANGE:					
CHANGE INSTRUCTIONS:					
SPECIAL REQUIREMENTS:					
SURFMEPP					
This work affects a fire zone boundary. Fabrication and/or staging of a non-flammable closure is required.					

WORK CERTIFICATION SIGNATURES

COMPLETION OF WORK REVIEW:	BADGE NO.:	SHOP/CODE:	PHONE:	DATE:
ACCEPTANCE OF COMPLETED WORK				
PHYSICAL INSPECTION	PHYSICAL INSPECTION COMPLETED:	BADGE NO.:	SHOP/CODE:	PHONE:
REQUIRED: ☐ YES ☒ NO				
RECORDS REVIEW:	BADGE NO.:	SHOP/CODE:	PHONE:	DATE:



LIST OF EFFECTIVE PAGES									
SHT NO.	CHG NO.	SHT NO.	CHG NO.	SHT NO.	CHG NO.	SHT NO.	CHG NO.	SHT NO.	CHG NO.
1-7									
J1-2									
M1-4									

1. SCOPE/PURPOSE

1.1 Title: Inspection, Repair, and Preservation of Aft Uptake Space; accomplish

1.2 Location of Work:

1.2.1 05 Level Weather, Frames between 246 and 272, Port and Starboard (Stbd)

1.2.2 01 Level Weather, 44 Feet 10 Inches Above Base Line (ABL), Frames between 370 and 387, Port and Stbd

1.2.3 Uptake Engine Room No. 2 (02-242-0-Q)

1.2.4 Uptake Engine Room No. 2 (01-248-0-Q)

1.2.5 Intake/Uptake Engine Room No. 2 (1-268-2-Q)

1.2.6 Ships Service Gas Turbine Generator (SSGTG) Exhaust Trunk (1-254-1-Q)

1.2.7 SSGTG Exhaust Trunk (1-370-0-Q)

1.2.8 Supply Department Office (1-254-0-Q)

1.2.9 Passage (1-254-6-L)

1.3 Identification:

1.3.1 Quantity (One Lot), Exterior Surface of 05 Level Deck Plating, Frames between 246 and 272, including vertical surface up to height of top of shroud from above 76 feet above base line, Port and Stbd

1.3.2 Quantity (One Lot), Exterior Surface of 01 Level Deck Plating, 44 Feet 10 Inches ABL, Frames between 370 and 387, Port and Stbd

1.3.3 Quantity (One EA), Boundary Layered Infrared Suppression System (BLISS) Cap, 2A Propulsion Gas Turbine Exhaust

1.3.4 Quantity (One EA), BLISS Cap, 2B Propulsion Gas Turbine Exhaust

1.3.5 Quantity (One EA), BLISS Cap, No. 2 SSGTG Exhaust

1.3.6 Quantity (One EA), BLISS Cap, No. 3 SSGTG Exhaust

1.3.7 Quantity (One EA), 2A Propulsion Gas Turbine Exhaust Duct

1.3.8 Quantity (One EA), 2B Propulsion Gas Turbine Exhaust Duct

1.3.9 Quantity (One EA), SSGTG No. 2 Exhaust Duct

1.3.10 Quantity (One EA), SSGTG No. 3 Exhaust Duct

2 TGI NO.:

SHIP:

AFT UPTAKE SPACE	AY	A	0
DDG-76	CHG/VER:		0/0

1.3.11 Quantity (One EA), 02 Level, 2A Module Gas Turbine Engine Deck Foundation and Bolting Ring

1.3.12 Quantity (One EA), 02 Level, 2B Module Gas Turbine Engine Deck Foundation and Bolting Ring

1.3.13 Quantity (One EA), 02 Level, Engine Room No. 2 SSGTG Deck Foundation and Bolting Ring

1.4 Security Classification: None.

1.5 Initial Condition: None.

1.6 Contractor work start date: 29/JUN/2026

1.7 Contractor work completion date: 8/DEC/2026

2. REFERENCES:

REF. NO.	DOCUMENT /DRAWING NUMBER	DOCUMENT/DRAWING TITLE	REV	CHG NO.	COPY REQ'D (Y/N)	SOURCE DOC (Y/N)	PARA	SEC	PG	CHP
1	NSI FY-26	NAVSEA Standard Items	-	1	N					
2	LI FY-26	Local Standard Items	-	ORG	N					
3	DWG 180-6219049	FDN ARR DWG DSGN ZONE 4520 BKLT NO. 1	T		Y				SE E N O T E	
4	DWG 100-6218924	UNIT STRL ARR DWG ASSY UNIT 2340	Y		Y				3-12	
5	DWG 100-6218929	UNIT STRUCTURAL ARR DWG-ASSY UNIT 2440	AA		Y				3-11	
6	DWG 100-6218925	DDG-51 CLASS UNIT STRUCT ARR DWG ASSY UNIT 2350	U		Y				SE E N O T E	
7	DWG 100-6218930	UNIT STRUCTURAL ARR DWG-ASSY UNIT 2450	Y		Y				SE E N O T E	
8	DWG 150-6218967	UNIT STRL ARR DWG ASSY UNIT 4510	V		Y				SE E N O T E	
9	DWG 150-6218968	UNIT STRUCTURAL ARR DWG-ASSY UNIT 4520	T		Y				SE E N O T E	
10	DWG 100-6218939	DDG-51 CLASS UNIT STRUCTURAL ARR DWG-ASSY UNIT 3240	R		Y				3-6	
11	DWG 100-6218943	UNIT STRL ARR DWG ASSY UNIT 3340	AB		Y				3-10	
12	DWG 100-6218940	UNIT STRL ARR DWG ASSY UNIT 3250	Y		Y				SE E N O T E	

REF. NO.	DOCUMENT /DRAWING NUMBER	DOCUMENT/DRAWING TITLE	REV	CHG NO.	COPY REQ'D (Y/N)	SOURCE DOC (Y/N)	PARA	SEC	PG	CHP
13	DWG 100-6218944	UNIT STRUCTURAL ARR DWG ASSY UNIT 3350	W		Y				SE E N O T E	
14	DWG 259-6218424	FAB & INSTL OF GTBR UPTAKE & AIR INTAKES ENG RM. NO.2 & ABOVE	Y		N					
15	DWG 259-6219488	FAB AND INSTL OF SS GTRB UPTAKE AND AIR INTAKES ENG ROOM NO.2 AND ABOVE	AA		N					
16	DWG 259-6219487	FAB & INSTL OF SS GTRB UPTAKE GENERATOR RM & ABOVE	Y		N					
17	DWG 259-8436353	SHIPALT DDG-51-76087 GTRB & SS GTRB BLISS CAP MODS & ML	A		Y				AL L	
18	LAR 76087/DDG7 2/1141796	EXHAUST ANCHOR FDN CHOCK NOT CONFIGURED LIKE DRAWING	-		Y				AL L	
19	TM SYSTEMS & SPECIFICAT IONS	SSPC Painting Manual Volume 2	-		N					
20	TM T9074-AS-GIB-010/271	Requirements for Nondestructive Testing Methods	1		N					
21	TM S9086-DA-STM-010/CH-100	Hull Structures	4		N					
22	MIL MIL-STD-2035	Nondestructive Testing Acceptable Criteria	A		N					

3. APPENDICES:

- 3.1 Appendix "J" TGI Job Summary Information Sheet
- 3.2 Appendix "M" TGI Material List
- 3.3 Appendix "D" Deficiency Form

4. GENERAL REQUIREMENTS:

4.1 Not Applicable.

5. PROCEDURE:

5.1 Accomplish a visual inspection of the current ship condition, listed in 1.3.1 through 1.3.13, located in 1.2.1 through 1.2.7, using 2.3 through 2.18 for guidance, and as designated by the SUPERVISOR.

5.1.1 Ensure to inspect each exterior vertical, horizontal, step platform, deck, and foundation surface, and each interior exhaust stack, uptake duct, anchor foundation, eductor, eductor nozzle, eductor foundation, flange joint, overhead, bulkhead, deck, restraint, steel channel, penetration, deck spool, ladder foundation, bolting ring, and pipe hanger.

5.1.2 Mark each identified and designated area requiring repair.

5.1.3 Submit one legible copy, in hard copy or approved transferrable media, of a report with a sketch listing results of the requirements of 5.1 to the SUPERVISOR.

4 TGI NO.:

SHIP:

AFT UPTAKE SPACE	AY	A	0
DDG-76	CHG/VER:		0/0

5.2 Remove each BLISS cap listed in 1.3.3 through 1.3.6, located in 1.2.1 and 1.2.2, using 2.17 and 2.18 for guidance.

5.3 Power tool clean to bare metal for each location reported in 5.1.3, listed in 1.3.1 through 1.3.13, located in 1.2.1 through 1.2.7, to include each exposed longitudinal, vertical, and transverse stiffener, for up to 2,980 square feet. Accomplish each requirement of Surface Preparation Specification SSPC-SP 11 of 2.19, as designated by the SUPERVISOR.

5.4 Accomplish a visual inspection in each location for coating removed in 5.3, listed in 1.3.1 through 1.3.13, located in 1.2.1 through 1.2.7 for structural integrity, deterioration, pitting, each crack, and area of damage or distortion, using 2.3 through 2.18 for guidance.

5.4.1 Mark each corroded, damaged and/or deteriorated area.

5.4.2 Submit one legible copy, in hard copy or approved transferable media, of a report with a sketch listing results of the requirements of 5.4 to the SUPERVISOR.

5.5 Accomplish each ultrasonic thickness measurement (UTM) up to 100 locations in each location reported in 5.4.2, listed in 1.3.1 through 1.3.13, located in 1.2.1 through 1.2.7 in accordance with Paragraph 6.7 of 2.20 and 2.21, as designated by the SUPERVISOR, using 2.3 through 2.18 for guidance. The acceptance criteria must be in accordance with 2.22.

5.5.1 Submit one legible copy, in hard copy or approved transferable media, of a report listing results of the requirements of 5.5 to the SUPERVISOR.

5.5.2 Ensure a sketch showing each location of each UTM reading, original material thickness, existing material thickness, and percentage of material thickness reduction.

5.6 Accomplish the following repairs to each BLISS Cap listed in 1.3.3 through 1.3.6, located in 1.2.1 and 1.2.2, in accordance with 2.14 through 2.18 as designated by the SUPERVISOR. See 5.15.4 and 5.15.5.

5.6.1 Remove existing and install new, up to 30 square feet of BLISS Cap.

5.7 Accomplish the following repairs reported in 5.1.3, 5.4.2, and 5.5.1, listed in 1.3.1, 1.3.2, and 1.3.7 through 1.3.13, located in 1.2.1 through 1.2.7, using 2.3 through 2.18 for guidance, as designated by the SUPERVISOR. See 5.15.4 and 5.15.5.

5.7.1 Base metal weld build-up, up to 160 square inches.

5.7.1.1 Ensure each base metal buildup area does not exceed 2 inches in diameter.

5.7.1.2 Estimate the base metal buildup repair to be one quarter inch thick for pricing purposes.

5.7.1.3 Fill each local pit and groove with weld metal prior to the application of each principal build-up layer.

5.7.1.4 Ensure each surface is ground smooth to metal.

5.7.2 Remove existing and install new, up to 94 square feet of plate for each bulkhead, overhead, and deck plate.

5.7.3 Remove existing and install new, up to 75 linear feet of longitudinal, vertical, and traverse stiffener.

5.7.4 Remove existing and install new, up to 5 square feet of eductor foundation and flange joint.

5.7.5 Remove existing and install new each deck spool, gasket and bolting ring.

5.7.6 Vee out and weld up to 25 linear feet of cracked, split, broken or damaged weld.

AFT UPTAKE SPACE	AY	A	0
DDG-76	CHG/VER:	0/0	

5.7.7 Chip and grind each surface flush in way of each repair.

5.7.8 Template exact size, configuration, and location from each existing shipboard condition.

5.7.9 Accomplish the requirements of 009-012 of 2.1, including Table 2, Columns A, B, and D, Lines One through 7.

5.7.10 Accomplish the requirements of 009-025 of 2.1 for a local air hose test of each new weld seam. Allowable leakage: None.

5.8 Accomplish the requirements of 009-032 of 2.1, including Table 2, Line(s) 3, for coating removed in 5.3, listed in 1.3.1.

5.9 Accomplish the requirements of 009-032 of 2.1, including Table 2, Line(s) 21, for coating removed in 5.3, listed in 1.3.2.

5.10 Accomplish the requirements of 009-032 of 2.1, including Table 3, Line(s) 22A, for coating removed in 5.3, located in 1.2.3 through 1.2.7.

5.11 Accomplish the requirements of 009-032 of 2.1, including Table 5, Line(s) 15A, for each Bliss Cap listed in 1.3.3 through 1.3.6.

5.12 Install each BLISS cap listed in 1.3.3 through 1.3.6, located in 1.2.1 and 1.2.2, in accordance with 2.17 and 2.18.

5.13 Confirm that all personnel have exited the space prior to closure of the space listed in 1.2.4 through 1.2.7. Designate one person to account for all personnel who may have entered the space.

5.14 Accomplish the requirements of 009-032 of 2.1 for each new and disturbed surface.

5.15 Notes:

5.15.1 Planner: Code 231A K. Watanabe, 243-4518
Planner: Code 234 T. Tsunoi, 070-7787-2058

5.15.2 Work Integration Manager (WIM): Code 333 T. Yaginuma, 080-6522-9560

5.15.3 This TGI meets the intent of DDG CSWT File No. 259-090.

5.15.4 Removal and installation of interferences, and gas free operation, preservation of boundary spaces relating to front loading structure repair in 5.6 and 5.7 are not included in this TGI. They will be covered by a DL in the future based on Contractor submitted condition report.

5.15.5 Materials for structural members relating to front loading repair will be provided in the future as a DL based on Contractor submitted condition report.

5.15.6 Work per this instruction involves cutting an access (or removal of a door) through a fire zone bulkhead, through the hull of the ship above the turn of the bilge, through ventilation components (ducting, plenums, etc.), or through any air-tight, fume-tight or watertight bulkheads normally used to control air flow in the event of a shipboard fire. A nonflammable closure is required in accordance with COMNAVSEASYS COM MSG R 261400Z JUL 12. The closure, if not continuously in use, shall be staged near the access, readily visible and accessible, so that any emergency responder can install the closure to affect proper air flow onboard the ship.

5.15.7 WPC will copy the following pages in reference.

REF. 2.3: Pages 4, 4A, 4B, 7A1-1, 9C1-1, 5A1-9, 5B1-9, 5C1-9, 5D1-9, 5E1-9, and 5F1-9.

AFT UPTAKE SPACE	AY	A	0
DDG-76	CHG/VER:	0/0	

REF. 2.6: Pages 3-8 and 5B-11.

REF. 2.7: Pages 7A-5, 7D-9, 5-11, 7-9, 3-12, and 5A-12.

REF. 2.8: Pages 5A-11, 5B-11, 7-11, and 3-11.

REF. 2.9: Pages 3A-2, 3-8, 3B-9, 3D-8, and 3G-9.

REF. 2.12: Pages 3-7, 5A-10, and 7B-10.

REF. 2.13: Pages 7-1, 3-11, 3A-11, 5A-7, and 6-11.

5.15.8 JCNs EM02-ZBX8, EM02-ZBX9, EM02-ZBY0, EM02-ZBY1, EM04-ZAL7, EX03-ZA15, and OD01-ZAO5 are related to this TGI.

5.16 Government Furnished Material (GFM):

5.16.1 SRF-JRMC will provide GFM listed in Appendix "M".

5.17 SRF-JRMC will provide the following service work: (TGI No. 38KB312387S02).

5.17.1 [C740] Crane and crane rigging service.

5.17.2 [X99E] Utility service, electrical.

5.17.3 [X99M] Utilities service, including water supply, steam supply, and low pressure air supply except onboard blasting work.

5.17.4 [C106.1] Safety inspection for SRF-JRMC employees.

5.17.5 [C106.2] Gas free inspection for SRF-JRMC employees.

5.17.6 [C133] QA Inspection for (G) symbol(s).

AFT UPTAKE SPACE	AY	A	0
DDG-76	CHG/VER:	0/0	

APPENDIX "J"

TGI JOB SUMMARY INFORMATION SHEET

SYSTEM:	PLANT NO.:	COMPONENT NAME: AFT UPTAKE SPACE	TYPE: AY	PHASE: A	REPEAT: 0	CU PH VERSION: 0	CASREP CAT:
CU PHASE TITLE: F/O - INSPECT, REPAIR, AND PRESERVE AFT UPTAKE SPACE							
PRIMARY COMPONENT:							
COMPONENT UNIT LIST (FOR ASSEMBLIES): 05LVL & ABV EXTERIOR MS							
ATTACHMENT LIST:							
ZONE MANAGER: YAGINUMA ,TAKEHIDE		ZONE:	COMPARTMENT:	LEVEL:	FRAME:	SIDE:	
JO: 38KB312387	KO: A01	TOTAL MAN HRS:	TOTAL MAT'L COST	TOTAL DURATION:	PLANNING ACCEPTANCE:		
CU PHASE DESCRIPTION: The purpose of this TGI is to inspect, repair, and preserve aft uptake space. Location of Work: 05 Level Weather, Frames between 246 and 272, Port and Starboard (Stbd) 01 Level Weather, 44 Feet 10 Inches Above Base Line (ABL), Frames between 370 and 387, Port and Stbd Uptake Engine Room No. 2 (02-242-0-Q) Uptake Engine Room No. 2 (01-248-0-Q) Intake/Uptake Engine Room No. 2 (1-268-2-Q) Ships Service Gas Turbine Generator (SSGTG) Exhaust Trunk (1-254-1-Q) SSGTG Exhaust Trunk (1-370-0-Q) Supply Department Office (1-254-0-Q) Passage (1-254-6-L)							

J-1 TGI NO.:

SHIP:

AFT UPTAKE SPACE	AY	A	0
DDG-76	CHG/VER:		0/0

J-2 TGI NO.:
SHIP:

AFT UPTAKE SPACE	AY	A	0
DDG-76	CHG/VER:		0/0

APPENDIX "M"

TGI MATERIAL LIST

SYSTEM:	PLANT NO.:	COMPONENT NAME:	TYPE:	PHASE:	REPEAT:	CU PH VERSION:	CASREP CAT:
		AFT UPTAKE SPACE	AY	A	0	0	

CU PHASE TITLE:

F/O - INSPECT, REPAIR, AND PRESERVE AFT UPTAKE SPACE

MATERIAL REFERENCES

REF NO.	DOCUMENT/DRAWING NUMBER	DOCUMENT/DRAWING TITLE	REV
1	259-8436353		

JOB ORDER:

38KB312387

KEY OP:

A01

MATERIAL LIST

ITEM NO.	PC NO.	REF NO.	M / C	DESCRIPTION	STOCK NUMBER	GENERIC MATL TYPE	LVL	QA	HAZ MAT	DOC NO.	QTY REQD/ UNIT	QTY USED/ UNIT
400			M	GASKET, FIBERGLASS, GASKET, FIBROUS GLASS, WIRE-REINFORCED PLAIN, TAPE, SPEC: HH-P-31, TYPE I, CLASS 2, SIZE: 1/2"W X 1/8"THK X 20FT L, REMARKS: NON ASBESTOS REQUIRED, C234 T. TSUNOI, 070-7787-2058 ORDER FOR KTR	9B 5330 LL4924382		NA	4	N		14/RO	

NOTES:

M-1

TGI NO.:	AFT UPTAKE SPACE	AY	A	0
SHIP:	DDG-76	CHG/VER:	0/0	

MATERIAL LIST

ITEM NO.	PC NO.	REF NO.	M / C	DESCRIPTION	STOCK NUMBER	GENERIC MATL TYPE	LVL	QA	HAZ MAT	DOC NO.	QTY REQD/ UNIT	QTY USED/ UNIT
401			M	GASKET, FIBERGLASS, GASKET, FIBROUS GLASS, WIRE-REINFORCED PLAIN, CLOTH, SPEC: HH-P-31, TYPE I, CLASS 1, MATERIAL: FIBER GLASS, WIRE INSERT, FIBER GLASS SIZE: 81-11/16" OD X 76-7/16" ID X 3/8" THK, BOLT BIW CAT# 52248-469, C234 T. TSUNOI, 070-7787-2058 ORDER FOR KTR	9B 5330 LL9810157		NA	4	N		4/EA	
402			M	FERRULE, FERRULE, FIBROUS GLASS, WIRE-REINFORCED PLAIN, CLOTH, SPEC: HH-P-31, TYPE I, CLASS 1, SIZE: 31/32"OD X 21/32"ID X 1/2" THK, REMARKS: NON ASBESTOS REQUIRED, BIW CAT NO. 54638-027, C234 T. TSUNOI, 070-7787-2058 ORDER FOR KTR	9B 5340 LL4941032		NA	4	N		350/EA	
403			M	WASHER,2, WASHER, FIBROUS GLASS, WIRE-REINFORCED PLAIN, CLOTH, SPEC: HH-P-31, TYPE I, CLASS 1 SIZE: 2" OD X 21/32" ID, 3/8" THK. BIW CAT#: 52419-026 C234 T. TSUNOI, 070-7787-2058 ORDER FOR KTR	9Z 5310 LL4917124		NA	4	N	53507439	450/EA	
404			M	GASKET, FIBERGLASS, GASKET, FIBROUS GLASS, WIRE-REINFORCED PLAIN, CLOTH, SPEC: HH-P-31, TYPE I, CLASS 1, SIZE: 88-11/16" OD X 83-7/16" ID X 3/8" THK, BOLT CIRCLE DIA: 86-11/16", 40 BOLT HOLES, 25/32" DIA HOLES, HOLES EQUALLY SPACED, BIW CAT#: 52248-442 C234 T. TSUNOI, 070-7787-2058 ORDER FOR KTR	9B 5330 LL9810187		NA	4	N		2/EA	

M-2

TGI NO.:	AFT UPTAKE SPACE	AY	A	0
SHIP:	DDG-76	CHG/VER:	0/0	

MATERIAL LIST

ITEM NO.	PC NO.	REF NO.	M / C	DESCRIPTION	STOCK NUMBER	GENERIC MATL TYPE	LVL	QA	HAZ MAT	DOC NO.	QTY REQD/ UNIT	QTY USED/ UNIT
405			M	GASKET, FIBERGLASS, GASKET, FIBROUS GLASS, WIRE-REINFORCED PLAIN, CLOTH, SPEC: HH-P-31, TYPE I, CLASS 1, SIZE: 53-11/16"OD X 48-7/16"ID X 3/8"THK, BOLT CIRCLE DIA: 51-11/16", 24 BOLT HOLES, 25/32" DIA HOLES, HOLES EQUALLY SPACED, BIW CAT NO. 52248-434, C234 T. TSUNOI, 070-7787-2058 ORDER FOR KTR	9B 5330 LL9604082		NA	4	N		3/EA	
406			M	FERRULE, FERRULE, FIBROUS GLASS, WIRE-REINFORCED PLAIN, CLOTH, SPEC: HH-P-31, TYPE I, CLASS 1, SIZE: 31/32"OD X 21/32"ID X 3/8"LG, REMARKS: NON ASBESTOS REQUIRED, BIW CAT#: 54638-035, C234 T. TSUNOI, 070-7787-2058 ORDER FOR KTR	9B 5340 LL4941033		NA	4	N		150/EA	
407			M	GASKET, FIBERGLASS , GASKET, FIBROUS GLASS, WIRE-REINFORCED PLAIN, CLOTH, SPEC: HH-P-31, TYPE I, CLASS 1, SIZE: 62-11/16"OD X 57-7/16"ID X 3/8"THK, BOLT CIRCLE DIA: 60-11/16", 30 BOLT HOLES, 25/32" DIA HOLES, EQUALLY SPACED, BIW CAT NO. 52248-426, C234 T. TSUNOI, 070-7787-2058 ORDER FOR KTR	9B 5330 LL4941030		NA	4	N		2/EA	
408	105	1	M	GASKET, FIBERGLASS, GASKET, FIBROUS GLASS, WIRE-REINFORCED PLAIN, CLOTH, SPEC: HH-P-31, TYPE I, CLASS 1, SIZE: 104-7/8" OD X 95-1/8" ID X 3/8" THK, BOLT CIRCLE DIA: 102-3/8", 40 BOLT HOLES, 9/16" DIA HOLES, EQUAL SPACED, BIW CAT#: 52248-710 (OLD: 88033-507), C234 T. TSUNOI, 070-7787-2058 ORDER FOR KTR	9B 5330 LL7051201		NA	4	N		2/EA	

M-3

TGI NO.:	AFT UPTAKE SPACE	AY	A	0
SHIP:	DDG-76	CHG/VER:	0/0	

MATERIAL LIST

ITEM NO.	PC NO.	REF NO.	M / C	DESCRIPTION	STOCK NUMBER	GENERIC MATL TYPE	LVL	QA	HAZ MAT	DOC NO.	QTY REQD/ UNIT	QTY USED/ UNIT
409	119	1	M	GASKET, FIBERGLASS, GASKET, FIBROUS GLASS, WIRE-REINFORCED PLAIN, CLOTH, SPEC: HH-P-31, TYPE I, CLASS 1, SIZE: 60-7/8" OD X 51-1/8" ID X 3/8" THK, BOLT CIRCLE DIA: 58-3/8", 24 BOLT HOLES, 9/16" DIA HOLES, EQUALLY SPACED, BIW CAT#: 52248-728 (OLD: 88033-493), C234 T. TSUNOI, 070-7787-2058 ORDER FOR KTR	9B 5330 LL7051200		NA	4	N		1/EA	
410	124	1	M	GASKET,FLAT,PREFOMED, GASKET, SIZE: 53-1/2" OD X 51" ID X 0.375" THK, BOLT CIRCLE DIA: 52-1/2", 40EA OF 7/16" DIA HOLES EQUAL SPACED. HH-P-31 TY I CL 1 (BIW CAT#: 52248-701) (OLD: 88034-741) C234 T. TSUNOI, 070-7787-2058 ORDER FOR KTR	9B 5330 LL9301066		NA	4	N		1/EA	
411			M	GASKET, FIBERGLASS, GASKET, FIBROUS GLASS, WIRE-REINFORCED PLAIN, CLOTH, SPEC: HH-P-31, TYPE I, CLASS 1, SIZE: 106-11/16"OD X 101-7/16"ID X 3/8"THK, BOLT CIRCLE DIA: 104-11/16", 40 BOLT HOLES, 25/32" DIA HOLES, HOLES EQUALLY SPACED, BIW CAT NO. 52248-451 C234 T. TSUNOI, 070-7787-2058 ORDER FOR KTR	9B 5330 LL4941031		NA	4	N		2/EA	

M-4

TGI NO.:	AFT UPTAKE SPACE	AY	A	0
SHIP:	DDG-76	CHG/VER:	0/0	

☐ NUCLEAR☐ NON-NUCLEAR

APPENDIX "D"

DEFICIENCY FORM

1. SHIP/HULL NO.:	2a. DL or DR No. (Circle One)	2b. REVISION:	3a. COMPONENT NAME:	3b. TYPE:	3c. PHASE:	3d. REPEAT:
DDG-76			AFT UPTAKE SPACE	AY	A	0
4a. ICN: 38KB312387		4b. KEY OP: A01	5. LOC SPACE/LVL:	FRAME:	P/S/C:	6. CAUSED BY:

7. DESCRIPTION:

8. ORIGINATOR:	NAME:	BADGE:	SHOP/CODE:	DATE:	PHONE NO.:
----------------	-------	--------	------------	-------	------------

9. CORRECTIVE ACTION:

10. EVALUATOR:	NAME:	BADGE:	SHOP/CODE:	DATE:	PHONE NO.:
----------------	-------	--------	------------	-------	------------

FOR NON-NUCLEAR USE ONLY

11. RFD/RFW REQ'D ☐	LAR REQ'D ☐	SRD/PLAN REV REQ'D ☐
ILS MOD REQ'D ☐	DWG NO.: _____ S/A NO.: _____	

12. ISOLATION SATISFACTORY:	SIGN:	BADGE:	SHOP/CODE:	DATE:	PHONE NO.:
--------------------------------	-------	--------	------------	-------	------------

13. SUBSAFE OQE RECORD?	SIGN:	BADGE:	SHOP/CODE:	DATE:	PHONE NO.
YES ☐ NO ☐					

14. CORRECTIVE ACTION COMPLETE:	SIGN:	BADGE:	SHOP/CODE:	DATE:	PHONE NO.

15. INSPECTION REQ'D?	INSPECTION COMPLETE/SIGN:	BADGE:	SHOP/CODE:	DATE:	PHONE NO.
:YES ☐ NO ☐					

16. RECORDS REVIEW COMPLETE (DR ONLY)	SIGN:	BADGE:	SHOP/CODE:	DATE:	PHONE NO.

DL's ISSUED
(DR ONLY)

☐ NON-NUCLEAR

1. SHIP/HULL NO.:	2a. DL or DR No. (Circle One)	2b. REVISION:	3a. COMPONENT NAME:	3b. TYPE:	3c. PHASE:	3d. REPEAT:
DDG-76			AFT UPTAKE SPACE	AY	A	0

[illegible]