

STATEMENT OF WORK

1. Objective/Requirements

The information listed below is required to complete the purchase of a Haas ST-35Y Lathe at Kennedy Space Center (KSC).

2. Characteristics, Scope, and Specs

LINE	PART NO.	DESCRIPTION	QTY.
1	ST-35Y	Haas Y Axis CNC Lathe Y Axis CNC Lathe Swing Max Swing Dia 21" Std Turret 12-station BMT65, 1" Turning Tools Max Spd Live Tooling 4000 RPM Standard Capacities Chuck 12" Hyd Chuck, A2-8 Max Cut Dia (BMT65) 13.75" Max Cut Length 32.5" Bar Cap 4.0" Between Centers 32.5" Travel X Axis 9.4" Y Axis +/- 2.0" Z Axis 32.5" Feedrates Rapids X, Y 472 ipm Rapids Z 945 ipm Spindle A2-8 Spindle Spindle Bore 4.62" 40 hp Direct Speed Belt Drive Max Spd 3200 RPM Coolant System 55 Gal Tank w/ 1 hp pump Controller Features Control Touch Screen Media Display M-Code; M-130 Early Power Failure Detection Module Ethernet Interface Rigid Tapping Spindle Orientation 1GB Program Memory Power Surge Protection Memory Lock Keyswitch USB port	1

		BMT65 Toolholder Kit 3 ea 1" OD Toolholder 1 ea 1" ID Boring Bar Holder 1 ea 1.5" ID Boring Bar Holder 1 ea 1.5" ID Split Boring Bar Holder BMT65 Live Toolholder Kit 1 ea 90 Deg 1 ea Straight Misc 1 Year Warranty Std 230V, 3phz	
Options			
2	32GB	Expanded on-board solid-state memory allows storing, running, and editing large programs directly at the machine. Eliminates security risks posed by external storage devices such as USB Thumb-Drives and SD Disks.	1
3	HV-ISO-XFRMR	Internal High-Voltage Isolated Transformer for 380-480V operation.	1
4	LT-6K-UP	6000-rpm Live Tooling Speed Upgrade; increases the maximum speed of the driven tools from 4000 rpm to 6000 rpm. Requires LT-4K, LT-BMT65-12, or LT-BMT65-24 4000-rpm live tooling.	1
5	LT-BMT65-24Y	4000 RPM Live Tooling with C Axis: Includes 24-station (half-index) BMT65 turret. Accepts industry-standard base-mount tooling. Use live tooling to perform secondary operations (milling, drilling, flatting, and tapping) on the face and around the diameter of parts. The fully synchronized C axis provides precise interpolated bidirectional motion for positioning and repeatability. The 24-station BMT65 turret offers half-station indexing that increases your available tool stations. The turret will index every 15 degrees, rather than every 30 degrees. Y Series Machines Only	1
6	PTS-2	The Haas fully programmable hydraulic tailstock can be activated via the part program or controlled directly by the operator with the standard foot switch. Closed-loop positioning allows you to stop the tailstock anywhere along its travel. Compact, robust castings provide superior rigidity, and a proprietary quill design damps vibration. This tailstock features an MT4 taper.	1
7	VOP-B-ST-20Y-35Y	VOP-B for ST-20Y through ST-35Y models; includes 6000-rpm li	1

3. Place of Performance

NASA/ Kennedy Space Center
BOSS Receiving - M6-0744
POC: Jeremy Parr
Kennedy Space Center, FL 32899

4. Period of Performance

Need by 7/31/2026