

SPECIAL PACKAGING INSTRUCTION			CODE ID 98747	SPI NO. (TPQ) F01-047-5928	
			SHEET 1 OF 4		
PART OR DRAWING NO. 16B6514-133	NATIONAL STOCK NO. 1560-01-047-5928 WF	CURRENT REV E	ILL. K. KNIGHTON P.S. K. RESTORFF CHK. S. PEELER AUTH. N. CORONADO		
ITEM NOMENCLATURE DOOR, ACCESS, AIRCRAFT		ORIGINAL DATE 78206			
MILITARY PRESERVATION IAW MIL-STD-2073			PACKING AS SPECIFIED BELOW AND BILL OF MATERIALS		
SERVICEABLE METHOD: 10			LEVEL	SPEC	STYLE TYPE CL VRTY GR TR
UNSERVICEABLE METHOD: 10			A	ASTM D6251	A III 2 B
QUP 001			B	ASTM D5118	FTC V13c
ICQ 000			LEVEL A LEVEL B		
CLEANING & DRYING: IAW MIL-STD-2073			GROSS CU FT	19.060	10.836
PRESERVATIVE: N/A			GROSS WT LBS	115	44
			DESIGN FRAGILITY G	110	110
MARKING IAW MIL-STD-129			LENGTH WIDTH DEPTH		
SPECIAL MARKINGS:			CNTR I.D.		
A) SPI NO. F01-047-5928			LEVEL A:	49 1/2	36 1/4 11
MARK THE SPI NUMBER ON THE IDENTIFICATION SIDE OF CONTAINER.			LEVEL B:	47 1/4	34 10
B) REUSABLE CONTAINER & DUNNAGE DO NOT DESTROY.			CNTR O.D.		
			LEVEL A:	51 5/8	38 3/8 16 5/8
			LEVEL B:	49 1/8	35 7/8 10 5/8
CLOSURE			ITEM DIM	45 1/4	30 3/4 7
LEVEL A: IAW: ASTM D6251			ITEM WT.	28 LBS	
LEVEL B: IAW: ASTM D1974					
REVISIONS					
LTR	DESCRIPTION				DATE
E	UPDATED DIMENSIONS, ADDED DISTRIBUTION STATEMENT AND DESTRUCTION NOTICE				19024
DISTRIBUTION STATEMENT D: DISTRIBUTION AUTHORIZED TO DOD AND U.S. DOD CONTRACTORS ONLY, ADMINISTRATIVE OR OPERATIONAL USE, 16 JANUARY 2019. OTHER REQUESTS FOR THIS DOCUMENT SHALL BE REFERRED TO 406 SCMS/GULAA, (PACKAGING DIVISION), HILL AFB, UTAH 84056.					
DESTRUCTION NOTICE: FOLLOW THE PROCEDURES IN DOD 5220.22-M, NATIONAL INDUSTRIAL SECURITY PROGRAM OPERATING MANUAL (NISPO), SECTION 5-705, OR DOD 5200.1-R, INFORMATION SECURITY PROGRAM, CHAPTER VI. FOR UNCLASSIFIED, LIMITED DOCUMENTS, DESTROY BY ANY METHOD THAT WILL PREVENT DISCLOSURE OF CONTENTS OR RECONSTRUCTION OF THE DOCUMENT.					

SPI NO. F01-047-5928

SPECIAL PACKAGING INSTRUCTION	CODE ID 98747	SPI NO. (TPD) F01-047-5928
ITEM NOMENCLATURE DOOR, ACCESS, AIRCRAFT		SHEET 3 OF 4

CAUTION NOTICES

NOTICE 1: ASSETS PACKAGED IN ACCORDANCE WITH PREVIOUS EDITIONS OF THIS SPI DO NOT REQUIRE REPACKAGING IF THE INTEGRITY OF THE SPI IS MAINTAINED.

NOTICE 2: SEE SPIRES FOR A COMPLETE LISTING OF NSN's ASSIGNED TO THIS SPI.

NOTICE 3: PACKAGING MATERIAL MAY BE SUBSTITUTED IF IT MEETS THE REQUIREMENTS OF MIL-STD-2073, PROVIDES EQUAL OR BETTER PROTECTION AND THERE IS NO INCREASED COST TO THE GOVERNMENT.

NOTICE 4: FOR LEVEL A PACKAGING REQUIREMENTS, LEVEL B PACKS SHALL BE OVERBOXED IN A LEVEL A SPECIFIED CONTAINER SHOWN ON PAGE 1 UNDER PACKAGING LEVEL A.

NOTICE 5: OVERSEAS AND FMS PACKAGING MUST MEET THE REQUIREMENTS OF LEVEL A PACKAGING.

INTERNATIONAL STANDARDS FOR PHYTOSANITARY MEASURES

REVISION OF ISPM NO. 15

REVISION OF WOOD PACKAGING MATERIAL FOR INTERNATIONAL TRADE

THE FOLLOWING STATEMENT IS IN COMPLIANCE WITH THE UNITED NATIONS-IMPLEMENTED RESTRICTIONS ON WOOD PACKAGING MATERIAL (WPM). THIS REQUIREMENT IS SPECIFICALLY CONCERNED WITH INVASIVE SPECIES SUCH AS THE PINEWOOD NEMATODE. WPM IS DEFINED AS WOOD PALLETS, SKIDS, LOAD BOARDS, PALLET COLLARS, WOODEN BOXES, REELS, DUNNAGE, CRATES, FRAMES, AND CLEATS. THE STATEMENT BELOW CITES THE REQUIREMENTS IN DETAIL AND COVERS LUMBER FOR BUILDING CONTAINERS AND PALLETS USED FOR DELIVERIES, RESULTING IN SHIPMENTS WORLDWIDE (DIRECT, OR THROUGH AIR LOGISTICS CENTERS (ALC), CONTAINER CONSOLIDATION POINTS (CCP), OR OTHER BASES).

WOODEN LUMBER, WOODEN PALLET AND PACKAGING/CONTAINER STATEMENT:

ALL WOODEN LUMBER, WOODEN PALLETS, AND WOODEN CONTAINERS PRODUCED ENTIRELY OR IN PART OF WOOD PACKAGING MATERIAL (WPM) SHALL BE CONSTRUCTED FROM DEBARKED WOOD IN ADDITION TO THE APPLICATION OF HEAT-TREATED (HT) MATERIAL (HT TO 56 DEGREES CENTIGRADE OR 133 DEGREES FAHRENHEIT FOR 30 MINUTES). CERTIFICATION/MARKING IS REQUIRED BY AN ACCREDITED AGENCY RECOGNIZED BY THE AMERICAN LUMBER STANDARDS COMMITTEE (ALSC). FOR REFERENCE DOCUMENTATION, SEE LATEST REVISION OF "INTERNATIONAL STANDARDS FOR PHYTOSANITARY MEASURES (ISPM NO. 15), "REGULATION OF WOOD PACKAGING MATERIAL IN INTERNATIONAL TRADE."

NOTES

1. USE ADHESIVE A-A-59692 TYPE II OR EQUAL TO LAMINATE REF.-2 AND -3 TO ACHIEVE REQUIRED THICKNESS.
2. SCRIBE AROUND ITEM FOR CONTOUR SIZE AND DIMENSION FOR REF.-3; TO ENSURE A SNUG FIT.
3. WRAP ITEM IN REF.-4 AND SECURE WITH REF.-5 ENSURING TAPE DOES NOT MAKE CONTACT WITH SURFACE OF ITEM PRIOR TO PLACING REF.-3 ON ITEM.

SPECIAL PACKAGING INSTRUCTION

CODE ID
98747

SPI NO. (TP)
F01-047-5928

ITEM NOMENCLATURE
DOOR, ACCESS, AIRCRAFT

SHEET 4 OF 4

