

SPECIAL PACKAGING INSTRUCTION			CODE ID 98747	SPI NO. (TPD) F00-914-1329	
			SHEET 1 OF 4		
PART OR DRAWING NO. 219A967	NATIONAL STOCK NO. 1630-00-914-1329	CURRENT REV F	ILL. D. NAY P.S. W. MONSON CHK. K. RESTORFF AUTH. N. CORDONADO		
ITEM NOMENCLATURE WHEEL, LANDING GEAR		ORIGINAL DATE 89311			
MILITARY PRESERVATION IAW MIL-STD-2073					
SERVICEABLE METHOD: 20		PACKING AS SPECIFIED BELOW AND BILL OF MATERIALS			
UNSERVICEABLE METHOD: 20		LEVEL SPEC STYLE TYPE CL VRTY GR TR			
QUP 001		A ASTM D6251 A III 2 B			
ICQ 000		B ASTM D5118 RSC V3c			
CLEANING & DRYING: IAW MIL-STD-2073		LEVEL A LEVEL B			
PRESERVATIVE: MIL-PRF-81322 CODE 12 OR EQUAL		GROSS CU FT 4.106 2.770			
		GROSS WT LBS 61 47			
		DESIGN FRAGILITY G 110 110			
MARKING IAW MIL-STD-129		CNTR I.D. LENGTH WIDTH DEPTH			
SPECIAL MARKINGS:		LEVEL A: 19 3/4 19 3/4 13			
A) SPI NO. F00-914-1329		LEVEL B: 19 19 12			
MARK THE SPI NUMBER ON THE IDENTIFICATION SIDE OF CONTAINER.		CNTR O.D.			
B) REUSABLE CONTAINER & DUNNAGE DO NOT DESTROY.		LEVEL A: 21 3/4 21 3/4 15			
		LEVEL B: 19 3/8 19 3/8 12 3/4			
CLOSURE		ITEM DIM 18 1/2 18 1/2 11 3/4			
LEVEL A: IAW: ASTM D6251		ITEM WT. 44 LBS			
LEVEL B: IAW: ASTM D1974					
REVISIONS					
LTR	DESCRIPTION				DATE
F	ADDED DISTRIBUTION STATEMENT AND DESTRUCTION NOTICE				18192
DISTRIBUTION STATEMENT D: DISTRIBUTION AUTHORIZED TO DEPARTMENT OF DEFENSE AND U.S. DOD CONTRACTORS ONLY, ADMINISTRATIVE OR OPERATIONAL USE, 28 JUNE 2018. OTHER REQUESTS FOR THIS DOCUMENT SHALL BE REFERRED TO 406 SCMS/GULAA, (PACKAGING DIVISION), HILL AFB, UTAH 84056.					
DESTRUCTION NOTICE: FOLLOW THE PROCEDURES IN DOD 5220.22-M, NATIONAL INDUSTRIAL SECURITY PROGRAM OPERATING MANUAL (NISOPM), SECTION 5-705, OR DOD 5200.1-R, INFORMATION SECURITY PROGRAM, CHAPTER VI. FOR UNCLASSIFIED, LIMITED DOCUMENTS, DESTROY BY ANY METHOD THAT WILL PREVENT DISCLOSURE OF CONTENTS OR RECONSTRUCTION OF THE DOCUMENT.					

SPI NO. F00-914-1329

SPECIAL PACKAGING INSTRUCTION			CODE ID 98747	SPI NO. (TPD) F00-914-1329
ITEM NOMENCLATURE WHEEL, LANDING GEAR			SHEET 2 OF 4	
-3	A/R	TAPE, PACKAGING	3 X AS REQUIRED	ASTM D5486 TYPE I OR V
-2	A/R	WRAP	AS REQUIRED	A-A-3174 TYPE I, CLASS 1, GRADE A, FIN. 1
-1	2	PAD, TOP & BOTTOM	19 X 19 X 1/8	ASTM D4727 CF, DOM, SW, GR. 200
P/N	QTY REQD	NOMENCLATURE OR DESCRIPTION	SIZE: (INCHES UNLESS SPECIFIED) TOLERANCES ON FRAC. ± 1/8, DECIMAL ± .10, ANGLES ± 1°	MATERIAL SPECIFICATION

SPECIAL PACKAGING INSTRUCTION	CODE ID 98747	SPI NO. (TPO) F00-914-1329
ITEM NOMENCLATURE WHEEL, LANDING GEAR		SHEET 3 OF 4

CAUTION NOTICES

NOTICE 1: ASSETS PACKAGED IN ACCORDANCE WITH PREVIOUS EDITIONS OF THIS SPI DO NOT REQUIRE REPACKAGING IF THE INTEGRITY OF THE SPI IS MAINTAINED.

NOTICE 2: SEE SPIRES FOR A COMPLETE LISTING OF NSN's ASSIGNED TO THIS SPI.

NOTICE 3: PACKAGING MATERIAL MAY BE SUBSTITUTED IF IT MEETS THE REQUIREMENTS OF MIL-STD-2073, PROVIDES EQUAL OR BETTER PROTECTION AND THERE IS NO INCREASED COST TO THE GOVERNMENT.

NOTICE 4: FOR LEVEL A PACKAGING REQUIREMENTS, LEVEL B PACKS SHALL BE OVERBOXED IN A LEVEL A SPECIFIED CONTAINER SHOWN ON PAGE 1 UNDER PACKAGING LEVEL A.

NOTICE 5: OVERSEAS AND FMS PACKAGING MUST MEET THE REQUIREMENTS OF LEVEL A PACKAGING.

INTERNATIONAL STANDARDS FOR PHYTOSANITARY MEASURES
REVISION OF ISPM NO. 15
REVISION OF WOOD PACKAGING MATERIAL FOR INTERNATIONAL TRADE

THE FOLLOWING STATEMENT IS IN COMPLIANCE WITH THE UNITED NATIONS-IMPLEMENTED RESTRICTIONS ON WOOD PACKAGING MATERIAL (WPM). THIS REQUIREMENT IS SPECIFICALLY CONCERNED WITH INVASIVE SPECIES SUCH AS THE PINWOOD NEMATODE. WPM IS DEFINED AS WOOD PALLETS, SKIDS, LOAD BOARDS, PALLET COLLARS, WOODEN BOXES, REELS, DUNNAGE, CRATES, FRAMES, AND CLEATS. THE STATEMENT BELOW CITES THE REQUIREMENTS IN DETAIL AND COVERS LUMBER FOR BUILDING CONTAINERS AND PALLETS USED FOR DELIVERIES, RESULTING IN SHIPMENTS WORLDWIDE (DIRECT, OR THROUGH AIR LOGISTICS CENTERS (ALC), CONTAINER CONSOLIDATION POINTS (CCP), OR OTHER BASES).

WOODEN LUMBER, WOODEN PALLET AND PACKAGING/CONTAINER STATEMENT:

ALL WOODEN LUMBER, WOODEN PALLETS, AND WOODEN CONTAINERS PRODUCED ENTIRELY OR IN PART OF WOOD PACKAGING MATERIAL (WPM) SHALL BE CONSTRUCTED FROM DEBARKED WOOD IN ADDITION TO THE APPLICATION OF HEAT-TREATED (HT) MATERIAL (HT TO 56 DEGREES CENTIGRADE OR 133 DEGREES FAHRENHEIT FOR 30 MINUTES). CERTIFICATION/MARKING IS REQUIRED BY AN ACCREDITED AGENCY RECOGNIZED BY THE AMERICAN LUMBER STANDARDS COMMITTEE (ALSC). FOR REFERENCE DOCUMENTATION, SEE LATEST REVISION OF "INTERNATIONAL STANDARDS FOR PHYTOSANITARY MEASURES (ISPM NO. 15), "REGULATION OF WOOD PACKAGING MATERIAL IN INTERNATIONAL TRADE."

SPECIAL PACKAGING INSTRUCTION

CODE ID
98747

SPI NO. (TPD)
F00-914-1329

ITEM NOMENCLATURE
WHEEL, LANDING GEAR

SHEET 4 OF 4

