

FUNCTIONAL ASSESSMENT PLAN (FAP)

FINISHING OF HARDWOOD FLOORS

1503010

FINISHING OF HARDWOOD FLOORS FAP

<u>Assessment Levels (AL)</u>		<u>Assessment Frequency (Freq)</u>	<u>Method of Assessment (MOA)</u>
AL1	Start assessment at this Level	A – Annually Q – Quarterly M – Once per month BW – Once every 13-16 days W – Once per week R – As required	PS – Periodic Sampling VCC – Validated Customer Complaints UV – Unscheduled Visits CE – Customer’s Evaluation
AL2	Add this Level if Contractor performance for AL1 is Unsatisfactory		
AL3	Add this Level if Contractor performance at AL1 or AL2 is Unsatisfactory		
Note: Return to appropriate Assessment Level when performance improves.			Note: The first method listed in the MOA column below is the primary assessment method.

Spec Item	Performance Objective	Performance Standard	MOA	Assessment Level			Sample Size			Freq
				AL1	AL2	AL3	UOM (total)	Normal	Reduced	
3.1	Scheduled Services The Contractor shall provide scheduled floor services to ensure facilities are clean and have a uniform shine.	Facilities are clean and have a uniform shine. Work is completed in accordance with the Contractor’s schedule.	PS/VC C/UV		N/A	N/A		100%	0%	R
3.1.2	Floor Care The Contractor shall provide floor care services to ensure they are clean and sightly.	Floors are clean and have a uniform shine. Contractor shall remove by sanding all layers of floor finish down to raw wood. Contractor shall take all precautions to minimize the spreading of any dust particles created by this sanding. Contractor is responsible for removing and properly disposing of all sawdust and litter on a daily basis. Contractor shall thoroughly clean floor surface prior to applying a liberal and	PS/VC C/UV		N/A	N/A		100%	0%	R

Spec Item	Performance Objective	Performance Standard	MOA	Assessment Level			Sample Size			Freq
				AL1	AL2	AL3	UOM (total)	Normal	Reduced	
		uniform coat of penetrating sealer with a minimum coverage per manufacturer's instructions. Contractor shall apply two (2) coats of finish Contractor shall re-apply per manufacturer's instructions all name, logos, basketball court with NCAA volleyball game lines. The Contractor shall feather all game lines and shall have distinct edges with no overlap and matching existing lines. Contractor shall install new three (3) inch by four (4) inch vented cove base per manufacturer's instructions.								
3.1.2.1	Dust Mopping The Contractor shall dust mop all gymnasium floors.	Floors are free of debris and dust.	PS/VC C/UV		N/A	N/A		100%	0%	R
3.1.2.2	Buffing The Contractor shall scuff buff gymnasium floors to meet acceptable industry standards.	Floors are abraded enough to refinish. Floors are totally clean with no debris in edges or corners. Floors have been prepared to allow for even refinish.	PS/VC C/UV		N/A	N/A		100%	0%	R
3.1.2.3	Touch Up Painting The Contractor shall touch up/repaint Court lines, lettering, and logos at appropriate time in process.	Floors are clean, free of previously applied coat, and have a uniform finish. Games lines, lettering and logos are properly touched up, smooth and even in appearance. Sport Court lines have been touched up to meet sport standard and appear untouched.	PS/VC C/UV		N/A	N/A		100%	0% 100%	1 R

Spec Item	Performance Objective	Performance Standard	MOA	Assessment Level			Sample Size			Freq
				AL1	AL2	AL3	UOM (total)	Normal	Reduced	
		Floors are properly coated and protected. Services are performed at specified dates.								
3.1.2.4	Finishing Floors The Contractor shall seal any areas where finish is completely worn off prior to applying a minimum of two (2) coats of finish.	Floors are clean, free of previously applied coat, and have a uniform finish. Final coat of finish is applied after touch up painting game lines, lettering and logos are complete and dry. Floors are properly coated and protected. There is no finish on or near the rollers under the bleachers. Finished product shall have a uniform shine. Services have met the specified frequencies.	PS/VC C/UV		N/A	N/A		100%	0%	R
3.1.2.5	Replacement of Gymnasium Floor The Contractor shall sand existing floor. Requirements for replacement of gymnasium floor is provided in (J-1503010-07).	Floors are clean, free of previously applied coat, and have a uniform finish. Final coat of finish is applied after touch up painting game lines, lettering and logos are complete and dry. Floors are properly coated and protected. There is no finish on or near the rollers under the bleachers.								
4	Non-recurring Work Non-recurring work may be ordered utilizing WAFA in accordance with Section H or on a task order in accordance with the PROCEDURES FOR ISSUING	Non-recurring work may be ordered utilizing WAFA in accordance with Section H or on a task order in accordance with the PROCEDURES FOR ISSUING ORDERS clause in Section G. The order will specify the	PS/VC C/UV				EA	100%	N/A	As reqd

Spec Item	Performance Objective	Performance Standard	MOA	Assessment Level			Sample Size			Freq
				AL1	AL2	AL3	UOM (total)	Normal	Reduced	
	ORDERS clause in Section G. The order will specify the exact locations and types of work to be accomplished. The period of performance will be specified in each order.	exact locations and types of work to be accomplished. The period of performance will be specified in each order.								

MONTHLY PERFORMANCE ASSESSMENT SUMMARY

Contract #: NXXXXX-11-D-XXXX Installation/Site: _____
 Annex/sub-annex: 1503010 Custodial Month/Year: _____

Spec Item	Title	AL1 Rating						AL2/AL3 Rating			VCC	Safety	
		E	VG	S	M	U	# Samples	A	U	# Samples		Issues	# Samples
3.1	Scheduled Services												
3.1.2	Floor Care												
3.1.2.1	Dust Mopping												
3.1.2.2	Buffing Floors												
3.1.2.3	Touch Up Painting												
3.1.2.4	Finishing Floors												
4	IDIQ												
Comments:													
Recommended Actions:													
		Technical Ratings (mark using "X")											
		E	VG	S	M	U							
Overall Technical Rating for FFP Work													
Overall Technical Rating for IDIQ Work													
SPAR Signature: _____ Date: _____													