

SPECIFICATIONS 0001
UCR Fish Screen
Upper Colorado River Recovery Program

1. Product Features

Salient Characteristics:

- One (1) fish screen
 - Total of 6 panels
 - Each panel shall measure 48-inches wide and 80 inches long
 - Screens shall be constructed of metal suitable for submersion in water (stainless steel or aluminum)
 - Screen material shall be rounded bars to prevent injury to small fish (wedgewire style screens do not meet the requirement)
 - The aperture width between screens should be less than 1/2-inch
 - Screens shall be mounted in metal frames

Capabilities: The USFWS is seeking to purchase a fish screen that will prevent fish from entering a water control structure into a wetland site. The screens must fit in an existing frame on the control structure, dimensions listed below. The screen should be constructed of metal suitable for submersion in water, preferably aluminum for weight concerns. The screen material should be rounded bars to prevent injury to smaller fish that can pass through the screen gaps—wedge wire style screens do not meet this requirement. The aperture width between screen bars should be less than ½-inch, i.e. the screen should exclude fish wider than ½”-inch. The screen should be mounted on metal frames that will allow their installation into the existing water control structure, dimensions listed below.

- The screen must consist of 6 panels, with each panel measuring 48-inches wide and 80-inches long.

2. Delivery

Prices quoted must be FOB Destination

“F.o.b. destination” means --Free of expense to the Government delivered, on board the carrier’s conveyance, at a specified delivery point where the consignee’s facility (plant, warehouse, store, lot, or other location to which shipment can be made) is located; and

Supplies shall be delivered to the destination consignee’s wharf (if destination is a port city and supplies are for export), warehouse unloading platform, or receiving dock, at the expense of the contractor. The Government shall not be liable for any delivery, storage, demurrage, accessorial, or other charges involved before the actual delivery (or “constructive placement” as defined in carrier tariffs) of the supplies to the destination, unless such charges are caused by an act or order of the Government acting in its contractual capacity. If rail carrier is used, supplies shall be

delivered to the specified unloading platform of the consignee. If motor carrier (including “piggyback”) is used, supplies shall be delivered to truck tailgate at the unloading platform of the consignee, except when the supplies delivered meet the requirements of Item 568 of the National Motor Freight Classification for “heavy or bulky freight.” When supplies meeting the requirements of the referenced Item 568 are delivered, unloading (including movement to the tailgate) shall be performed by the consignee, with assistance from the truck driver, if requested. If the contractor uses rail carrier or freight forwarder for less than carload shipments, the contractor shall ensure that the carrier will furnish tailgate delivery when required, if transfer to truck is required to complete delivery to consignee.

Contractor responsibilities. The contractor shall --

- (1)(i) Pack and mark the shipment to comply with contract specifications; or
- (ii) In the absence of specifications, prepare the shipment in conformance with carrier requirements;
- (2) Prepare and distribute commercial bills of lading;
- (3) Deliver the shipment in good order and condition to the point of delivery specified in the contract;
- (4) Be responsible for any loss of and/or damage to the goods occurring before receipt of the shipment by the consignee at the delivery point specified in the contract;
- (5) Furnish a delivery schedule and designate the mode of delivering carrier; and
- (6) Pay and bear all charges to the specified point of delivery.

2.1 Delivery Location:

Product shall be delivered to the following location no later than **X** days after receipt of an order.

445 West Gunnison Ave., Suite 140
Grand Junction, CO 81501

2.2 Delivery Instructions

No later than three days prior to delivery, please contact the Point of Contact listed below, to arrange a specific time for delivery. Unloading the product is the sole responsibility of the delivery carrier. No labor or equipment will be provided by the government to unload the supplies. Delivery truck will need a liftgate for delivery.

3. Technical Point of Contact (POC):

Travis Francis
Travis_francis@fws.gov
970-287-9346

4. Inspection/Acceptance

Inspection and acceptance will be carried out in accordance with FAR 52.212-4(a) by the USFWS Contracting Officer’s Representative (COR) or an authorized designee.