

SPECIAL PACKAGING INSTRUCTION			CODE ID 98747	SPI NO. (TPD) F01-625-6969	
			SHEET 1 OF 4		
PART OR DRAWING NO. 004024-0	NATIONAL STOCK NO. 5840-01-625-6969 FD	CURRENT REV A	ILL. D. NAY P.S. M. MERRILL		
ITEM NOMENCLATURE EXCITER, RADIO FREQUENCY		ORIGINAL DATE 16111	CHK. B. TOMAC AUTH. N. CORDADO		
MILITARY PRESERVATION IAW MIL-STD-2073			PACKING AS SPECIFIED BELOW AND BILL OF MATERIALS		
SERVICEABLE METHOD: GX			LEVEL	SPEC	STYLE TYPE CL VRTY GR TR
UNSERVICEABLE METHOD: GX			A	ASTM D6251	A III 2 B
QUP 001			B	ASTM D5118	RSC V3c
ICQ 000			LEVEL A LEVEL B		
CLEANING & DRYING: IAW MIL-STD-2073			GROSS CU FT	11.306	6.848
PRESERVATIVE: N/A			GROSS WT LBS	147	50
			DESIGN FRAGILITY G	60	60
MARKING IAW MIL-STD-129			LENGTH WIDTH DEPTH		
SPECIAL MARKINGS:			CNTR I.D.		
A) SPI NO. F01-625-6969			LEVEL A:	31 1/4	27 3/4
MARK THE SPI NUMBER ON THE IDENTIFICATION SIDE OF CONTAINER.			LEVEL B:	30 1/2	27 13 1/4
B) REUSABLE CONTAINER & DUNNAGE DO NOT DESTROY.					
C) ESD PROTECTION AND LABELS REQUIRED			CNTR O.D.		
D) DO NOT OPEN UNTIL READY FOR USE/ INSPECTION			LEVEL A:	33 1/4	29 3/4
			LEVEL B:	30 7/8	27 3/8
			ITEM DIM	22 1/2	19 5 1/4
			ITEM WT.	40 LBS	
CLOSURE			REVISIONS		
LEVEL A: IAW: ASTM D6251			LTR	DESCRIPTION	DATE
LEVEL B: IAW: ASTM D1974			A	ADDED DISTRIBUTION STATEMENT AND DESTRUCTION NOTICE. CHANGED LEVEL A DIMENSIONS/UPDATED BOM	18072
DISTRIBUTION STATEMENT D: DISTRIBUTION AUTHORIZED TO DEPARTMENT OF DEFENSE AND U.S. DOD CONTRACTORS ONLY, ADMINISTRATIVE OR OPERATIONAL USE, 12 MARCH 2018. OTHER REQUESTS FOR THIS DOCUMENT SHALL BE REFERRED TO 406 SCMS/GULAA, (PACKAGING DIVISION), HILL AFB, UTAH 84056.					
DESTRUCTION NOTICE: FOLLOW THE PROCEDURES IN DOD 5220.22-M, NATIONAL INDUSTRIAL SECURITY PROGRAM OPERATING MANUAL (NISPOM), SECTION 5-705, OR DOD 5200.1-R, INFORMATION SECURITY PROGRAM, CHAPTER VI. FOR UNCLASSIFIED, LIMITED DOCUMENTS, DESTROY BY ANY METHOD THAT WILL PREVENT DISCLOSURE OF CONTENTS OR RECONSTRUCTION OF THE DOCUMENT.					

SPI NO. F01-625-6969

SPECIAL PACKAGING INSTRUCTION	CODE ID 98747	SPI NO. (TPD) F01-625-6969
ITEM NOMENCLATURE EXCITER, RADIO FREQUENCY		SHEET 2 OF 4

--	--	--	--	--

-7	A/R	PACKAGING TAPE	3 X AS REQUIRED	ASTM D5486 TYPE I OR V
-6	1	BARRIER BAG	30 X 26 (ID)	MIL-DTL-117 TYPE I, CLASS F, STYLE 1
-5	A/R	CUSHION/WRAP	AS REQUIRED	A-A-59135 CLASS 1, GRADE B
-4	2	CUSHION, END	23 X 9 X 2	A-A-59136 CLASS 1, GRADE B
-3	2	CUSHION, SIDE	30 1/2 X 9 X 2	A-A-59136 CLASS 1, GRADE B
-2	2	CUSHION, TOP & BOTTOM	30 1/2 X 27 X 2	A-A-59136 CLASS 1, GRADE B
-1	2	SKID (LEVEL A ONLY)	4 X 4 (NDM) X 29 3/4	ASTM D6199 CLASS 2
P/N	QTY REQD	NOMENCLATURE OR DESCRIPTION	SIZE: (INCHES UNLESS SPECIFIED) TOLERANCES ON FRAC. ± 1/8, DECIMAL ± .10, ANGLES ± 1°	MATERIAL SPECIFICATION

SPECIAL PACKAGING INSTRUCTION	CODE ID 98747	SPI NO. (TPD) F01-625-6969
ITEM NOMENCLATURE EXCITER, RADIO FREQUENCY		SHEET 3 OF 4
<i>CAUTION NOTICES</i> NOTICE 1: ASSETS PACKAGED IN ACCORDANCE WITH PREVIOUS EDITIONS OF THIS SPI DO NOT REQUIRE REPACKAGING IF THE INTEGRITY OF THE SPI IS MAINTAINED. NOTICE 2: SEE SPIRES FOR A COMPLETE LISTING OF NSN's ASSIGNED TO THIS SPI. NOTICE 3: PACKAGING MATERIAL MAY BE SUBSTITUTED IF IT MEETS THE REQUIREMENTS OF MIL-STD-2073, PROVIDES EQUAL OR BETTER PROTECTION AND THERE IS NO INCREASED COST TO THE GOVERNMENT. NOTICE 4: OVERSEAS AND FMS PACKAGING MUST MEET THE REQUIREMENTS OF LEVEL A PACKAGING. <i>INTERNATIONAL STANDARDS FOR PHYTOSANITARY MEASURES</i> <i>REVISION OF ISPM NO. 15</i> <i>REVISION OF WOOD PACKAGING MATERIAL FOR INTERNATIONAL TRADE</i> THE FOLLOWING STATEMENT IS IN COMPLIANCE WITH THE UNITED NATIONS-IMPLEMENTED RESTRICTIONS ON WOOD PACKAGING MATERIAL (WPM). THIS REQUIREMENT IS SPECIFICALLY CONCERNED WITH INVASIVE SPECIES SUCH AS THE PINEWOOD NEMATODE. WPM IS DEFINED AS WOOD PALLETS, SKIDS, LOAD BOARDS, PALLET COLLARS, WOODEN BOXES, REELS, DUNNAGE, CRATES, FRAMES, AND CLEATS. THE STATEMENT BELOW CITES THE REQUIREMENTS IN DETAIL AND COVERS LUMBER FOR BUILDING CONTAINERS AND PALLETS USED FOR DELIVERIES, RESULTING IN SHIPMENTS WORLDWIDE (DIRECT, OR THROUGH AIR LOGISTICS CENTERS (ALC), CONTAINER CONSOLIDATION POINTS (CCP), OR OTHER BASES). WOODEN LUMBER, WOODEN PALLET AND PACKAGING/CONTAINER STATEMENT: ALL WOODEN LUMBER, WOODEN PALLETS, AND WOODEN CONTAINERS PRODUCED ENTIRELY OR IN PART OF WOOD PACKAGING MATERIAL (WPM) SHALL BE CONSTRUCTED FROM DEBARKED WOOD IN ADDITION TO THE APPLICATION OF HEAT-TREATED (HT) MATERIAL (HT TO 56 DEGREES CENTIGRADE OR 133 DEGREES FAHRENHEIT FOR 30 MINUTES). CERTIFICATION/MARKING IS REQUIRED BY AN ACCREDITED AGENCY RECOGNIZED BY THE AMERICAN LUMBER STANDARDS COMMITTEE (ALSC). FOR REFERENCE DOCUMENTATION, SEE LATEST REVISION OF "INTERNATIONAL STANDARDS FOR PHYTOSANITARY MEASURES (ISPM NO. 15), "REGULATION OF WOOD PACKAGING MATERIAL IN INTERNATIONAL TRADE." <i>NOTES</i> 1. USE REF.-5 TO FILL ANY VOIDS AND ENSURE A SNUG FIT.		

SPECIAL PACKAGING INSTRUCTION

CODE ID
98747

SPI NO. (TPD)
F01-625-6969

ITEM NOMENCLATURE
EXCITER, RADIO FREQUENCY

SHEET 4 OF 4

