

SPECIAL PACKAGING INSTRUCTION			CODE ID 98747	SPI NO. (TPD) F01-583-3787	
			SHEET 1 OF 3		
PART OR DRAWING NO. A9070-080901	NATIONAL STOCK NO. 5840-01-583-3787 FD	CURRENT REV B	ILL. D. NAY P.S. M. MERRILL		
ITEM NOMENCLATURE TRANSMITTER, RADAR		ORIGINAL DATE 13183	CHK. R. TOMAC AUTH. N. CORDADO		
MILITARY PRESERVATION IAW MIL-STD-2073			PACKING AS SPECIFIED BELOW AND BILL OF MATERIALS		
SERVICEABLE METHOD: 41			LEVEL	SPEC	STYLE TYPE CL VRTY GR TR
UNSERVICEABLE METHOD: 41			A	ASTM D6251	A III 2 B
QUP 001			B	ASTM D6251	A III 2 A
ICQ 000			LEVEL A LEVEL B		
CLEANING & DRYING: IAW MIL-STD-2073			GROSS CU FT 15.986 15.986		
PRESERVATIVE: N/A			GROSS WT LBS 292 292		
			DESIGN FRAGILITY G 85 85		
MARKING IAW MIL-STD-129			CNTR I.D.		
SPECIAL MARKINGS:			LENGTH WIDTH DEPTH		
A) SPI NO. F01-583-3787			LEVEL A: 39 25 1/2 19		
MARK THE SPI NUMBER ON THE IDENTIFICATION SIDE OF CONTAINER.			LEVEL B: 39 25 1/2 19		
B) REUSABLE CONTAINER & DUNNAGE DO NOT DESTROY.			CNTR O.D.		
C) NOT FOR OUTSIDE STORAGE			LEVEL A: 41 27 1/2 24 1/2		
D) CAUTION LIFT BY BASE ONLY			LEVEL B: 41 27 1/2 24 1/2		
E) FRAGILE LABELS			ITEM DIM 34 20 1/2 14		
			ITEM WT. 167 LBS		
CLOSURE			REVISIONS		
LEVEL A: IAW: ASTM D6251			LTR	DESCRIPTION	DATE
LEVEL B: IAW: ASTM D6251			B	CHANGED METHOD OF PRESERVATION, REMOVED ESD LABELS, AND ADDED STRAPPING. ADDED DISTRIBUTION STATEMENT & DESTRUCTION NOTICE	17362
DISTRIBUTION STATEMENT D: DISTRIBUTION AUTHORIZED TO DOD AND U.S. DOD CONTRACTORS ONLY, ADMINISTRATIVE OR OPERATIONAL USE, 28 DECEMBER 2017. OTHER REQUESTS FOR THIS DOCUMENT SHALL BE REFERRED TO 406 SCMS/GULAA, (PACKAGING DIVISION), HILL AFB, UTAH 84056.					
DESTRUCTION NOTICE: FOLLOW THE PROCEDURES IN DOD 5220.22-M, NATIONAL INDUSTRIAL SECURITY PROGRAM OPERATING MANUAL (NISPO), SECTION 5-705, OR DOD 5200.1-R, INFORMATION SECURITY PROGRAM, CHAPTER VI. FOR UNCLASSIFIED, LIMITED DOCUMENTS, DESTROY BY ANY METHOD THAT WILL PREVENT DISCLOSURE OF CONTENTS OR RECONSTRUCTION OF THE DOCUMENT.					

SPI NO. F01-583-3787

SPECIAL PACKAGING INSTRUCTION	CODE ID 98747	SPI NO. (TPD) F01-583-3787
ITEM NOMENCLATURE TRANSMITTER, RADAR		SHEET 2 OF 3

CAUTION NOTICES

NOTICE 1: ASSETS PACKAGED IN ACCORDANCE WITH PREVIOUS EDITIONS OF THIS SPI DO NOT REQUIRE REPACKAGING IF THE INTEGRITY OF THE SPI IS MAINTAINED.

NOTICE 2: SEE SPIRES FOR A COMPLETE LISTING OF NSN's ASSIGNED TO THIS SPI.

NOTICE 3: PACKAGING MATERIAL MAY BE SUBSTITUTED IF IT MEETS THE REQUIREMENTS OF MIL-STD-2073, PROVIDES EQUAL OR BETTER PROTECTION AND THERE IS NO INCREASED COST TO THE GOVERNMENT.

NOTICE 4: OVERSEAS AND FMS PACKAGING MUST MEET THE REQUIREMENTS OF LEVEL A PACKAGING.

INTERNATIONAL STANDARDS FOR PHYTOSANITARY MEASURES

REVISION OF ISPM NO. 15

REVISION OF WOOD PACKAGING MATERIAL FOR INTERNATIONAL TRADE

THE FOLLOWING STATEMENT IS IN COMPLIANCE WITH THE UNITED NATIONS-IMPLEMENTED RESTRICTIONS ON WOOD PACKAGING MATERIAL (WPM). THIS REQUIREMENT IS SPECIFICALLY CONCERNED WITH INVASIVE SPECIES SUCH AS THE PINEWOOD NEMATODE. WPM IS DEFINED AS WOOD PALLETS, SKIDS, LOAD BOARDS, PALLET COLLARS, WOODEN BOXES, REELS, DUNNAGE, CRATES, FRAMES, AND CLEATS. THE STATEMENT BELOW CITES THE REQUIREMENTS IN DETAIL AND COVERS LUMBER FOR BUILDING CONTAINERS AND PALLETS USED FOR DELIVERIES, RESULTING IN SHIPMENTS WORLDWIDE (DIRECT, OR THROUGH AIR LOGISTICS CENTERS (ALC), CONTAINER CONSOLIDATION POINTS (CCP), OR OTHER BASES).

WOODEN LUMBER, WOODEN PALLET AND PACKAGING/CONTAINER STATEMENT:

ALL WOODEN LUMBER, WOODEN PALLETS, AND WOODEN CONTAINERS PRODUCED ENTIRELY OR IN PART OF WOOD PACKAGING MATERIAL (WPM) SHALL BE CONSTRUCTED FROM DEBARKED WOOD IN ADDITION TO THE APPLICATION OF HEAT-TREATED (HT) MATERIAL (HT TO 56 DEGREES CENTIGRADE OR 133 DEGREES FAHRENHEIT FOR 30 MINUTES). CERTIFICATION/MARKING IS REQUIRED BY AN ACCREDITED AGENCY RECOGNIZED BY THE AMERICAN LUMBER STANDARDS COMMITTEE (ALSC). FOR REFERENCE DOCUMENTATION, SEE LATEST REVISION OF "INTERNATIONAL STANDARDS FOR PHYTOSANITARY MEASURES (ISPM NO. 15), "REGULATION OF WOOD PACKAGING MATERIAL IN INTERNATIONAL TRADE."

NOTES

1. DEPENDING ON WHICH NSN IS TO BE PACKAGED EXTRA CUSHIONING, REF.-6, MAY BE REQUIRED TO ENSURE A SNUG FIT.

-7	A/R	STRAPPING	3/4 X .015 X AS REQUIRED	ASTM D3953 TYPE 1, RD, FINISH A
-6	A/R	WRAP/CUSHION	AS REQUIRED	A-A-59135 CLASS 1, GRADE A 
-5	1	BARRIER BAG	40 1/2 X 54 (ID)	MIL-DTL-117 TYPE I, CLASS E, STYLE 1
-4	2	CUSHION, END	21 1/2 X 15 X 2	A-A-59136 CLASS 1, GRADE A
-3	2	CUSHION, SIDE	39 X 15 X 2	A-A-59136 CLASS 1, GRADE A
-2	2	CUSHION, TOP & BOTTOM	39 X 25 1/2 X 2	A-A-59136 CLASS 1, GRADE A
-1	2	SKID	4 X 4 (NDM) X 27 1/2	ASTM D6199 CLASS 2
P/N	QTY REQD	NOMENCLATURE OR DESCRIPTION	SIZE: (INCHES UNLESS SPECIFIED) TOLERANCES ON FRAC. $\pm \frac{1}{8}$, DECIMAL $\pm .10$, ANGLES $\pm 1^\circ$	MATERIAL SPECIFICATION

SPECIAL PACKAGING INSTRUCTION

CODE ID
98747

SPI NO. (TPO)
F01-583-3787

ITEM NOMENCLATURE
TRANSMITTER, RADAR

SHEET 3 OF 3

