

## Salient Characteristics

### **CLIN 0001: Firefighting Truck with Increased Throughput**

- Three seat cab equivalent or better.
- Tank 1200 liters, drawers for equipment, lighting, roto bridge and siren in blue.
- One pump, two reels each 60 plus 30 meters hose, each with its own set of nozzles and gun handle with a flow of 120 liters per minute.
- Honda GH270 or equivalent Briggs and Stratton. Drive unit. AR pump. Working safe pressure, fixed platform, 20 bar r.p.
- Machine directive 2006/42/EC and applicable harmonized standards: EN 1846-2:2012, EN 1846-3+A1:2008, PN-EN 60204-1:2010. Complies also with the standard IEC 60364-7-717:2010

#### **Description of the pump:**

- minimum two pulleys and a total of 90 meters (60+30 meters) of hose, each
- Safe working pressure compared to all other competitive modules in Europe of this type at 15-25 bar
- Water mist extinguishing technology, which uses water mist and a minimum of water, and achieves a double effect, cooling and extinguishing at the same time, with amounts of water up to 30% of existing systems. Of course, there remains a nozzle for a classic jet up to 15 meters.
- Minimum measuring instruments (pressure analog pointer, amount of water analog, meter of working hours digital and mechanical (manual) valves)
- Foam mixer or other retardant (can also be used as a means of disinfecting streets or public buildings or a means of controlling spilled dangerous and/or toxic substances on asphalt roads, urban environment, HAZMAT fires, etc., detergent for spilled oils and many other uses) from 0.1 to 3%,)

#### **(Set of 4 nozzles for each reel separately, 8 nozzles in total)**

- Pistol grip with control ergonomic valve
- 1. water mist/line, up to 20 meters direct jet, water curtain from 10 to 150 degrees
- 2nd type nozzle FFM100 multi-purpose - needle for forest fires (in a set with an extension for entry during urban fires,) consumption app. 25-50 liters/min. landfill fires, layered combustible material, (eg hay, paper, sawdust and the like) with a maximum of 50 liters per min.
- 3. multi-purpose nozzle FFC200, edge of forest fires, but also especially specially developed for chimney fires, which are very common in the country and are often the cause of serious fires, extinguishes a chimney with 5-10 liters of water. Nozzle change time 7-8 seconds.
- 4. Nozzle special for foam for forest, urban, fires from highly flammable liquids, the possibility of using a special foam to cover leaked dangerous substances, prevention of hazmat disasters and similar situations
- Starting the equipment with a key, its own battery

**Salient Characteristics Continued on Next Page**

## **CLIN 0002: ATV Quadricycles**

| <b>DIMENSIONS</b>                                                                                                                                                                                                                                                 |                                                                    |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------|
| Length x Width x Height                                                                                                                                                                                                                                           | 2310 X 1264 X 1420 mm                                              |
| Wheelbase                                                                                                                                                                                                                                                         | 1480 mm                                                            |
| Minimum ground clearance                                                                                                                                                                                                                                          | 285 mm                                                             |
| Minimum turning radius                                                                                                                                                                                                                                            | 7,6 m                                                              |
| Vehicle weight                                                                                                                                                                                                                                                    | 447 kg                                                             |
| Carrying capacity                                                                                                                                                                                                                                                 | 240 kg                                                             |
| Tank capacity                                                                                                                                                                                                                                                     | 30 l                                                               |
| <b>ΑΓΡΕΓΑΤ</b>                                                                                                                                                                                                                                                    |                                                                    |
| Type                                                                                                                                                                                                                                                              | V2CIL, 4TSOHC, 8V, water cooling                                   |
| Volume                                                                                                                                                                                                                                                            | 800 cc                                                             |
| Maximum torque                                                                                                                                                                                                                                                    | 75 Nm - 6000                                                       |
| Maximum power                                                                                                                                                                                                                                                     | *OFF-ROAD 50 KW (68 HP) -7000                                      |
| Fuel supply                                                                                                                                                                                                                                                       | EFI BOSCH Germany or similar                                       |
| Ignition and control                                                                                                                                                                                                                                              | ECU BOSCH Germany or similar                                       |
| Gearbox                                                                                                                                                                                                                                                           | CVT with engine braking CVTECH CANADA or similar                   |
| Power transmission                                                                                                                                                                                                                                                | Selective 2 WD/4WD + front differential lock (automatic rear lock) |
| Maximum speed                                                                                                                                                                                                                                                     | 60 km/h *OFF-ROAD 105 km/h                                         |
| <b>CHASSIS</b>                                                                                                                                                                                                                                                    |                                                                    |
| Wheel suspension - front/rear                                                                                                                                                                                                                                     | Double cross shoulders independent                                 |
| Shock absorbers                                                                                                                                                                                                                                                   | Oil shock absorbers                                                |
| Brakes – front/back                                                                                                                                                                                                                                               | Hydraulic – 2XDISK / 2XDISK                                        |
| Rims – front/rear                                                                                                                                                                                                                                                 | Aluminum 14" / 14" or equivalent                                   |
| Tires – front/rear                                                                                                                                                                                                                                                | 26x9-14 / 26x11-14 or equivalent                                   |
| <b>STANDARD EQUIPMENT</b>                                                                                                                                                                                                                                         |                                                                    |
| Minimum: EPS power steering, aluminum wheels, digital control panel, two-piece seat, backrests and handrails for passengers, 12V socket, USB socket, electric winch, trailer hook with el. signal link, LED daytime running lights, mirrors, gas shock absorbers. |                                                                    |

**Salient Characteristics continued on next page**

## CLIN 0003: Light Off-Road Pickup Trucks

| Cabin                                                                    | Type of Drive | Doors | Seats           | Engine min | Transmission   |
|--------------------------------------------------------------------------|---------------|-------|-----------------|------------|----------------|
| Double cabin                                                             | 4x4           | 4     | 4 + 1           | 2.4 D-4D   | 6              |
| Technical characteristics                                                |               |       | Unit of measure |            | 2.4 D-4D (4x4) |
| Engine displacement                                                      |               |       | cm <sub>3</sub> |            | 2393           |
| Maximum power                                                            |               |       | KS at rpm       |            | 150/3400       |
| Maximum torque                                                           |               |       | Nm at rpm       |            | 400/1600-2000  |
| Transmission                                                             |               |       | Type            |            | 6-speed manual |
| Maximum speed                                                            |               |       | Km/h            |            | 170            |
| Acceleration (0-100 km/h)                                                |               |       | Seconds         |            | 12.8           |
| Consumption (combined cycle)                                             |               |       | l/100 km        |            | 8.5-9.7        |
| CO2 emissions (combined cycle)                                           |               |       | g/km            |            | 224-256        |
| Fuel                                                                     |               |       |                 |            | Diesel         |
| Eco norm                                                                 |               |       |                 |            | Euro 6         |
| Dimensions                                                               |               |       | Unit of measure |            | Double cabin   |
| Total length                                                             |               |       | mm              |            | 5,330          |
| Overall width                                                            |               |       | mm              |            | 1855/1900      |
| Total height                                                             |               |       | mm              |            | 1,815          |
| Wheelbase                                                                |               |       | mm              |            | 3,085          |
| Distance between the front wheels - track                                |               |       | mm              |            | 1,535          |
| Distance between the rear wheels - track                                 |               |       | mm              |            | 1,550          |
| Front overhang (distance between the center of the wheel and the bumper) |               |       | mm              |            | 985            |
| Rear curtain                                                             |               |       | mm              |            | 1,255          |
| Minimum clearance (ground clearance)                                     |               |       | mm              |            | 310            |
| Approach angle (front bumper)                                            |               |       | °               |            | 29             |
| Approach angle (rear bumper)                                             |               |       | °               |            | 26             |
| Cargo area                                                               |               |       | Unit of measure |            | Double cabin   |
| Total length minimum                                                     |               |       | mm              |            | 1,555          |
| Overall width minimum                                                    |               |       | mm              |            | 1,540          |
| Total height minimum                                                     |               |       | mm              |            | 480            |

Cargo area with open section for the fire extinguishing system.

**Salient Characteristics Continued on Next Page**

## Equipment levels of Off-Road Truck

VSC - Vehicle Stability Control (VSC)

- Distribution of braking force and assistance during sudden braking (EBD + BA)
- Active control of the four-wheel drive through the A-TRC system (Active Traction Control), which includes:
  - automatic blocking of wheels that slip and automatic redistribution of torque to the wheels with the best contact with the ground
  - electronic engine speed control
- Anti-lock braking system (ABS)
- 2 two-stage frontal airbags on the front seats
- 2 side airbags on the front seats
- 2 'Curtain' type airbags on the front and rear seats
- Driver's knee airbag
- Incline start assist (NAS)
- Halogen headlights with automatic activation (light sensor)
- Stylized black steel rims with 265/65 R17 All terrain tires
- Standard spare tire, mounted under the cargo floor
- Front and rear fenders
- Heated exterior side mirrors (black housing)
- Adjustment of headrests on all seats
- Steering wheel with height and depth adjustment
- Locking of the rear door of the cargo area
- Flashers, integrated in the side exterior mirrors
- Reinforced suspension
- Rear differential lock
- LED rear brake lights
- Front tire angle display
- Automatic front halogen headlights with automatic daytime running lights
- Bumpers in body color
- Engine Stop & Start system (not for single cabin)
- Radio CD/MP3/WMA with Aux-in and USB ports, 4 speakers (2 for Single cabin) and antenna + Bluetooth
- Vehicle drift reduction system when towing a trailer (TSC)
- Audible signal for locked lights and locked ignition key on instrument panel
- Fixed rear window
- 12 V electrical socket in front
- Pitch&Bounce Control system, control of lowering and lifting of the front during strong stopping and starting, as well as when going over uneven surfaces
- Additional protection of the chassis and tank
- Monochrome multi-information LCD display in the instrument panel
- Central locking with remote control
- Gear change indicator for optimal consumption
- Steering wheel controls to control the audio system and phone
- Arm rest and tool box, cup holder and lockable compartment
- Rear fixed glass heating
- Mirrors and opening handles – black
- Manual adjustment of the front seats
- Air conditioner with pollen filter and clean air filter
- Additional heating of the engine and heating of the air in the cabin through an electric ceramic heater in the air conditioner; fuel heating, reinforced starter and alternator

- Pockets on the back of the front seats and in the rear doors
- Green tinted side and rear glass
- Heating in the footwell for the rear passengers
- Front and rear electrically regulated windows
- Grab bars over the heads and in front of the doors for front and rear passengers
- 4.2" multi-information display - on-board computer

#### **CLIN 0004: Fire Extinguishing System, Pickup Truck:**

- To be utilized with one of the Pickup trucks with double cabin.
- MOTOR: Maximum normal flow 120 liters in minute (20-120, depending on nozzle and situation)
- PUMP: Working pump with working safe pressure fixed platform, 20 bars
- WHITLO: Roller winch with brakes
- RESERVOIR: Tank minimum 350liters, maximum 400 liters
- NOZZLES: nozzles, pistol grip, Foam tank minimum 25 liters
- Hose length 35+30 meters, with the option of up to 100 meters of working pressure retention, internal diameter 19mm

#### **CLIN 0005: Modular Fire Extinguishing System for ATV– Pickup Diaphragm Pump**

- To be utilized with Quadricycle ATV

| Engine     | Fuel     | Electric and battery start | Power   | Pump  | Maximum pressure | Maximum flow |
|------------|----------|----------------------------|---------|-------|------------------|--------------|
| B&S XR2100 | Gasoline | Yes                        | 13,5 HP | AR813 | 50 bars          | 80 l/min     |

| CHARACTERISTICS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |         |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|
| <ul style="list-style-type: none"> <li>• 2 mm resistant tank.</li> <li>• Maximum flow 120 L per minute</li> <li>• Working pump with working safe pressure fixed platform, 20 bars</li> <li>• AISI-304 stainless steel.</li> <li>• 2 internal partitions that prevent the passage of water from one side to the other, in order to ensure the stability of the vehicle.</li> <li>• Foam system.</li> <li>• 450 l water tank.</li> <li>• Hose and hose reel from 70 m to 80 bars.</li> <li>• Long range.</li> </ul> |         |
| WATER TANK DIMENSIONS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |         |
| Overall width                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 1300 mm |
| Basic width                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 1000 mm |
| Height                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | 510 mm  |
| Depth                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 750 mm  |

**Nothing Follows**

DRAFT

DRAFT