

Design pressure(s) marked on this unit shall not be less than the values marked on the compressor unit or as outlined in section 8.2 or ANSI/ASHRAE 15 and 6.2 of CAN/CSA-B52 for the refrigerant used in the system. After charging, the equipment is to be marked with refrigerant and oil used. Not suitable for use with ammonia (R717).

Las presiones de diseño indicadas en esta unidad no deben ser menores que los valores indicados en el compresor o como especificado en la sección 8.2 o ANSI/ASHRAE 15 y 6.2 del CAN/CSA-B52 para el refrigerante usado en el sistema. Después de cargado, el equipo debe ser marcado con el refrigerante y aceite en uso. No utilice este equipo con amoníaco (R717).

21502701

HEATCRAFT

REFRIGERATION PRODUCTS LLC

LISTED
UNIT COOLER
648L



ANSI/NBSF7



COMPONENT

MODEL NO.

BML250BA

SERIAL NO.

D06K04939

MOTOR CIRCUIT

VOLTS	PH	HZ	QTY	HP EA
208 — 230	1	60	3	1/4

FLA EA.	MCA	MOPD
1.8	5.9	20

(DEFROST) HEATER CIRCUIT

VOLTS	PH	AMPS	WATTS
208 — 230	1	33.7	7750

DEFROST CONTROL RATING

FLA	LRA	VA	REFRIGERANT	Design Pressure PSIG
16	65	125	12,22,502,404A	300

HEATCRAFT

REFRIGERATION PRODUCTS LLC

PART NO.	MODEL NO.			SERIAL NO.
86514101	BDT0750L6C			T06L 00946
VOLTS	PHASE	HERTZ	MIN. CIRC.	MAX. OVERCURRENT
208-230	3	60	750 C WIRE	PROTECTIVE DEVICE
200-220	3	50	60.00	AMPS
COMPRESSOR		COND. FAN MOTOR		
RLA	LRA	QTY.	HP.	FLA.EA
27.6	161	1	1/3	2.7
DESIGN PRESS. PSIG		EVAP. FAN MTR. MAX. AMPS		
HIGH SIDE	LOW SIDE	DEFROST HTR.		
450	178	MAX. AMPS		
REFRIGERANT		FOR	OUT	DOOR USE
TYPE	WEIGHT	EVAP. TEMP. F		
R404a		MIN. MAX.		
		-40 0		

LISTED
CONDENSING UNIT
233R



IMPORTANT

This product has a one year warranty from the date of manufacture. During that period, no unauthorized warranty repairs will be honored. If you believe a problem or defect exists, please call (770) 465-5600.



