HARSH OUTDOOR ENVIRONMENT
120 Minute Back-up Emergency Lighting Inverter

Emergency and Security Lights, Stadium, Gymnasium, Amphitheater, Convention Center, Parking Structure, Telecommunication, Military, Inland Non-Control Environment, Ocean Front Battery Backup System, Dusty and Uncontrolled Environments

120 minutes Battery Backup Time @ full load

3R Indoor and Outdoor standard painted steel cabinet, Stainless steel and Zinc anodized aluminum cabinet option

Emergency Lighting Approved

UL 924 with 120 minutes of VRLA batteries to power emergency lighting circuits.

State of Art Technology

High Frequency PWM double conversion use Digital Signal Processing for control, measurement to protect the load. The Harsh Environment UPS is always on-line, eliminating noise, spikes, sags, and brownouts. Should utility power fail, the inverter provides uninterrupted output power to the critical load. This high frequency unit is listed to UL1778 and UL924 by CSA.

Display (local and remote)

The Harsh Environment UPS provides one of the most comprehensive monitoring packages. Its 4 line X 20 character back-lit LCD panel continuously display and monitor vital power line conditions and status of the unit.

Global Monitoring System (GMS)

The Harsh Environment UPS can communicate with computers, and serial devices via its local RS232/RS485/RJ45 ports standard on every model making HEUPS compatible with today's most popular devices. Optional dry contacts are also available for remote monitoring and annunciation. GMS options includes dial-up modem, fax, alpha pager, beeper, email, and internet web page for monitoring or retrieving event logs and system status information.

Alarms

The Harsh Environment UPS offers local alarm and optional remote display with sound alert (including unit status). It also offers most extensive method of remote alarm notification via pager, email, fax, voice annunciation and website. The system can advise multiple recipients

Small Footprint Cabinet

The Harsh Environment UPS requires less floorspace than most other UPS systems and Stackable Cabinet Rack are available as an option for more space savings. Its compact, lightweight design saves overall space, facilitates handling, and keeps shipping costs to a minimum.

Input Power Factor Correction

The Harsh Environment UPS pays for itself by correcting input current draw to reduce your utility bill without compromising power quality.

Isolation, Including Output Neutral To Ground Bonding

The Harsh Environment UPS provides the galvanic electrical isolation required by FIPS PUB 94 (Federal Information Processing Standard) and it qualifies as a true, separately derived power source as defined by the National Electrical Code, Article 250-5d. This isolation allows the HEUPS to offer excellent RF noise filtering and single point grounding for sensitive electronic equipment (standard on all models with different input/output voltages).

Distribution (optional)

Normally On and OFF Output breakers are available with optional trip alarm as well as customer selectable time delay.

Safegard™ Battery Management System

OnLine Power has designed (patent pending) a process for the real time ability to charge and monitor the battery system. This system utilizes a microprocessor technology to monitor the batteries critical levels and apply charging cycles in a method substantially increasing battery life.

HE Model
2.1 to 17 kW

Listed to UL1778 and UL924 by CSA

Built-in Input Power Factor Correction

Modular Assembly for Ease of Installation

LCD Panel for Monitoring

Global Monitoring System (GMS)

94% Efficiency (typ.)

Pulse Width Modulated (PWM)

Generator Compatible with Automatic Governor max 2Hz per second

Transformerless Technology (Same Input/Output voltage only)

Double Conversion Technology

Battery Exerciser

Small Foot Print Cabinet

1 Year Warranty

OnLine POWER

Harsh Environment UPS Specifications

120 minutes Battery Backup Time @ full load

Power Rating:	2.1, 3, 3.5, 5, 5.25, 6, 7, 7.5, 8.75, 10, 10.5, 12.5, 14, 15, 17 KW
Input Voltage:	120, 208, 240, 277, or 480 VAC
Input/Output Connection:	Terminal Blocks, 14 AWG to 2/0 AWG wire range
Input Frequency:	Slew rate of 2Hz/sec
Output Voltages:	120, 208, 240, 277, or 480 VAC
Output Freq. (Inverter Operation):	60 Hz ±0.5 Hz
Voltage Regulation:	±3%
Output Wave Form:	Sine-Wave
Optional Input Protection:	Input circuit breaker provided protection to the unit, load and personnel. Input Circuit Breaker will be higher interruption rated (10, 42, and 65 KAIC)
Optional Output Protection:	Internal Electronic overload protection. Circuit breaker provides inherent over-load protection. Input circuit breaker is offered with custom kaic rating. Output circuit breaker is offered with custom kaic rating.
Output Power Factor:	1.0 unity
Efficiency:	Greater than 90% typical
Isolation:	Complete from line. Output neutral bonded to ground
Noise Isolation:	-120 dB Common-Mode; -60 dB Transverse-Mode
Battery:	Sealed maintenance-free (AGM) battery
Optional Battery:	Long life, high temperature
Recharge Time:	Conforms to UL Standard
External Battery:	Provisions for hardwire connection of optional external battery cabinets or DC source.
Environmental:	
Humidity:	0 - 95% RH w/ no condensation
Operating Temperature:	-20° to 50°C. (-4° to 122°F) electronics only.
Storage Temperature:	-20° to 70°C. (-4° to 158°F) electronics only.
Altitude:	Up to 13,000 ft
Safety Agencies:	Listed to UL1778, and UL924 by CSA

kVA/kW	*Model Numbers	Input Volt.	Output Volt.	** BTUs/Hr (Typical)	*** WEIGHT (lbs)	Cabinet Size W x H x D (Standard Battery)
3.0/2.1	HE3.0XYY2HN1-VA	120/208/240/277	120/208/240/277	1037	1252	39" x 73.5" x 20"
3.0/3.0	HE3.0XYY2HN1			1037	1366	
5.0/3.5	HE5.0XYY2HN1-VA			1146	1471	
5.0/5.0	HE5.0XYY2HN1			1419	1794	
7.5/5.25	HE7.5XYY2HN1-VA			1620	2206	51" x 77.5" x 33.5"
6.0 kW	HE6.0XYY2HN1			1965	1956	
8.0 kW	HE8.0XYY2HN1-VA			2600	2308	
10.0/7.0	HE010XYY2HN1-VA			2800	2502	
10.0/10.0	HE010XYY2HN1			3057	3388	
12.5/8.75	HE012XYY2HN1-VA			2702	3256	
12.5/12.5	HE012XYY2HN1			3700	4177	
15.0/10.5	HE015XYY2HN1-VA			3212	3912	
15.0/15.0	HE015XYY2HN1			5000	5512	
20.0/14.00	HE020XYY2HN1			5200	5644	
****17 kW	HE017XYY2HN1-VA			5400	6144	

** (Input Voltage) X: (A-120, B=208, D=240, R=277 V)*
** (Output Voltage) YY: (01-120, 13=208, 04=240, 25=277 V)*
** (For 480 V I/O units model numbers consult factory)*
*** For fast transfer BtU/Hr, Reduce 100 BTU/Hr per kW*
**** Battery weight varies with type of battery and battery manufacturer.*
***** Need additional battery cabinet, consult factory*

STANDARD FEATURES

- Back-lit LCD Display for monitoring
- RS 232 & RS 485 ports for metering, measuring, and diagnostic.
- System pre-wired for optional Global Monitoring System (GMS)
- Battery Breaker
- Inverter Test Switch
- Generator Compatible with Automatic Governor (Slew Rate 2Hz/sec.)
- High Frequency PWM with Digital Signal Processing Technology
- Built-in Input Power Factor Correction

OPTIONS

- Extended Warranty and Service Plans
- Lifting Ear NEMA 3R and NEMA 4
- Monitoring via RS232 and RS485
- Duplex 120V Receptacle for Service
- Make before break Maintenance Bypass Switch and Electronic Maintenance Bypass Switch
- External Maintenance Bypass Switch (wrap around type)
- Main Input and/or Output Circuit Breaker (with custom KAIC)
- TVSS
- Secondary Auxiliary Output Circuit Breakers (Main or max. 24 total)
- Spare Part Kits Available
- Runtime Up to 13 Hours
- High Isolation Transformer with Harmonic Reduction (up to K-50)
- Heater Strip with Thermostat Control
- Heating Pad Assy for Battery System
- Seismic Mounting Brackets
- (5) Form "C" Contacts Alarms
- Output Distribution Limit
- Long Life Battery
- Stainless Steel, Zinc Anodized Aluminum Cabinets
- Global Monitoring System
  LOCAL
  - Local PC via RS232 and RS485
  - Event logging up to 500

  REMOTE
  - Dial-up
    - Voice (10 event logging), numeric pager
    - Voice, data, fax, pager, PC, e-mail, event logging up to 500
    - Voice, data, fax, pager, PC, e-mail, and measurement (500 event logging plus graphic)
  - Web/SNMP:
    System status, measurement, alarm notification, event logging and password protected configuration.

Consult Factory for more features and options

Specifications are subject to change without prior notification.

Los Angeles, CA
Phone: (800) 227-8899
Fax: (323) 721-3929
www.onlinepower.com

125-DS-2H-11-19
© Copyright OnLine Power Inc. All rights reserved.