Mini Harsh Environment System (PBC II)

For Indoor and Outdoor applications

Stadium, Gymnasium, Amphitheater, Convention Center, Parking Structure, Emergency and Security Lights, Telecommunication, Military, Inland Non-Control Environment, Ocean Front Battery Backup System, Dusty and Uncontrolled Environments

Mini HE Models (500-1600 W)

- **UL1778 and CAN/CSA C22.2 No107.1-95**
- **Tested and Certified to Bellcore**
- **Operation Temp. (-40 to 58˚C.)**
- **Provide power conditioning and transient filtering**
- **Uninterrupted, ±0.5% voltage regulated, continuous sinewave out for use with "normally on" lighting fixtures and exit lamps**
- **Shock and Vibration:** GR-63-CORE ISSUE 1 section 4.3
- **Vibration and Earthquake:** GR-63-CORE ISSUE 1 section 4.4
- **Salt and Fog:** Per GR-487-core R3-165
- **TVSS** (Transient Voltage Surge Suppression)
  - AC power connections to the battery backup systems are protected from lightning and electrical surges in accordance with ANSI C62.41-1991 category C3 and UL1449 second edition.
  - Grounding is in accordance with Article 250 of the National Electrical Code (ANSI/ NFPA70), and Section 10 of the Canadian Electrical Code Part I (CSA C22.1-94).
- **Electromagnetic Compatibility (EMC):** FCC Part 15 Subpart J-Class B, Bellcore TA 1089, EN 55022 (1991)/CISPR 22 Class A
- **Reliability**
  - The predicted Mean Time Between Failures (MTBF) of unit is exceeding 86,000 hours at full power output.
  - The products all comply with the requirements of Bellcore document TY-TSY-000357, Issue 1, December 1987, "Component Reliability Assurance Requirements for Telecommunications Equipment".
- **ESD:** Meets all ESD requirements specified in Bellcore GR-1089-CORE, Issue 1A, July 1996.
- **Cabinet:** The Unit is designed and tested to the NEMA 12 environmental standard. The enclosures are designed for indoor unconditioned or outdoor unprotected use compliant with applicable sections of Bellcore GR-487-CORE, Issue 1, October, 1995.
  - Bellcore Rain intrusion test performed in addition to UL 50 tests.

NEMA 4 totally enclosed
Standard painted
Aluminum

Mini Harsh Environment Specifications

INPUT SPECIFICATIONS

Nominal Input Voltage:
120, 220, 240, or 277 VAC single phase

Input Voltage Range:
-20% to +15%

Input Frequency:
60 or 50 Hz, ±5%

Overcurrent Protection:
Circuit breaker

Power Connection:
Hard wired (TB)

Input Configuration:
2 wire plus ground

ENVIRONMENT

Operating Temperature:
-40°C to +58°C

Storage & Transport Temp.:
-40°C to +60°C

Operating Relative Humidity:
0 to 100%

Solar Loading:
Q_S = 70 W/ft^2

Operating Altitude:
-1000 to +13,000 feet, referenced to sea level. Temperature Compensated Battery Charger

OUTPUT SPECIFICATIONS

Output Voltage:
Same voltage as Input or Multiple Output 120/240, 120/208 or 120/277 VAC

Voltage Regulation:
±0.5% (LU)

Frequency:
60 Hz ±0.5 Hz, or 50 Hz ±5%

Harmonic Distortion:
<5% THD; <3% Single Harmonic

Crest Factor:
3 to 1

Power Factor:
0.7 leading load to 1.0 P.F.

Noise Rejection:
-120 dB common mode;
-60 dB normal mode

Battery Back-up Times:
Range from 30 min to 10 hrs. Consult Factory for longer backup time.

PHYSICAL SPECIFICATIONS

Mounting:
Pad Mount, Pole Mount Provision

Accessibility:
All servicing is through the front; no side or back required, and Cable Entry from Bottom or Side (Nema 3R or 4 Cabinets)

OPTIONS

- Pole Mounting Provision
- Battery Heating Pad
- Extended Warranty and Service Plans
- Lifting Eyes NEMA 3R and 4
- Monitoring via RS232 and RS485
- Secondary Auxiliary Output Circuit Breakers: Main or max. 9 total
- Spare Part Kits Available
- Door Intrusion Alarm Contacts
- Certified Zone 4 Seismic Bracket

NEMA 4 Cabinets	Model No	Max. Watts	*Backup time Range	*(Qty.) Battery	Cabinet Size
	LU1.6XXX	500	30min - 10hrs	(8) 12V 96 VDC	33" Wide 42" High 17" Deep
		700	30min - 8hrs		
		800	30min - 7hrs		
		1000	30min - 6hrs		
		1300	30min - 4.5hrs		
		1400	30min - 4hrs		
		1600	30min - 3.5hrs		

* Internal batteries. Longer backup times available with external battery cabinets.

Specifications are subject to change without prior notification.

TBS6069B-60109 © Copyright OnLine Power, Inc. All rights reserved.

Los Angeles, CA
Phone: (800) 227-8899
Fax: (323) 721-3929
www.onlinepower.com