Power Wave 4 Specifications

Power Rating: 60, 80, 100, 120, 160 kVA
(also available upon request 200, 240, 300, 400, 500 kVA)

InputVoltage: 208Y/120 V or 480Y/277 VAC (-15% to +15%)

OutputVoltages: 208Y/120 V or 480Y/277 VAC

Output Frequency (Inverter Operation): 60 Hz ±1 Hz

Voltage Regulation: ±1% at 100% unbalanced load

OutputVoltageWave Form: Sine-Wave <2% THD.

Crest Factor: 3:1 Typical

Surge Protection: The UPS will protect itself and the load against surges as defined in ANSI/IEEE C62.41 Categories A and B.

Isolation: True galvanic isolated

Battery: Sealed maintenance-free VRLA or Long Life Battery (available upon request)

RechargeTime: Varies per KVA and conforms to UL924.

Environmental:

Humidity: 0 - 90% (non-condensing)

OperatingTemperature: UPS: 0° to 40°C. (32° - 104°F)

Battery: 20° to 30°C. (68° - 86°F) higher temperature batteries are available for special order

StorageTemperature: -20° to 60°C. (-4° - 140°F) electronics only.

Altitude: Up to 5,000 ft

Inverter Cabinet (Off-white color):

60kVA: 34"W x 63"H x 31.5"D
80-160kVA: 55.5"W x 63"H x 31.5"D
200-300kVA: 86.5"W x 63"H x 31.5"D
400kVA: 133"W x 71"H x 39.5"D
500kVA: 178"W x 71"H x 39.5"D

Battery Cabinet (Matte Black color):
51"W x 70"H x 30.5"D

Battery	Sealed Lead Acid VRLA	NICAD
No. of batteries	29	271 Cells
Voltage Range	295 - 410V	285 - 415V
Low Batt Volt (warning)	320 VDC	305 VDC
Low Batt Shut Down	295 VDC	285 VDC
Boost Charge	402 VDC	415 VDC
Float Charge	390 VDC	410 VDC

KVA/KW	Input - Output Voltages	MODEL NUMBERS	DC Voltage		** Weights (lbs)	
					UPS	Each Battery Cab (#) of Cab
60 / 48	208/120 - 208/120 480/277 - 480/277	PW060B05ATT3 PW060H09ATT3	348	11942 11942	1724 1724	4135 (2)
80 / 64	208/120 - 208/120 480/277 - 480/277	PW080B05ATT3 PW080H09ATT3	348	15695 15695	2276 2276	5005 (2)
100 / 80	208/120 - 208/120 480/277 - 480/277	PW100B05ATT3 PW100H09ATT3	348	18425 18425	2984 2984	5005 (3)
120 / 96	208/120 - 208/120 480/277 - 480/277	PW120B05ATT3 PW120H09ATT3	348	22178 22178	3138 3138	5005 (3)
160 / 128	208/120 - 208/120 480/277 - 480/277	PW160B05ATT3 PW160H09ATT3	348	29684 29684	3868 3868	5030 (4)
200 / 160	208/120 - 208/120 480/277 - 480/277	PW200B05ATT3 PW200H09ATT3	348	39238 39238	5746 5746	5030 (5)
240 / 192	208/120 - 208/120 480/277 - 480/277	PW240B05ATT3 PW240H09ATT3	348	44356 44356	6229 6229	5030 (6)
*300 / 240	208/120 - 208/120 480/277 - 480/277	PW300B05ATT3 PW300H09ATT3	348	55616 55616	7293 7293	*
*400 / 320	208/120 - 208/120 480/277 - 480/277	PW400B05ATT3 PW400H09ATT3	348	78476 78476	9061 9061	*
*500 / 400	208/120 - 208/120 480/277 - 480/277	PW500B05ATT3 PW500H09ATT3	348	98948 98948	10166 10166	*

* Units are available only upon request.

STANDARD FEATURES

- 6 pulse or 12 pulse controlled rectifier (12 pulse for 80 kVA & up)
- Input main circuit breakers
- Data and events LCD display
- Built-in Transient Voltage Surge Suppressor
- EMI suppression
- PWM methodology (DSP)
- Isolation transformer at output for True galvanic isolation
- Modular design to facilitate ease and speed of service
- Cold start function: UPS can be started with battery power only without an AC source
- Green Mode Operation
- Multi-CPU design: Several CPUs are employed in control circuit and critical functions are designed with parallel redundancy for added reliability
- Protection against misuse: circuit breaker on/off sensor, and power supply sensor, the user cannot cause UPS damage by operator error.
- Intelligent charger: UPS will automatically recharge with temperature compensation.
- Intelligent battery test
- Redundant power supply
- RS-232 / RS-485 for varies accessory options
- External Shutdown- two pairs of terminals for UPS shut down
- DB9 Connection-4 of RS-485 & 1 of RS-232:
  The following are some connection examples of optional modules
  - CNR21 (RS-232): UPSCOM- Software for PC Monitoring, SNMP card
  - CNR9 (RS-485): DCMAN- Battery Monitoring Module
  - CNR10 (RS-485): UPSCAN- Remote Control Panel
  - CNR12,13,14,15,17,18,19 (RS-485): UPSCALL- Auto Dialing Module
  - CNR11: for transferring RS-485 into RS-232

OPTIONS

- Remote control panel UPSCAN™
- Software for PC monitoring UPSCAN™
- Auto dialing module UPSCAN™
- Battery Monitoring module DCMAN™
- Output Circuit Breaker
- Battery Exerciser
- 8 Dry contacts: INVON,OVL,FAULT, SS, BYPASS, BACK-UP, BATL, COM.

Specifications are subject to change without prior notification.

120-DS-3-18
© Copyright OnLine Power, Inc. All rights reserved.

Los Angeles, CA
Phone: (800) 227-8899
Fax: (323) 721-3929
www.onlinepower.com