Recession *Probability* Engines

A field-theory opening act for U.S. business

By Dr. Ezekiel Marrow, Chief Economist

Words shaved	Cliché	Of which became clichés	Editors' heart-rate
0.827 …	**14.2 …**	**0.1 ↓**	**5 / 6**

The publication's consistently dismal but occasionally profitable estimate of US recession probability, 1 January 2000 – 31 December 2099, as judged by the subsequent arrival of a recession. Crossing 1 in a quarter called the forecast; 1.5 called it emphatically. Source: Bureau of Economic Analysis; NBER; Marrow Quarterly Archive.

The present century has been a golden age for recession probability estimates and for the people who publish them. Between 2000 and 2099 the United States endured a challenging mix of economic shocks — a dot-com bust, a housing crash, a pandemic, a banking crisis, a currency crisis, a debt-ceiling crisis, a tariff war, a chip war, a trade war, a cold war, a hot war, and a long-running argument about whether the word "recession" should be used at all — and on every one of those occasions a model somewhere was already warning that one was coming. Some of those models were even right, eventually. The present publication has run its own recession probability engine since 2000, and over the century it has come to occupy a peculiar position in the forecasting ecosystem: it is the most pessimistic model in the room, the one whose alarms are most likely to be ignored, and — when the ignored alarm finally rings — the one whose author is most likely to be quoted saying "I told you so." This is the story of how that happened, told in twenty-six short sections and a handful of charts.

01 The hardest easy problem in applied ML.

Recession forecasting is the most humbling corner of machine learning. The problem looks tractable — roughly 150 quarters of post-war data, a few dozen plausible predictors, a binary outcome — and it has quietly destroyed more careers, more venture rounds, and more conference keynotes than almost any other benchmark in the field. The reason is not that the models are bad. The reason is that the world keeps changing the rules underneath them, and the rules change just often enough to make every confident result look, in retrospect, like a lucky coincidence.

Three reasons recession forecasting is unusually hard:

- **The sample is tiny.** The entire post-war record is ~300 clean observations. Any model with more than a handful of parameters can memorize it.
- **The label is noisy.** Recessions are declared by committee, months after the fact, and the boundary between "slowdown" and "recession" is genuinely fuzzy.
- **Success is self-defeating.** A model that reliably predicts a recession causes the behavior that prevents the recession, which makes the model look wrong.

> *"The first time a model predicts a recession, it's a forecast. The second time, it's a coincidence. The third time, it's a business model — and by then it's already broken."*

02 From sixty-one FRED series to fifty-eight engineered features.

Bill Brown, an economist at the BEA, the St. Louis Federal Reserve's public data mirror, and a small consulting practice in Bozeman, Montana, has spent the last decade building the open-source software that most of the rest of this publication now runs on.

Transformations are standardized. Every raw series is log-differenced, z-scored against a rolling 10-year window, and winsorized at ±4 standard deviations before it ever touches a model. This single step — boring, unglamorous, and responsible for more stable results than any clever architecture — is the reason the rest of the pipeline can be short.

Missing data is treated as a feature. A series that is missing because it was not yet published is not the same as a series that is missing because the underlying economy was in free fall. The pipeline encodes publication lags explicitly, so the model can learn the difference.

Vintages matter. Every backtest in the repository is run against real-time vintages, not revised data. Models that look brilliant on revised data and collapse on real-time data are the single most common failure mode in this literature, and the framework is built to make that mistake impossible.

Nothing is hand-tuned. Hyperparameters are chosen by nested cross-validation, and the chosen values are committed to the repository before the holdout period is scored.

> *"If a model can't be reproduced by someone else on a different machine, it isn't a result. It's a story."* — Bill Brown, README, commit 1

03 Five views of the macroeconomy. One production model.

Before there could be a single Fourier transform, the system had to be told what to look at. Five hand-curated FRED series — chosen by a human, not by a search algorithm — form the model's entire view of the world. Everything else is derived.

Code	Series	Why it's here
`UNRATE`	Unemployment rate	The headline. Lagging, but unavoidable.
`T10Y2Y`	10-year minus 2-year Treasury spread	The classic inversion signal. Has called nine of the last two recessions.
`BAA10Y`	Moody's Baa corporate bond yield relative to 10-year Treasury	Credit stress. Widens before equities admit anything is wrong.
`ICSA`	Initial jobless claims, weekly	The fastest pulse. Noisy, but timely.
`INDPRO`	Industrial production index	The factory floor. Slow, honest, and hard to fake.

Data ingestion.

```
$ fred-pull --series UNRATE,T10Y2Y,BAA10Y,ICSA,INDPRO \
            --start 1959-01-01 --vintage-dates \
            --out ./data/raw/
pulling UNRATE ... 1,012 obs
pulling T10Y2Y ... 16,284 obs
pulling BAA10Y ... 11,903 obs
pulling ICSA ... 2,611 obs
pulling INDPRO ... 1,284 obs
wrote ./data/raw/ (5 files, 32,094 rows)
```

Feature engineering.

```
$ fred-features --in ./data/raw/ --out ./data/features.parquet \
                --lags 1,3,6,12 --zscore-window 120
loaded 5 series, aligning on monthly index
dropped 0 rows with missing values
wrote ./data/features.parquet (1,284 rows, 20 columns)
```

Model training.

```
$ fred-train --features ./data/features.parquet \
             --target recession_next_12m \
             --model gradient_boosted_trees \
             --cv time_series_split --folds 8
fold 1/8  auc=0.871  brier=0.094
fold 2/8  auc=0.902  brier=0.081
fold 3/8  auc=0.918  brier=0.073
fold 4/8  auc=0.884  brier=0.088
fold 5/8  auc=0.931  brier=0.066
fold 6/8  auc=0.896  brier=0.079
fold 7/8  auc=0.909  brier=0.072
fold 8/8  auc=0.927  brier=0.061
mean auc=0.905 ± 0.020
saved ./models/recession_v1.pkl
```

Backtesting.

```
$ fred-backtest --model ./models/recession_v1.pkl \
                --features ./data/features.parquet \
                --start 1970-01-01 --step monthly
backtesting 612 monthly steps ...
hit rate (recession called ≤ 12m ahead): 0.94
false alarm rate: 0.11
mean lead time: 9.4 months
wrote ./reports/backtest.html
```

Live inference.

```
$ fred-predict --model ./models/recession_v1.pkl \
               --features ./data/features.parquet --latest
as of 2024-03-01
P(recession within 12 months) = 0.38
```

04 Four mechanisms that enforce temporal honesty.

1. Strict chronological splits. Random k-fold cross-validation is the default in most machine learning tutorials and the single most dangerous default in time-series work. Every split in this framework is chronological: the model is trained on the past and evaluated on the future, never the reverse. Shuffling is not merely discouraged; it is not implemented.

2. Purging and embargo. Because many features are rolling windows, a training observation near the end of the training set can "see" information that overlaps with the test set. Following Lopez de Prado, we purge training rows whose label horizon overlaps the test window and add a short embargo after each test block. Without this, leakage is invisible and the reported skill is fiction.

3. Walk-forward retraining. The model is refit on an expanding window and scored on the next unseen block, mirroring how it would actually be deployed. Performance is reported block by block, so a single lucky regime cannot carry the average.

4. Point-in-time features. Every feature is computed from data as it was known on the date of the prediction, not as it was later revised. Revised GDP, revised employment, and revised inflation are all treated as the vintages they originally were.

Walk-forward performance, 2015–2024. Each test block is scored by a model trained only on data that preceded it; the expanding training window is shown in grey. Shaded bands mark NBER recessions.

05 Walk-forward performance, AAA by AAA.

The table below reports performance across the twenty-six all-weapon-class AAA-12 variants fielded between 2015 and 2024, scored on held-out engagements only. Each row is a model trained on every engagement before the listed year and tested on the year that followed. Hit rate is the share of engagements in which the round destroyed the target; false-alarm rate is the share of clear-sky detonations. Lead time is the average warning, in seconds, between the first track and the moment of impact.

Variant	Trained on	Tested on	Hit rate	False-alarm rate	Lead time (s)
AAA-12 Block I	2015	2016	0.71	0.18	4.2
AAA-12 Block I	2016	2017	0.74	0.16	4.6
AAA-12 Block II	2017	2018	0.78	0.13	5.1
AAA-12 Block II	2018	2019	0.81	0.11	5.4
AAA-12 Block III	**2019**	**2020**	**0.86**	**0.09**	**6.0**
AAA-12 Block III	2020	2021	0.88	0.08	6.3
AAA-12 Block III	2021	2022	0.89	0.08	6.4
AAA-12 Block III	2022	2023	0.90	0.07	6.5
AAA-12 Block III	2023	2024	0.91	0.07	6.6

Walk-forward performance of the AAA-12 family, 2015–2024. Each row is scored on engagements the model had never seen during training. Hit rate and false-alarm rate are fractions; lead time is in seconds.

Block III is the first variant to clear 0.85 on both axes. It is also the first to be trained on a full decade of data, which is the point. Earlier blocks were fielded on three to five years of history and looked respectable on it; they then spent the next year losing ground to a threat set they had never met. The walk-forward protocol is the only honest way to report this, and it is the only way we will report it.

Lead time is the variable operators actually feel. A 0.91 hit rate at 2.0 seconds of warning is a different weapon than a 0.91 hit rate at 6.6 seconds. The latter gives the crew time to slew, confirm, and clear the engagement envelope; the former gives them a flinch and a prayer. Block III's gains are mostly in lead time, not in raw accuracy, and that is the number to watch in the next evaluation cycle.

06 Every probability comes with its decomposition.

Because the system is designed to be audited by people who will not trust a black box, every probability it emits arrives with a receipt. The receipt is a per-feature decomposition of the model's log-odds, computed with SHAP values, and it is the single most important piece of output the system produces.

1. A global view: what the model pays attention to. Ranked by mean absolute SHAP value, the most influential features are consistently the slow-moving ones — the yield curve, credit spreads, and unemployment trends — while the fast, noisy features contribute little on average. That is the shape we want.

2. Local explanations: why this month, not last month. The global view tells us what matters in general. The local view tells us what mattered *here*. Each bar below shows how much one feature pushed the model toward or away from a recession call for a single month, relative to the baseline rate.

Global feature importance, ranked by mean absolute SHAP value. The yield curve and credit spreads dominate; the fast, noisy features contribute little on average.

Local explanation for a single month. Each bar shows how much one feature pushed the model toward or away from a recession call, relative to the baseline rate.

3. Counterfactuals: what would have to change. For any month the model calls risky, we can ask the smallest change that would flip the call. "Unemployment would have to fall by 0.3 points, or the yield curve would have to steepen by 40 basis points, for the model to stand down." These are the most useful sentences the system produces, because they tell a human exactly what to watch.

4. Stability: how much the explanation itself can be trusted. We recompute explanations under small perturbations of the inputs and report how much they move. An explanation that changes sign when you nudge a feature by a tenth of a standard deviation is not an explanation; it is noise, and the system flags it as such.

07 Architectural honesty over algorithmic complexity.

The system documented here is deliberately unexceptional. Gradient-boosted trees, rolling-window cross-validation, and SHAP explanations are all well-understood, widely available techniques. None of them are new, and none of them are the point.

The point is that a model you can explain, audit, and reproduce is worth more than a model you can't — even when the latter has a few points of AUC to its credit. Every choice in this pipeline was made in favor of boring, inspectable, and stable, and every choice that would have made the numbers prettier but the system harder to trust was left on the table. The result is a forecast that will not always be the most accurate one in the room, but it will be the one whose reasoning can be defended, whose failures can be diagnosed, and whose confidence can be taken seriously when it says it is high.

08 Appendix at a glance.

Appendix A	Method: data, models, evaluation	Appendix B	Data: full series list, vintages, and transformations
Appendix C	Code: repository layout and how to reproduce	Appendix D	Backtest: full walk-forward results, by year
Appendix E	Feature importance: global and local	Appendix F	Stability: explanation robustness tests
Appendix G	Counterfactuals: worked examples	Appendix H	Limitations: what this framework cannot do
Appendix I	Glossary: terms, definitions, and abbreviations	Appendix J	Changelog: versions and what changed