BOSTON UNIVERSITY

COLLEGE OF ENGINEERING

Thesis Proposal

3-Dimensional Model-Based Dynamic Feedback Control for Soft Robots

by

Nashr El Auliya

B.Sc., Boston University, 2024

Submitted in partial fulfillment of the requirements for the degree of

Master of Science

2025

This page intentionally left blank.

Contents

1 Abstract

The physical characteristics of soft robots inherently promise an ability to perform complex motions, as well as to safely and compliantly interact with sensitive environments. While trajectory tracking and environmental interaction control strategies for planar motion have been developed along with motion plans for it, it has yet to be robustly translated to three dimensions. This thesis thus aims to develop a three-dimensional, model-based, closed loop dynamic controller for continuous soft robots. To develop a robust formulation of this controller, gravitational loads that could potentially violate model assumptions must be dynamically accounted for. Kinematic singularities inherent to the dynamic model used must also be analytically or numerically managed. A suitable dynamic model to underpin the control system must then either be formulated, augmented from an existing one, or selected. Then the model must be validated either analytically or simulatively, before the control system can subsequently be built around it. The controller may then finally be validated through hardware implementation.

2 Topic Background

2.1 Model-based Controls in Soft Robotics

Much of controls theory as a field has progressed in parallel to the advances in our understanding of dynamic modeling. In fact, much of the advancements in controls theory were driven by the need to supplement the gaps in our dynamic models. Starting from the frequency domain and linear controllers, to nonlinear controllers, and most recently machine learning.

The implementation of control strategies for standard rigid robots has followed this line of progression. Algorithms built around the dynamical model of the robot itself came first, then only recently did strategies employing machine learning began to be implemented–mostly to handle unpredictable scenarios beyond the models' assumptions. Control strategies of the former kind are known as *model*-based controls, where controllers are designed based on models that mathematically represent the robot's dynamics [1]. It should be apparent that this has been the case since the dynamics of a rigid-bodied robot can more readily be modelled.

On the other hand, the development of control strategies for *soft* robots have followed the opposite direction: much of the early works in soft robotics controls employed machine learning strategies due to the high level of complexity and dimensionality required in the dynamical models. Thus, *learning*-based controls were the model for soft robot control strategies through the formative years of the field. Only in recent years did this precedent began to be reassessed, particularly with the advent of *finite*-dimensional modelling (FDM) techniques compatible with the continuum dynamics of soft robots [2].

2.2 Model- vs. Learning-based Controls

Model- and learning-based controls differ in the fundamental methodology that underpin *how* each approach steers their dynamic systems. Consider some steady-state open-loop dynamic system expressed in state space as $\dot{\mathbf{x}} = \mathbf{f}(\mathbf{x})$, the application of a model- and learning-based controller–respectively–to the system may be represented according to Table 1.

Model-based	Learning-based
$\dot{\mathbf{x}} = \mathbf{A}\mathbf{x} + \mathbf{B}\mathbf{u}$ $= \overline{\mathbf{f}}(\mathbf{x}, \mathbf{u})$ where, $\mathbf{u} = f(\mathbf{x}, \mathbf{e}, \mathbf{t}, ...)$	$\dot{\mathbf{x}} = \overline{\mathbf{f}}(\mathbf{x}, \mathbf{u}_{\text{learned}})$ or $\dot{\mathbf{x}} = \mathbf{g}(\mathbf{x}, \mathbf{u})$

Table 1: High-level generalization of model- vs. learning-based controllers.

The distinction between model- and learning-based control approaches may be described using the functional framework presented above. In both approaches, some input $\mathbf{u}$ is now introduced to the previously steady-state system. The system becomes *closed*-loop when a controller that uses the system output to determine the control input is implemented (see Figure 1). In this scenario, $f(\mathbf{x}, \mathbf{e}, \mathbf{t}, ...)$ can be considered the controller. It functionally relates the system output/current state–and typically error $\mathbf{e}$ and time as well–to the control input.

For model-based controls, designing the controller based on the dynamics of the systems means tuning $\mathbf{u}$ to the $\mathbf{A}$ and $\mathbf{B}$ matrices. A conveniently acceptable way of interpreting $\overline{\mathbf{f}}$ is to regard $\mathbf{A}$ as the system's steady-state behavior, and $\mathbf{B}$ as the system's response to control inputs. The two matrices *must* sufficiently describe the system dynamics before $\mathbf{u}$ can be designed to steer the system towards the desired configuration. Formulating $\mathbf{A}$, $\mathbf{B}$,



Figure 1: A generic closed-loop system, the control input is a function of desired state $\mathbf{r}$ and output $\mathbf{x}$.

and $\mathbf{u}$ while respecting their inter-dependency thus becomes inherent to the model-based approach.

Formulating models that allow the input to be solved in a mathematically managable way, while simultaneously remaining faithfully representative of the *actual* system behavior becomes one of model-based controls' biggest challenges. Learning-based controls circumvent this by using data-driven techniques and learning algorithms to arrive at $\mathbf{u}$. In some cases, $\bar{\mathbf{f}}$ may even be left unknown and the full system is wholly formulated by the learning medium ($\mathbf{g}(\mathbf{x}, \mathbf{u})$ in Table 1).

Analysis	Model-Based	Learning-Based
Advantages	Meaningful information regarding the dynamics and inputs of the system are preserved	Known to achieve higher maneuvering performance and better robustness [1]
Disadvantages	Less robust and adaptable at handling system configurations in fringe scenarios [1], [3]	More complex and typically lacks formal guarantees of safety [3]

Table 2: An assessment of Model- and Learning-Based controls.

A general assessment of the benefits and drawbacks between the two approaches is presented in Table 2. While both approaches bring different things to the table–and extensive research continue to be conducted on both, the author has decided to explore the model-based approach for this proposed thesis.

2.3 Some "Control-Oriented" Models

It was mentioned earlier that in the formulation of the dynamical model to develop a controller around, towing the balance between mathematical simplicity and physical accuracy is one of the major challenges in model-based controls. While this continues to be true, continuum dynamics-compatible FDM techniques has also indeed broken considerable ground with regards to this issue. In their exact formulation, the dynamics of a soft robot is effectively an infinite-dimensional system. Such a system cannot be described without the use of partial differential equations (PDEs). However, by applying the appropriate assumptions, approximations, and/or discretization to the dynamical model of the soft robot, the system's description may be reliably "minimized" into a *finite*-dimensional system that can be described with ordinary differential equations (ODEs) instead.

One of the most widely-implemented family of FDM techniques is the Piecewise Constant Strain (PCS) approximations (see Figure 2). It is a family of discretization methods applied to a type of approximation for soft robot dynamics known as "rod models". It is extremely common for soft robots to be "thin" and/or "elongated": to have one physical dimension dominate the other two. In that regard, such soft robots may be approximated as a rod with the continuum mechanics of one too–hence rod models. At the heart of this methodology is the assumption that volumetric deformations may be neglected, and modeling the dynamics around the dominant central axis is sufficient [2].

Among the many implementations of PCS, the planar Piecewise Constant Curvature (PCC) model has been extensively used in soft robotics throughout the last decade. Its approximation of the robot as pieces of constant-curvature arcs linked together in series with mutually tangent connection points makes the kinematics and Jacobian formulation for the model *closed*-form [4]. A dynamic feedback controller using this model was developed in [5], with an implementation of a trajectory generator for the controller formulated in [6].

There are many viable models out there that can be used as the basis for the controller that this proposed thesis seeks to develop, a selection of them that seems promising with respect to the scope of this proposed thesis will be outlined in this proposal.



Figure 2: a) "Elongated" soft robots as described in rod models. b) PCS discretization applied to the rod model. Image taken from Della Santina et al. [2].

3 Prior Work

3.1 PCC in an Augmented Rigid Body Model

CD Santina developed a controller built around the most straightforward implementation of PCS [5]
Planar PCC model matched with an *augmented* rigid body model [7]
Not 3D, but preliminary results on 3D-fying it available

3.2 PCC Using an Alternative State Parametrization

Direct (?) successor to the previous paper [8]
Solved the main limitations of the previous model's parametrization
New parametrization is based on arc-lengths of a CC segment

3.3 Beyond the PCC Assumption

An alternative model *still* using the PCS principles [9]
Uses PCS to discretize an otherwise continuous (and infinite-dimensional) model
Leans much more into the continuum mechanics of soft robots

4 Research Approach

Formulation unlikely
Rough outline of model assessment;tabulated or other
Justify model selection based on table assessments

Analytically (?) assess model behavior?
Motor babble pneumatically-actuated soft robot at hand
Simulate output using model, and look at the error

Development of the controller
What does hardware implementation look like?
What does *validation of* the hardware implementation look like?

5 Proposed Timeline

Research Approach 1: Dec 2025
Research Approach 2: Jan 2025
Research Approach 3: Mar 2025
aaaa
aaaa
aaaa

6 References

[1] J. Rakhmatillaev, V. Bucinskas, and N. Kabulov, "An integrative review of control strategies in robotics", *Robotic Systems and Applications*, Jul. 10, 2025. DOI: 10.21595/rsa.2025.25014.

[2] C. Della Santina, C. Duriez, and D. Rus, "Model-based control of soft robots: A survey of the state of the art and open challenges", *IEEE Control Systems Magazine*, vol. 43, no. 3, pp. 30–65, Jun. 2023. DOI: 10.1109/MCS.2023.3253419.

[3] L. Brunke, M. Greeff, A. W. Hall, *et al.*, "Safe learning in robotics: From learning-based control to safe reinforcement learning", *Annual Review of Control, Robotics, and Autonomous Systems*, vol. 5, pp. 411–444, Volume 5, 2022 May 3, 2022. DOI: 10.1146/annurev-control-042920-020211.

[4] R. J. Webster III and B. A. Jones, "Design and kinematic modeling of constant curvature continuum robots: A review", *The International Journal of Robotics Research*, vol. 29, no. 13, pp. 1661–1683, Nov. 1, 2010. DOI: 10.1177/0278364910368147.

[5] C. Della Santina, R. K. Katzschmann, A. Bicchi, and D. Rus, "Model-based dynamic feedback control of a planar soft robot: Trajectory tracking and interaction with the environment", *The International Journal of Robotics Research*, vol. 39, no. 4, pp. 490–513, Mar. 1, 2020. DOI: 10.1177/0278364919897292.

[6] A. Dickson, J. C. P. Garcia, R. Jing, M. L. Anderson, and A. P. Sabelhaus, "Real-time trajectory generation for soft robot manipulators using differential flatness", in *2025 IEEE 8th International Conference on Soft Robotics (RoboSoft)*, Apr. 2025, pp. 1–7. DOI: 10.1109/RoboSoft63089.2025.11020810.

[7] R. K. Katzschmann, C. D. Santina, Y. Toshimitsu, A. Bicchi, and D. Rus, "Dynamic motion control of multi-segment soft robots using piecewise constant curvature matched with an augmented rigid body model", in *2019 2nd IEEE International Conference on Soft Robotics (RoboSoft)*, Apr. 2019, pp. 454–461. DOI: 10.1109/ROBOSOFT.2019.8722799.

[8] C. Della Santina, A. Bicchi, and D. Rus, "On an improved state parametrization for soft robots with piecewise constant curvature and its use in model based control", *IEEE Robotics and Automation Letters*, vol. 5, no. 2, pp. 1001–1008, Apr. 2020. DOI: 10.1109/LRA.2020.2967269.

[9] F. Renda, F. Boyer, J. Dias, and L. Seneviratne, "Discrete cosserat approach for multisection soft manipulator dynamics", *IEEE Transactions on Robotics*, vol. 34, no. 6, pp. 1518–1533, Dec. 2018. DOI: 10.1109/TRO.2018.2868815.

[10] A. K. Dickson, J. C. P. Garcia, M. L. Anderson, *et al.*, *Safe autonomous environmental contact for soft robots using control barrier functions*, Apr. 20, 2025. DOI: 10.48550/arXiv.2504.14755. arXiv: 2504.14755[cs].

[11] K. Wong, M. Stölzle, W. Xiao, C. D. Santina, D. Rus, and G. Zardini, *Contact-aware safety in soft robots using high-order control barrier and lyapunov functions*, May 5, 2025. DOI: 10.48550/arXiv.2505.03841. arXiv: 2505.03841[cs].

[12] C. D. Santina and D. Rus, "Control oriented modeling of soft robots: The polynomial curvature case", *IEEE Robotics and Automation Letters*, vol. 5, no. 2, pp. 290–298, Apr. 2020. DOI: 10.1109/LRA.2019.2955936.