

# G09/G16 MATLAB Toolbox

A parsing and visualisation toolbox for Gaussian 09/16 output files

Sebastiano Trusso

CNR – Istituto per i Processi Chimico-Fisici (IPCF), Messina, Italy

Version 1.0 — 2026

## Contents

|          |                                                               |           |
|----------|---------------------------------------------------------------|-----------|
| <b>1</b> | <b>Introduction</b>                                           | <b>3</b>  |
| <b>2</b> | <b>File I/O utilities</b>                                     | <b>4</b>  |
| 2.1      | G09_read_lines . . . . .                                      | 4         |
| 2.2      | G09_check_gaussian_match / G16_check_gaussian_match . . . . . | 4         |
| <b>3</b> | <b>Core data extraction</b>                                   | <b>5</b>  |
| 3.1      | G09_route / G16_route . . . . .                               | 5         |
| 3.2      | G09_structure / G16_structure . . . . .                       | 5         |
| 3.3      | G09_energy / G16_energy . . . . .                             | 6         |
| 3.4      | G09_charge_mult / G16_charge_mult . . . . .                   | 7         |
| 3.5      | G09_convergence / G16_convergence . . . . .                   | 7         |
| 3.6      | G09_dipole_polar / G16_dipole_polar . . . . .                 | 8         |
| 3.7      | G09_nmodes / G16_nmodes . . . . .                             | 8         |
| 3.8      | G09_spectra / G16_spectra . . . . .                           | 9         |
| <b>4</b> | <b>Atomic charges</b>                                         | <b>11</b> |
| 4.1      | G09_charges / G16_charges . . . . .                           | 11        |
| 4.2      | G09_charges_fchk (G09 only) . . . . .                         | 12        |
| <b>5</b> | <b>Formatted checkpoint (.fchk) support</b>                   | <b>13</b> |
| 5.1      | G09_fchk_read (G09 only) . . . . .                            | 13        |
| <b>6</b> | <b>Molecule and normal-mode visualisation</b>                 | <b>14</b> |
| 6.1      | G09_draw_molecule / G16_draw_molecule . . . . .               | 14        |
| 6.2      | G09_draw_mode / G16_draw_mode . . . . .                       | 15        |
| 6.3      | G09_modeViewer / G16_modeViewer . . . . .                     | 15        |
| 6.4      | G09_animate_mode / G16_animate_mode . . . . .                 | 16        |
| <b>7</b> | <b>Orbital energy analysis</b>                                | <b>18</b> |
| 7.1      | G09_orbital_energies / G16_orbital_energies . . . . .         | 18        |
| 7.2      | G09_draw_orbital / G16_draw_orbital . . . . .                 | 19        |
| <b>8</b> | <b>Response properties (G16 only)</b>                         | <b>20</b> |
| 8.1      | G16_hypersolar . . . . .                                      | 20        |
| 8.2      | G16_tddft . . . . .                                           | 20        |

|           |                                                                                  |           |
|-----------|----------------------------------------------------------------------------------|-----------|
| <b>9</b>  | <b>Structural analysis utilities</b>                                             | <b>22</b> |
| 9.1       | G09_get_bond_length / G16_get_bond_length . . . . .                              | 22        |
| 9.2       | G09_gaussian_version / G16_gaussian_version . . . . .                            | 22        |
| 9.3       | G09_restart / G16_restart . . . . .                                              | 23        |
| 9.4       | G_read_input (shared, no G09_/G16_ prefix) . . . . .                             | 23        |
| 9.5       | G09_list / G16_list . . . . .                                                    | 24        |
| <b>10</b> | <b>One-call data extraction</b>                                                  | <b>25</b> |
| 10.1      | G09_read_all / G16_read_all . . . . .                                            | 25        |
| 10.2      | G09_batch_read_all / G16_batch_read_all . . . . .                                | 25        |
| <b>11</b> | <b>Report generation</b>                                                         | <b>27</b> |
| 11.1      | G09_write_report / G16_write_report . . . . .                                    | 27        |
| 11.2      | Function reference . . . . .                                                     | 28        |
| 11.3      | Selected signatures . . . . .                                                    | 29        |
| 11.4      | Notes on the port . . . . .                                                      | 30        |
| <b>12</b> | <b>Worked examples</b>                                                           | <b>33</b> |
| 12.1      | example_1.m — Structure, vibrational mode, and charges . . . . .                 | 33        |
| 12.2      | example_2.m — Infrared and Raman spectra . . . . .                               | 34        |
| 12.3      | example_3.m — Energetics . . . . .                                               | 35        |
| 12.4      | example_4.m — Recovering and restyling graphics handles . . . . .                | 37        |
| <b>13</b> | <b>Publication and licensing</b>                                                 | <b>39</b> |
| 13.1      | Declaration of Generative AI and AI-assisted technologies in the writing process | 39        |
| 13.2      | Note on the Use of AI-Assisted Development Tools . . . . .                       | 39        |
| 13.3      | Licence . . . . .                                                                | 39        |
| 13.4      | Citation . . . . .                                                               | 39        |

# 1 Introduction

This manual documents the **G09/G16 Toolbox**, a set of MATLAB functions for parsing, analysing, and visualising Gaussian 09 and Gaussian 16 output files (`.out/.log`) and formatted checkpoint files (`.fchk`). The toolbox covers:

- extraction of molecular geometry, energies, thermochemistry, dipole moment, polarisability, and hyperpolarisability;
- vibrational analysis: normal modes, IR/Raman spectra, and interactive mode visualisation;
- molecular-orbital energy diagrams and TD-DFT excited-state analysis;
- 3D molecular structure rendering (CPK ball-and-stick models) with atomic charge and dipole overlays;
- utility functions for bond-length tables, Gaussian version detection, restart-file generation, and toolbox self-documentation.

Function names follow the `G09_xxx/G16_xxx` convention, indicating which Gaussian version's output format the function targets. Where the two versions behave identically, this manual documents them in a single combined subsection (`G09_xxx / G16_xxx`); where behaviour differs, the differences are called out explicitly.

Every parsing function that reads a `.out/.log` file accepts an optional `'Lines'` Name-Value parameter: a cell array of pre-read file lines. This lets `G09_read_all/G16_read_all` read the file from disk once and reuse the same lines across every sub-parser, instead of each function re-reading and re-splitting the file independently. Passing `'Lines'` is entirely optional — omitting it falls back to reading the file normally.

**Wrong-toolbox warning.** Because Gaussian 09 and Gaussian 16 output formats differ, using the wrong toolbox on a file (e.g. `G16_energy` on a Gaussian 09 file) can silently misparse it rather than raising an obvious error — for example, `G16_dipole_polar` on a Gaussian 09 file returns `NaN` for the polarisability instead of an error. To catch this, every function that reads a file from disk checks the Gaussian-version citation line (`"Gaussian NN, Revision X.YY,"`) it just read and prints a non-blocking `warning(...)` if `NN` does not match the toolbox being used, suggesting the other one instead. The check runs only once per actual disk read (see Section 2.2), so `G09_read_all/G16_read_all` produce a single warning, not one per sub-parser.

## 2 File I/O utilities

### 2.1 G09\_read\_lines

```
lines = G09_read_lines(filename)
```

Low-level reader used internally by every other **G09\_XXX** parser. Reads a Gaussian 09 output file and returns a cell array of lines, with line endings stripped. Transparently handles CRLF line endings (as produced by Windows G09W builds) and ISO-8859-1 (Latin-1) encoding.

G16 parsers read files directly with the platform default encoding rather than calling a separate **G16\_read\_lines** helper; the 'Lines' parameter interface is identical across both toolboxes.

### 2.2 G09\_check\_gaussian\_match / G16\_check\_gaussian\_match

```
ok = G09_check_gaussian_match(lines, filename)
ok = G16_check_gaussian_match(lines, filename)
```

Internal helper, called automatically by every function that reads a **.out/.log** file from disk (not part of the typical user-facing API, but documented here for completeness). Scans the already-read **lines** (no extra disk I/O) for the "**Gaussian NN, Revision X.YY,**" citation line printed near the top of every output file. If found and **NN** does not match the toolbox (9 for **G09\_\***, 16 for **G16\_\***), prints a non-blocking warning suggesting the other toolbox; otherwise does nothing. Returns **true** if no mismatch was detected (or the version is unknown), **false** if a warning was issued.

Because this check lives inside each function's own "read the file fresh from disk" branch, it only fires when a file is actually opened — if a function receives pre-read **lines** via the 'Lines' parameter (e.g. every sub-parser called by **G09\_read\_all/G16\_read\_all**), it skips both the disk read and the check, so a single call to **read\_all** produces exactly one warning, not one per sub-parser.

## 3 Core data extraction

### 3.1 G09\_route / G16\_route

```
route = G09_route(filename)
route = G16_route(filename)
route = G16_route(filename, 'Lines', lines)
```

Extracts the complete route section (the # line(s) between the two ---- separators) as a single string.

| Option  | Default | Description                                                 |
|---------|---------|-------------------------------------------------------------|
| 'Lines' | {}      | Pre-read file lines (Section 2.1); read normally if omitted |

```
r = G09_route('indaco.log');
% '# opt freq=raman b3lyp/6-311++g(d,p) nosymm geom=connectivity field
=x+50'
```

Both `G09_route/G16_route` and `G09_charge_mult/ G16_charge_mult` now accept the 'Lines' option, consistent with the rest of the toolbox.

### 3.2 G09\_structure / G16\_structure

```
mol = G09_structure(filename)
mol = G09_structure(filename, 'step', 'last')
mol = G09_structure(filename, 'step', 'first')
mol = G09_structure(filename, 'step', N)

mol = G16_structure(filename)
mol = G16_structure(filename, 'orientation', 'standard')
mol = G16_structure(filename, 'orientation', 'input')
```

Extracts the molecular geometry from a Gaussian output file.

**Difference:** Gaussian 09 writes only "Input orientation:" blocks (never "Standard orientation:"), so `G09_structure` has no 'orientation' option. Gaussian 16 can write either, so `G16_structure` exposes 'orientation' = 'standard' (default, falls back to input if absent) | 'input' | 'auto'.

| Option        | Default           | Description                                                           |
|---------------|-------------------|-----------------------------------------------------------------------|
| 'step'        | 'last'            | Which geometry block to extract: 'first', 'last', or an integer index |
| 'orientation' | 'auto' (G16 only) | 'standard'   'input'   'auto'                                         |
| 'Lines'       | {}                | Pre-read file lines; read normally if omitted                         |

| Field        | Type   | Description                                                      |
|--------------|--------|------------------------------------------------------------------|
| .symbols     | cell   | Atomic symbols                                                   |
| .xyz         | double | Coordinates in Å (X Y Z)                                         |
| .Z           | int    | Atomic numbers                                                   |
| .Natoms      | int    | Number of atoms                                                  |
| .step        | int    | Index of the extracted step (1-based)                            |
| .n_steps     | int    | Total geometry blocks found in the file                          |
| .orientation | char   | 'Input orientation' (always, G09) or<br>'standard'/'input' (G16) |
| .filename    | char   | Source file name                                                 |

```
mol = G09_structure('indaco.log');
mol = G16_structure('calc.out', 'orientation', 'input');
```

### 3.3 G09\_energy / G16\_energy

```
en = G09_energy(filename)
en = G09_energy(filename, 'step', 'last')
en = G09_energy(filename, 'step', N)
```

Extracts SCF energy and thermochemistry data.

| Field        | Type    | Description                                                                       |
|--------------|---------|-----------------------------------------------------------------------------------|
| .SCF         | double  | SCF energy (Hartree)                                                              |
| .method      | char    | Method string, e.g. 'RB3LYP'                                                      |
| .ZPE_corr    | double  | Zero-point correction (Hartree)                                                   |
| .U_corr      | double  | Thermal correction to energy (Hartree)                                            |
| .H_corr      | double  | Thermal correction to enthalpy (Hartree)                                          |
| .G_corr      | double  | Thermal correction to Gibbs free energy (Hartree)                                 |
| .E0          | double  | SCF + ZPE (Hartree)                                                               |
| .U           | double  | SCF + U_corr (Hartree, G16 only)                                                  |
| .H           | double  | SCF + H_corr (Hartree)                                                            |
| .G           | double  | SCF + G_corr (Hartree)                                                            |
| .S_JmolK     | double  | Entropy $S$ (J mol <sup>-1</sup> K <sup>-1</sup> , G09)                           |
| .ZPE_kJ      | double  | Zero-point energy (kJ/mol)                                                        |
| .T, .P       | double  | Temperature (K), pressure (atm)                                                   |
| .has_thermo  | logical | false for opt-only jobs (no freq); *_corr, E0, U, H, G, T, P are NaN in that case |
| .G_kJ, .H_kJ | double  | $G$ , $H$ in kJ/mol (G09)                                                         |
| .filename    | char    |                                                                                   |

| Option  | Default | Description                                                 |
|---------|---------|-------------------------------------------------------------|
| 'step'  | 'last'  | Which SCF block to extract: 'last', 'first', or integer $N$ |
| 'Lines' | {}      | Pre-read file lines                                         |

### 3.4 G09\_charge\_mult / G16\_charge\_mult

```
[charge, mult] = G09_charge_mult(filename)
[charge, mult] = G16_charge_mult(filename)
[charge, mult] = G16_charge_mult(filename, 'Lines', lines)
```

Extracts molecular charge and spin multiplicity from the "Charge = ... Multiplicity = ..." line. Format identical across G09 and G16.

```
[q, m] = G09_charge_mult('indaco.log'); % q = 0, m = 1
```

### 3.5 G09\_convergence / G16\_convergence

```
cv = G09_convergence(filename)
cv = G09_convergence(filename, 'plot', true)

cv = G16_convergence(filename)
cv = G16_convergence(filename, 'plot', true)
```

Extracts geometry-optimisation convergence criteria (Max/RMS Force, Max/RMS Displacement) at every optimisation step, together with their thresholds and whether/when the job converged. Block format identical across G09 and G16.

| Option | Default | Description                                               |
|--------|---------|-----------------------------------------------------------|
| 'plot' | false   | Plot the four convergence series against their thresholds |

| Field                                                             | Type    | Description                              |
|-------------------------------------------------------------------|---------|------------------------------------------|
| .MaxForce,<br>.RMSForce                                           | vector  | Max / RMS force per step (a.u.)          |
| .MaxDisp,<br>.RMSDisp                                             | vector  | Max / RMS displacement per step (a.u.)   |
| .thr_MaxForce,<br>.thr_RMSForce,<br>.thr_MaxDisp,<br>.thr_RMSDisp | double  | Corresponding convergence thresholds     |
| .converged                                                        | logical | Whether all four criteria were satisfied |
| .conv_step                                                        | int/NaN | Step at which convergence was reached    |
| .Nsteps                                                           | int     | Number of optimisation steps found       |
| .filename                                                         | char    |                                          |

```
cv = G16_convergence('V_E00t.out', 'plot', true);
cv.converged
cv.conv_step
```

### 3.6 G09\_dipole\_polar / G16\_dipole\_polar

```
dp = G09_dipole_polar(filename)
dp = G09_dipole_polar(filename, 'units', 'Debye')

dp = G16_dipole_polar(filename)
dp = G16_dipole_polar(filename, 'units', 'SI')
```

Extracts the dipole moment and polarisability tensor.

**Differences between G09 and G16:** G09 prints "Exact polarizability:" as six values on a single line (upper triangle, row order), rather than G16's formatted Alpha(0;0)/Alpha(-w;w) blocks. G09 has no dynamic (laser-frequency-dependent) polarisability unless requested via Polar=OptRot or similar keywords, and additionally prints a "Diagonal vibrational polarizability:" line (3 values, returned in .alpha\_vib). An approximate CPHF tensor, if printed by G09 ("Approx polarizability:"), is returned in .alpha\_approx. G16 instead reports full dynamic polarisability entries per laser frequency (.alpha\_dyn) and modal derivatives .dmu\_dQ/.dalpha\_dQ (related to IR intensities and Raman activities; for exact scaled values use G16\_spectra instead).

| Option  | Default | Description                                                    |
|---------|---------|----------------------------------------------------------------|
| 'units' | 'au'    | 'au'   'Debye' (dipole only, G09) / 'Debye' (full, G16)   'SI' |
| 'Lines' | {}      | Pre-read file lines                                            |

| Field                                   | Description                                                                       |
|-----------------------------------------|-----------------------------------------------------------------------------------|
| .mu_x, .mu_y, .mu_z, .mu_tot, .mu_units | Dipole components, magnitude, unit string                                         |
| .alpha_iso, .alpha_aniso                | Isotropic polarisability, anisotropy                                              |
| .alpha_tensor, .alpha_units             | $3 \times 3$ static tensor (a.u.), unit string                                    |
| .alpha_vib, .has_alpha_vib              | Diagonal vibrational polarisability (a.u.), logical (G09)                         |
| .alpha_approx                           | CPHF approximate tensor (a.u.), NaN if absent (G09)                               |
| .alpha_dyn, .N_dyn                      | Struct array of dynamic polarisability entries (per laser frequency), count (G16) |
| .dmu_dQ, .dalpha_dQ, .has_deriv         | Dipole/polarisability derivatives w.r.t. normal modes, logical (G16)              |
| .filename                               |                                                                                   |

### 3.7 G09\_nmodes / G16\_nmodes

```
nm = G09_nmodes(filename)
nm = G09_nmodes(filename, 'modes', [5 10 20])

nm = G16_nmodes(filename)
```



```
nm = G16_nmodes(filename, 'section', 'last')
```

Extracts normal-mode displacement vectors.

G09 writes only one *Harmonic frequencies* section per file (even for opt+freq jobs), so `G09_nmodes` has no `'section'` option — it is implicit. G16 may contain more than one such section (e.g. a preliminary and a final one) and defaults to the last.

| Option    | Default           | Description                              |
|-----------|-------------------|------------------------------------------|
| 'modes'   | []                | Restrict output to specific mode indices |
| 'section' | 'last' (G16 only) | 'last'   'first'                         |
| 'Lines'   | {}                | Pre-read file lines                      |

  

| Field       | Description                                                                          |
|-------------|--------------------------------------------------------------------------------------|
| .freq,      | .IR, Frequencies ( $\text{cm}^{-1}$ ), IR intensities (KM/Mole), Raman activities    |
| .Raman      | ( $\text{\AA}^4/\text{AMU}$ , [] if absent)                                          |
| .redmass,   | Reduced masses (AMU), force constants ( $\text{mDyne}/\text{\AA}$ )                  |
| .frconst    |                                                                                      |
| .symmetry   | Symmetry labels                                                                      |
| .disp       | $[N_{\text{atoms}} \times 3 \times N_{\text{modes}}]$ Cartesian displacement vectors |
| .Nmodes,    |                                                                                      |
| .Natoms,    |                                                                                      |
| .has_Raman, |                                                                                      |
| .filename   |                                                                                      |

### 3.8 G09\_spectra / G16\_spectra

```
sp = G09_spectra(filename)
sp = G09_spectra(filename, Name, Value, ...)

sp = G16_spectra(filename)
sp = G16_spectra(filename, 'section', 'last')
```

Extracts IR/Raman line spectra and generates Lorentzian-broadened continuous spectra.

G09 writes only one Harmonic-frequencies section per file, so `G09_spectra` needs no `'section'` parameter; `G16_spectra` exposes it to select which section to use when more than one is present.

| Option      | Default           | Description                                 |
|-------------|-------------------|---------------------------------------------|
| 'FWHM'      | 10                | Lorentzian FWHM ( $\text{cm}^{-1}$ )        |
| 'xmin'      | 0                 | Lower wavenumber limit ( $\text{cm}^{-1}$ ) |
| 'xmax'      | 4000              | Upper wavenumber limit ( $\text{cm}^{-1}$ ) |
| 'dx'        | 1                 | Grid step ( $\text{cm}^{-1}$ )              |
| 'normalize' | false             | Normalise continua to maximum = 1           |
| 'plot'      | false             | Generate figure                             |
| 'section'   | 'last' (G16 only) | 'last'   'first'                            |
| 'Lines'     | {}                | Pre-read file lines                         |

| Field                  | Description                                                                            |
|------------------------|----------------------------------------------------------------------------------------|
| .freq,<br>.Raman       | .IR, Frequencies ( $\text{cm}^{-1}$ ), IR intensities, Raman activities ([] if absent) |
| .has_Raman,<br>.Nmodes | Logical, number of modes                                                               |
| .x,<br>.Raman_cont     | .IR_cont, Wavenumber grid, broadened IR/Raman continua                                 |
| .FWHM,<br>.filename    |                                                                                        |

```
sp = G16_spectra('calc.out', 'FWHM', 15, 'xmin', 400, 'plot', true);
```

## 4 Atomic charges

### 4.1 G09\_charges / G16\_charges

```
ch = G09_charges(filename)
ch = G09_charges(filename, 'type', 'APT')
ch = G09_charges(filename, 'mode', 'heavy')
ch = G09_charges(filename, 'plot', true, 'threshold', 0.05)
```

Extracts Mulliken or APT atomic charges and optionally renders them on the 3D structure, with an optional dipole-moment arrow overlay.

**Robustness:** handles all known Mulliken label variants across Gaussian revisions/OSes (e.g. "Mulliken atomic charges:" on G09 Rev. A.02/Windows and some Linux builds; "Mulliken charges:" on G09 Rev. B.01/C.01/D.01 and on all G16 revisions), by matching any line containing the charge-type keyword and "charges:", excluding "Sum of" and H-summed lines. The exact label found is reported in `ch.label`.

| Option            | Default     | Description                                                                                   |
|-------------------|-------------|-----------------------------------------------------------------------------------------------|
| 'type'            | 'Mulliken'  | 'Mulliken'   'APT'                                                                            |
| 'mode'            | 'atom'      | 'atom'   'heavy' (H charges summed onto heavy atoms)                                          |
| 'plot'            | true        | Render labels on the 3D structure                                                             |
| 'AtomScale'       | 0.35        | CPK sphere scale                                                                              |
| 'BondTol'         | 1.30        | Bond detection tolerance                                                                      |
| 'FontSize'        | 8           | Charge-label font size                                                                        |
| 'ColorScale'      | 'RdBu'      | 'RdBu' (blue=neg/red=pos)   'none'                                                            |
| 'threshold'       | 0           | Hide labels with $ q  < \text{threshold}$                                                     |
| 'ShowDipole'      | false       | Overlay the total dipole moment vector                                                        |
| 'DipoleOrigin'    | 'negcharge' | Arrow anchor: 'negcharge' (centroid of negative charges)   'poscharge'   'centroid'   [x y z] |
| 'DipoleScale'     | 1.0         | Arrow length, Å per Debye                                                                     |
| 'DipoleColor'     | [0 0.6 0]   | Arrow colour                                                                                  |
| 'DipoleLineWidth' | 2.5         | Arrow line width                                                                              |
| 'ShowDipoleLabel' | true        | Annotate the arrow with $ \mu $                                                               |
| 'DipoleFontSize'  | 11          | Dipole label font size                                                                        |
| 'DipoleUnits'     | 'Debye'     | Units for $ \mu $ : 'Debye'   'au'                                                            |
| 'Lines'           | {}          | Pre-read file lines                                                                           |

| Field                 | Description                                             |
|-----------------------|---------------------------------------------------------|
| .symbols,<br>.charges | Atomic symbols, per-atom charges (e)                    |
| .charges_H            | H-summed charges on heavy atoms                         |
| .sum_q                | Sum of all charges ( $\approx 0$ for neutral molecules) |
| .type, .label         | 'Mulliken'/'APT', exact header label found              |
| .Natoms               |                                                         |

## 4.2 G09\_charges\_fchk (G09 only)

```
ch_out = G09_charges_fchk(mol, ch)
ch_out = G09_charges_fchk(mol, ch, Name, Value, ...)
```

Visualises atomic charges directly from a `G09_fchk_read` struct, without requiring the corresponding `.log/.out` file. Mirrors the interface of `G09_charges` exactly, so the two can be used interchangeably once `data.mol` and `data.ch` are available.

| Option       | Default | Description                                                                                                                                                                             |
|--------------|---------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 'mode'       | 'atom'  | 'atom'   'heavy' (requires <code>ch.charges_H</code> non-empty — <code>.fchk</code> files have no native H-summed data; use <code>G09_charges</code> on the <code>.log</code> for that) |
| 'plot'       | true    |                                                                                                                                                                                         |
| 'AtomScale'  | 0.35    |                                                                                                                                                                                         |
| 'BondTol'    | 1.30    |                                                                                                                                                                                         |
| 'FontSize'   | 8       |                                                                                                                                                                                         |
| 'ColorScale' | 'RdBu'  | 'RdBu'   'none'                                                                                                                                                                         |
| 'threshold'  | 0       |                                                                                                                                                                                         |

```
data = G09_fchk_read('3typ.fchk');
ch    = G09_charges_fchk(data.mol, data.ch); %
      default
ch    = G09_charges_fchk(data.mol, data.ch, 'plot', false, 'threshold',
      0.05);
ch    = G09_charges_fchk(data.mol, data.ch, 'ColorScale', 'none'); %
      drop-in for G09_charges
```

Requires `mol` with fields `.symbols`, `.xyz`, `.Natoms`, `.filename`, and `ch` with fields `.charges`, `.symbols`, `.type`, `.Natoms` (`.charges_H` optional).

No equivalent `G16_charges_fchk` has been provided yet: since `.fchk` format is identical for G09 and G16, `G09_charges_fchk` can be used with `.fchk` files from either program version.

## 5 Formatted checkpoint (.fchk) support

### 5.1 G09\_fchk\_read (G09 only)

```
data = G09_fchk_read(filename)
data = G09_fchk_read(filename, 'verbose', false)
```

Reads a Gaussian 09/16 formatted checkpoint file (.fchk), generated with `formchk jobname.chk jobname.fchk`. Uses a single generic section parser (no hard-coded line counts) and is compatible with both G09 and G16 .fchk files.

Supersedes the old .fck/newzmat-format reader: reads the modern .fchk ASCII format, returns SI-ready fields (XYZ in Å, dipole in Debye), and needs no external helper functions. Despite the G09\_ prefix, this function works on .fchk files produced by *either* G09 or G16, since the formatted-checkpoint layout does not depend on the Gaussian version.

| Option    | Default | Description                           |
|-----------|---------|---------------------------------------|
| 'verbose' | true    | Print progress messages while parsing |

**Output struct data** (grouped by section):

| Field                                     | Description                                                      |
|-------------------------------------------|------------------------------------------------------------------|
| .title, .method, .basis                   | First line, method (e.g. 'RB3LYP'), basis set (e.g. 'def2SVPP')  |
| .Nat, .charge, .mult                      | Number of atoms, molecular charge, spin multiplicity             |
| .Nelec, .Nalpha, .Nbeta                   | Total, alpha, beta electron counts                               |
| .Nbasis, .Nbasis_indep                    | Basis functions, independent basis functions                     |
| .symbols, .AN, .masses                    | Atomic symbols, atomic numbers, real atomic masses (AMU)         |
| .xyz, .xyz_bohr                           | Coordinates (Å), coordinates (Bohr)                              |
| .SCF_energy, .total_energy, .virial_ratio | SCF energy, total energy (Hartree), virial ratio ( $\approx 2$ ) |
| .alpha_orb_energies, .beta_orb_energies   | MO energies (Hartree); beta is [] if RHF                         |
| .alpha_MO_coeff                           | Alpha MO coefficients (column-major)                             |
| .mulliken_charges                         | Mulliken charges (e)                                             |
| .HOMO_idx, .HOMO_eV, .LUMO_eV, .gap_eV    | Frontier-orbital summary                                         |
| .gradient, .rms_force                     | Cartesian gradient (Hartree/Bohr), RMS force                     |

## 6 Molecule and normal-mode visualisation

### 6.1 G09\_draw\_molecule / G16\_draw\_molecule

```
G09_draw_molecule(mol)
G09_draw_molecule(mol, 'Name', Value, ...)
```

Renders a 3D CPK ball-and-stick model from a mol struct (as returned by `G09_structure/G16_structure`), with bonds detected automatically from a covalent-radius criterion and drawn as 1, 2, or 3 parallel lines according to an estimated bond order.

| Option       | Default          | Description                                                                                                                                                                                                                                                                                                                                                                                                             |
|--------------|------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 'AtomScale'  | 0.35             | Sphere radius as a fraction of the covalent radius                                                                                                                                                                                                                                                                                                                                                                      |
| 'BondTol'    | 1.30             | Bond tolerance: bonded if $d < (r_1 + r_2) \times \text{BondTol}$                                                                                                                                                                                                                                                                                                                                                       |
| 'ShowLabels' | true             | Show atom labels ("C1", "H2", ...)                                                                                                                                                                                                                                                                                                                                                                                      |
| 'ShowLegend' | true             | Show the element-colour legend                                                                                                                                                                                                                                                                                                                                                                                          |
| 'Title'      | filename         | Figure title                                                                                                                                                                                                                                                                                                                                                                                                            |
| 'BgColor'    | [0.95 0.95 0.95] | Axes background colour                                                                                                                                                                                                                                                                                                                                                                                                  |
| 'Ax'         | (new figure)     | Draw into an existing axes handle                                                                                                                                                                                                                                                                                                                                                                                       |
| 'ShowAxes'   | false            | Draw a small Cartesian X/Y/Z reference triad, anchored at the lower-left-front corner of the plotted molecule                                                                                                                                                                                                                                                                                                           |
| 'AxesLength' | []               | Length of the X/Y/Z arrows, in Å ([] = auto, 20% of the molecule's bounding-box diagonal)                                                                                                                                                                                                                                                                                                                               |
| 'BondList'   | []               | [ $N_{\text{bonds}} \times 2$ ] or [ $N_{\text{bonds}} \times 3$ ] explicit atom-index pairs (optionally with a 3rd column giving a pre-computed bond order 1/2/3) to draw as bonds, bypassing the BondTol distance criterion ([] = auto-detect). Used by <code>G09_animate_mode/G16_animate_mode</code> to keep a fixed bond topology (and, with the 3rd column, a fixed bond order) across all frames of an animation |

```
mol = G09_structure('zeatin.out');
G09_draw_molecule(mol);
G09_draw_molecule(mol, 'ShowLabels', false, 'AtomScale', 0.4);
G09_draw_molecule(mol, 'ShowAxes', true);
```

**Bond order (single/double/triple).** For C-C and C-O pairs, bond order is estimated purely from bond length (any other element pair, including C-N, is always drawn as a single bond) and rendered as 1/2/3 parallel lines in the usual chemical-drawing convention — a geometric estimate, not Gaussian's own bond-order analysis (e.g. Wiberg/NBO indices). The C-C double/single threshold is deliberately set to 1.36 Å rather than the generic reference-length midpoint ( $\approx 1.44$  Å): symmetric aromatic rings have essentially equal C-C bond lengths ( $\approx 1.39$ – $1.40$  Å, with no real single/double alternation to recover from geometry alone), so the generic midpoint would classify every ring bond as double. With the adjusted threshold, aromatic rings are instead rendered as all-single — a more honest depiction than an arbitrary alternating pattern, since the true bond order is  $\approx 1.5$  all the way around the ring.

**Why C-N is excluded.** C-N was classified by length in an earlier version of the toolbox, using the same kind of threshold as C-C/C-O. Unlike C-C, a single threshold cannot separate aromatic C-N (e.g. pyridine rings,  $\approx 1.34$  Å) from a genuine C=N: on asymmetric pyridine-like rings this produced one ring C-N bond rendered double and its chemically-equivalent neighbour rendered single, an inconsistent and misleading picture. C-N is therefore always drawn as a single bond, regardless of length.

No differences between the G09 and G16 versions beyond the input struct's origin.

## 6.2 G09\_draw\_mode / G16\_draw\_mode

```
G09_draw_mode(mol, nm, mode_idx)
G09_draw_mode(mol, nm, mode_idx, 'Name', Value, ...)
```

Renders a single vibrational normal mode as displacement arrows over the CPK structure.

| Option       | Default     | Description                 |
|--------------|-------------|-----------------------------|
| 'Scale'      | 1.5         | Arrow length scale          |
| 'ArrowColor' | [1 0.4 0.1] | Arrow colour                |
| 'AtomScale'  | 0.35        | CPK sphere scale factor     |
| 'BondTol'    | 1.30        | Bond detection tolerance    |
| 'ShowLabels' | false       | Show atom index labels      |
| 'FlipSign'   | false       | Invert all arrow directions |

**Why 'FlipSign' exists.** Normal-mode eigenvectors have an arbitrary overall sign — a mode and its 180°-phase-shifted twin are physically identical. If the arrows point opposite to GaussView's rendering for a given mode, set 'FlipSign', true to flip them. This is purely cosmetic and has no effect on frequencies or intensities.

## 6.3 G09\_modeViewer / G16\_modeViewer

```
G09_modeViewer(filename)
G09_modeViewer(filename, 'Name', Value, ...)
```

Interactive selector GUI for browsing vibrational modes. Reads the structure and all normal modes via `G09_structure/G09_nmodes`, then opens a window listing every mode (index, frequency, symmetry). Selecting an entry calls `G09_draw_mode` to render that mode in a new figure window; previously drawn mode figures stay open, so different modes (or render settings) can be compared side by side.

### Window controls:

- *Order by:* sort the mode list by mode number (default), IR intensity, or Raman intensity (descending; only offered when Raman data is present). The current selection is preserved across reordering.
- A text box to set a custom title on the current mode figure.
- A control for every `G09_draw_mode` option (`Scale`, `ArrowColor`, `AtomScale`, `BondTol`, `ShowLabels`, `FlipSign`); changing any of them immediately redraws the selected mode in a new figure. Arrow colour can be set from a named preset (Or-

ange/Red/Blue/Green/Black/ Magenta) or a custom colour.

- A *Save figure...* button exporting the target mode figure to JPEG, EPS, or PDF (EPS/PDF as true vector graphics).
- An *Animate mode (MP4)...* button exporting an MP4 animation of the currently selected mode via `G09_animate_mode/ G16_animate_mode`, using the current Scale/AtomScale/ BondTol/ShowLabels/FlipSign settings and, automatically, the camera orientation of the currently displayed mode figure (a manual rotation carries over into the animation).

Name-Value arguments passed to `G09_modeViewer` pre-populate the corresponding option control(s), e.g. `G09_modeViewer('file.log', 'Scale', 2, 'ShowLabels', true)`.

```
G09_modeViewer('V_E00t.out');  
G16_modeViewer('INDACO_E025_ppDP.LOG', 'Scale', 2, 'ShowLabels', true)  
;
```

See also `G09_structure/G16_structure`, `G09_nmodes/G16_nmodes`, `G09_draw_mode/G16_draw_mode`, `G09_animate_mode/G16_animate_mode`.

## 6.4 G09\_animate\_mode / G16\_animate\_mode

```
outfile = G09_animate_mode(mol, nm, mode_idx)  
outfile = G09_animate_mode(mol, nm, mode_idx, 'Name', Value, ...)  
  
outfile = G16_animate_mode(mol, nm, mode_idx)
```

Exports an MP4 animation of a single vibrational mode: the molecule oscillates along the mode's displacement vector (equilibrium  $\pm$  amplitude), in the style of GaussView's mode animations, and the result is saved via `VideoWriter` ('MPEG-4' profile). A figure window opens and animates live while the video is rendered; avoid interacting with it until the function returns.

| Option           | Default   | Description                                                                                                                                                                                                              |
|------------------|-----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 'Filename'       | [] (auto) | Output path; default <source>_mode<N>.mp4, .mp4 appended if missing                                                                                                                                                      |
| 'Scale'          | 1.5       | Displacement amplitude scale, same meaning as <code>G09_draw_mode/G16_draw_mode</code> 's 'Scale'                                                                                                                        |
| 'FlipSign'       | false     | Invert the displacement direction                                                                                                                                                                                        |
| 'AtomScale'      | 0.35      | See <code>G09_draw_molecule/G16_draw_molecule</code>                                                                                                                                                                     |
| 'BondTol'        | 1.30      | See <code>G09_draw_molecule/G16_draw_molecule</code> ; also used to compute the fixed bond list (see below)                                                                                                              |
| 'ShowLabels'     | false     | See <code>G09_draw_molecule/G16_draw_molecule</code>                                                                                                                                                                     |
| 'FramesPerCycle' | 30        | Frames per oscillation period                                                                                                                                                                                            |
| 'NCycles'        | 2         | Number of periods rendered                                                                                                                                                                                               |
| 'FPS'            | 20        | Video frame rate                                                                                                                                                                                                         |
| 'View'           | []        | [azimuth elevation] in degrees, the starting camera orientation ([] = MATLAB's default 3D view, azimuth= -37.5, elevation= 30). Pass the output of MATLAB's own <code>view(ax)</code> to match an already-rotated figure |
| 'ShowWaitbar'    | true      | Print rendering progress to the command window                                                                                                                                                                           |



```
mol = G16_structure('V_E00t.out');
nm = G16_nmodes('V_E00t.out');
G16_animate_mode(mol, nm, 70, 'Scale', 2, 'FPS', 25);
```

**Fixed bond list and bond order.** Bonds (and their estimated order, 1/2/3) are computed once from the *equilibrium* geometry (via `G09_get_bond_length/G16_get_bond_length`, using 'BondTol' as the tolerance) and passed to `G09_draw_molecule/G16_draw_molecule` through its 'BondList' parameter (atom-index pairs plus a 3rd bond-order column), instead of being re-detected from instantaneous inter-atomic distances on every frame. Without this, bonds would flicker in and out — and double/triple bonds would flicker to/from single — as oscillating atoms cross the relevant distance thresholds.

**No graphical waitbar.** Rendering progress is printed to the command window rather than shown with MATLAB's `waitbar`: on some MATLAB versions, `waitbar` itself was found to error intermittently across many rapid updates ("Not enough input arguments" inside its own internal `title()` call).

**Axes handling.** Each frame's axes are deleted and recreated (rather than cleared with `cla`) before redrawing: in this 3D-plus-lighting configuration, `cla(ax)` was found to leave stale graphics objects behind, causing the exported video to show all frames superimposed instead of one at a time.

No differences between the G09 and G16 versions beyond the input structs' origin.

See also `G09_draw_molecule/G16_draw_molecule`, `G09_draw_mode/G16_draw_mode`, `G09_modeViewer/G16_modeViewer`, `G09_get_bond_length/G16_get_bond_length`.

## 7 Orbital energy analysis

### 7.1 G09\_orbital\_energies / G16\_orbital\_energies

```
oe = G09_orbital_energies(filename)
oe = G09_orbital_energies(filename, 'step', 'last')
oe = G09_orbital_energies(filename, 'step', N)
```

Extracts molecular orbital energies (HOMO/LUMO and the full occupied/virtual spectrum) from a Gaussian 09/16 output file, by parsing the "Alpha occ. eigenvalues --" / "Alpha virt. eigenvalues --" lines printed by Gaussian's population analysis (and the corresponding "Beta" lines for open-shell calculations). These blocks repeat once per SCF calculation in the file (e.g. once per optimisation step); the 'step' option selects which block to report, consistently with G09\_energy/G09\_structure.

| Option | Default | Description                                                         |
|--------|---------|---------------------------------------------------------------------|
| 'step' | 'last'  | Which eigenvalue block to use: 'first', 'last', or an integer index |

**Output struct** oe (energies in Hartree unless noted):

| Field                         | Type    | Description                                          |
|-------------------------------|---------|------------------------------------------------------|
| .alpha_occ                    | vector  | Occupied alpha orbital energies                      |
| .alpha_virt                   | vector  | Virtual alpha orbital energies                       |
| .beta_occ                     | vector  | Occupied beta orbital energies ( [] if closed-shell) |
| .beta_virt                    | vector  | Virtual beta orbital energies ( [] if closed-shell)  |
| .has_beta                     | logical | <b>true</b> for open-shell (UHF/UKS) calculations    |
| .HOMO / .LUMO                 | double  | Highest occupied / lowest unoccupied orbital energy  |
| .gap                          | double  | LUMO -- HOMO                                         |
| .HOMO_alpha / .LUMO_alpha     | double  | Alpha HOMO/LUMO (== .HOMO/.LUMO for closed-shell)    |
| .HOMO_beta / .LUMO_beta       | double  | Beta HOMO/LUMO ( [] if closed-shell)                 |
| .HOMO_eV / .LUMO_eV / .gap_eV | double  | Same three quantities, in eV                         |
| .step                         | int     | Block index actually used                            |
| .Nsteps                       | int     | Number of eigenvalue blocks found in the file        |
| .filename                     | char    | Source file name                                     |

```
oe = G09_orbital_energies('V_E00t.out');
fprintf('HOMO-LUMO gap = %.3f eV\n', oe.gap_eV);
```

For open-shell (UHF/UKS) calculations, HOMO and LUMO are computed as  $\max(\text{HOMO}_\alpha, \text{HOMO}_\beta)$  and  $\min(\text{LUMO}_\alpha, \text{LUMO}_\beta)$  respectively, so .gap always refers to the smallest alpha/beta HOMO-LUMO gap. No differences between the G09 and G16 versions beyond the parsed file's origin.

## 7.2 G09\_draw\_orbital / G16\_draw\_orbital

```
G09_draw_orbital(oe)
G09_draw_orbital(oe, 'Name', Value, ...)
```

Draws a molecular-orbital energy-level diagram from the struct returned by `G09_orbital_energies`/`G16_orbital_energies` showing a user-selected number of occupied/virtual levels around the frontier orbitals and highlighting the HOMO–LUMO transition with an arrow labelled with the gap value.

| Option             | Default                              | Description                                                                                   |
|--------------------|--------------------------------------|-----------------------------------------------------------------------------------------------|
| 'NLevels'          | 5                                    | Number of occupied/virtual levels shown on each side of the frontier orbitals                 |
| 'Units'            | 'eV'                                 | Energy units: 'eV' or 'Hartree'                                                               |
| 'Ax'               | (new figure)                         | Draw into an existing axes handle                                                             |
| 'OccColor'         | [0.25 0.25 0.70]                     | Colour for non-frontier occupied levels                                                       |
| 'VirtColor'        | [0.70 0.30 0.25]                     | Colour for non-frontier virtual levels                                                        |
| 'HOMOColor'        | [0.00 0.45 0.85]                     | Highlight colour for the HOMO                                                                 |
| 'LUMOCOLOR'        | [0.90 0.35 0.00]                     | Highlight colour for the LUMO                                                                 |
| 'ArrowColor'       | [0.15 0.60 0.15]                     | HOMO→LUMO transition arrow colour                                                             |
| 'ShowLabels'       | true                                 | Annotate each level with its energy value                                                     |
| 'ShowSpins'        | true                                 | Draw a paired-electron arrow glyph ( $\uparrow\downarrow$ ) on occupied levels                |
| 'FontSize'         | 8                                    | Font size for level energy-value labels                                                       |
| 'FrontierFontSize' | 13                                   | Font size for the HOMO/LUMO tags and the gap annotation                                       |
| 'ArrowHeadSize'    | 0.2                                  | HOMO–LUMO arrow head size, as a fraction of the arrow length (passed to <code>quiver</code> ) |
| 'Title'            | filename or 'Orbital Energy Diagram' | Figure title                                                                                  |

```
oe = G09_orbital_energies('a1.out');
G09_draw_orbital(oe)
G09_draw_orbital(oe, 'NLevels', 8, 'Units', 'Hartree')
```

Requires the `oe` struct returned by `G09_orbital_energies`/`G16_orbital_energies` and errors if `alpha_occ`/`alpha_virt` are missing or empty. No differences between the G09 and G16 versions beyond the input struct's origin.

## 8 Response properties (G16 only)

### 8.1 G16\_hyperpolar

```
hp = G16_hyperpolar(filename)
hp = G16_hyperpolar(filename, 'units', 'au')      % default
hp = G16_hyperpolar(filename, 'units', 'esu')     % 10-30 esu
hp = G16_hyperpolar(filename, 'units', 'SI')      % 10-50 C3 m3 J-2
```

Extracts the dipole hyperpolarisability  $\beta$  (static, dynamic, and vibrational contributions) from a Gaussian 16 output file.

| Option  | Default | Description                                                                                                    |
|---------|---------|----------------------------------------------------------------------------------------------------------------|
| 'units' | 'au'    | 'au'   'esu' (10 <sup>-30</sup> esu)   'SI' (10 <sup>-50</sup> C <sup>3</sup> m <sup>3</sup> J <sup>-2</sup> ) |

| Field             | Description                                                                                              |
|-------------------|----------------------------------------------------------------------------------------------------------|
| .beta0.par_z,     | Parallel / perpendicular component of static $\beta(0;0,0)$ along $z$                                    |
| .beta0.perp_z     |                                                                                                          |
| .beta0.vec_x/y/z, | Vector components and magnitude $ \beta_{\text{vec}} $                                                   |
| .beta0.beta_vec   |                                                                                                          |
| .beta0.tensor     | All Cartesian tensor components ( $xxx, xyx, \dots, zzz$ )                                               |
| .beta_dyn         | Struct array, one entry per laser frequency: .lambda_nm, .par_z, .perp_z, .vec_x/y/z, .beta_vec, .tensor |
| .N_dyn            | Number of dynamic (laser) frequencies found                                                              |
| .beta_vib,        | Diagonal vibrational hyperpolarisability, logical                                                        |
| .has_vib          |                                                                                                          |
| .filename         |                                                                                                          |

```
hp = G16_hyperpolar('V_E00t.out');
hp.beta0.beta_vec      % static beta modulus, a.u.
hp.beta_dyn(1).lambda_nm % wavelength of the first dynamic entry (nm)
hp.beta_dyn(1).beta_vec % |beta| at that frequency
```

### 8.2 G16\_tddft

```
td = G16_tddft(filename)
td = G16_tddft(filename, 'nstates', N)      % first N states only
td = G16_tddft(filename, 'plot', true)      % also generate UV-Vis plot
td = G16_tddft(filename, 'FWHM_eV', 0.3)    % broadening FWHM (eV)
```

Extracts TD-DFT excited states and generates a Gaussian-broadened UV-Vis spectrum.

| Option    | Default | Description                            |
|-----------|---------|----------------------------------------|
| 'nstates' | Inf     | Load only the first $N$ excited states |
| 'plot'    | false   | Generate the UV-Vis plot               |
| 'FWHM_eV' | 0.30    | Gaussian broadening FWHM (eV)          |

| Field                  | Description                                                                                                                           |
|------------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| .n, .mult              | State index; multiplicity label (e.g. 'Singlet-A', 'Triplet-B')                                                                       |
| .eV, .nm, .f           | Excitation energy (eV), wavelength (nm), oscillator strength                                                                          |
| .S2, .has_S2           | $\langle S^2 \rangle$ expectation value (0 for pure singlets), logical                                                                |
| .trans                 | Cell array, one $[N_{\text{contrib}} \times 3]$ matrix per state: columns [MO_from, MO_to, coeff] (MO_to < 0 denotes a de-excitation) |
| .Nstates               | Total number of excited states loaded                                                                                                 |
| .x_nm, .eps_cont       | Wavelength grid (100–1000 nm), Gaussian-broadened UV-Vis spectrum (arb. units)                                                        |
| .FWHM_eV,<br>.filename |                                                                                                                                       |

```

td = G16_tddft('violacein_td.out');
plot(td.x_nm, td.eps_cont)      % UV-Vis spectrum
stem(td.nm, td.f)              % transition stem plot
td.trans{2}                    % transitions contributing to the 2nd
    state

```

No G09 equivalent is provided: TD-DFT excited-state analysis and hyperpolarisability response properties in this toolbox are currently supported only for Gaussian 16 output files.

## 9 Structural analysis utilities

### 9.1 G09\_get\_bond\_length / G16\_get\_bond\_length

```
bondTable = G09_get_bond_length(mol)
bondTable = G09_get_bond_length(mol, 'Name', Value, ...)
```

Builds the bond-length table of a molecule from a `mol` struct (fields `.symbols`, `.xyz`), detecting bonds via a covalent-radius criterion, and returns a MATLAB table.

| Option      | Default    | Description                                                                  |
|-------------|------------|------------------------------------------------------------------------------|
| 'Tolerance' | 1.15       | Multiplicative factor on the sum of covalent radii for the bonding criterion |
| 'IncludeH'  | true       | Include bonds involving hydrogen atoms                                       |
| 'SortBy'    | 'distance' | Sort by 'distance' (ascending) or 'atom' (atom index)                        |
| 'SaveAs'    | ''         | Path (.xlsx or .csv) to save the table to; not saved if omitted              |

Output columns: Atom1, Sym1, Atom2, Sym2, Distance Ang.

```
T = G09_get_bond_length(mol, 'SortBy', 'atom');
T = G16_get_bond_length(mol, 'IncludeH', false, 'SaveAs', 'bonds.xlsx');
```

The bonding criterion is purely geometric (covalent radii), not derived from Gaussian's own connectivity/topology matrix — suitable for quick structural analysis, not as the "official" G09/G16 connectivity.

### 9.2 G09\_gaussian\_version / G16\_gaussian\_version

```
gv = G09_gaussian_version(filename)
gv = G16_gaussian_version(filename)
```

Detects which Gaussian version/revision produced a `.out/.log/.fchk` file.

For `.out/.log` files, reads the "Gaussian NN, Revision X.YY," citation line printed near the top of the file (works for any NN: 09, 16, ...). `.fchk` files do not store this information at all; in that case the function looks for a sibling `.log/.out` file with the same base name in the same folder and reads the version from there. If no sibling file is found, `.major/.revision/.full` are returned empty and a warning is issued.

| Field                  | Description                                                 |
|------------------------|-------------------------------------------------------------|
| <code>.major</code>    | Gaussian major version, e.g. 9, 16 ([] if unknown)          |
| <code>.revision</code> | Revision string, e.g. 'A.02', 'C.01' ('' if unknown)        |
| <code>.full</code>     | Citation line as printed, e.g. 'Gaussian 09, Revision A.02' |
| <code>.source</code>   | 'out/log'   'fchk-sibling:<path>'   'unknown'               |
| <code>.filename</code> |                                                             |

```
gv = G09_gaussian_version('a1.out');          % gv.major = 16, gv.
revision = 'C.01'
```

```
gv = G16_gaussian_version('molecule.fchk'); % falls back to molecule.
out/.log if present
```

### 9.3 G09\_restart / G16\_restart

```
gjf_file = G09_restart(filename)
gjf_file = G09_restart(filename, 'Name', Value, ...)

gjf_file = G16_restart(filename)
gjf_file = G16_restart(filename, 'Name', Value, ...)
```

Generates a Gaussian 09/16 input file (.gjf) to restart a calculation from a geometry found in an existing .log/.out file. `G16_restart` reads geometry via `G16_structure` (so it follows that function's Standard/Input orientation handling); otherwise the two functions are identical.

| Option        | Default              | Description                                                          |
|---------------|----------------------|----------------------------------------------------------------------|
| 'step'        | 'last'               | 'last'   'first'   integer $N$ — which geometry step to restart from |
| 'output'      | <base>_restarted.gjf | Output .gjf path                                                     |
| 'extra_route' | ''                   | Additional keywords appended to the route section                    |
| 'nproc'       | 0                    | %nprocshared override (0 = keep/omit)                                |
| 'mem'         | ''                   | %mem override ('' = keep/omit)                                       |

If the source output file has no %chk line (common in Gaussian 09 Windows output), the checkpoint name is derived from the source file name instead. The generated .gjf is valid for restarting under either Gaussian 09 or Gaussian 16, and can be read back with `G_read_input`.

Returns the path of the generated .gjf file.

### 9.4 G\_read\_input (shared, no G09\_/G16\_ prefix)

```
ginp = G_read_input(filename)
```

Reads a Gaussian *input* file (.gjf, .com, or .in) and extracts the link0 commands, route section, title, charge/multiplicity, and starting Cartesian geometry.

The Gaussian input file format does not differ between Gaussian 09 and Gaussian 16, so this is the toolbox's only function without a `G09_/G16_` prefix pair: an identical copy is kept in both the `G09/` and `G16/` folders, so it is available regardless of which toolbox you have on the MATLAB path. Only Cartesian-coordinate geometry blocks are supported (not Z-matrix input).

| Field     | Type   | Description                                                            |
|-----------|--------|------------------------------------------------------------------------|
| .symbols  | cell   | Atomic symbols                                                         |
| .xyz      | double | Starting coordinates in Å (X Y Z)                                      |
| .Natoms   | int    | Number of atoms                                                        |
| .charge   | int    | Total molecular charge                                                 |
| .mult     | int    | Spin multiplicity                                                      |
| .title    | char   | Title/comment line(s), joined with a space                             |
| .route    | char   | Full route section, single line                                        |
| .method   | char   | Method parsed from the route (e.g. 'b3lyp'), '' if not found           |
| .basis    | char   | Basis set parsed from the route (e.g. '6-311+g(d,p)'), '' if not found |
| .chk      | char   | %chk link0 value, '' if absent                                         |
| .mem      | char   | %mem link0 value, '' if absent                                         |
| .nproc    | char   | %nprocshared/%nproc link0 value, '' if absent                          |
| .filename | char   | Source file path                                                       |

ginp has the same .symbols/.xyz/.Natoms/ .filename fields as the struct returned by G09\_structure/G16\_structure, so it can be passed directly to G09\_draw\_molecule/G16\_draw\_molecule or G09\_get\_bond\_length/G16\_get\_bond\_length without any conversion.

```
ginp = G_read_input('molecule.gjf');
G16_draw_molecule(ginp, 'ShowAxes', true);
fprintf('%s/%s, charge %d, mult %d\n', ginp.method, ginp.basis, ...
        ginp.charge, ginp.mult);
```

## 9.5 G09\_list / G16\_list

```
G09_list()
T = G09_list()

G16_list()
T = G16_list()
```

Lists every G09\*.m/G16\*.m function found in the toolbox folder, printing the function name and its H1 description line (sorted alphabetically). Also returns the same information as a table with columns .Name, .Description, .File.

```
G09_list();
T = G16_list();
T(contains(T.Description, 'dipole', 'IgnoreCase', true), :)
```



## 10 One-call data extraction

### 10.1 G09\_read\_all / G16\_read\_all

```
T = G09_read_all(filename)
T = G16_read_all(filename)
```

Runs the full set of G09\_XXX/G16\_XXX parsers on a single output file and collects the results into one struct T. The file is read from disk once and the resulting lines are passed to every sub-parser via their 'Lines' option, instead of each sub-parser independently re-reading and re-splitting the file.

| Field             | Source function               | Description                                          |
|-------------------|-------------------------------|------------------------------------------------------|
| .charge           | G09/G16_charges               | Mulliken and APT atomic charges (plotting disabled)  |
| .energy           | G09/G16_energy                | SCF energy and thermochemistry                       |
| .structure        | G09/G16_structure             | Optimized molecular structure                        |
| .dipolar          | G09/G16_dipole_polarizability | Dipole moment and polarisability                     |
| .nmodes           | G09/G16_nmodes                | IR/Raman vibrational normal modes, if present        |
| .spectra          | G09/G16_spectra               | Frequencies, IR/Raman intensities, simulated spectra |
| .route            | G16_route (G16 only)          | Gaussian route section details                       |
| .chargemol.charge | G16_charge_mult               | Total molecular charge, spin multiplicity            |
| .chargemol.mol    | (G16 only)                    |                                                      |

```
T = G16_read_all('zeatin.out');
disp(T.energy)
G16_draw_molecule(T.structure);
```

**Known discrepancy:** the current G09\_read\_all does *not* populate .route or .chargemol, unlike G16\_read\_all, which retains both. If parity with G16\_read\_all is required, add

```
T.route = G09_route(filename, 'Lines', lines);
[c, m] = G09_charge_mult(filename, 'Lines', lines);
T.chargemol.charge = c;
T.chargemol.mol = m;
```

to G09\_read\_all.m.

### 10.2 G09\_batch\_read\_all / G16\_batch\_read\_all

```
T = G09_batch_read_all(folder)
T = G09_batch_read_all(folder, 'Recursive', true)
T = G09_batch_read_all(folder, 'WriteReports', true)
T = G09_batch_read_all(folder, 'SaveAs', 'summary.xlsx')

T = G16_batch_read_all(folder)
```

Scans folder for .log/.out files (case-insensitive), runs G09\_read\_all/G16\_read\_all (plus G09\_orbital\_energies/G16\_orbital\_energies, for the HOMO-LUMO gap) on each, and re-

turns one row per file — useful for screening many calculations at once (conformers, scans, batches of jobs) without calling `read_all` file-by-file.

A file that fails to parse (e.g. an incomplete/crashed job, or a file from the other Gaussian version run through the wrong toolbox) does *not* stop the batch: its row is filled with NaN and the caught error message is recorded in the `.Status` column instead.

| Option         | Default | Description                                                                                             |
|----------------|---------|---------------------------------------------------------------------------------------------------------|
| 'Recursive'    | false   | Also scan subfolders                                                                                    |
| 'WriteReports' | false   | Write a <code>G09_write_report/G16_write_report .txt</code> next to each source file                    |
| 'SaveAs'       | ''      | Path to save the summary table ( <code>.csv</code> or <code>.xlsx</code> , inferred from the extension) |

| Field                             | Description                                         |
|-----------------------------------|-----------------------------------------------------|
| .File                             | Source file path                                    |
| .Natoms                           | Atom count (from <code>.structure.Natoms</code> )   |
| .SCF_Hartree                      | SCF energy                                          |
| .E0_Hartree                       | SCF + ZPE                                           |
| .G_kJmol                          | Gibbs free energy, kJ/mol                           |
| .mu_tot,<br>.mu_units             | Dipole magnitude and its units                      |
| .HOMO_eV,<br>.LUMO_eV,<br>.Gap_eV | Frontier orbital energies and gap, eV               |
| .Status                           | 'ok', or the caught error message if parsing failed |

```
T = G16_batch_read_all('results/', 'WriteReports', true);
T(T.Gap_eV == min(T.Gap_eV), :) % smallest HOMO-LUMO gap
```

## 11 Report generation

### 11.1 G09\_write\_report / G16\_write\_report

```
outfile = G09_write_report(T)
outfile = G09_write_report(T, outfile)

outfile = G16_write_report(T)
outfile = G16_write_report(T, outfile)
```

Writes a human-readable text report from a `G09_read_all`/`G16_read_all` struct `T`, formatting a summary of every field present in `T` into a plain `.txt` file. If `outfile` is omitted, the file is named after the source Gaussian file (e.g. `'zeatin.out' → 'zeatin_report.txt'`) in the current folder.

| Argument             | Default                                | Description                                                              |
|----------------------|----------------------------------------|--------------------------------------------------------------------------|
| <code>T</code>       | (required)                             | Struct returned by <code>G09_read_all</code> / <code>G16_read_all</code> |
| <code>outfile</code> | <code>&lt;source&gt;_report.txt</code> | Output <code>.txt</code> path                                            |

Returns the path written to. Sections are included only if the corresponding field is present in `T`, in this order: route, charge/multiplicity, molecular structure (full Cartesian coordinate table), energetics (with thermochemistry if available), dipole moment and polarisability (including the dynamic polarisability table, if present), atomic charges (full per-atom table, sum of charges, dipole-from-charges overlay if computed), vibrational normal modes (frequency/IR/Raman/reduced mass/symmetry table), and a summary of the simulated IR/Raman spectra.

The full broadened-spectrum continuum arrays (`T.spectra.x`, `.IR_cont`, `.Raman_cont`) are deliberately *not* dumped into the report — only the grid range, FWHM, and whether Raman data is present are summarised. Access those arrays directly from `T.spectra` for plotting or export.

```
T = G16_read_all('zeatin.out');
G16_write_report(T);                % -> zeatin_report.txt
G16_write_report(T, 'zeatin_summary.txt'); % explicit output path
```

No differences between the G09 and G16 versions beyond the input struct's origin and the report header ("Gaussian 09"/"Gaussian 16 Calculation Report").

See also `G09_read_all`/`G16_read_all`.

`G16parser` is a Python 3 port of the G16 MATLAB toolbox, covering the same parsing, checkpoint-analysis, and static-visualisation functionality described in the previous sections. It is installable as a standard editable package and exposes one `g16_xxx` function per MATLAB `G16_xxx` counterpart, each returning a `Struct` object (attribute access, e.g. `mol.xyz`, `ch.dipole.Debye`) instead of a MATLAB struct.

```
cd G16parser
pip install -e .
```

```
import G16parser as g16

mol = g16.g16_structure('molecule.out')
g16.g16_draw_molecule(mol, show_axes=True)

ch = g16.g16_charges('molecule.out', show_dipole=True)
```

```
oe = g16.g16_orbital_energies('molecule.out')
g16.g16_draw_orbital(oe)

T = g16.g16_read_all('molecule.out')    # everything in one call,
    single file read
```

**Requirements:** Python  $\geq 3.9$ , numpy, pandas, matplotlib (installed automatically via `pip install -e .`). No Gaussian installation or compiled dependency is needed.

## 11.2 Function reference

Every function mirrors its MATLAB `G16_xxx` counterpart in name, parameters (in `snake_case`), defaults, and returned fields — see the corresponding MATLAB subsection earlier in this manual for full parameter/field documentation. All extraction functions accept an optional `lines=` parameter (pre-read file lines) mirroring the MATLAB `'Lines'` option; `g16_read_all` uses this internally to read the file exactly once.

| Function                          | Description                                                                                                                                                                                                                                    |
|-----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>g16_read_input</code>       | Reads a Gaussian <i>input</i> file ( <code>.gjf/.com/.in</code> ): link0 commands, route, title, charge/multiplicity, and starting geometry — output <code>Struct</code> is compatible with <code>g16_draw_molecule/g16_get_bond_length</code> |
| <code>g16_structure</code>        | Molecular geometry (symbols, xyz as <code>np.ndarray</code> , atom count)                                                                                                                                                                      |
| <code>g16_energy</code>           | SCF energy and thermochemistry                                                                                                                                                                                                                 |
| <code>g16_convergence</code>      | Geometry-optimisation convergence criteria per step ( <code>plot=True</code> for a matplotlib figure)                                                                                                                                          |
| <code>g16_charges</code>          | Mulliken/APT atomic charges, optional dipole overlay and 3D plot                                                                                                                                                                               |
| <code>g16_dipole_polar</code>     | Dipole moment and (static/dynamic) polarisability                                                                                                                                                                                              |
| <code>g16_nmodes</code>           | Vibrational normal-mode displacement vectors                                                                                                                                                                                                   |
| <code>g16_spectra</code>          | IR/Raman spectra (stick + Lorentzian-broadened continuum)                                                                                                                                                                                      |
| <code>g16_orbital_energies</code> | HOMO/LUMO and the full occupied/virtual MO spectrum                                                                                                                                                                                            |
| <code>g16_charge_mult</code>      | Molecular charge and spin multiplicity                                                                                                                                                                                                         |
| <code>g16_route</code>            | Route section string                                                                                                                                                                                                                           |
| <code>g16_get_bond_length</code>  | Bond-length table (pandas DataFrame) from covalent radii                                                                                                                                                                                       |
| <code>g16_gaussian_version</code> | Detects the Gaussian version/revision (works on <code>.fchk</code> via a sibling <code>.log/.out</code> )                                                                                                                                      |
| <code>g16_hyperpolar</code>       | Dipole hyperpolarisability ( $\beta$ )                                                                                                                                                                                                         |
| <code>g16_tddft</code>            | TD-DFT excited states                                                                                                                                                                                                                          |
| <code>g16_read_all</code>         | Runs the full extraction set in one call, reading the file only once                                                                                                                                                                           |
| <code>g16_restart</code>          | Generates a <code>.gjf</code> restart input file from an existing output file                                                                                                                                                                  |
| <code>g16_batch_read_all</code>   | Runs <code>g16_read_all</code> (+ <code>g16_orbital_energies</code> ) over every <code>.log/.out</code> file in a folder and aggregates the key results into one summary DataFrame; per-file failures are recorded, not fatal                  |
| <code>g16_draw_molecule</code>    | 3D CPK ball-and-stick render (matplotlib <code>mplot3d</code> )                                                                                                                                                                                |
| <code>g16_draw_mode</code>        | 3D structure with a vibrational mode's displacement arrows                                                                                                                                                                                     |
| <code>g16_draw_orbital</code>     | Orbital energy-level diagram with HOMO–LUMO gap arrow                                                                                                                                                                                          |
| <code>g16_animate_mode</code>     | Exports an MP4 animation of a vibrational mode (requires <code>ffmpeg</code> on PATH)                                                                                                                                                          |
| <code>g16_mode_viewer</code>      | Interactive Tkinter window to browse/render vibrational modes, sortable by mode number, IR, or Raman intensity, with an "Animate mode (MP4)..." button                                                                                         |
| <code>g16_list</code>             | Lists every function in the toolbox with its one-line description (pandas DataFrame)                                                                                                                                                           |
| <code>g16_write_report</code>     | Writes a human-readable <code>.txt</code> summary report from a <code>g16_read_all</code> <code>Struct</code>                                                                                                                                  |

### 11.3 Selected signatures

```

g16_read_input(filename)
g16_structure(filename, orientation="auto", step="last", lines=None)
g16_energy(filename, step="last", lines=None)
g16_convergence(filename, plot=False, lines=None)
g16_nmodes(filename, section="last", modes=None, lines=None)

```

```

g16_spectra(filename, FWHM=10, xmin=0, xmax=4000, dx=1, normalize=
    False,
            plot=False, section="last", lines=None)
g16_charges(filename, type="Mulliken", mode="atom", plot=True,
            atom_scale=0.35, bond_tol=1.30, font_size=8, color_scale="
            RdBu",
            threshold=0.0, show_dipole=False, dipole_origin="negcharge
            ",
            dipole_scale=1.0, dipole_color=(0, 0.6, 0),
            dipole_line_width=2.5,
            show_dipole_label=True, dipole_font_size=11, dipole_units
            ="Debye",
            lines=None)
g16_draw_molecule(mol, atom_scale=0.35, bond_tol=1.30, show_labels=
    True,
                    show_legend=True, title="", bg_color=(0.95, 0.95,
                    0.95),
                    ax=None, show_axes=False, axes_length=None,
                    bond_list=None)
g16_animate_mode(mol, nm, mode_idx, filename=None, scale=1.5,
    flip_sign=False,
                    atom_scale=0.35, bond_tol=1.30, show_labels=False,
                    frames_per_cycle=30, n_cycles=2, fps=20, view=None)
g16_mode_viewer(filename, scale=1.5, atom_scale=0.35, bond_tol=1.30,
    show_labels=False, flip_sign=False, arrow_color=None,
    font_size=10, **extra_opts)
g16_get_bond_length(mol, tolerance=1.15, include_h=True,
    sort_by="distance", save_as="")
g16_hyperpolar(filename, units="au", lines=None)
g16_tddft(filename, nstates=math.inf, plot=False, fwhm_ev=0.30, lines=
    None)
g16_restart(filename, step="last", output="", extra_route="", nproc=0,
    mem="")
g16_batch_read_all(folder, recursive=False, write_reports=False,
    save_as="")
g16_write_report(T, outfile=None)

```

## 11.4 Notes on the port

**Test suite.** A pytest suite lives in `G16parser/tests/` (pip install `-e ".[test]"` then `pytest` from the `G16parser/` folder). Most tests need one real Gaussian 16 `.out/.log` file dropped into `tests/fixtures/` (any filename); without one, those tests are skipped rather than failed, so the suite stays runnable out of the box. `tests/fixtures/water.gjf` is a small hand-written synthetic input file (not from a real calculation) used for the `g16_read_input` tests, which do not depend on the optional real-output fixture.

**Continuous integration.** The test suite runs automatically on every push/pull request to main via GitHub Actions (`.github/workflows/python-tests.yml`), against Python 3.9 and 3.12 on Ubuntu. Coverage is Python-only: running the MATLAB `G09_*.m/G16_*.m` functions in CI would additionally require a valid MATLAB licence (MathWorks' `matlab-actions/setup-matlab` GitHub Action needs one even for public repositories), so the MATLAB side of the toolbox continues to be verified manually.

**3D interactivity.** matplotlib’s `mplot3d` has no MATLAB-style `rotate3d` widget; use the interactive backend’s normal mouse/toolbar controls instead.

**Naming exception: `g16_read_input`.** On the MATLAB side this function has no version prefix at all (`G_read_input`, identical copies in both the `G09/` and `G16/` folders) because the Gaussian input file format does not differ between versions. Since only a `G16parser` Python package exists (there is no separate `G09parser`), the port simply follows this package’s `g16_` naming convention like every other function here.

**`g16_restart` and `g16_batch_read_all`** port `G16_restart.m` and `G16_batch_read_all.m` only — there is no Python equivalent of `G09_restart.m/G09_batch_read_all.m`, consistent with every other `G09`-only MATLAB function (e.g. `G09_fchk_read`), since this package only targets Gaussian 16 output.

**Backend selection.** The package forces the `TkAgg` matplotlib backend (if `Tk` is available and `pyplot` has not been imported yet) instead of the native macOS backend: on some older matplotlib releases, interactively rotating a 3D plot with the native Cocoa backend can segfault the whole Python process. Call `matplotlib.use(...)` yourself *before* importing `G16parser` if a different backend is needed.

**Bug found during porting, MATLAB-side only:** in the original `G16_tddft.m`, MATLAB’s `regexp` silently drops the optional trailing `<S**2>=` capture group (a MATLAB-specific regex-engine quirk), so `td.S2` is always `NaN` in MATLAB even when the tag is present in the file. This Python port’s `re`-based parser does not have that bug and extracts `S2` correctly. Consider this a known discrepancy between the two implementations rather than a porting error.

**`g16_mode_viewer`** is a Tkinter rewrite of `G16_modeViewer.m`’s `uifigure` GUI, with the same controls (mode selector, order-by, per-option redraw, title, save-as PDF/EPS/JPEG, and an “Animate mode (MP4)...” button wired to `g16_animate_mode`, using the current option values and the displayed mode figure’s camera orientation). One simplification: “target figure” always means the most recently drawn mode window, not whichever window the user last clicked on (MATLAB’s `groot().CurrentFigure` has no simple Tkinter equivalent). In an IPython/Spyder console with the Tk graphics backend active, the viewer detects the running event loop and returns to the prompt immediately instead of blocking; run as a plain script, it blocks until the viewer window is closed.

**Known issue:** `g16_mode_viewer` can segfault when run from *inside* Spyder’s IPython console (a crash inside ipykernel’s own periodic Tk event-loop pump, not in this toolbox’s code) — confirmed working correctly when run from a plain terminal/script instead:

```
python3 -c "import G16parser as g16; g16.g16_mode_viewer('file.out
  ')"
```

All other functions, including static plots, work fine inside Spyder.

**`g16_animate_mode`** mirrors `G09_animate_mode.m/ G16_animate_mode.m`: it oscillates the molecule along the mode’s displacement vector and saves an MP4 via

`matplotlib.animation.FuncAnimation` with `FFMpegWriter`. **Requires ffmpeg installed and on PATH** (brew install ffmpeg on macOS, `sudo apt install ffmpeg` on Ubuntu/Debian) — `matplotlib` does not bundle a video encoder itself; without it the call fails with `FileNotFoundError: ... 'ffmpeg' at the final encoding step` (frame generation itself does not need ffmpeg). Bonds are computed once from the equilibrium geometry via `g16_get_bond_length` and passed to `g16_draw_molecule` through its `bond_list` parameter, so they stay fixed across all frames instead of flickering as instantaneous distances cross `bond_tol`. By default the animation uses `matplotlib`'s default 3D view; pass `view=(ax.azim, ax.elev)` to start from an already-rotated figure's orientation instead.

`g16_write_report` takes the `Struct` returned by `g16_read_all` and writes the same section-by-section plain-text report as `G09_write_report.m/G16_write_report.m` (route, charge/multiplicity, structure, energetics, dipole/polarisability, atomic charges, normal modes, spectra summary), using Python `getattr`-based field checks so that sections are included only when present, exactly mirroring the MATLAB `isfield` logic.

**Bond order (single/double/triple).** `g16_draw_molecule` mirrors `G09_draw_molecule.m/G16_draw_molecule.m`: for C-C and C-O pairs, bond order is estimated purely from bond length (any other element pair, including C-N, is always drawn as a single bond) and rendered as 1/2/3 parallel lines. This is a geometric estimate, not Gaussian's own bond-order analysis (e.g. Wiberg/NBO indices). The `bond_list` parameter accepts an optional 3rd column with a pre-computed order, used by `g16_animate_mode` (via `g16_get_bond_length`) to keep both bond topology and bond order fixed across all animation frames. The C-C double/single threshold is set to 1.36 Å rather than the generic reference-length midpoint, so symmetric aromatic rings (C-C  $\approx$  1.39–1.40 Å, no real length alternation) render as all-single instead of all-double. C-N is deliberately excluded from length-based classification: on asymmetric pyridine-like rings a single threshold produced one ring C-N bond rendered double and its chemically-equivalent neighbour rendered single — see the MATLAB `G09_draw_molecule/G16_draw_molecule` subsection earlier in this manual for the full rationale.



## 12 Worked examples

Four self-contained scripts in G16/ (`example_1.m`, `example_2.m`, `example_3.m`, `example_4.m`) demonstrate the toolbox end to end on a single real DFT calculation: `test_2.out`, a geometry optimisation of Violacein (G. Cassone et al., *Phys. Chem. Chem. Phys.*, doi: 10.1039/d6cp01164k). Each script only needs G16/ on the MATLAB path and `test_2.out` in the current folder.

### 12.1 `example_1.m` — Structure, vibrational mode, and charges

Covers `G16_structure`/`G16_draw_molecule` (3D structure rendering), `G16_nmodes`/`G16_draw_mode` (a single vibrational mode, #91, the main C=C stretch), and `G16_charges` (Mulliken charges with a dipole moment overlay), all rendered from the same camera angle and each exported to its own PDF.

```
%% G16 Toolbox -- Example #1: structure, vibrational mode, and charges
%
%   Demonstrates three core G16_*.m functions on a real DFT
%   calculation:
%       1) G16_structure + G16_draw_molecule -- 3D structure rendering
%       2) G16_nmodes   + G16_draw_mode      -- a single vibrational
%       mode
%       3) G16_charges                -- Mulliken charges +
%       dipole
%
%   Data file: test_2.out -- DFT geometry optimisation of Violacein.
%   Reference: G. Cassone et al., Phys. Chem. Chem. Phys.,
%               doi: 10.1039/d6cp01164k
%
%   Requirements: G16/ on the MATLAB path, test_2.out in the current
%   folder. Running this script creates three PDFs in the current
%   folder: test_2_mol.pdf, test_2_mode_91.pdf, test_2_charges.pdf.

clear
close all
clc

filename = 'test_2.out';

% Camera orientation shared by all three figures below, so the
% molecule
% is viewed from the same angle in every plot.
view_az = -16.4417;
view_el = 44.0197;

%% 1) Structure -- load the optimised geometry and render it in 3D
mol = G16_structure(filename);

% Create the axes up front so it can be tweaked (view angle, export)
% after G16_draw_molecule has finished drawing into it.
ax1 = axes;
set(ax1, 'Visible', 'off');
G16_draw_molecule(mol, 'Title', 'Violacein', 'Ax', ax1);
set(ax1, 'View', [view_az, view_el]);

% ContentType 'vector' gives a crisp publication figure but is slow
% for
% a molecule this size; use 'image' instead for a quick low-effort
% preview.
```

```

exportgraphics(ax1, 'test_2_mol.pdf', 'ContentType', 'vector');

%% 2) Vibrational mode -- mode #91 is the main C=C stretch
nm = G16_nmodes(filename);

ax2 = axes;
set(ax2, 'Visible', 'off');
G16_draw_mode(mol, nm, 91);
set(ax2, 'View', [view_az, view_el]);

% Replace only the molecule-name line of the auto-generated two-line
% title; the second line (mode number, frequency, IR/Raman intensity)
% is left untouched.
t = get(gca, 'Title');
t.String(1) = {'Violacein'};
set(gca, 'Title', t);

exportgraphics(gca, 'test_2_mode_91.pdf', 'ContentType', 'vector');

%% 3) Atomic charges -- Mulliken charges with a dipole moment overlay
G16_charges(filename, 'Plot', true, 'ShowDipole', true);
set(gca, 'View', [view_az, view_el]);

t = get(gca, 'Title');
t.String = {'Violacein - Mulliken Charges (atom)'};
set(gca, 'Title', t);

exportgraphics(gca, 'test_2_charges.pdf', 'ContentType', 'vector');

fprintf('\nDone. Figures: structure, mode 91, Mulliken charges.\n');
fprintf('Saved: test_2_mol.pdf, test_2_mode_91.pdf, test_2_charges.pdf\n');

```

## 12.2 example\_2.m — Infrared and Raman spectra

Demonstrates G16\_spectra two ways: a manual plot built directly from its raw `sp.x/sp.Raman_cont` output fields, and the function's own built-in two-panel Raman+IR auto-plot (`'plot', true`), restyled afterwards with larger, bold axis labels for a print-ready figure. Both are exported to PDF.

```

%% G16 Toolbox -- Example #2: Infrared and Raman spectra
%
%   Demonstrates G16_spectra on a real DFT calculation, two ways:
%   1) Manual plot -- build a single Raman continuum plot directly
%   from the raw sp.x/sp.Raman_cont fields returned by
%   G16_spectra.
%   2) Built-in plot -- let G16_spectra draw its own two-panel
%   Raman+IR figure ('plot', true), then restyle the axes/labels
%   afterwards (larger, bold text) for a print-ready figure.
%
%   Data file: test_2.out -- DFT geometry optimisation of Violacein.
%   Reference: G. Cassone et al., Phys. Chem. Chem. Phys.,
%   doi: 10.1039/d6cp01164k
%
%   Requirements: G16/ on the MATLAB path, test_2.out in the current
%   folder. Running this script creates two PDFs in the current
%   folder: test_2_raman_manual.pdf, test_2_ir_raman.pdf.

```

```

clear; close all; clc
filename = 'test_2.out';
%% 1) Manual plot -- Raman continuum only, from the raw sp fields
sp = G16_spectra(filename);
fig1 = figure('Color', 'white');
plot(sp.x, sp.Raman_cont, 'LineWidth', 2);
xlabel('Wavenumber (cm-1)', 'FontWeight', 'bold');
ylabel('Raman activity (A4 AMU-1)', 'FontWeight', 'bold');
set(gca, 'FontSize', 12);
exportgraphics(fig1, 'test_2_raman_manual.pdf', 'ContentType', 'vector');
%% 2) Built-in two-panel plot (Raman + IR), then restyled
% 'FWHM' broadens the Lorentzian lines and 'xmin' crops the noisy
% low-frequency tail; 'plot', true triggers G16_spectra's own
% two-subplot Raman/IR figure (see G16_plot_spectra, local to
% G16_spectra.m).
G16_spectra(filename, 'FWHM', 15, 'xmin', 400, 'plot', true);
fig2 = gcf;
% G16_spectra creates the Raman axes first, then the IR axes below it;
% findobj returns them in reverse creation order, so flip to restore
% [Raman; IR].
axs = flipud(findobj(fig2, 'Type', 'axes'));
ax_raman = axs(1);
ax_ir = axs(2);
% Upsize the auto-generated labels (FontSize 10, regular weight) to a
% bolder, larger style for a print-ready figure.
set([ax_raman, ax_ir], 'FontSize', 12);
xlabel(ax_raman, 'Wavenumber (cm-1)', 'FontWeight', 'bold',
       'FontSize', 12);
ylabel(ax_raman, 'Raman activity (A4 AMU-1)', 'FontWeight', 'bold',
       'FontSize', 12);
xlabel(ax_ir, 'Wavenumber (cm-1)', 'FontWeight', 'bold',
       'FontSize', 12);
ylabel(ax_ir, 'IR intensity (KM mol-1)', 'FontWeight', 'bold',
       'FontSize', 12);
exportgraphics(fig2, 'test_2_ir_raman.pdf', 'ContentType', 'vector');
fprintf('\nDone. Figures: manual Raman plot, built-in IR+Raman plot.\n');
fprintf('Saved: test_2_raman_manual.pdf, test_2_ir_raman.pdf\n');

```

### 12.3 example\_3.m — Energetics

Demonstrates `G16_orbital_energies`, `G16_energy`, and `G16_convergence`, renders the HOMO-LUMO diagram via `G16_draw_orbital`, and combines all three structs into a one-line summary — a small-scale taste of what `G16_read_all`/`G16_write_report` do at full scale across every extraction function.

```

%% G16 Toolbox -- Example #3: Energetics
%
% Demonstrates G16_orbital_energies, G16_energy, and G16_convergence
% on a real DFT calculation, then combines their results into a
% one-line summary -- a small taste of what G16_read_all/
% G16_write_report do at full scale across every extraction function
%
% Also renders the HOMO-LUMO diagram via G16_draw_orbital.
%

```

```

% Data file: test_2.out -- DFT geometry optimisation of Violacein.
% Reference: G. Cassone et al., Phys. Chem. Chem. Phys.,
% doi: 10.1039/d6cp01164k
%
% Requirements: G16/ on the MATLAB path, test_2.out in the current
% folder. Each function already prints its own formatted summary to
% the command window (shown below as a reference for what to expect
% on this file); this script does not repeat those printouts.
Running
% it creates test_2_orbital_diagram.pdf in the current folder.

clear; close all; clc
filename = 'test_2.out';
%% 1) HOMO-LUMO gap -- detailed data in the oe structure
oe = G16_orbital_energies(filename);
% Console output for this file:
% -- G16_orbital_energies (step 3/3): test_2.out --
% HOMO = -0.190210 Ha (-5.1759 eV)
% LUMO = -0.096890 Ha (-2.6365 eV)
% Gap = 0.093320 Ha (2.5394 eV)

% Orbital energy-level diagram (title defaults to the source filename)
G16_draw_orbital(oe);
exportgraphics(gcf, 'test_2_orbital_diagram.pdf', 'ContentType', 'vector');
%% 2) Energy and thermochemistry -- detailed data in the en structure
en = G16_energy(filename);
% Console output for this file:
% -- G16_energy: test_2.out --
% Method : RB3LYP
% SCF : -1160.20276011 Ha
% ZPE : +0.29182000 Ha (766.17 kJ/mol)
% E0+ZPE : -1159.91094000 Ha
% H : -1159.88988100 Ha
% G : -1159.96045200 Ha
% S : 621.4460 J/(mol.K)
% T = 298.15 K, P = 1.00000 atm

%% 3) Geometry-optimisation convergence -- detailed data in the cv
structure
cv = G16_convergence(filename);
% Console output for this file:
% G16_convergence: test_2.out
% Steps read : 11
% Converged : YES (step 10)
% Last step : MaxF=1.00e-06 (thr 1.50e-05) RMSF=0.00e+00 (thr
1.00e-05)
% MaxD=1.24e-04 (thr 6.00e-05) RMSD=2.50e-05 (thr
4.00e-05)

%% 4) Combine all three into a one-line summary
if cv.converged
conv_label = sprintf('YES (step %d/%d)', cv.conv_step, cv.Nsteps);
else
conv_label = sprintf('NO (%d steps read)', cv.Nsteps);
end
fprintf('\nSummary for %s:\n', filename);
fprintf(' HOMO-LUMO gap : %.3f eV\n', oe.gap_eV);

```

```

if en.has_thermo
    fprintf('  Gibbs energy   : %.2f kJ/mol\n', en.G_kJ);
else
    fprintf('  Gibbs energy   : n/a (no frequency/thermochemistry job)\n');
end
fprintf('  Converged          : %s\n', conv_label);

```

## 12.4 example\_4.m — Recovering and restyling graphics handles

Shows how to reach back into a figure already drawn by `G16_draw_molecule` and restyle every part of it after the fact (title, axis labels, legend, atom spheres, bond lines, atom-label text), rather than only being able to set style options at call time.

**The key gotcha this example exists to document:** most of the graphics objects `G16_draw_molecule` creates (all bond lines, and every atom sphere after the first drawn for a given element) are created with `'HandleVisibility', 'off'`, so they do not clutter the legend or turn up in a plain `findobj` search. Reaching them requires `findall` instead of `findobj`. Title, axis labels, and the legend itself keep the default (`'on'`) visibility, so either function finds those. The script also re-enables the axes (`axis(ax, 'on')`) to reveal the X/Y/Z labels, which `G16_draw_molecule` always creates but hides by calling `axis(ax, 'off')` internally; and separates the atom-label text objects from the title/axis-label text objects (all four share `Type = 'text'`) with a `setdiff`.

```

%% Example 4
%% Recover graphics handles from G16_draw_molecule and restyle them
mol = G16_structure('test_2.out');
G16_draw_molecule(mol, 'Title', 'Violacein');

ax = gca;
fig = gcf;

%% 1) Title -- always visible (HandleVisibility default 'on')
title(ax, 'Violacein (DFT-optimised)', 'FontSize', 13, ...
      'FontWeight', 'bold', 'Interpreter', 'tex');

%% 2) Axis labels -- G16_draw_molecule calls axis(ax,'off'), so labels
%    exist but are not shown until the axis is switched back on
axis(ax, 'on');
xlabel(ax, 'X (\AA)', 'FontSize', 11, 'Interpreter', 'latex');
ylabel(ax, 'Y (\AA)', 'FontSize', 11, 'Interpreter', 'latex');
zlabel(ax, 'Z (\AA)', 'FontSize', 11, 'Interpreter', 'latex');

%% 3) Legend -- created with default HandleVisibility, findobj works
fine
hleg = findobj(fig, 'Type', 'Legend');
set(hleg, 'FontSize', 10, 'Location', 'northeast', 'Box', 'on');

%% 4) Atom spheres (Surface objects) -- use findall: most have
%    HandleVisibility 'off' (only the first atom per element is 'on')
hatoms = findall(ax, 'Type', 'Surface');
set(hatoms, 'FaceAlpha', 0.9, 'EdgeColor', 'none');

%% 5) Bond lines -- all created with HandleVisibility 'off', findall
%    required
hbonds = findall(ax, 'Type', 'Line');

```

```

set(hbonds, 'LineWidth', 2.5, 'Color', [0.35 0.35 0.35]);

%% 6) Atom-label text objects only, excluding Title/XLabel/YLabel/
    ZLabel
%    (these are also Type='text', so must be explicitly subtracted out
    )
htitle_h = get(ax, 'Title');
hxlabs   = get(ax, 'XLabel');
hyllabs  = get(ax, 'YLabel');
hzllabs  = get(ax, 'ZLabel');
halltext = findall(ax, 'Type', 'Text');
hatomlbl = setdiff(halltext, [htitle_h; hxlabs; hyllabs; hzllabs]);
set(hatomlbl, 'FontSize', 8, 'FontWeight', 'bold');

%% 7) Background / figure colour
set(ax, 'Color', [1 1 1]);
set(fig, 'Color', [1 1 1]);

exportgraphics(fig, 'test_2_mol_restyled.pdf', 'ContentType', 'vector
    ');

```

## 13 Publication and licensing

### 13.1 Declaration of Generative AI and AI-assisted technologies in the writing process

During the preparation of this work, the author(s) used Claude (Anthropic) to assist with code drafting, refactoring, and documentation of the G09/G16 toolbox and its associated user manual. After using this tool, the author(s) reviewed and edited the content as needed and take full responsibility for the content of the publication.

### 13.2 Note on the Use of AI-Assisted Development Tools

Portions of the codebase and documentation described in this manual — including the G09\_/G16\_ MATLAB function pairs, the `g16toolbox` Python package, the `G09_modeViewer.m`/ `G16_modeViewer.m` interactive GUIs, and this reference manual — were developed with the assistance of Claude (Anthropic), an AI-based coding tool, used interactively under the direct supervision of the author. All AI-generated code was tested against reference Gaussian 09/16 output files and reviewed by the author prior to inclusion. Algorithm design, scientific validation, and correctness of results remain the sole responsibility of the author.

### 13.3 Licence

This software is released under the **BSD 3-Clause License**, an OSI-approved open source license accepted by SoftwareX. See the `LICENSE.txt` file distributed with the source code for the full licence text.

### 13.4 Citation

If this toolbox contributes to published research, please acknowledge it by citing the source repository:

S. Trusso, *G09/G16 Toolbox: MATLAB and Python libraries for parsing, analysing and visualising Gaussian 09/16 output files*, [https://github.com/nello62/Gaussian09G16\\_output\\_Matlab\\_parser](https://github.com/nello62/Gaussian09G16_output_Matlab_parser) (accessed July 26, 2026).