

Problem 701: Insert into a Binary Search Tree

Problem Information

Difficulty: Medium

Acceptance Rate: 73.32%

Paid Only: No

Tags: Tree, Binary Search Tree, Binary Tree


Problem Description

You are given the `root` node of a binary search tree (BST) and a `value` to insert into the tree. Return `_the root node of the BST after the insertion_`. It is **guaranteed** that the new value does not exist in the original BST.

Notice that there may exist multiple valid ways for the insertion, as long as the tree remains a BST after insertion. You can return **any** of them.

Example 1:



Input: `root = [4,2,7,1,3]`, `val = 5` **Output:** `[4,2,7,1,3,5]` **Explanation:** Another accepted tree is: 

Example 2:

Input: `root = [40,20,60,10,30,50,70]`, `val = 25` **Output:** `[40,20,60,10,30,50,70,null,null,25]`

Example 3:

Input: `root = [4,2,7,1,3,null,null,null,null,null]`, `val = 5` **Output:** `[4,2,7,1,3,5]`

Constraints:

* The number of nodes in the tree will be in the range `[0, 104]`. * `-108 <= Node.val <= 108` * All the values `Node.val` are **unique**. * `-108 <= val <= 108` * It's **guaranteed** that `val` does not exist in the original BST.

Code Snippets

C++:

```
/**
 * Definition for a binary tree node.
 * struct TreeNode {
 *   int val;
 *   TreeNode *left;
 *   TreeNode *right;
 *   TreeNode() : val(0), left(nullptr), right(nullptr) {}
 *   TreeNode(int x) : val(x), left(nullptr), right(nullptr) {}
 *   TreeNode(int x, TreeNode *left, TreeNode *right) : val(x), left(left),
 *   right(right) {}
 * };
 */
class Solution {
public:
    TreeNode* insertIntoBST(TreeNode* root, int val) {

    }
};
```

Java:

```
/**
 * Definition for a binary tree node.
 * public class TreeNode {
 *   int val;
 *   TreeNode left;
 *   TreeNode right;
 *   TreeNode() {}
 *   TreeNode(int val) { this.val = val; }
 *   TreeNode(int val, TreeNode left, TreeNode right) {
 *     this.val = val;
 *     this.left = left;
 *     this.right = right;
 *   }
 * }
```

```

* }
* }
*/

class Solution {
public TreeNode insertIntoBST(TreeNode root, int val) {

}

}

```

Python3:

```

# Definition for a binary tree node.
# class TreeNode:
#     def __init__(self, val=0, left=None, right=None):
#         self.val = val
#         self.left = left
#         self.right = right
class Solution:
    def insertIntoBST(self, root: Optional[TreeNode], val: int) ->
Optional[TreeNode]:

```