

Problem 600: Non-negative Integers without Consecutive Ones

Problem Information

Difficulty: **Hard**

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

Given a positive integer

n

, return the number of the integers in the range

$[0, n]$

whose binary representations

do not

contain consecutive ones.

Example 1:

Input:

$n = 5$

Output:

5

Explanation:

Here are the non-negative integers ≤ 5 with their corresponding binary representations: 0 : 0
1 : 1 2 : 10 3 : 11 4 : 100 5 : 101 Among them, only integer 3 disobeys the rule (two consecutive ones) and the other 5 satisfy the rule.

Example 2:

Input:

n = 1

Output:

2

Example 3:

Input:

n = 2

Output:

3

Constraints:

$1 \leq n \leq 10$

9

Code Snippets

C++:

```
class Solution {  
public:  
    int findIntegers(int n) {
```

```
}  
};
```

Java:

```
class Solution {  
    public int findIntegers(int n) {  
  
    }  
}
```

Python3:

```
class Solution:  
    def findIntegers(self, n: int) -> int:
```

Python:

```
class Solution(object):  
    def findIntegers(self, n):  
        """  
        :type n: int  
        :rtype: int  
        """
```

JavaScript:

```
/**  
 * @param {number} n  
 * @return {number}  
 */  
var findIntegers = function(n) {  
  
    };
```

TypeScript:

```
function findIntegers(n: number): number {  
  
    };
```

C#:

```
public class Solution {  
    public int FindIntegers(int n) {  
  
    }  
}
```

C:

```
int findIntegers(int n) {  
  
}
```

Go:

```
func findIntegers(n int) int {  
  
}
```

Kotlin:

```
class Solution {  
    fun findIntegers(n: Int): Int {  
  
    }  
}
```

Swift:

```
class Solution {  
    func findIntegers(_ n: Int) -> Int {  
  
    }  
}
```

Rust:

```
impl Solution {  
    pub fn find_integers(n: i32) -> i32 {  
  
    }  
}
```

Ruby:

```
# @param {Integer} n
# @return {Integer}
def find_integers(n)

end
```

PHP:

```
class Solution {

    /**
     * @param Integer $n
     * @return Integer
     */
    function findIntegers($n) {

    }

}
```

Dart:

```
class Solution {
  int findIntegers(int n) {

  }

}
```

Scala:

```
object Solution {
  def findIntegers(n: Int): Int = {

  }

}
```

Elixir:

```
defmodule Solution do
  @spec find_integers(n :: integer) :: integer
  def find_integers(n) do

  end

end
```

Erlang:

```
-spec find_integers(N :: integer()) -> integer().  
find_integers(N) ->  
.
```

Racket:

```
(define/contract (find-integers n)  
  (-> exact-integer? exact-integer?)  
  )
```

Solutions

C++ Solution:

```
/*  
 * Problem: Non-negative Integers without Consecutive Ones  
 * Difficulty: Hard  
 * Tags: dp  
 *  
 * Approach: Dynamic programming with memoization or tabulation  
 * Time Complexity: O(n * m) where n and m are problem dimensions  
 * Space Complexity: O(n) or O(n * m) for DP table  
 */  
  
class Solution {  
public:  
    int findIntegers(int n) {  
  
    }  
};
```

Java Solution:

```
/**  
 * Problem: Non-negative Integers without Consecutive Ones  
 * Difficulty: Hard  
 * Tags: dp  
 *  
 * Approach: Dynamic programming with memoization or tabulation
```

```

* Time Complexity: O(n * m) where n and m are problem dimensions
* Space Complexity: O(n) or O(n * m) for DP table
*/

class Solution {
public int findIntegers(int n) {

}

}

```

Python3 Solution:

```

"""
Problem: Non-negative Integers without Consecutive Ones
Difficulty: Hard
Tags: dp

Approach: Dynamic programming with memoization or tabulation
Time Complexity: O(n * m) where n and m are problem dimensions
Space Complexity: O(n) or O(n * m) for DP table
"""

class Solution:
    def findIntegers(self, n: int) -> int:
        # TODO: Implement optimized solution
        pass

```

Python Solution:

```

class Solution(object):
    def findIntegers(self, n):
        """
        :type n: int
        :rtype: int
        """

```

JavaScript Solution:

```

/**
 * Problem: Non-negative Integers without Consecutive Ones
 * Difficulty: Hard

```

```

* Tags: dp
*
* Approach: Dynamic programming with memoization or tabulation
* Time Complexity:  $O(n * m)$  where  $n$  and  $m$  are problem dimensions
* Space Complexity:  $O(n)$  or  $O(n * m)$  for DP table
*/

/**
* @param {number} n
* @return {number}
*/
var findIntegers = function(n) {

};

```

TypeScript Solution:

```

/**
* Problem: Non-negative Integers without Consecutive Ones
* Difficulty: Hard
* Tags: dp
*
* Approach: Dynamic programming with memoization or tabulation
* Time Complexity:  $O(n * m)$  where  $n$  and  $m$  are problem dimensions
* Space Complexity:  $O(n)$  or  $O(n * m)$  for DP table
*/

function findIntegers(n: number): number {

};

```

C# Solution:

```

/*
* Problem: Non-negative Integers without Consecutive Ones
* Difficulty: Hard
* Tags: dp
*
* Approach: Dynamic programming with memoization or tabulation
* Time Complexity:  $O(n * m)$  where  $n$  and  $m$  are problem dimensions
* Space Complexity:  $O(n)$  or  $O(n * m)$  for DP table

```

```

*/

public class Solution {
    public int FindIntegers(int n) {

    }
}

```

C Solution:

```

/*
 * Problem: Non-negative Integers without Consecutive Ones
 * Difficulty: Hard
 * Tags: dp
 *
 * Approach: Dynamic programming with memoization or tabulation
 * Time Complexity: O(n * m) where n and m are problem dimensions
 * Space Complexity: O(n) or O(n * m) for DP table
 */

int findIntegers(int n) {

}

```

Go Solution:

```

// Problem: Non-negative Integers without Consecutive Ones
// Difficulty: Hard
// Tags: dp
//
// Approach: Dynamic programming with memoization or tabulation
// Time Complexity: O(n * m) where n and m are problem dimensions
// Space Complexity: O(n) or O(n * m) for DP table

func findIntegers(n int) int {

}

```

Kotlin Solution:

```

class Solution {
    fun findIntegers(n: Int): Int {

    }
}

```

Swift Solution:

```

class Solution {
    func findIntegers(_ n: Int) -> Int {

    }
}

```

Rust Solution:

```

// Problem: Non-negative Integers without Consecutive Ones
// Difficulty: Hard
// Tags: dp
//
// Approach: Dynamic programming with memoization or tabulation
// Time Complexity: O(n * m) where n and m are problem dimensions
// Space Complexity: O(n) or O(n * m) for DP table

impl Solution {
    pub fn find_integers(n: i32) -> i32 {

    }
}

```

Ruby Solution:

```

# @param {Integer} n
# @return {Integer}
def find_integers(n)

end

```

PHP Solution:

```

class Solution {

```

```

/**
 * @param Integer $n
 * @return Integer
 */
function findIntegers($n) {

}

}

```

Dart Solution:

```

class Solution {
  int findIntegers(int n) {

  }

}

```

Scala Solution:

```

object Solution {
  def findIntegers(n: Int): Int = {

  }

}

```

Elixir Solution:

```

defmodule Solution do
  @spec find_integers(n :: integer) :: integer
  def find_integers(n) do

  end

end

```

Erlang Solution:

```

-spec find_integers(N :: integer()) -> integer().
find_integers(N) ->

.

```

Racket Solution:

```
(define/contract (find-integers n)
  (-> exact-integer? exact-integer?)
)
```