

# Problem 339: Nested List Weight Sum

## Problem Information

**Difficulty:** Medium

**Acceptance Rate:** 85.82%

**Paid Only:** Yes

**Tags:** Depth-First Search, Breadth-First Search

## Problem Description

You are given a nested list of integers `nestedList`. Each element is either an integer or a list whose elements may also be integers or other lists.

The **depth** of an integer is the number of lists that it is inside of. For example, the nested list `[1,[2,2],[[3],2],1]` has each integer's value set to its **depth**.


Return `_` the sum of each integer in `nestedList` multiplied by its **depth**.

**Example 1:**



**Input:** `nestedList = [[1,1],2,[1,1]]` **Output:** 10 **Explanation:** Four 1's at depth 2, one 2 at depth 1.  $1*2 + 1*2 + 2*1 + 1*2 + 1*2 = 10$ .

**Example 2:**



**Input:** `nestedList = [1,[4,[6]]]` **Output:** 27 **Explanation:** One 1 at depth 1, one 4 at depth 2, and one 6 at depth 3.  $1*1 + 4*2 + 6*3 = 27$ .

**Example 3:**

**Input:** `nestedList = [0]` **Output:** 0

**\*\*Constraints:\*\***

\* `1 <= nestedList.length <= 50` \* The values of the integers in the nested list is in the range  
`[-100, 100]`. \* The maximum **\*\*depth\*\*** of any integer is less than or equal to `50`.

## Code Snippets

**C++:**

```
/**
 * // This is the interface that allows for creating nested lists.
 * // You should not implement it, or speculate about its implementation
 * class NestedInteger {
 * public:
 * // Constructor initializes an empty nested list.
 * NestedInteger();
 *
 * // Constructor initializes a single integer.
 * NestedInteger(int value);
 *
 * // Return true if this NestedInteger holds a single integer, rather than a
 * nested list.
 * bool isInteger() const;
 *
 * // Return the single integer that this NestedInteger holds, if it holds a
 * single integer
 * // The result is undefined if this NestedInteger holds a nested list
 * int getInteger() const;
 *
 * // Set this NestedInteger to hold a single integer.
 * void setInteger(int value);
 *
 * // Set this NestedInteger to hold a nested list and adds a nested integer
 * to it.
 * void add(const NestedInteger &ni);
 *
 * // Return the nested list that this NestedInteger holds, if it holds a
 * nested list
 * // The result is undefined if this NestedInteger holds a single integer
 * const vector<NestedInteger> &getList() const;
```

```

* };
*/
class Solution {
public:
int depthSum(vector<NestedInteger>& nestedList) {

}
};

```

## Java:

```

/**
 * // This is the interface that allows for creating nested lists.
 * // You should not implement it, or speculate about its implementation
 * public interface NestedInteger {
 * // Constructor initializes an empty nested list.
 * public NestedInteger();
 *
 * // Constructor initializes a single integer.
 * public NestedInteger(int value);
 *
 * // @return true if this NestedInteger holds a single integer, rather than a
 * nested list.
 * public boolean isInteger();
 *
 * // @return the single integer that this NestedInteger holds, if it holds a
 * single integer
 * // The result is undefined if this NestedInteger holds a nested list
 * public Integer getInteger();
 *
 * // Set this NestedInteger to hold a single integer.
 * public void setInteger(int value);
 *
 * // Set this NestedInteger to hold a nested list and adds a nested integer
 * to it.
 * public void add(NestedInteger ni);
 *
 * // @return the nested list that this NestedInteger holds, if it holds a
 * nested list
 * // The result is undefined if this NestedInteger holds a single integer
 * public List<NestedInteger> getList();
 * }

```

```

*/
class Solution {
public int depthSum(List<NestedInteger> nestedList) {

}
}

```

### Python3:

```

# """
# This is the interface that allows for creating nested lists.
# You should not implement it, or speculate about its implementation
# """
#class NestedInteger:
# def __init__(self, value=None):
# """
# If value is not specified, initializes an empty list.
# Otherwise initializes a single integer equal to value.
# """
#
#
# def isInteger(self):
# """
# @return True if this NestedInteger holds a single integer, rather than a
# nested list.
# :rtype bool
# """
#
#
# def add(self, elem):
# """
# Set this NestedInteger to hold a nested list and adds a nested integer elem
# to it.
# :rtype void
# """
#
#
# def setInteger(self, value):
# """
# Set this NestedInteger to hold a single integer equal to value.
# :rtype void
# """
#
#
# def getInteger(self):
# """

```

```
# @return the single integer that this NestedInteger holds, if it holds a
single integer
# The result is undefined if this NestedInteger holds a nested list
# :rtype int
# """
#
# def getList(self):
# """
# @return the nested list that this NestedInteger holds, if it holds a nested
list
# The result is undefined if this NestedInteger holds a single integer
# :rtype List[NestedInteger]
# """

class Solution:
def depthSum(self, nestedList: List[NestedInteger]) -> int:
```