

Problem 1798: Maximum Number of Consecutive Values You Can Make

Problem Information

Difficulty: **Medium**

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

You are given an integer array

coins

of length

n

which represents the

n

coins that you own. The value of the

i

th

coin is

coins[i]

. You can

make

some value

x

if you can choose some of your

n

coins such that their values sum up to

x

.

Return the

maximum number of consecutive integer values that you

can

make

with your coins

starting

from and

including

0

.

Note that you may have multiple coins of the same value.

Example 1:

Input:

coins = [1,3]

Output:

2

Explanation:

You can make the following values: - 0: take [] - 1: take [1] You can make 2 consecutive integer values starting from 0.

Example 2:

Input:

coins = [1,1,1,4]

Output:

8

Explanation:

You can make the following values: - 0: take [] - 1: take [1] - 2: take [1,1] - 3: take [1,1,1] - 4: take [4] - 5: take [4,1] - 6: take [4,1,1] - 7: take [4,1,1,1] You can make 8 consecutive integer values starting from 0.

Example 3:

Input:

coins = [1,4,10,3,1]

Output:

20

Constraints:

coins.length == n

1 <= n <= 4 * 10

4

1 <= coins[i] <= 4 * 10

4

Code Snippets

C++:

```
class Solution {
public:
    int getMaximumConsecutive(vector<int>& coins) {

    }
};
```

Java:

```
class Solution {
    public int getMaximumConsecutive(int[] coins) {

    }
}
```

Python3:

```
class Solution:
    def getMaximumConsecutive(self, coins: List[int]) -> int:
```

Python:

```
class Solution(object):
    def getMaximumConsecutive(self, coins):
```

```
"""
:type coins: List[int]
:rtype: int
"""
```

JavaScript:

```
/**
 * @param {number[]} coins
 * @return {number}
 */
var getMaximumConsecutive = function(coins) {

};
```

TypeScript:

```
function getMaximumConsecutive(coins: number[]): number {

};
```

C#:

```
public class Solution {
    public int GetMaximumConsecutive(int[] coins) {

    }
}
```

C:

```
int getMaximumConsecutive(int* coins, int coinsSize) {

}
```

Go:

```
func getMaximumConsecutive(coins []int) int {

}
```

Kotlin:

```

class Solution {
    fun getMaximumConsecutive(coins: IntArray): Int {

    }
}

```

Swift:

```

class Solution {
    func getMaximumConsecutive(_ coins: [Int]) -> Int {

    }
}

```

Rust:

```

impl Solution {
    pub fn get_maximum_consecutive(coins: Vec<i32>) -> i32 {

    }
}

```

Ruby:

```

# @param {Integer[]} coins
# @return {Integer}
def get_maximum_consecutive(coins)

end

```

PHP:

```

class Solution {

    /**
     * @param Integer[] $coins
     * @return Integer
     */
    function getMaximumConsecutive($coins) {

    }

}

```

Dart:

```
class Solution {  
  int getMaximumConsecutive(List<int> coins) {  
  
  }  
}
```

Scala:

```
object Solution {  
  def getMaximumConsecutive(coins: Array[Int]): Int = {  
  
  }  
}
```

Elixir:

```
defmodule Solution do  
  @spec get_maximum_consecutive(coins :: [integer]) :: integer  
  def get_maximum_consecutive(coins) do  
  
  end  
end
```

Erlang:

```
-spec get_maximum_consecutive(Coins :: [integer()]) -> integer().  
get_maximum_consecutive(Coins) ->  
.
```

Racket:

```
(define/contract (get-maximum-consecutive coins)  
  (-> (listof exact-integer?) exact-integer?)  
  )
```

Solutions

C++ Solution:

```

/*
 * Problem: Maximum Number of Consecutive Values You Can Make
 * Difficulty: Medium
 * Tags: array, greedy, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
public:
    int getMaximumConsecutive(vector<int>& coins) {

    }
};

```

Java Solution:

```

/**
 * Problem: Maximum Number of Consecutive Values You Can Make
 * Difficulty: Medium
 * Tags: array, greedy, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
    public int getMaximumConsecutive(int[] coins) {

    }
}

```

Python3 Solution:

```

"""
Problem: Maximum Number of Consecutive Values You Can Make
Difficulty: Medium
Tags: array, greedy, sort

```



```

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(1) to O(n) depending on approach
"""

class Solution:
    def getMaximumConsecutive(self, coins: List[int]) -> int:
        # TODO: Implement optimized solution
        pass

```

Python Solution:

```

class Solution(object):
    def getMaximumConsecutive(self, coins):
        """
        :type coins: List[int]
        :rtype: int
        """

```

JavaScript Solution:

```

/**
 * Problem: Maximum Number of Consecutive Values You Can Make
 * Difficulty: Medium
 * Tags: array, greedy, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
 * @param {number[]} coins
 * @return {number}
 */
var getMaximumConsecutive = function(coins) {

};

```

TypeScript Solution:

```

/**
 * Problem: Maximum Number of Consecutive Values You Can Make
 * Difficulty: Medium
 * Tags: array, greedy, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

function getMaximumConsecutive(coins: number[]): number {

};

```

C# Solution:

```

/*
 * Problem: Maximum Number of Consecutive Values You Can Make
 * Difficulty: Medium
 * Tags: array, greedy, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

public class Solution {
    public int GetMaximumConsecutive(int[] coins) {

    }
}

```

C Solution:

```

/*
 * Problem: Maximum Number of Consecutive Values You Can Make
 * Difficulty: Medium
 * Tags: array, greedy, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach

```

```

*/

int getMaximumConsecutive(int* coins, int coinsSize) {

}

```

Go Solution:

```

// Problem: Maximum Number of Consecutive Values You Can Make
// Difficulty: Medium
// Tags: array, greedy, sort
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

func getMaximumConsecutive(coins []int) int {

}

```

Kotlin Solution:

```

class Solution {
    fun getMaximumConsecutive(coins: IntArray): Int {

    }
}

```

Swift Solution:

```

class Solution {
    func getMaximumConsecutive(_ coins: [Int]) -> Int {

    }
}

```

Rust Solution:

```

// Problem: Maximum Number of Consecutive Values You Can Make
// Difficulty: Medium
// Tags: array, greedy, sort

```

```
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

impl Solution {
    pub fn get_maximum_consecutive(coins: Vec<i32>) -> i32 {

    }
}
```

Ruby Solution:

```
# @param {Integer[]} coins
# @return {Integer}
def get_maximum_consecutive(coins)

end
```

PHP Solution:

```
class Solution {

    /**
     * @param Integer[] $coins
     * @return Integer
     */
    function getMaximumConsecutive($coins) {

    }
}
```

Dart Solution:

```
class Solution {
    int getMaximumConsecutive(List<int> coins) {

    }
}
```

Scala Solution:

```
object Solution {  
  def getMaximumConsecutive(coins: Array[Int]): Int = {  
  
  }  
}
```

Elixir Solution:

```
defmodule Solution do  
  @spec get_maximum_consecutive(coins :: [integer]) :: integer  
  def get_maximum_consecutive(coins) do  
  
  end  
end
```

Erlang Solution:

```
-spec get_maximum_consecutive(Coins :: [integer()]) -> integer().  
get_maximum_consecutive(Coins) ->  
.
```

Racket Solution:

```
(define/contract (get-maximum-consecutive coins)  
  (-> (listof exact-integer?) exact-integer?)  
)
```