

Problem 3106: Lexicographically Smallest String After Operations With Constraint

Problem Information

Difficulty: **Medium**

Acceptance Rate: 62.79%

Paid Only: No

Tags: String, Greedy

Problem Description

You are given a string `s` and an integer `k`.

Define a function `distance(s1, s2)` between two strings `s1` and `s2` of the same length `n` as:

* The **sum** of the **minimum distance** between `s1[i]` and `s2[i]` when the characters from `'a'` to `'z'` are placed in a **cyclic** order, for all `i` in the range `[0, n - 1]`.

For example, `distance("ab", "cd") == 4`, and `distance("a", "z") == 1`.

You can **change** any letter of `s` to **any** other lowercase English letter, **any** number of times.

Return a string denoting the **lexicographically smallest** string `t` you can get after some changes, such that `distance(s, t) <= k`.

Example 1:

Input: `s = "zbbz", k = 3`

Output: `"aaaz"`

Explanation:

Change `s` to `"aaaz"`. The distance between `"zbbz"` and `"aaaz"` is equal to `k = 3`.

Example 2:

Input: `s = "xaxcd", k = 4`

Output: `"aawcd"`

Explanation:

The distance between "xaxcd" and "aawcd" is equal to $k = 4$.

Example 3:

Input: `s = "lol", k = 0`

Output: `"lol"`

Explanation:

It's impossible to change any character as $k = 0$.

Constraints:

$1 \leq s.length \leq 100$ $0 \leq k \leq 2000$ `s` consists only of lowercase English letters.

Code Snippets

C++:

```
class Solution {
public:
    string getSmallestString(string s, int k) {

    }
};
```

Java:

```
class Solution {  
    public String getSmallestString(String s, int k) {  
  
    }  
}
```

Python3:

```
class Solution:  
    def getSmallestString(self, s: str, k: int) -> str:
```