

Problem 1120: Maximum Average Subtree

Problem Information

Difficulty: **Medium**

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

Given the

root

of a binary tree, return

the maximum

average

value of a

subtree

of that tree

. Answers within

10

-5

of the actual answer will be accepted.

A

subtree


of a tree is any node of that tree plus all its descendants.

The

average

value of a tree is the sum of its values, divided by the number of nodes.

Example 1:



Input:

root = [5,6,1]

Output:

6.00000

Explanation:

For the node with value = 5 we have an average of $(5 + 6 + 1) / 3 = 4$. For the node with value = 6 we have an average of $6 / 1 = 6$. For the node with value = 1 we have an average of $1 / 1 = 1$. So the answer is 6 which is the maximum.

Example 2:

Input:

root = [0,null,1]

Output:

1.00000

Constraints:

The number of nodes in the tree is in the range

[1, 10

4

]

.

$0 \leq \text{Node.val} \leq 10$

5

Code Snippets

C++:

```
/**
 * Definition for a binary tree node.
 * struct TreeNode {
 *     int val;
 *     TreeNode *left;
 *     TreeNode *right;
 *     TreeNode() : val(0), left(nullptr), right(nullptr) {}
 *     TreeNode(int x) : val(x), left(nullptr), right(nullptr) {}
 *     TreeNode(int x, TreeNode *left, TreeNode *right) : val(x), left(left),
right(right) {}
 * };
 */
class Solution {
public:
    double maximumAverageSubtree(TreeNode* root) {
```

```
}  
};
```

Java:

```
/**  
 * Definition for a binary tree node.  
 * public class TreeNode {  
 *     int val;  
 *     TreeNode left;  
 *     TreeNode right;  
 *     TreeNode() {}  
 *     TreeNode(int val) { this.val = val; }  
 *     TreeNode(int val, TreeNode left, TreeNode right) {  
 *         this.val = val;  
 *         this.left = left;  
 *         this.right = right;  
 *     }  
 * }  
 */  
  
class Solution {  
    public double maximumAverageSubtree(TreeNode root) {  
  
    }  
}
```

Python3:

```
# Definition for a binary tree node.  
# class TreeNode:  
#     def __init__(self, val=0, left=None, right=None):  
#         self.val = val  
#         self.left = left  
#         self.right = right  
class Solution:  
    def maximumAverageSubtree(self, root: Optional[TreeNode]) -> float:
```

Python:

```
# Definition for a binary tree node.  
# class TreeNode(object):
```

```

# def __init__(self, val=0, left=None, right=None):
#     self.val = val
#     self.left = left
#     self.right = right
class Solution(object):
    def maximumAverageSubtree(self, root):
        """
        :type root: Optional[TreeNode]
        :rtype: float
        """

```

JavaScript:

```

/**
 * Definition for a binary tree node.
 * function TreeNode(val, left, right) {
 *   this.val = (val===undefined ? 0 : val)
 *   this.left = (left===undefined ? null : left)
 *   this.right = (right===undefined ? null : right)
 * }
 */
/**
 * @param {TreeNode} root
 * @return {number}
 */
var maximumAverageSubtree = function(root) {

};

```

TypeScript:

```

/**
 * Definition for a binary tree node.
 * class TreeNode {
 *   val: number
 *   left: TreeNode | null
 *   right: TreeNode | null
 *   constructor(val?: number, left?: TreeNode | null, right?: TreeNode | null)
 *   {
 *     this.val = (val===undefined ? 0 : val)
 *     this.left = (left===undefined ? null : left)
 *     this.right = (right===undefined ? null : right)
 *   }
 * }

```

```

* }
* }
*/

function maximumAverageSubtree(root: TreeNode | null): number {

};

```

C#:

```

/**
 * Definition for a binary tree node.
 * public class TreeNode {
 *     public int val;
 *     public TreeNode left;
 *     public TreeNode right;
 *     public TreeNode(int val=0, TreeNode left=null, TreeNode right=null) {
 *         this.val = val;
 *         this.left = left;
 *         this.right = right;
 *     }
 * }
 */
public class Solution {
    public double MaximumAverageSubtree(TreeNode root) {

    }
}

```

C:

```

/**
 * Definition for a binary tree node.
 * struct TreeNode {
 *     int val;
 *     struct TreeNode *left;
 *     struct TreeNode *right;
 * };
 */
double maximumAverageSubtree(struct TreeNode* root) {

}

```

Go:

```
/**
 * Definition for a binary tree node.
 * type TreeNode struct {
 *     Val int
 *     Left *TreeNode
 *     Right *TreeNode
 * }
 */
func maximumAverageSubtree(root *TreeNode) float64 {

}
```

Kotlin:

```
/**
 * Example:
 * var ti = TreeNode(5)
 * var v = ti.`val`
 * Definition for a binary tree node.
 * class TreeNode(var `val`: Int) {
 *     var left: TreeNode? = null
 *     var right: TreeNode? = null
 * }
 */
class Solution {
    fun maximumAverageSubtree(root: TreeNode?): Double {

    }
}
```

Swift:

```
/**
 * Definition for a binary tree node.
 * public class TreeNode {
 *     public var val: Int
 *     public var left: TreeNode?
 *     public var right: TreeNode?
 *     public init() { self.val = 0; self.left = nil; self.right = nil; }
 *     public init(_ val: Int) { self.val = val; self.left = nil; self.right = nil; }
 * }
 */
```

```

* public init(_ val: Int, _ left: TreeNode?, _ right: TreeNode?) {
* self.val = val
* self.left = left
* self.right = right
* }
* }
*/
class Solution {
func maximumAverageSubtree(_ root: TreeNode?) -> Double {

}
}

```

Rust:

```

// Definition for a binary tree node.
// #[derive(Debug, PartialEq, Eq)]
// pub struct TreeNode {
//     pub val: i32,
//     pub left: Option<Rc<RefCell<TreeNode>>>,
//     pub right: Option<Rc<RefCell<TreeNode>>>,
// }
//
// impl TreeNode {
//     #[inline]
//     pub fn new(val: i32) -> Self {
//         TreeNode {
//             val,
//             left: None,
//             right: None
//         }
//     }
// }
use std::rc::Rc;
use std::cell::RefCell;
impl Solution {
    pub fn maximum_average_subtree(root: Option<Rc<RefCell<TreeNode>>>) -> f64 {

    }
}

```

Ruby:

```
# Definition for a binary tree node.
# class TreeNode
# attr_accessor :val, :left, :right
# def initialize(val = 0, left = nil, right = nil)
# @val = val
# @left = left
# @right = right
# end
# end
# @param {TreeNode} root
# @return {Float}
def maximum_average_subtree(root)

end
```

PHP:

```
/**
 * Definition for a binary tree node.
 * class TreeNode {
 * public $val = null;
 * public $left = null;
 * public $right = null;
 * function __construct($val = 0, $left = null, $right = null) {
 * $this->val = $val;
 * $this->left = $left;
 * $this->right = $right;
 * }
 * }
 */
class Solution {

/**
 * @param TreeNode $root
 * @return Float
 */
function maximumAverageSubtree($root) {

}

}
```

Dart:

```
/**
 * Definition for a binary tree node.
 * class TreeNode {
 *   int val;
 *   TreeNode? left;
 *   TreeNode? right;
 *   TreeNode([this.val = 0, this.left, this.right]);
 * }
 */
class Solution {
  double maximumAverageSubtree(TreeNode? root) {

  }
}
```

Scala:

```
/**
 * Definition for a binary tree node.
 * class TreeNode(_value: Int = 0, _left: TreeNode = null, _right: TreeNode =
 * null) {
 *   var value: Int = _value
 *   var left: TreeNode = _left
 *   var right: TreeNode = _right
 * }
 */
object Solution {
  def maximumAverageSubtree(root: TreeNode): Double = {

  }
}
```

Elixir:

```
# Definition for a binary tree node.
#
# defmodule TreeNode do
#   @type t :: %__MODULE__{
#     val: integer,
#     left: TreeNode.t() | nil,
#     right: TreeNode.t() | nil
```

```

# }
# defstruct val: 0, left: nil, right: nil
# end

defmodule Solution do
  @spec maximum_average_subtree(root :: TreeNode.t | nil) :: float
  def maximum_average_subtree(root) do

  end
end

```

Erlang:

```

%% Definition for a binary tree node.
%%
%% -record(tree_node, {val = 0 :: integer(),
%% left = null :: 'null' | #tree_node{},
%% right = null :: 'null' | #tree_node{}}).

-spec maximum_average_subtree(Root :: #tree_node{} | null) -> float().
maximum_average_subtree(Root) ->
.

```

Racket:

```

; Definition for a binary tree node.
#|

; val : integer?
; left : (or/c tree-node? #f)
; right : (or/c tree-node? #f)
(struct tree-node
  (val left right) #:mutable #:transparent)

; constructor
(define (make-tree-node [val 0])
  (tree-node val #f #f))

|#

(define/contract (maximum-average-subtree root)
  (-> (or/c tree-node? #f) flonum?)

```

```
)
```

Solutions

C++ Solution:

```
/*
 * Problem: Maximum Average Subtree
 * Difficulty: Medium
 * Tags: tree, search
 *
 * Approach: DFS or BFS traversal
 * Time Complexity: O(n) where n is number of nodes
 * Space Complexity: O(h) for recursion stack where h is height
 */

/**
 * Definition for a binary tree node.
 * struct TreeNode {
 *     int val;
 *     TreeNode *left;
 *     TreeNode *right;
 *     TreeNode() : val(0), left(nullptr), right(nullptr) {
 * // TODO: Implement optimized solution
 *     return 0;
 * }
 *     TreeNode(int x) : val(x), left(nullptr), right(nullptr) {
 * // TODO: Implement optimized solution
 *     return 0;
 * }
 *     TreeNode(int x, TreeNode *left, TreeNode *right) : val(x), left(left),
 *     right(right) {
 * // TODO: Implement optimized solution
 *     return 0;
 * }
 * };
 */

class Solution {
public:
    double maximumAverageSubtree(TreeNode* root) {
```

```
}  
};
```

Java Solution:

```
/**  
 * Problem: Maximum Average Subtree  
 * Difficulty: Medium  
 * Tags: tree, search  
 *  
 * Approach: DFS or BFS traversal  
 * Time Complexity:  $O(n)$  where  $n$  is number of nodes  
 * Space Complexity:  $O(h)$  for recursion stack where  $h$  is height  
 */  
  
/**  
 * Definition for a binary tree node.  
 * public class TreeNode {  
 *     int val;  
 *     TreeNode left;  
 *     TreeNode right;  
 *     TreeNode() {  
 // TODO: Implement optimized solution  
 return 0;  
 }  
 *     TreeNode(int val) { this.val = val; }  
 *     TreeNode(int val, TreeNode left, TreeNode right) {  
 *         this.val = val;  
 *         this.left = left;  
 *         this.right = right;  
 *     }  
 * }  
 */  
  
class Solution {  
    public double maximumAverageSubtree(TreeNode root) {  
  
    }  
}
```

Python3 Solution:

```

"""
Problem: Maximum Average Subtree
Difficulty: Medium
Tags: tree, search

Approach: DFS or BFS traversal
Time Complexity: O(n) where n is number of nodes
Space Complexity: O(h) for recursion stack where h is height
"""

# Definition for a binary tree node.
# class TreeNode:
# def __init__(self, val=0, left=None, right=None):
# self.val = val
# self.left = left
# self.right = right
class Solution:
def maximumAverageSubtree(self, root: Optional[TreeNode]) -> float:
# TODO: Implement optimized solution
pass

```

Python Solution:

```

# Definition for a binary tree node.
# class TreeNode(object):
# def __init__(self, val=0, left=None, right=None):
# self.val = val
# self.left = left
# self.right = right
class Solution(object):
def maximumAverageSubtree(self, root):
"""
:type root: Optional[TreeNode]
:rtype: float
"""

```

JavaScript Solution:

```

/**
 * Problem: Maximum Average Subtree
 * Difficulty: Medium
 * Tags: tree, search

```

```

*
* Approach: DFS or BFS traversal
* Time Complexity: O(n) where n is number of nodes
* Space Complexity: O(h) for recursion stack where h is height
*/

/**
* Definition for a binary tree node.
* function TreeNode(val, left, right) {
*   this.val = (val===undefined ? 0 : val)
*   this.left = (left===undefined ? null : left)
*   this.right = (right===undefined ? null : right)
* }
*/
/**
* @param {TreeNode} root
* @return {number}
*/
var maximumAverageSubtree = function(root) {

};

```

TypeScript Solution:

```

/**
* Problem: Maximum Average Subtree
* Difficulty: Medium
* Tags: tree, search
*
* Approach: DFS or BFS traversal
* Time Complexity: O(n) where n is number of nodes
* Space Complexity: O(h) for recursion stack where h is height
*/

/**
* Definition for a binary tree node.
* class TreeNode {
*   val: number
*   left: TreeNode | null
*   right: TreeNode | null
*   constructor(val?: number, left?: TreeNode | null, right?: TreeNode | null)

```

```

{
* this.val = (val===undefined ? 0 : val)
* this.left = (left===undefined ? null : left)
* this.right = (right===undefined ? null : right)
* }
* }
*/

function maximumAverageSubtree(root: TreeNode | null): number {

};

```

C# Solution:

```

/*
* Problem: Maximum Average Subtree
* Difficulty: Medium
* Tags: tree, search
*
* Approach: DFS or BFS traversal
* Time Complexity: O(n) where n is number of nodes
* Space Complexity: O(h) for recursion stack where h is height
*/

/**
* Definition for a binary tree node.
* public class TreeNode {
* public int val;
* public TreeNode left;
* public TreeNode right;
* public TreeNode(int val=0, TreeNode left=null, TreeNode right=null) {
* this.val = val;
* this.left = left;
* this.right = right;
* }
* }
*/

public class Solution {
public double MaximumAverageSubtree(TreeNode root) {

}

}

```

C Solution:

```
/*
 * Problem: Maximum Average Subtree
 * Difficulty: Medium
 * Tags: tree, search
 *
 * Approach: DFS or BFS traversal
 * Time Complexity: O(n) where n is number of nodes
 * Space Complexity: O(h) for recursion stack where h is height
 */

/**
 * Definition for a binary tree node.
 * struct TreeNode {
 *     int val;
 *     struct TreeNode *left;
 *     struct TreeNode *right;
 * };
 */
double maximumAverageSubtree(struct TreeNode* root) {

}
```

Go Solution:

```
// Problem: Maximum Average Subtree
// Difficulty: Medium
// Tags: tree, search
//
// Approach: DFS or BFS traversal
// Time Complexity: O(n) where n is number of nodes
// Space Complexity: O(h) for recursion stack where h is height

/**
 * Definition for a binary tree node.
 * type TreeNode struct {
 *     Val int
 *     Left *TreeNode
 *     Right *TreeNode
 * }
 */
```

```

func maximumAverageSubtree(root *TreeNode) float64 {

}

```

Kotlin Solution:

```

/**
 * Example:
 * var ti = TreeNode(5)
 * var v = ti.`val`
 * Definition for a binary tree node.
 * class TreeNode(var `val`: Int) {
 *     var left: TreeNode? = null
 *     var right: TreeNode? = null
 * }
 */
class Solution {
    fun maximumAverageSubtree(root: TreeNode?): Double {

    }
}

```

Swift Solution:

```

/**
 * Definition for a binary tree node.
 * public class TreeNode {
 *     public var val: Int
 *     public var left: TreeNode?
 *     public var right: TreeNode?
 *     public init() { self.val = 0; self.left = nil; self.right = nil; }
 *     public init(_ val: Int) { self.val = val; self.left = nil; self.right = nil; }
 *     public init(_ val: Int, _ left: TreeNode?, _ right: TreeNode?) {
 *         self.val = val
 *         self.left = left
 *         self.right = right
 *     }
 * }
 */
class Solution {

```

```

func maximumAverageSubtree(_ root: TreeNode?) -> Double {

}

}

```

Rust Solution:

```

// Problem: Maximum Average Subtree
// Difficulty: Medium
// Tags: tree, search
//
// Approach: DFS or BFS traversal
// Time Complexity: O(n) where n is number of nodes
// Space Complexity: O(h) for recursion stack where h is height

// Definition for a binary tree node.
// #[derive(Debug, PartialEq, Eq)]
// pub struct TreeNode {
//     pub val: i32,
//     pub left: Option<Rc<RefCell<TreeNode>>>,
//     pub right: Option<Rc<RefCell<TreeNode>>>,
// }
//
// impl TreeNode {
//     #[inline]
//     pub fn new(val: i32) -> Self {
//         TreeNode {
//             val,
//             left: None,
//             right: None
//         }
//     }
// }

use std::rc::Rc;
use std::cell::RefCell;

impl Solution {
    pub fn maximum_average_subtree(root: Option<Rc<RefCell<TreeNode>>>) -> f64 {

    }

}

```

Ruby Solution:

```
# Definition for a binary tree node.
# class TreeNode
# attr_accessor :val, :left, :right
# def initialize(val = 0, left = nil, right = nil)
# @val = val
# @left = left
# @right = right
# end
# end
# @param {TreeNode} root
# @return {Float}
def maximum_average_subtree(root)

end
```

PHP Solution:

```
/**
 * Definition for a binary tree node.
 * class TreeNode {
 * public $val = null;
 * public $left = null;
 * public $right = null;
 * function __construct($val = 0, $left = null, $right = null) {
 * $this->val = $val;
 * $this->left = $left;
 * $this->right = $right;
 * }
 * }
 */
class Solution {

    /**
     * @param TreeNode $root
     * @return Float
     */
    function maximumAverageSubtree($root) {

    }

}
```

Dart Solution:

```
/**
 * Definition for a binary tree node.
 * class TreeNode {
 *   int val;
 *   TreeNode? left;
 *   TreeNode? right;
 *   TreeNode([this.val = 0, this.left, this.right]);
 * }
 */
class Solution {
  double maximumAverageSubtree(TreeNode? root) {

  }
}
```

Scala Solution:

```
/**
 * Definition for a binary tree node.
 * class TreeNode(_value: Int = 0, _left: TreeNode = null, _right: TreeNode =
 * null) {
 *   var value: Int = _value
 *   var left: TreeNode = _left
 *   var right: TreeNode = _right
 * }
 */
object Solution {
  def maximumAverageSubtree(root: TreeNode): Double = {

  }
}
```

Elixir Solution:

```
# Definition for a binary tree node.
#
# defmodule TreeNode do
#   @type t :: %__MODULE__{
#     val: integer,
#     left: TreeNode.t() | nil,
```

```

# right: TreeNode.t() | nil
# }
# defstruct val: 0, left: nil, right: nil
# end

defmodule Solution do
  @spec maximum_average_subtree(root :: TreeNode.t | nil) :: float
  def maximum_average_subtree(root) do

  end
end

```

Erlang Solution:

```

%% Definition for a binary tree node.
%%
%% -record(tree_node, {val = 0 :: integer(),
%% left = null :: 'null' | #tree_node{},
%% right = null :: 'null' | #tree_node{}}).

-spec maximum_average_subtree(Root :: #tree_node{} | null) -> float().
maximum_average_subtree(Root) ->
.

```

Racket Solution:

```

; Definition for a binary tree node.
#|

; val : integer?
; left : (or/c tree-node? #f)
; right : (or/c tree-node? #f)
(struct tree-node
  (val left right) #:mutable #:transparent)

; constructor
(define (make-tree-node [val 0])
  (tree-node val #f #f))

|#

```

```
(define/contract (maximum-average-subtree root)
  (-> (or/c tree-node? #f) flonum?)
)
```