

# Problem 1383: Maximum Performance of a Team

## Problem Information

Difficulty: **Hard**

Acceptance Rate: 0.00%

Paid Only: No

## Problem Description

You are given two integers

$n$

and

$k$

and two integer arrays

$speed$

and

$efficiency$

both of length

$n$

. There are

$n$

engineers numbered from

1

to

n

.

speed[i]

and

efficiency[i]

represent the speed and efficiency of the

i

th

engineer respectively.

Choose

at most

k

different engineers out of the

n

engineers to form a team with the maximum

performance

.

The performance of a team is the sum of its engineers' speeds multiplied by the minimum efficiency among its engineers.

Return

the maximum performance of this team

. Since the answer can be a huge number, return it

modulo

10

9

+ 7

.

Example 1:

Input:

$n = 6$ ,  $\text{speed} = [2, 10, 3, 1, 5, 8]$ ,  $\text{efficiency} = [5, 4, 3, 9, 7, 2]$ ,  $k = 2$

Output:

60

Explanation:

We have the maximum performance of the team by selecting engineer 2 (with speed=10 and efficiency=4) and engineer 5 (with speed=5 and efficiency=7). That is, performance =  $(10 + 5) * \min(4, 7) = 60$ .

Example 2:

Input:

$n = 6$ ,  $\text{speed} = [2, 10, 3, 1, 5, 8]$ ,  $\text{efficiency} = [5, 4, 3, 9, 7, 2]$ ,  $k = 3$

Output:

68

Explanation:

This is the same example as the first but  $k = 3$ . We can select engineer 1, engineer 2 and engineer 5 to get the maximum performance of the team. That is,  $\text{performance} = (2 + 10 + 5) * \min(5, 4, 7) = 68$ .

Example 3:

Input:

$n = 6$ ,  $\text{speed} = [2, 10, 3, 1, 5, 8]$ ,  $\text{efficiency} = [5, 4, 3, 9, 7, 2]$ ,  $k = 4$

Output:

72

Constraints:

$1 \leq k \leq n \leq 10$

5

$\text{speed.length} == n$

$\text{efficiency.length} == n$

$1 \leq \text{speed}[i] \leq 10$

5

$1 \leq \text{efficiency}[i] \leq 10$

8

## Code Snippets

### C++:

```
class Solution {
public:
    int maxPerformance(int n, vector<int>& speed, vector<int>& efficiency, int k)
    {

    }
};
```

### Java:

```
class Solution {
    public int maxPerformance(int n, int[] speed, int[] efficiency, int k) {

    }
}
```

### Python3:

```
class Solution:
    def maxPerformance(self, n: int, speed: List[int], efficiency: List[int], k:
int) -> int:
```

### Python:

```
class Solution(object):
    def maxPerformance(self, n, speed, efficiency, k):
        """
        :type n: int
        :type speed: List[int]
        :type efficiency: List[int]
        :type k: int
        :rtype: int
        """
```

### JavaScript:

```

/**
 * @param {number} n
 * @param {number[]} speed
 * @param {number[]} efficiency
 * @param {number} k
 * @return {number}
 */
var maxPerformance = function(n, speed, efficiency, k) {

};

```

### TypeScript:

```

function maxPerformance(n: number, speed: number[], efficiency: number[], k:
number): number {

};

```

### C#:

```

public class Solution {
    public int MaxPerformance(int n, int[] speed, int[] efficiency, int k) {

    }
}

```

### C:

```

int maxPerformance(int n, int* speed, int speedSize, int* efficiency, int
efficiencySize, int k) {

}

```

### Go:

```

func maxPerformance(n int, speed []int, efficiency []int, k int) int {

}

```

### Kotlin:

```

class Solution {
    fun maxPerformance(n: Int, speed: IntArray, efficiency: IntArray, k: Int):

```

```
Int {  
  
}  
}
```

### Swift:

```
class Solution {  
    func maxPerformance(_ n: Int, _ speed: [Int], _ efficiency: [Int], _ k: Int)  
    -> Int {  
  
    }  
}
```

### Rust:

```
impl Solution {  
    pub fn max_performance(n: i32, speed: Vec<i32>, efficiency: Vec<i32>, k: i32)  
    -> i32 {  
  
    }  
}
```

### Ruby:

```
# @param {Integer} n  
# @param {Integer[]} speed  
# @param {Integer[]} efficiency  
# @param {Integer} k  
# @return {Integer}  
def max_performance(n, speed, efficiency, k)  
  
end
```

### PHP:

```
class Solution {  
  
    /**  
     * @param Integer $n  
     * @param Integer[] $speed  
     * @param Integer[] $efficiency  
     * @param Integer $k
```

```

* @return Integer
*/
function maxPerformance($n, $speed, $efficiency, $k) {

}
}

```

### Dart:

```

class Solution {
  int maxPerformance(int n, List<int> speed, List<int> efficiency, int k) {

  }
}

```

### Scala:

```

object Solution {
  def maxPerformance(n: Int, speed: Array[Int], efficiency: Array[Int], k:
  Int): Int = {

  }
}

```

### Elixir:

```

defmodule Solution do
  @spec max_performance(n :: integer, speed :: [integer], efficiency ::
  [integer], k :: integer) :: integer
  def max_performance(n, speed, efficiency, k) do

  end
end

```

### Erlang:

```

-spec max_performance(N :: integer(), Speed :: [integer()], Efficiency ::
[integer()], K :: integer()) -> integer().
max_performance(N, Speed, Efficiency, K) ->
.

```

### Racket:



```
(define/contract (max-performance n speed efficiency k)
  (-> exact-integer? (listof exact-integer?) (listof exact-integer?)
    exact-integer? exact-integer?)
  )
```

## Solutions

### C++ Solution:

```
/*
 * Problem: Maximum Performance of a Team
 * Difficulty: Hard
 * Tags: array, greedy, sort, queue, heap
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
public:
    int maxPerformance(int n, vector<int>& speed, vector<int>& efficiency, int k)
    {

    }

};
```

### Java Solution:

```
/**
 * Problem: Maximum Performance of a Team
 * Difficulty: Hard
 * Tags: array, greedy, sort, queue, heap
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
    public int maxPerformance(int n, int[] speed, int[] efficiency, int k) {
```

```
}  
}
```

### Python3 Solution:

```
"""  
Problem: Maximum Performance of a Team  
Difficulty: Hard  
Tags: array, greedy, sort, queue, heap  
  
Approach: Use two pointers or sliding window technique  
Time Complexity: O(n) or O(n log n)  
Space Complexity: O(1) to O(n) depending on approach  
"""  
  
class Solution:  
    def maxPerformance(self, n: int, speed: List[int], efficiency: List[int], k:  
int) -> int:  
    # TODO: Implement optimized solution  
    pass
```

### Python Solution:

```
class Solution(object):  
    def maxPerformance(self, n, speed, efficiency, k):  
        """  
        :type n: int  
        :type speed: List[int]  
        :type efficiency: List[int]  
        :type k: int  
        :rtype: int  
        """
```

### JavaScript Solution:

```
/**  
 * Problem: Maximum Performance of a Team  
 * Difficulty: Hard  
 * Tags: array, greedy, sort, queue, heap  
 */
```

```

* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(1) to O(n) depending on approach
*/

/**
 * @param {number} n
 * @param {number[]} speed
 * @param {number[]} efficiency
 * @param {number} k
 * @return {number}
 */
var maxPerformance = function(n, speed, efficiency, k) {

};

```

### TypeScript Solution:

```

/**
 * Problem: Maximum Performance of a Team
 * Difficulty: Hard
 * Tags: array, greedy, sort, queue, heap
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

function maxPerformance(n: number, speed: number[], efficiency: number[], k: number): number {

};

```

### C# Solution:

```

/*
 * Problem: Maximum Performance of a Team
 * Difficulty: Hard
 * Tags: array, greedy, sort, queue, heap
 *
 * Approach: Use two pointers or sliding window technique

```

```

* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(1) to O(n) depending on approach
*/

public class Solution {
public int MaxPerformance(int n, int[] speed, int[] efficiency, int k) {

}
}

```

### C Solution:

```

/*
* Problem: Maximum Performance of a Team
* Difficulty: Hard
* Tags: array, greedy, sort, queue, heap
*
* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(1) to O(n) depending on approach
*/

int maxPerformance(int n, int* speed, int speedSize, int* efficiency, int
efficiencySize, int k) {

}

```

### Go Solution:

```

// Problem: Maximum Performance of a Team
// Difficulty: Hard
// Tags: array, greedy, sort, queue, heap
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

func maxPerformance(n int, speed []int, efficiency []int, k int) int {

}

```

### Kotlin Solution:

```
class Solution {  
    fun maxPerformance(n: Int, speed: IntArray, efficiency: IntArray, k: Int):  
    Int {  
  
    }  
}
```

### Swift Solution:

```
class Solution {  
    func maxPerformance(_ n: Int, _ speed: [Int], _ efficiency: [Int], _ k: Int)  
    -> Int {  
  
    }  
}
```

### Rust Solution:

```
// Problem: Maximum Performance of a Team  
// Difficulty: Hard  
// Tags: array, greedy, sort, queue, heap  
//  
// Approach: Use two pointers or sliding window technique  
// Time Complexity: O(n) or O(n log n)  
// Space Complexity: O(1) to O(n) depending on approach  
  
impl Solution {  
    pub fn max_performance(n: i32, speed: Vec<i32>, efficiency: Vec<i32>, k: i32)  
    -> i32 {  
  
    }  
}
```

### Ruby Solution:

```
# @param {Integer} n  
# @param {Integer[]} speed  
# @param {Integer[]} efficiency  
# @param {Integer} k  
# @return {Integer}
```

```
def max_performance(n, speed, efficiency, k)

end
```

### PHP Solution:

```
class Solution {

    /**
     * @param Integer $n
     * @param Integer[] $speed
     * @param Integer[] $efficiency
     * @param Integer $k
     * @return Integer
     */
    function maxPerformance($n, $speed, $efficiency, $k) {

    }

}
```

### Dart Solution:

```
class Solution {
  int maxPerformance(int n, List<int> speed, List<int> efficiency, int k) {

  }

}
```

### Scala Solution:

```
object Solution {
  def maxPerformance(n: Int, speed: Array[Int], efficiency: Array[Int], k:
    Int): Int = {

  }

}
```

### Elixir Solution:

```
defmodule Solution do
  @spec max_performance(n :: integer, speed :: [integer], efficiency ::
```

```
[integer], k :: integer) :: integer
def max_performance(n, speed, efficiency, k) do

end
end
```

### Erlang Solution:

```
-spec max_performance(N :: integer(), Speed :: [integer()], Efficiency ::
[integer()], K :: integer()) -> integer().
max_performance(N, Speed, Efficiency, K) ->
.
```

### Racket Solution:

```
(define/contract (max-performance n speed efficiency k)
  (-> exact-integer? (listof exact-integer?) (listof exact-integer?)
    exact-integer? exact-integer?)
  )
```