

# Problem 3187: Peaks in Array

## Problem Information

Difficulty: **Hard**

Acceptance Rate: 0.00%

Paid Only: No

## Problem Description

A

peak

in an array

arr

is an element that is

greater

than its previous and next element in

arr

.

You are given an integer array

nums

and a 2D integer array

queries

.

You have to process queries of two types:

queries[i] = [1, l

i

, r

i

]

, determine the count of

peak

elements in the

subarray

nums[l

i

..r

i

]

.

queries[i] = [2, index

i

, val

i

]

, change

nums[index

i

]

to

val

i

.

Return an array

answer

containing the results of the queries of the first type in order.

Notes:

The

first

and the

last

element of an array or a subarray

cannot

be a peak.

Example 1:

Input:

nums = [3,1,4,2,5], queries = [[2,3,4],[1,0,4]]

Output:

[0]

Explanation:

First query: We change

nums[3]

to 4 and

nums

becomes

[3,1,4,4,5]

.

Second query: The number of peaks in the

[3,1,4,4,5]

is 0.

Example 2:

Input:

nums = [4,1,4,2,1,5], queries = [[2,2,4],[1,0,2],[1,0,4]]

Output:

[0,1]

Explanation:

First query:

nums[2]

should become 4, but it is already set to 4.

Second query: The number of peaks in the

[4,1,4]

is 0.

Third query: The second 4 is a peak in the

[4,1,4,2,1]

.

Constraints:

$3 \leq \text{nums.length} \leq 10$

5

$1 \leq \text{nums}[i] \leq 10$

5

$1 \leq \text{queries.length} \leq 10$

5

`queries[i][0] == 1`

or

`queries[i][0] == 2`

For all

i

that:

`queries[i][0] == 1`

:

`0 <= queries[i][1] <= queries[i][2] <= nums.length - 1`

`queries[i][0] == 2`

:

`0 <= queries[i][1] <= nums.length - 1`

,

`1 <= queries[i][2] <= 10`

5

## Code Snippets

**C++:**

```
class Solution {  
public:
```

```
vector<int> countOfPeaks(vector<int>& nums, vector<vector<int>>& queries) {

}

};
```

### Java:

```
class Solution {
public List<Integer> countOfPeaks(int[] nums, int[][] queries) {

}

}
```

### Python3:

```
class Solution:
def countOfPeaks(self, nums: List[int], queries: List[List[int]]) ->
List[int]:
```

### Python:

```
class Solution(object):
def countOfPeaks(self, nums, queries):
"""
:type nums: List[int]
:type queries: List[List[int]]
:rtype: List[int]
"""
```

### JavaScript:

```
/**
 * @param {number[]} nums
 * @param {number[][]} queries
 * @return {number[]}
 */
var countOfPeaks = function(nums, queries) {

};
```

### TypeScript:

```
function countOfPeaks(nums: number[], queries: number[][]): number[] {

};
```

### C#:

```
public class Solution {
    public IList<int> CountOfPeaks(int[] nums, int[][] queries) {

    }
}
```

### C:

```
/**
 * Note: The returned array must be malloced, assume caller calls free().
 */
int* countOfPeaks(int* nums, int numsSize, int** queries, int queriesSize,
int* queriesColSize, int* returnSize) {

}
```

### Go:

```
func countOfPeaks(nums []int, queries [][]int) []int {

}
```

### Kotlin:

```
class Solution {
    fun countOfPeaks(nums: IntArray, queries: Array<IntArray>): List<Int> {

    }
}
```

### Swift:

```
class Solution {
    func countOfPeaks(_ nums: [Int], _ queries: [[Int]]) -> [Int] {

    }
}
```



### Rust:

```
impl Solution {  
    pub fn count_of_peaks(nums: Vec<i32>, queries: Vec<Vec<i32>>) -> Vec<i32> {  
  
    }  
}
```

### Ruby:

```
# @param {Integer[]} nums  
# @param {Integer[][]} queries  
# @return {Integer[]}  
def count_of_peaks(nums, queries)  
  
end
```

### PHP:

```
class Solution {  
  
    /**  
     * @param Integer[] $nums  
     * @param Integer[][] $queries  
     * @return Integer[]  
     */  
    function countOfPeaks($nums, $queries) {  
  
    }  
}
```

### Dart:

```
class Solution {  
    List<int> countOfPeaks(List<int> nums, List<List<int>> queries) {  
  
    }  
}
```

### Scala:

```
object Solution {  
    def countOfPeaks(nums: Array[Int], queries: Array[Array[Int]]): List[Int] = {  
  
    }  
}
```

```
}  
}
```

### Elixir:

```
defmodule Solution do  
  @spec count_of_peaks(nums :: [integer], queries :: [[integer]]) :: [integer]  
  def count_of_peaks(nums, queries) do  
  
  end  
end
```

### Erlang:

```
-spec count_of_peaks(Nums :: [integer()], Queries :: [[integer()]]) ->  
[integer()].  
count_of_peaks(Nums, Queries) ->  
.
```

### Racket:

```
(define/contract (count-of-peaks nums queries)  
  (-> (listof exact-integer?) (listof (listof exact-integer?)) (listof  
    exact-integer?))  
  )
```

## Solutions

### C++ Solution:

```
/*  
 * Problem: Peaks in Array  
 * Difficulty: Hard  
 * Tags: array, tree  
 *  
 * Approach: Use two pointers or sliding window technique  
 * Time Complexity: O(n) or O(n log n)  
 * Space Complexity: O(h) for recursion stack where h is height  
 */
```

```

class Solution {
public:
    vector<int> countOfPeaks(vector<int>& nums, vector<vector<int>>& queries) {

    }
};

```

### Java Solution:

```

/**
 * Problem: Peaks in Array
 * Difficulty: Hard
 * Tags: array, tree
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(h) for recursion stack where h is height
 */

class Solution {
    public List<Integer> countOfPeaks(int[] nums, int[][] queries) {

    }
}

```

### Python3 Solution:

```

"""
Problem: Peaks in Array
Difficulty: Hard
Tags: array, tree

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(h) for recursion stack where h is height
"""

class Solution:
    def countOfPeaks(self, nums: List[int], queries: List[List[int]]) -> List[int]:

```

```
# TODO: Implement optimized solution
pass
```

### Python Solution:

```
class Solution(object):
    def countOfPeaks(self, nums, queries):
        """
        :type nums: List[int]
        :type queries: List[List[int]]
        :rtype: List[int]
        """
```

### JavaScript Solution:

```
/**
 * Problem: Peaks in Array
 * Difficulty: Hard
 * Tags: array, tree
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(h) for recursion stack where h is height
 */

/**
 * @param {number[]} nums
 * @param {number[][]} queries
 * @return {number[]}
 */
var countOfPeaks = function(nums, queries) {

};
```

### TypeScript Solution:

```
/**
 * Problem: Peaks in Array
 * Difficulty: Hard
 * Tags: array, tree
 *
```

```

* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(h) for recursion stack where h is height
*/

function countOfPeaks(nums: number[], queries: number[][]): number[] {

};

```

### C# Solution:

```

/*
* Problem: Peaks in Array
* Difficulty: Hard
* Tags: array, tree
*
* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(h) for recursion stack where h is height
*/

public class Solution {
    public IList<int> CountOfPeaks(int[] nums, int[][] queries) {

    }
}

```

### C Solution:

```

/*
* Problem: Peaks in Array
* Difficulty: Hard
* Tags: array, tree
*
* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(h) for recursion stack where h is height
*/

/**
* Note: The returned array must be malloced, assume caller calls free().

```

```

*/
int* countOfPeaks(int* nums, int numsSize, int** queries, int queriesSize,
int* queriesColSize, int* returnSize) {

}

```

### Go Solution:

```

// Problem: Peaks in Array
// Difficulty: Hard
// Tags: array, tree
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(h) for recursion stack where h is height

func countOfPeaks(nums []int, queries [][]int) []int {

}

```

### Kotlin Solution:

```

class Solution {
fun countOfPeaks(nums: IntArray, queries: Array<IntArray>): List<Int> {

}

}

```

### Swift Solution:

```

class Solution {
func countOfPeaks(_ nums: [Int], _ queries: [[Int]]) -> [Int] {

}

}

```

### Rust Solution:

```

// Problem: Peaks in Array
// Difficulty: Hard
// Tags: array, tree

```

```
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(h) for recursion stack where h is height

impl Solution {
    pub fn count_of_peaks(nums: Vec<i32>, queries: Vec<Vec<i32>>>) -> Vec<i32> {

    }
}
```

### Ruby Solution:

```
# @param {Integer[]} nums
# @param {Integer[][]} queries
# @return {Integer[]}
def count_of_peaks(nums, queries)

end
```

### PHP Solution:

```
class Solution {

    /**
     * @param Integer[] $nums
     * @param Integer[][] $queries
     * @return Integer[]
     */
    function countOfPeaks($nums, $queries) {

    }

}
```

### Dart Solution:

```
class Solution {
    List<int> countOfPeaks(List<int> nums, List<List<int>> queries) {

    }
}
```

### Scala Solution:

```
object Solution {  
  def countOfPeaks(nums: Array[Int], queries: Array[Array[Int]]): List[Int] = {  
  
  }  
}
```

### Elixir Solution:

```
defmodule Solution do  
  @spec count_of_peaks(nums :: [integer], queries :: [[integer]]) :: [integer]  
  def count_of_peaks(nums, queries) do  
  
  end  
end
```

### Erlang Solution:

```
-spec count_of_peaks(Nums :: [integer()], Queries :: [[integer()]]) ->  
[integer()].  
count_of_peaks(Nums, Queries) ->  
.
```

### Racket Solution:

```
(define/contract (count-of-peaks nums queries)  
  (-> (listof exact-integer?) (listof (listof exact-integer?)) (listof  
    exact-integer?))  
)
```