

Problem 450: Delete Node in a BST

Problem Information

Difficulty: **Medium**

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

Given a root node reference of a BST and a key, delete the node with the given key in the BST. Return

the

root node reference

(possibly updated) of the BST


.

Basically, the deletion can be divided into two stages:

Search for a node to remove.

If the node is found, delete the node.

Example 1:



Input:


root = [5,3,6,2,4,null,7], key = 3

Output:

[5,4,6,2,null,null,7]

Explanation:

Given key to delete is 3. So we find the node with value 3 and delete it. One valid answer is [5,4,6,2,null,null,7], shown in the above BST. Please notice that another valid answer is [5,2,6,null,4,null,7] and it's also accepted.



Example 2:

Input:

root = [5,3,6,2,4,null,7], key = 0

Output:

[5,3,6,2,4,null,7]

Explanation:

The tree does not contain a node with value = 0.

Example 3:

Input:

root = [], key = 0

Output:

[]

Constraints:

The number of nodes in the tree is in the range

[0, 10

4

]

.

-10

5

$\leq \text{Node.val} \leq 10$

5

Each node has a

unique

value.

root

is a valid binary search tree.

-10

5

$\leq \text{key} \leq 10$

5

Follow up:

Could you solve it with time complexity

$O(\text{height of tree})$

?

Code Snippets

C++:

```
/**
 * Definition for a binary tree node.
 * struct TreeNode {
 *   int val;
 *   TreeNode *left;
 *   TreeNode *right;
 *   TreeNode() : val(0), left(nullptr), right(nullptr) {}
 *   TreeNode(int x) : val(x), left(nullptr), right(nullptr) {}
 *   TreeNode(int x, TreeNode *left, TreeNode *right) : val(x), left(left),
 *   right(right) {}
 * };
 */
class Solution {
public:
    TreeNode* deleteNode(TreeNode* root, int key) {
```

```
}  
};
```

Java:

```
/**  
 * Definition for a binary tree node.  
 * public class TreeNode {  
 *     int val;  
 *     TreeNode left;  
 *     TreeNode right;  
 *     TreeNode() {}  
 *     TreeNode(int val) { this.val = val; }  
 *     TreeNode(int val, TreeNode left, TreeNode right) {  
 *         this.val = val;  
 *         this.left = left;  
 *         this.right = right;  
 *     }  
 * }  
 */  
  
class Solution {  
    public TreeNode deleteNode(TreeNode root, int key) {  
  
    }  
}
```

Python3:

```
# Definition for a binary tree node.  
# class TreeNode:  
#     def __init__(self, val=0, left=None, right=None):  
#         self.val = val  
#         self.left = left  
#         self.right = right  
class Solution:  
    def deleteNode(self, root: Optional[TreeNode], key: int) ->  
        Optional[TreeNode]:
```

Python:

```

# Definition for a binary tree node.
# class TreeNode(object):
# def __init__(self, val=0, left=None, right=None):
# self.val = val
# self.left = left
# self.right = right
class Solution(object):
def deleteNode(self, root, key):
    """
    :type root: Optional[TreeNode]
    :type key: int
    :rtype: Optional[TreeNode]
    """

```

JavaScript:

```

/**
 * Definition for a binary tree node.
 * function TreeNode(val, left, right) {
 * this.val = (val===undefined ? 0 : val)
 * this.left = (left===undefined ? null : left)
 * this.right = (right===undefined ? null : right)
 * }
 */
/**
 * @param {TreeNode} root
 * @param {number} key
 * @return {TreeNode}
 */
var deleteNode = function(root, key) {

};

```

TypeScript:

```

/**
 * Definition for a binary tree node.
 * class TreeNode {
 * val: number
 * left: TreeNode | null
 * right: TreeNode | null
 * constructor(val?: number, left?: TreeNode | null, right?: TreeNode | null)
 * {

```

```

* this.val = (val===undefined ? 0 : val)
* this.left = (left===undefined ? null : left)
* this.right = (right===undefined ? null : right)
* }
* }
*/

function deleteNode(root: TreeNode | null, key: number): TreeNode | null {

};

```

C#:

```

/**
 * Definition for a binary tree node.
 * public class TreeNode {
 *     public int val;
 *     public TreeNode left;
 *     public TreeNode right;
 *     public TreeNode(int val=0, TreeNode left=null, TreeNode right=null) {
 *         this.val = val;
 *         this.left = left;
 *         this.right = right;
 *     }
 * }
 */
public class Solution {
    public TreeNode DeleteNode(TreeNode root, int key) {

    }
}

```

C:

```

/**
 * Definition for a binary tree node.
 * struct TreeNode {
 *     int val;
 *     struct TreeNode *left;
 *     struct TreeNode *right;
 * };
 */

```

```

struct TreeNode* deleteNode(struct TreeNode* root, int key) {

}

```

Go:

```

/**
 * Definition for a binary tree node.
 * type TreeNode struct {
 *     Val int
 *     Left *TreeNode
 *     Right *TreeNode
 * }
 */
func deleteNode(root *TreeNode, key int) *TreeNode {

}

```

Kotlin:

```

/**
 * Example:
 * var ti = TreeNode(5)
 * var v = ti.`val`
 * Definition for a binary tree node.
 * class TreeNode(var `val`: Int) {
 *     var left: TreeNode? = null
 *     var right: TreeNode? = null
 * }
 */
class Solution {
fun deleteNode(root: TreeNode?, key: Int): TreeNode? {

}

}

```

Swift:

```

/**
 * Definition for a binary tree node.
 * public class TreeNode {
 *     public var val: Int

```



```

* public var left: TreeNode?
* public var right: TreeNode?
* public init() { self.val = 0; self.left = nil; self.right = nil; }
* public init(_ val: Int) { self.val = val; self.left = nil; self.right =
nil; }
* public init(_ val: Int, _ left: TreeNode?, _ right: TreeNode?) {
* self.val = val
* self.left = left
* self.right = right
* }
* }
*/
class Solution {
func deleteNode(_ root: TreeNode?, _ key: Int) -> TreeNode? {

}
}

```

Rust:

```

// Definition for a binary tree node.
// #[derive(Debug, PartialEq, Eq)]
// pub struct TreeNode {
//     pub val: i32,
//     pub left: Option<Rc<RefCell<TreeNode>>>,
//     pub right: Option<Rc<RefCell<TreeNode>>>,
// }
//
// impl TreeNode {
//     #[inline]
//     pub fn new(val: i32) -> Self {
//         TreeNode {
//             val,
//             left: None,
//             right: None
//         }
//     }
// }
use std::rc::Rc;
use std::cell::RefCell;
impl Solution {
    pub fn delete_node(root: Option<Rc<RefCell<TreeNode>>>, key: i32) ->

```

```

Option<Rc<RefCell<TreeNode>>> {

}

}

```

Ruby:

```

# Definition for a binary tree node.
# class TreeNode
# attr_accessor :val, :left, :right
# def initialize(val = 0, left = nil, right = nil)
# @val = val
# @left = left
# @right = right
# end
# end

# @param {TreeNode} root
# @param {Integer} key
# @return {TreeNode}
def delete_node(root, key)

end

```

PHP:

```

/**
 * Definition for a binary tree node.
 * class TreeNode {
 * public $val = null;
 * public $left = null;
 * public $right = null;
 * function __construct($val = 0, $left = null, $right = null) {
 * $this->val = $val;
 * $this->left = $left;
 * $this->right = $right;
 * }
 * }
 */

class Solution {

/**
 * @param TreeNode $root
 * @param Integer $key

```

```

* @return TreeNode
*/
function deleteNode($root, $key) {

}
}

```

Dart:

```

/**
 * Definition for a binary tree node.
 * class TreeNode {
 *   int val;
 *   TreeNode? left;
 *   TreeNode? right;
 *   TreeNode([this.val = 0, this.left, this.right]);
 * }
 */
class Solution {
  TreeNode? deleteNode(TreeNode? root, int key) {

  }
}

```

Scala:

```

/**
 * Definition for a binary tree node.
 * class TreeNode(_value: Int = 0, _left: TreeNode = null, _right: TreeNode =
null) {
 *   var value: Int = _value
 *   var left: TreeNode = _left
 *   var right: TreeNode = _right
 * }
 */
object Solution {
  def deleteNode(root: TreeNode, key: Int): TreeNode = {

  }
}

```

Elixir:

```

# Definition for a binary tree node.
#
# defmodule TreeNode do
#   @type t :: %__MODULE__{
#     val: integer,
#     left: TreeNode.t() | nil,
#     right: TreeNode.t() | nil
#   }
#   defstruct val: 0, left: nil, right: nil
# end

defmodule Solution do
  @spec delete_node(root :: TreeNode.t | nil, key :: integer) :: TreeNode.t | nil
  def delete_node(root, key) do

end
end

```

Erlang:

```

%% Definition for a binary tree node.
%%
%% -record(tree_node, {val = 0 :: integer(),
%% left = null :: 'null' | #tree_node{},
%% right = null :: 'null' | #tree_node{}}).

-spec delete_node(Root :: #tree_node{} | null, Key :: integer()) ->
#tree_node{} | null.
delete_node(Root, Key) ->
.

```

Racket:

```

; Definition for a binary tree node.
#|

; val : integer?
; left : (or/c tree-node? #f)
; right : (or/c tree-node? #f)
(struct tree-node
  (val left right) #:mutable #:transparent)

```

```

; constructor
(define (make-tree-node [val 0])
  (tree-node val #f #f))

|#

(define/contract (delete-node root key)
  (-> (or/c tree-node? #f) exact-integer? (or/c tree-node? #f))
  )

```

Solutions

C++ Solution:

```

/*
 * Problem: Delete Node in a BST
 * Difficulty: Medium
 * Tags: tree, search
 *
 * Approach: DFS or BFS traversal
 * Time Complexity: O(n) where n is number of nodes
 * Space Complexity: O(h) for recursion stack where h is height
 */

/**
 * Definition for a binary tree node.
 * struct TreeNode {
 *   int val;
 *   TreeNode *left;
 *   TreeNode *right;
 *   TreeNode() : val(0), left(nullptr), right(nullptr) {}
 *   TreeNode(int x) : val(x), left(nullptr), right(nullptr) {}
 *   TreeNode(int x, TreeNode *left, TreeNode *right) : val(x), left(left),
 *   right(right) {}
 * };
 */
class Solution {
public:
    TreeNode* deleteNode(TreeNode* root, int key) {

```

```
}  
};
```

Java Solution:

```
/**  
 * Problem: Delete Node in a BST  
 * Difficulty: Medium  
 * Tags: tree, search  
 *  
 * Approach: DFS or BFS traversal  
 * Time Complexity: O(n) where n is number of nodes  
 * Space Complexity: O(h) for recursion stack where h is height  
 */  
  
/**  
 * Definition for a binary tree node.  
 * public class TreeNode {  
 *     int val;  
 *     TreeNode left;  
 *     TreeNode right;  
 *     TreeNode() {  
 // TODO: Implement optimized solution  
 return 0;  
 }  
 *     TreeNode(int val) { this.val = val; }  
 *     TreeNode(int val, TreeNode left, TreeNode right) {  
 *         this.val = val;  
 *         this.left = left;  
 *         this.right = right;  
 *     }  
 * }  
 */  
  
class Solution {  
    public TreeNode deleteNode(TreeNode root, int key) {  
  
    }  
}
```

Python3 Solution:

```

"""
Problem: Delete Node in a BST
Difficulty: Medium
Tags: tree, search

Approach: DFS or BFS traversal
Time Complexity: O(n) where n is number of nodes
Space Complexity: O(h) for recursion stack where h is height
"""

# Definition for a binary tree node.
# class TreeNode:
# def __init__(self, val=0, left=None, right=None):
# self.val = val
# self.left = left
# self.right = right
class Solution:
def deleteNode(self, root: Optional[TreeNode], key: int) ->
Optional[TreeNode]:
# TODO: Implement optimized solution
pass

```

Python Solution:

```

# Definition for a binary tree node.
# class TreeNode(object):
# def __init__(self, val=0, left=None, right=None):
# self.val = val
# self.left = left
# self.right = right
class Solution(object):
def deleteNode(self, root, key):
"""
:type root: Optional[TreeNode]
:type key: int
:rtype: Optional[TreeNode]
"""

```

JavaScript Solution:

```

/**
 * Problem: Delete Node in a BST

```

```

* Difficulty: Medium
* Tags: tree, search
*
* Approach: DFS or BFS traversal
* Time Complexity: O(n) where n is number of nodes
* Space Complexity: O(h) for recursion stack where h is height
*/

/**
* Definition for a binary tree node.
* function TreeNode(val, left, right) {
*   this.val = (val===undefined ? 0 : val)
*   this.left = (left===undefined ? null : left)
*   this.right = (right===undefined ? null : right)
* }
*/
/**
* @param {TreeNode} root
* @param {number} key
* @return {TreeNode}
*/
var deleteNode = function(root, key) {

};

```

TypeScript Solution:

```

/**
* Problem: Delete Node in a BST
* Difficulty: Medium
* Tags: tree, search
*
* Approach: DFS or BFS traversal
* Time Complexity: O(n) where n is number of nodes
* Space Complexity: O(h) for recursion stack where h is height
*/

/**
* Definition for a binary tree node.
* class TreeNode {
*   val: number

```



```

* left: TreeNode | null
* right: TreeNode | null
* constructor(val?: number, left?: TreeNode | null, right?: TreeNode | null)
{
* this.val = (val===undefined ? 0 : val)
* this.left = (left===undefined ? null : left)
* this.right = (right===undefined ? null : right)
* }
* }
*/

function deleteNode(root: TreeNode | null, key: number): TreeNode | null {

};

```

C# Solution:

```

/*
* Problem: Delete Node in a BST
* Difficulty: Medium
* Tags: tree, search
*
* Approach: DFS or BFS traversal
* Time Complexity: O(n) where n is number of nodes
* Space Complexity: O(h) for recursion stack where h is height
*/

/**
* Definition for a binary tree node.
* public class TreeNode {
* public int val;
* public TreeNode left;
* public TreeNode right;
* public TreeNode(int val=0, TreeNode left=null, TreeNode right=null) {
* this.val = val;
* this.left = left;
* this.right = right;
* }
* }
*/
public class Solution {

```

```

public TreeNode DeleteNode(TreeNode root, int key) {

}

}

```

C Solution:

```

/*
 * Problem: Delete Node in a BST
 * Difficulty: Medium
 * Tags: tree, search
 *
 * Approach: DFS or BFS traversal
 * Time Complexity: O(n) where n is number of nodes
 * Space Complexity: O(h) for recursion stack where h is height
 */

/**
 * Definition for a binary tree node.
 * struct TreeNode {
 *     int val;
 *     struct TreeNode *left;
 *     struct TreeNode *right;
 * };
 */
struct TreeNode* deleteNode(struct TreeNode* root, int key) {

}

```

Go Solution:

```

// Problem: Delete Node in a BST
// Difficulty: Medium
// Tags: tree, search
//
// Approach: DFS or BFS traversal
// Time Complexity: O(n) where n is number of nodes
// Space Complexity: O(h) for recursion stack where h is height

/**
 * Definition for a binary tree node.

```

```

* type TreeNode struct {
*   Val int
*   Left *TreeNode
*   Right *TreeNode
* }
*/

func deleteNode(root *TreeNode, key int) *TreeNode {

}

```

Kotlin Solution:

```

/**
 * Example:
 * var ti = TreeNode(5)
 * var v = ti.`val`
 * Definition for a binary tree node.
 * class TreeNode(var `val`: Int) {
 *   var left: TreeNode? = null
 *   var right: TreeNode? = null
 * }
 */
class Solution {
    fun deleteNode(root: TreeNode?, key: Int): TreeNode? {

    }
}

```

Swift Solution:

```

/**
 * Definition for a binary tree node.
 * public class TreeNode {
 *   public var val: Int
 *   public var left: TreeNode?
 *   public var right: TreeNode?
 *   public init() { self.val = 0; self.left = nil; self.right = nil; }
 *   public init(_ val: Int) { self.val = val; self.left = nil; self.right = nil; }
 *   public init(_ val: Int, _ left: TreeNode?, _ right: TreeNode?) {
 *     self.val = val

```

```

* self.left = left
* self.right = right
* }
* }
*/
class Solution {
func deleteNode(_ root: TreeNode?, _ key: Int) -> TreeNode? {

}
}

```

Rust Solution:

```

// Problem: Delete Node in a BST
// Difficulty: Medium
// Tags: tree, search
//
// Approach: DFS or BFS traversal
// Time Complexity: O(n) where n is number of nodes
// Space Complexity: O(h) for recursion stack where h is height

// Definition for a binary tree node.
// #[derive(Debug, PartialEq, Eq)]
// pub struct TreeNode {
//     pub val: i32,
//     pub left: Option<Rc<RefCell<TreeNode>>>,
//     pub right: Option<Rc<RefCell<TreeNode>>>,
// }
//
// impl TreeNode {
//     #[inline]
//     pub fn new(val: i32) -> Self {
//         TreeNode {
//             val,
//             left: None,
//             right: None
//         }
//     }
// }

use std::rc::Rc;
use std::cell::RefCell;

```

```

impl Solution {
pub fn delete_node(root: Option<Rc<RefCell<TreeNode>>>, key: i32) ->
Option<Rc<RefCell<TreeNode>>> {

}
}

```

Ruby Solution:

```

# Definition for a binary tree node.
# class TreeNode
# attr_accessor :val, :left, :right
# def initialize(val = 0, left = nil, right = nil)
# @val = val
# @left = left
# @right = right
# end
# end

# @param {TreeNode} root
# @param {Integer} key
# @return {TreeNode}
def delete_node(root, key)

end

```

PHP Solution:

```

/**
 * Definition for a binary tree node.
 * class TreeNode {
 * public $val = null;
 * public $left = null;
 * public $right = null;
 * function __construct($val = 0, $left = null, $right = null) {
 * $this->val = $val;
 * $this->left = $left;
 * $this->right = $right;
 * }
 * }
 */
class Solution {

```

```

/**
 * @param TreeNode $root
 * @param Integer $key
 * @return TreeNode
 */
function deleteNode($root, $key) {

}
}

```

Dart Solution:

```

/**
 * Definition for a binary tree node.
 * class TreeNode {
 *   int val;
 *   TreeNode? left;
 *   TreeNode? right;
 *   TreeNode([this.val = 0, this.left, this.right]);
 * }
 */
class Solution {
  TreeNode? deleteNode(TreeNode? root, int key) {

  }
}

```

Scala Solution:

```

/**
 * Definition for a binary tree node.
 * class TreeNode(_value: Int = 0, _left: TreeNode = null, _right: TreeNode =
null) {
 *   var value: Int = _value
 *   var left: TreeNode = _left
 *   var right: TreeNode = _right
 * }
 */
object Solution {
  def deleteNode(root: TreeNode, key: Int): TreeNode = {

```

```
}  
}
```

Elixir Solution:

```
# Definition for a binary tree node.  
#  
# defmodule TreeNode do  
#   @type t :: %__MODULE__{  
#     val: integer,  
#     left: TreeNode.t() | nil,  
#     right: TreeNode.t() | nil  
#   }  
#   defstruct val: 0, left: nil, right: nil  
# end  
  
defmodule Solution do  
  @spec delete_node(root :: TreeNode.t | nil, key :: integer) :: TreeNode.t |  
    nil  
  def delete_node(root, key) do  
  
  end  
end
```

Erlang Solution:

```
%% Definition for a binary tree node.  
%%  
%% -record(tree_node, {val = 0 :: integer(),  
%% left = null :: 'null' | #tree_node{},  
%% right = null :: 'null' | #tree_node{}}).  
  
-spec delete_node(Root :: #tree_node{} | null, Key :: integer()) ->  
  #tree_node{} | null.  
delete_node(Root, Key) ->  
  .
```

Racket Solution:

```
; Definition for a binary tree node.
#|

; val : integer?
; left : (or/c tree-node? #f)
; right : (or/c tree-node? #f)
(struct tree-node
  (val left right) #:mutable #:transparent)

; constructor
(define (make-tree-node [val 0])
  (tree-node val #f #f))

|#

(define/contract (delete-node root key)
  (-> (or/c tree-node? #f) exact-integer? (or/c tree-node? #f))
  )
```